







Benefits

High quality design assures long-lasting performance.

Product Application

- Thoroughly clean contact surface before use.
- · Remove the release liner and apply with care to the part to be bonded, ensuring that no air is trapped between the tape and the substrate.
- · Apply with recommended application pressure of 15 pounds per inch of tape width.
- Once the tape has been applied, it cannot be removed and reused.
- Therefore, position tape carefully, assuring that it is in contact with all surfaces.
- If tape is misaligned, remove used unit, discard, and repeat application with new unit.
- Test product for system compatibility as individual application conditions can impact results.

Applications

Used in gasketing, sealing, polishing, noise, and vibration dampening, wiping, packaging protection, filtering, and many more applications.

Technical Data

| Application Temperature: | -34 to +250°F |
|---------------------------|------------------|
| Base: | Acrylic |
| Elongation: | 39% |
| Functional Temperature: | 0°F - 140°F |
| Hardness Range, Shore A: | 15 - 25 |
| Loop Tack: | 115oz/in typical |
| Shelf Life: | 12 Months |
| Thermal Condition (70°F): | 0.24 |

Size

3/8in x 50ft

CREATING INDUSTRIAL ADHESIVE, TAPE AND SEALANT SOLUTIONS THAT OUTPERFORM

