



High Temp Adhesive

ForzaBOND° **C-C360** is a flammable, high performance, neoprene contact adhesive.

Benefits

- Excellent Weather Resistance
- Excellent coverage
- Post formable
- · High temperature resistance
- 80% of final strength achieved upon bonding
- Full strength achieved in 24 hours
- Fast drying
- No ODS (Ozone Depleting Substances)
- No chlorinated solvents
- Sprayable/Rollable/Brushable

Product Application

- Be sure all surfaces are clean and free of grease, dirt, dust, etc. Apply to both surfaces to be bonded.
- Adhesive should be applied to each surface, allowed to dry (until non transferable to finger), then bonded under pressure.
- When brushing, multiple coats may be required on porous surfaces.
- When spraying, use of DeVilbiss JGA with FX tip and needle or Binks 2001 or 95 gun and 63B tip 2nd needle or similar equipment is satisfactory.
- Apply pressure with a hand laminate roller or nip roller. If adhesive is left to dry for over 30 minutes, parts should be re-coated.
- Normal coverage required with web spray pattern is approximately 80%. Initial bond is strong enough to allow cutting or trimming immediately although ultimate strength is achieved in approximately 24 hours.
- Store away from heat, flames or other sources of ignition. If spray tip clogs unscrew the spray tip from the gun and clean with a solvent such as lacquer thinner or acetone.
- Do not use a pin on the spray tip orifice.

Applications

ForzaBOND° **C-C360** is a flammable neoprene contact adhesive designed specifically for:

- Vinyl and rubber flooring in high-traffic areas
- Wall paneling and cladding
- Countertop lamination
- Roofing applications
- Bonding membrane materials in flat roofing

Technical Data

Appearance:	Clear or Blue
Shelf Life:	12 months
Solids:	15-21 %
Solvent:	Flammable
voc:	569 g/L
Viscosity:	250-300 cps
0:	

Sizes

1 Gallon Can	5 Gallon Pail
52 Gallon Drum	



