



Forza™
TAPE | A FORCE TO BE RECKONED WITH

Construction

C-T500

Foam Tape



ForzaTape® C-T500 is a foam tape used to seal against weather, dust, and vibration of equipment.

Benefits

- High quality design assures long-lasting performance.

Product Application

- Thoroughly clean contact surface before use.
- Remove the release liner and apply with care to the part to be bonded, ensuring that no air is trapped between the tape and the substrate.
- Apply with recommended application pressure of 15 pounds per inch of tape width.
- Once the tape has been applied, it cannot be removed and reused.
- Therefore, position tape carefully, assuring that it is in contact with all surfaces.
- If tape is misaligned, remove used unit, discard, and repeat application with new unit.
- Test product for system compatibility as individual application conditions can impact results.

Applications

ForzaBOND® C-T500 is used for gap filling and sealing in construction applications, including:

- Weather stripping for windows and doors
- Vibration dampening and noise reduction for roof curb mounts
- Various cushioning applications

Technical Data

Application Temperature:	-34 to +250°F
Base:	Acrylic
Elongation:	39%
Functional Temperature:	0°F - 140°F
Hardness Range, Shore A:	15 - 25
Loop Tack:	115oz/in typical
Shelf Life:	12 Months
Thermal Condition (70°F):	0.24

Size

3/8in x 50ft

CREATING INDUSTRIAL ADHESIVE, TAPE AND SEALANT SOLUTIONS THAT OUTPERFORM

402.731.9300
info@forzabuilt.com
www.forzabuilt.com



3211 Nebraska Ave, Suite 300
Council Bluffs, Iowa 51501