



ForzaTM
BOND | A FORCE TO BE RECKONED WITH

Construction

CC515



Pressure Sensitive Adhesive

ForzaBOND® CC515 is an aggressive and fast-drying pressure sensitive adhesive designed to bond a vast range of substrates.

Benefits

- Aggressive tack
- Polystyrene Safe
- Very fast drying
- No ODS (ozone depleting substances)

Product Application

- Designed as a portable, self-contained spray system for field or shop applications.
- Be sure all surfaces are clean and free of grease, dirt, duct, etc.
- Apply adhesive to both surfaces to be mated, at 80% to 100% coverage.
- Allow enough time (2-4 minutes or until dry to the touch) for the adhesive to become tacky before bonding.
- Parts should be mated with as much pressure as practical.
- Normal coverage required with web spray pattern is approximately 80%; however, porous surfaces may need a second coat.
- Initial bond is strong enough to allow cutting or trimming immediately, although ultimate strength is achieved in approximately 24 hours.



Applications

ForzaBOND® CC515 is an aggressive, fast-drying pressure-sensitive adhesive designed to bond a wide range of substrates, including:

- Carpet Installations
- Acoustic panel manufacturing and installation
- Backed roof membrane materials
- Prefabricated home and building manufacturing applications

Technical Data

Total Solids:	26-32%
VOC Content:	469 g/L
Appearance:	Clear or Green
Shelf Life:	12 Months
Dry Time:	2-4 Minutes*
Open Time:	Long
Solvent System:	Flammable
Spray Pattern:	Web

Packaging

13oz Aerosol Can	22L Disposable Canister
	108L Returnable Canister

Recommended Equipment

- FK20 Spray Gun
- FK30 Hose
- Use 6501B Spray Tip

Recommended Clean Up

- ForzaCLEAN FC-CAR (Citrus Cleaner)
- Organic Solvents

CREATING INDUSTRIAL ADHESIVE, TAPE, AND SEALANT SOLUTIONS THAT OUTPERFORM

402.731.9300
info@forzabuilt.com
www.forzabuilt.com



3211 Nebraska Ave, Suite 300
Council Bluffs, Iowa 51501