

ForzaSEAL® OA28 is a high performance, rollable advanced polymer adhesive specifically formulated to be used for most types of paneling installations.

Benefits

- · Rollable Adhesive
- Universal Application
- · Can be adhered immediately
- · Will not attack mudded joints
- · Environmentally safe
- Fast strength development
- Nonflammable
- Moisture, mold & mildew resistant
- · Strong, fast grab
- · Water-resistant bond
- Odorless
- VOC-Compliant

Product Application

- Keep clean and free of adhesive build-up to ensure proper application
- Place panel against surface and press firmly over entire surface, working from the edge of the panel where molding is installed outwards to the open edge.
- Using a roller over the entire installed wall panel is recommended.
- Bracing may be required if walls and panels are not flat.
- Panels used in conjunction with channel moldings should NOT fit tightly into the moldings.
- Leave a small area in the molding for expansion and follow panel manufacturer's recommendations.
- Any holes drilled through the panels for fasteners, pipes, or conduits should be oversized to allow for natural movement of the panel.
- Spread no more adhesive than can be installed in 20 minutes or less.

Applications

Specifically designed for installing fiber reinforced plastic, plastic laminate, wainscoting, and other wall coverings over many common porous and non-porous surfaces.

Compatible with wood, foam board, plastic, laminate, plywood, tub surrounds, metal, concrete vinyl, and non-porous building materials

Technical Data

Skin Time:	65 minutes
Elongation at Break:	198%
Shore A Hardness:	35 - 40
Color:	White
Viscosity:	100,000 cps
Application Temperature Range:	40 - 140°F
Shelf Life:	12 Months
Lap Shear Strength:	196 Psi
Sag:	Non-Sagging
Packaging	
1 Gallon	3.5 Gallon
5 Gallon	

Recommended Cleanup

Water Alcohol

