



**Forza**™  
**SEAL** | A FORCE TO BE RECKONED WITH

## Construction

# C-OS9



## Performance Polymer

ForzaSEAL® C-OS9 is a non-hazardous, high strength, single part moisture cure sealant.

### Benefits

- Highly weather resistant
- Immediately paintable
- No solvents or isocyanate
- Retains strong bond through impact, peel, flex, and changing temperature
- Non-yellowing
- Does not form bubbles, shrink or crack
- Low temperature flexibility (properties retained to -75°F)
- High UV resistance
- Doesn't attract dust or dirt

### Product Application

- Generally applied by extrusion, or trowel.
- Surfaces should be clean and free of dust, oil and grease.
- Aluminum and other metals may be primed for best adhesion.
- Apply between 34°F and 150°F, in damp and dry conditions.
- The majority of its strength is develops in the first 24 hours.
- Minimum cure time is overnight, but several days may be required for maximum performance, however cure time may be accelerated at higher temperatures (do not exceed 150°F for accelerated cure).
- Most parts do not require clamping, although heavy parts may require temporary clamping to ensure desired positioning.
- Easy clean up with wet rag or mineral spirits.

### Applications

ForzaSEAL® C-OS9 is designed for universal sealing applications in the construction industry, including:

- Crack filling on concrete
- Sealing around windows and door openings
- Sealing in gutter applications
- Roof penetrations

### Technical Data

Skin Time:	Less than 30mins @ 77°F/55% RH
Tensile Strength:	275 PSI
Elongation at Break:	275%
Shore A Hardness:	47
Color:	Gray, Black, White
Viscosity:	533,000 CPS
Temperature Range:	-75°F - 400°F for limited amount of time
Shelf Life:	12 months
Sag:	Non-Sag
Staining:	Non-Staining

### Sizes

20 oz Sausage	10.1 oz Cartridge
28 oz Cartridge	52 Gallon Drum
5 Gallon Pail	

Bead Widths (inch)	Linear Yield (FT) / oz
1/8	12.2 ft
1/4	3.05 ft
3/8	1.35 ft
1/2	9.2 in
5/8	5.88 in
3/5	4.08 in

CREATING INDUSTRIAL ADHESIVE, TAPE, AND SEALANT SOLUTIONS THAT OUTPERFORM

402.731.9300  
info@forzabuilt.com  
www.forzabuilt.com



3211 Nebraska Ave, Suite 300  
Council Bluffs, Iowa 51501