



ForzaTM

BOND | A FORCE TO BE RECKONED WITH

Industrial

R160

Epoxy Adhesive



ForzaBOND® R160 is a two-part, reactive adhesive with a very fast cure and a wide range of uses.

Benefits

- 1:1 ratio, easy mixing or dispensing
- 3 minute work life, 10 minute handling strength
- -60° to 250°F service temperature
- Resistant to water, salt, vehicle fuels and fluids, and many other substances

Product Application

- A two part 1:1 mix ratio
- Ensure flow from both sides of cartridge is possible, attach static mixer and gun out material.
- Apply mixed adhesive to one surface to be bonded then mate second surface.
- Surfaces should be clean and dry free of dust and debris in most cases no abrasion or solvent wipe is necessary.

Applications

ForzaBOND® R160 has a tenacious bond to wood, concrete, fiberglass, and most thermoset plastics. Carpet tack strip to concrete, metal, wood, and various other floor surfaces – carpet may be stretched as soon as 20 minutes after application. Bonds metal balusters in wood hand rails.

Technical Data

| | |
|----------------|---------------|
| Appearance: | Clear or Blue |
| Handling Time: | 10 min |
| Mix Ratio: | 15-21 % |
| Solids: | Flammable |
| VOC: | 569 g/L |

Sizes

| | |
|----------------------|---------------------|
| 300ml Dual Cartridge | 280ml Coaxial |
| 5 Gallon Pail | 50ml Dual Cartridge |

CREATING INDUSTRIAL ADHESIVE, TAPE, AND SEALANT SOLUTIONS THAT OUTPERFORM

402.731.9300
info@forzabuilt.com
www.forzabuilt.com



3211 Nebraska Ave, Suite 300
Council Bluffs, Iowa 51501