



**Pressure Sensitive Adhesive** 

**ForzaBOND® CC515** is an aggressive and fast-drying pressure sensitive adhesive designed to bond a vast range of substrates.

## **Benefits**

- Aggressive tack
- Polystyrene Safe
- · Very fast drying
- No ODS (ozone depleting substances)

# **Product Application**

- Designed as a portable, self-contained spray system for field or shop applications.
- Be sure all surfaces are clean and free of grease, dirt, duct, etc.
- Apply adhesive to both surfaces to be mated, at 80% to 100% coverage.
- Allow enough time (2-4 minutes or until dry to the touch) for the adhesive to become tacky before bonding.
- Parts should be mated with as much pressure as practical.
- Normal coverage required with web spray pattern is approximately 80%; however, porous surfaces may need a second coat.
- Initial bond is strong enough to allow cutting or trimming immediately, although ultimate strength is achieved in approximately 24 hours.



**ForzaBOND® CC515** is an aggressive, fast-drying pressure-sensitive adhesive designed to bond a wide range of substrates, including:

- Carpet Installations
- Acoustic panel manufacturing and installation
- Backed roof membrane materials
- Prefabricated home and building manufacturing applications

## **Technical Data**

Total Solids:	26-32%
VOC Content:	469 g/L
Appearance:	Clear or Green
Shelf Life:	12 Months
Dry Time:	2-4 Minutes*
Open Time:	Long
Solvent System:	Flammable
Spray Pattern:	Web
Packaging	
13oz Aerosol Can	22L Disposable Canister
	108L Returnable Canister

### **Recommended Equipment**

- FK20 Spray Gun
- FK30 Hose
- Use 6501B Spray Tip

#### **Recommended Clean Up**

- ForzaCLEAN FC-CAR (Citrus Cleaner)
  - Organic Solvents

CREATING INDUSTRIAL ADHESIVE, TAPE, AND SEALANT SOLUTIONS THAT OUTPERFORM

