



Forza™

TAPE

A FORCE TO BE RECKONED WITH

Transportation

T-T430



PE Sealing Tape



ForzaTape® T-T430 is a single coated PE sealing tape with an aggressive rubber based adhesive system specifically designed for applications that require very high tack, bond, and sealing properties.

Benefits

- High tack
- Extreme sealing
- High heat resistance
- Cold resistance

Product Application

- Ensure substrate is clean and dry, and free from dust, dirt, oil, wax, or silicone.
- Apply to the part to be bonded, ensuring that no air is trapped between the tape and the substrate.
- Apply adequate pressure when bonding.

Applications

ForzaTape® T-T430 provides excellent adhesion and sealing to a wide range of surfaces and conditions including: porous, low energy, cold, and damp surfaces. Applications Include:

- Field seaming and repair of polyethylene and polypropylene film/panel
- Adhesion to concrete walls, galvanized, aluminum, plywood, oriented strand board, waferboard, and pink foam insulation sheet.

Technical Data

Tape Thickness	8 mils
Adhesive Type	Synthetic Rubber
Adhesive Thickness	5 mils
Liner Thickness	3 mils
Min. Application Temperature	45°F
Typical Service Temperature	-20 - 160°F (SAFT 165°F)
Slit Colors	Charcoal, White

Packaging

7/8 x 30	Custom Sizing Available
----------	-------------------------

CREATING INDUSTRIAL ADHESIVE, TAPE AND SEALANT SOLUTIONS THAT OUTPERFORM

402.731.9300
info@forzabuilt.com
www.forzabuilt.com



3211 Nebraska Ave, Suite 300
Council Bluffs, Iowa 51501