



# Forza™

**BOND** | A FORCE TO BE RECKONED WITH

## Industrial C110



### High-Temp Adhesive



**ForzaBOND® C110** is a flammable, high performance, sprayable industrial contact adhesive.

### Benefits

- Post formable
- Excellent coverage
- High - temperature resistance
- 80% of final strength achieved upon bonding
- Full strength achieved in 24 hours
- Fast drying with long open time (30-45 minutes)
- No ODS (Ozone Depleting Substances)
- No chlorinated solvents
- Sprayable

### Product Application

- Be sure all surfaces are clean and free of grease, dirt, dust, etc. Apply to both surfaces to be bonded.
- Adhesive should be applied to each surface, allowed to dry (until non transferable to finger), then bonded under pressure.
- When brushing, multiple coats may be required on porous surfaces.
- When spraying, use of DeVilbiss JGA with FX tip and needle or Binks 2001 or 95 gun and 63B tip 2nd needle or similar equipment is satisfactory.
- Apply pressure with a hand laminate roller or nip roller. If adhesive is left to dry for over 30 minutes, parts should be re-coated.
- Normal coverage required with web spray pattern is approximately 80%. Initial bond is strong enough to allow cutting or trimming immediately although ultimate strength is achieved in approximately 24 hours.
- Store away from heat, flames or other sources of ignition. If spray tip clogs unscrew the spray tip from the gun and clean with a solvent such as lacquer thinner or acetone.
- Do not use a pin on the spray tip orifice.

### Applications

**ForzaBOND® C110** is designed for laminating and general bonding to substrates.

### Technical Data

Appearance:	Clear or Red
Shelf Life:	12 months
Solids:	15-21 %
Solvent:	Flammable
VOC:	593 g/L
Viscosity:	100-150 cps

### Sizes

1 Gallon Can	5 Gallon Pail
55 Gallon Drum	Quart

CREATING INDUSTRIAL ADHESIVE, TAPE, AND SEALANT SOLUTIONS THAT OUTPERFORM

402.731.9300  
info@forzabuilt.com  
www.forzabuilt.com



3211 Nebraska Ave, Suite 300  
Council Bluffs, Iowa 51501