



# Forza™

**SEAL** | A FORCE TO BE RECKONED WITH

## Industrial OS61



### Self-Leveling Performance Polymer

ForzaSEAL® OS61 is a self-leveling performance polymer designed for a variety of sealing applications.

### Benefits

- Self-leveling
- Weather resistant
- UV resistant
- Non-yellowing
- Flexible

### Product Application

- Generally applied by extrusion or trowel.
- Surfaces should be clean and free of dust, oil and grease.
- Aluminum and other metals may be primed for best adhesion.
- Apply between 34°F and 150°F, in damp and dry conditions.
- The majority of its strength is developed in the first 24 hours.
- Minimum cure time is overnight, but several days may be required for maximum performance, however cure time may be accelerated at higher temperatures (do not exceed 150°F for accelerated cure).
- Most parts do not require clamping, although heavy parts may require temporary clamping to ensure desired positioning.
- Easy clean up with wet rag or alcohol.

### Applications

ForzaSEAL® OS61 is designed to seal a wide variety of materials such as:

- Glass
- Steel
- Aluminum
- Marble
- Concrete
- Wood and Many Plastics

### Technical Data

Skin Time:	41 minutes
Tensile Strength:	261
Elongation at Break:	150%
Shore A Hardness:	28
Color:	Gray and White
Viscosity:	High
Temperature Range:	-75 – + 400°F
Shelf Life:	12 months
Sag:	Non
Staining:	Non

### Packaging

10.1 oz Cartridge	5 Gallon Pail
28 oz Cartridge	
20 oz Sausage	

CREATING INDUSTRIAL ADHESIVE, TAPE, AND SEALANT SOLUTIONS THAT OUTPERFORM

402.731.9300  
info@forzabuilt.com  
www.forzabuilt.com



3211 Nebraska Ave, Suite 300  
Council Bluffs, Iowa 51501