



Pressure Sensitive Adhesive



ForzaBOND® CC501 is a low VOC, CA compliant, aggressive and fast-drying pressure sensitive adhesive designed to bond a vast range of substrates.

Benefits

- Low VOC
- · Pressure sensitive adhesive
- Very fast drying
- Long lasting high tack (pressure sensitive)
- · Aggressive bonds to nearly any surface
- No ODS (ozone depleting substances)
- Bonds well to porous surfaces

Product Application

- ForzaBOND® TC466 is designed as a portable, self-contained spray system for field or shop applications.
- Be sure all surfaces are clean and free of grease, dirt, dust, etc.
- Normal coverage required with web spray pattern is approximately 80% to 100% coverage.
- Allow enough time (2-4 minutes or until dry to the touch) for bonding the adhesive to become tacky before bonding.
- Parts should be mated with as much pressure as practical.
- Initial bond is strong enough to allow cutting or trimming immediately, although ultimate strength is achieved in approximately 24 hours.

Applications

ForzaBOND® CC501 is a CA-compliant pressure-sensitive adhesive designed for temporary fixturing in construction applications, including:

- Bonding of backed carpet and roofing materials
- Construction of acoustical panels
- Temporary bonding of reveal strips in tilt-up concrete
- Foundation water-proof membrane

Technical Data

Total Solids:	30-38%
VOC Content:	37 g/L
Appearance:	Clear or Red
Shelf Life:	12 Months
Dry Time:	2-4 Minutes*
Open Time:	Long
Solvent System:	Methyl Acetate
Spray Pattern:	Web

Packaging

13oz Aerosol Can	22L Disposable Canister
	108L Returnable Canister

Recommended Equipment

- FK20 Gun
- FK30 Hose
- Use 6501B Spray Tip

Recommended Cleanup

- FC-CAR (citrus cleaner)
- Organic Solvents

CREATING INDUSTRIAL ADHESIVE, TAPE, AND SEALANT SOLUTIONS THAT OUTPERFORM

