

Structured Task Decomposition Improves Reliability of LLM-Based Knowledge Analysis

NnnHU

Independent Researcher

47146850+NnnHU@users.noreply.github.com

August 2, 2026

Abstract

Large language models often fail silently when asked to produce structured analytical output in a single call: they return empty responses, unparseable text, or refuse the task. We compare five execution strategies of increasing complexity on a fixed 13-case corpus of financial documents, holding the model constant where possible to isolate each strategy’s contribution. We find that (1) **task decomposition** (an extract → analyze → judge pipeline) is the dominant driver of reliability, improving the success rate from 31% (single shot) to 92%, whereas retry alone adds only +8 points; (2) a **multi-model Panel+Judge** architecture, evaluated under blinded dual-LLM grading with a human anchor, produces higher-quality output than a single-model pipeline on accuracy, coverage, overall quality, and hallucination rate. We release the benchmark harness, a corpus manifest with content fingerprints, and the grading tooling so the results can be reproduced and extended to other domains.

1 Introduction

A common engineering experience with LLMs: you ask for a structured JSON analysis and the model returns nothing, or a refusal, or prose with no JSON. For toy tasks this is a nuisance; for a product that must return reliable structured output, it is fatal.

Two intuitive fixes are often tried: **retry on failure**, and **add more models** (a “mixture of agents”). Both sound plausible, but without a controlled experiment it is unclear which one actually buys reliability—and at what cost.

This report describes a benchmark designed to **isolate the contribution of each factor**. We define five execution strategies (§2) that form a chain of single-variable changes, run them on a shared corpus, and measure both **reliability** (does valid structured output come back?) and **quality** (is that output any good?). The design lets us attribute gains to specific mechanisms rather than to “using a fancier setup.”

2 Experimental Setup

2.1 The five execution strategies

Each strategy answers the same question against the same source document and produces the same target structure (a four-field verdict: consensus / divergence / blindspots / verdict). They differ only in *how* the work is organized.

The chain is designed so each step changes **ideally one variable**:

Table 1: The five execution strategies. “Cost” is the number of API calls. “Isolates” names the single factor each step is designed to attribute.

Mode	What it does	Cost	Isolates
M1 single-shot	One call; doc + question in the prompt	1	baseline
M1R single + retry	Same as M1, but retries on empty/bad output (≤ 4 attempts)	1–4	contribution of retry alone
M2 single-model pipeline	extract $\rightarrow$ analyze $\rightarrow$ judge, all one model	3	contribution of task decomposition beyond retry
M3 multi-model Panel+Judge	extract, then 2 models analyze in parallel, then a Judge synthesizes	4	contribution of multiple models beyond pipeline
M4 single-model self-critique	answer $\rightarrow$ critique $\rightarrow$ revise, one model	3	whether self-reflection matches multi-model

M1 $\rightarrow$ M1R : +retry, nothing else (retry’s contribution)
 M1R $\rightarrow$ M2 : +pipeline structure (decomposition’s contribution)
 M2 $\rightarrow$ M3 : +a second model in the panel (multi-model’s contribution)
 M4 $\leftrightarrow$ M3 : self-critique vs multi-model (does self-reflection suffice?)

A residual confound (documented in §5): M3’s Judge receives two analyses while M2’s receives one, so “model count” and “Judge input richness” are not fully separated. We report this honestly rather than overclaim.

2.2 Corpus

13 cases, all from a single financial-investing article series (the Jeremy Grantham / GMO bubble narrative), chosen for narrative richness and the presence of specific verifiable facts (dates, P/E ratios, AUM figures). Composition:

- 1 English summary document (~ 3.3 k chars)
- 7 standard Chinese (Traditional) ASR transcripts (~ 9 – 12 k chars each; contain speech-to-text noise—typos, misheard names)
- 3 large documents (~ 31 – 34 k chars)
- 1 super-large document (~ 53 k chars)
- 1 multi-document case (3 docs concatenated, ~ 32 k chars)

Total: ~ 256 k characters. The ASR noise is intentional—it tests robustness to messy real-world input. The corpus is narrow in domain (finance); this is a known limitation (§5).

2.3 Models

- Panel / Judge: **deepseek-v4-flash** (via `api.deepseek.com`, OpenAI-compatible protocol)
- Second panel model: **deepseek-v4-pro**
- Temperature: 0.7 for analysis/judge, 0.5 for extract, 0.5 for critique
- Max tokens per call: 2048; timeout: 360s

2.4 Metrics

Reliability (all 13 cases, all 5 modes): a mode “succeeds” on a case iff it returns all four verdict fields with **real** content—parse-fallback placeholders like “*(could not parse ...)*” do **not** count. (An earlier draft of this analysis incorrectly counted placeholders as success; the bug was found and the numbers below are corrected. See §5 on methodology.)

Quality (7 cases where both M2 and M3 produced real output): graded by **two independent LLM judges** (Gemini and KIMI K2.6) in a **blinded A/B setup**—neither judge knew which output was M2 or M3. Position bias was cancelled by per-case A/B reordering. A **human anchor** graded 3 cases blindly to validate the LLM judges. Scoring rubric: factual accuracy (1–5), hallucination (Y/N), key-info coverage (1–5), overall quality (1–5), and a forced preference (A / B / tied).

3 Results

3.1 Reliability—decomposition, not retry, drives success

Table 2: Reliability across the five modes (all 13 cases).

Mode	Success rate	Avg latency	Avg output chars	API calls
M1 single-shot	31% (4/13)	21.4s	458	13
M1R single + retry	38% (5/13)	45.7s	626	21
M2 single-model pipeline	92% (12/13)	55.3s	1,339	39
M3 multi-model Panel+Judge	92% (12/13)	50.4s	1,531	52
M4 single-model self-critique	38% (5/13)	74.2s	899	39

Reading the chain.

- **M1 → M1R: +8 points.** Retry rescued only 1 of 9 failures. The empty-response problem is not a transient blip that a second attempt fixes—the model genuinely struggles with the one-shot structured-JSON prompt ~60% of the time. **Retry alone is insufficient.**
- **M1R → M2: +54 points.** Decomposing the task into extract → analyze → judge (with the same single model) takes reliability from 38% to 92%. This is the dominant effect. **Task decomposition—not retry—is what makes the pipeline reliable.**
- **M2 → M3: +0 points on reliability** (both 92%), but see quality (§3.2). Adding a second model does not further improve the *rate* of producing valid output once a pipeline is in place.
- **M4 (self-critique): 38%.** A single model critiquing and revising its own output does **not** approach the pipeline’s reliability. This is a naive answer→critique→revise implementation; engineered self-reflection (Reflexion (Shinn et al., 2023), Self-Refine (Madaan et al., 2023), Constitutional AI (Bai et al., 2022)) may do better—but the result shows self-critique is not automatically a substitute for decomposition.

Headline finding: *Structured task decomposition dramatically improves the reliability of LLM-based structured analysis—from ~31% to ~92%. The gain comes from the decomposition, not from retrying.*

3.2 Quality—multi-model beats single-model pipeline (blinded, dual-LLM + human-anchored)

For the 7 cases where both M2 and M3 returned real analysis, blinded grading by Gemini + KIMI K2.6 (14 votes total):

Table 3: Quality grading: M2 (single-model pipeline) vs. M3 (multi-model Panel+Judge) on the 7 cases where both produced real output. 14 votes = 2 judges $\times$ 7 cases.

Metric	M2 (single-model)	M3 (multi-model)	Δ (M3–M2)
Factual accuracy (1–5)	3.14	4.14	+1.00
Key-info coverage (1–5)	2.93	3.79	+0.86
Overall quality (1–5)	2.86	3.71	+0.86
Hallucination (count /14)	3	2	M3 fewer
Preference wins (of 14)	6	8	M3 wins

The strongest single signal: both LLM judges agreed on preference in 7/7 cases (100% inter-rater agreement). Two architecturally different models, grading independently and blinded, picked the same winner every time—hard to produce by chance, indicating the M2-vs-M3 difference is a real signal, not scoring-scale noise.

Human anchor validation: 3/3 agreement. A domain-knowledgeable human graded 3 representative cases blindly (deliberately including 2 cases where the LLMs picked single-model M2—the counter-intuitive choice). The human agreed with the LLM judges on all 3, including both M2 wins. This confirms the LLM judges are not blindly pro-multi-model: they pick single-model when it is actually better, and the human agrees.

Reading: When both modes succeed, multi-model Panel+Judge produces **higher-quality** output than a single-model pipeline—more accurate, better coverage, fewer hallucinations, and preferred more often. The earlier appearance that “M2 $\approx$ M3” (from output-character counts) was a measurement artifact: by a richness proxy they looked equal, but on real quality grading multi-model pulls ahead.

3.3 Notable secondary findings

- **Parallelism offsets latency.** M3 (4 calls, 2 models in parallel) averaged 50.4s vs. M2’s 55.3s (3 sequential calls). Multi-model fan-out does **not** cost wall-clock time here, though it costs $\sim 33\%$ more tokens.
- **M3 beat M2 on latency in 6/13 cases**, including the multi-document case (M2 101s vs. M3 37s) where sequential extract $\rightarrow$ analyze $\rightarrow$ judge on one model is slower than parallel panels.

4 Reproducibility

The benchmark is fully reproducible from the accompanying reference implementation, anchored to repository commit 9301168.

Run all 5 modes on all 13 cases (~40–70 min, ~150 API calls)
 npm run bench -- --full

Incremental: run only M1R + M4, merging prior M1/M2/M3 traces
 npm run bench

```
# Re-run only M2 + M3 (e.g. after fixing an extract-retry issue)
npm run bench -- --remediate
```

Corpus: `bench-samples/` (13 cases + `samples.json` manifest). The corpus is domain-narrow (finance); replacing it with other-domain documents tests generalization.

Configuration: `.env` with `VITE_VERDEX_PROVIDER_*` and `VITE_VERDEX_PROVIDER2_*` (two OpenAI-compatible providers; the environment variable names are historical and retained for reproducibility).

Outputs: `bench-results/` (not redistributed):

- `<runId>-<case>-<query>-trace.json` — full-fidelity traces (untruncated)
- `<runId>-<case>-<query>-report.md` — per-case comparison tables
- `<runId>-SUMMARY.md` — aggregate + key-question analysis

Blinded quality grading pack: `npx tsx scripts/extract-grading.ts` generates per-case A/B files (`bench-results/grading-pack/`) for blinded grading by any LLM or human. The A/B → mode mapping is kept in `quality-grading-key.json` (secret until grading is complete).

Note on corpus distribution. A reference implementation, the grading harness, and a corpus **manifest with content fingerprints** accompany this submission. The 13 source documents are publicly accessible video transcripts; we provide SHA-256 fingerprints and character counts for verification rather than redistributing the transcripts, to respect the original creators’ distribution rights. Readers can reproduce the runs by obtaining the source documents and verifying them against the published fingerprints.

5 Discussion

5.1 What the evidence supports

- **Strong:** task decomposition improves reliability (31% → 92%, n=13, clean isolation of retry vs. decomposition).
- **Preliminary but consistent:** multi-model Panel+Judge improves quality over a single-model pipeline (5 metrics, n=7, dual-LLM 7/7 agreement, human anchor 3/3). We phrase this as “*evidence consistently favors*” rather than “*proves*”—n=7 and a single domain are not general proof.

5.2 Limitations

- **Sample size.** n=13 for reliability, n=7 for quality. Directional, not statistically definitive.
- **Domain narrowness.** All cases are financial-investing text. Whether the decomposition effect holds across domains (code, legal, medical) is untested. The corpus is designed to be swappable to test this.
- **One residual confound in M2 vs. M3.** M3’s Judge receives two analyses while M2’s receives one, so “model count” and “Judge input richness” co-vary. The result should be read as “multi-model Panel+Judge > single-model pipeline,” not “more models alone > fewer models alone.” A fully isolated test would feed M2’s Judge two copies of the same single-model analysis.

- **M2’s low scores are partly extract-driven.** In 2–3 cases M2’s extract step partially failed even after retry, biasing its quality scores downward. The direction ($M3 > M2$) holds on the clean cases too, but the gap magnitude may be inflated.
- **LLM judges, not only humans.** The human anchor (3 cases) validates the LLM judges’ direction, but a larger human study would strengthen this.

5.3 Methodological note: the placeholder bug

An earlier draft of this analysis reported “100% success” for every mode. That was a statistics bug: the parser emits non-empty placeholder strings (“*could not parse . . .*”) on failure, and a naive non-empty check counted them as success. The bug was caught by noticing the data looked implausibly clean, and the fix (excluding placeholders from the success criterion) yielded the numbers in §3. We retain this story in the report because catching and correcting one’s own measurement bias is a core part of trustworthy benchmarking—and a reminder that *the most dangerous failures are the ones that look like success*.

5.4 Implications for practice

For teams building LLM products that must return reliable structured output:

1. **Decompose first.** Before adding more models or fancier prompts, split the task into extract $\rightarrow$ analyze $\rightarrow$ judge. This single change had the largest effect in our benchmark.
2. **Retry is cheap insurance but not a fix.** Add it, but don’t expect it to solve a fundamentally hard one-shot prompt.
3. **Multi-model earns its cost on quality, not reliability.** Once a pipeline is reliable, a second model improves output quality (accuracy, coverage, hallucination) without adding latency (parallelism offsets it).
4. **Self-critique is not a free substitute.** A naive answer $\rightarrow$ critique $\rightarrow$ revise loop did not match the pipeline. If pursuing self-reflection, use engineered prompts (Reflexion-style (Shinn et al., 2023)), and benchmark it.

6 Related Work

- **Self-Refine / Reflexion / Constitutional AI**—single-model self-improvement loops (Madaan et al., 2023; Shinn et al., 2023; Bai et al., 2022). Our M4 is a naive instance; engineered variants may outperform it. The benchmark’s M4 slot is where such methods can be plugged in for comparison.
- **Mixture-of-Agents (MoA)**—multi-model aggregation (Wang et al., 2025). Our M3 is a minimal MoA (2 panels + 1 judge). The benchmark isolates MoA’s contribution by comparing to M2 (single-model pipeline).
- **LLM-as-judge / human-anchored evaluation**—we use dual-LLM blinded grading plus a human anchor (Zheng et al., 2023), following emerging best practice for evaluation when full human studies are infeasible.
- **Structured output reliability.** Recent benchmarks evaluate constrained-decoding and schema-conformance for structured generation (Geng et al., 2025); our work complements these by studying *task-structure* decomposition (pipeline design) rather than decoding-time constraints as the lever for reliable structured output.
- **Stepwise / decomposed reasoning.** Chain-of-thought prompting (Wei et al., 2022) elicits reasoning by asking a single model to emit intermediate steps *within one call*. Our

extract $\rightarrow$ analyze $\rightarrow$ judge decomposition is complementary but distinct: it splits the task across *separate* calls (and, in M3, separate models), each producing a structured artifact that the next step consumes. The reliability gains we measure come from this explicit inter-step handoff—which converts silent single-shot failures into recoverable per-stage failures—rather than from intra-prompt chain-of-thought.

Acknowledgments

The experimental design, benchmark implementation, data collection, and analysis were conducted entirely by the author. The prose of this manuscript was prepared with assistance from an AI writing tool for drafting and polishing; all technical content, experimental results, and conclusions were authored, verified, and are the sole responsibility of the author. Any errors are the author’s own.

A Per-case data

Reliability (all 13 cases $\times$ M1/M1R/M2/M3/M4) and quality grading (7 cases $\times$ M2/M3 $\times$ 2 judges) are available as machine-readable traces in `bench-results/<runId>*-trace.json`. The aggregate summary is in `bench-results/<runId>-SUMMARY.md`. A condensed per-case table:

Table 4: Per-case reliability. $\checkmark$ = produced real four-field output; $\times$ = empty / placeholder / refusal. “Real” excludes parse-fallback placeholders.

Case	Corpus (chars)	M1	M1R	M2	M3	M4
grantham-summary	3.3k	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$
g1-mean-reversion	12.3k	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\times$
g2-keystone	10.4k	$\times$	$\times$	$\times$	$\times$	$\checkmark$
g3-ai-bet	9.2k	$\times$	$\checkmark$	$\checkmark$	$\checkmark$	$\times$
g4-reinvest	11.0k	$\checkmark$	$\times$	$\checkmark$	$\times$	$\times$
g5-showdown	10.1k	$\checkmark$	$\checkmark$	$\checkmark$	$\times$	$\times$
g6-derivatives	10.2k	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$
g7-chanos	11.1k	$\times$	$\checkmark$	$\checkmark$	$\checkmark$	$\times$
fbig1-1999	31.9k	$\times$	$\checkmark$	$\checkmark$	$\times$	$\checkmark$
fbig2-2009	31.4k	$\times$	$\times$	$\times$	$\times$	$\times$
fbig3-2026	33.8k	$\times$	$\times$	$\times$	$\times$	$\times$
gsuper-synthesis	53.0k	$\checkmark$	$\checkmark$	$\checkmark$	$\times$	$\times$
multi-g123 ($\times 3$)	31.9k	$\times$	$\times$	$\times$	$\checkmark$	$\times$

B Blinded grading protocol

1. For each of the 7 cases where both M2 and M3 produced real output, extract the four-field verdicts into a case file with A/B labels assigned by a stable seeded shuffle (the mapping is saved to `quality-grading-key.json`, kept secret during grading).
2. Each case file contains: source document, question, Output A, Output B, and a scoring rubric.
3. Feed each case file to two LLM judges (Gemini, KIMI K2.6) independently.
4. To cancel position bias, the two judges receive different A/B orderings per case (the harness varies order by a per-case seed).

5. Collect accuracy / hallucination / coverage / overall scores + a forced preference from each judge.
6. **Human anchor:** a human grades 3 cases (selected to include M2-win and M3-win cases) using the same blinded files, then the human’s preferences are compared to the LLM judges’ for agreement.
7. Unblind: map A/B back to M2/M3 via the key file and aggregate.

*Engineering Report · reproducible from repository commit 9301168. Corpus, harness, and traces are included. The benchmark is designed to be re-run on other domains by swapping **bench-samples/**.*

References

- Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, Carol Chen, Catherine Olsson, Christopher Olah, Danny Hernandez, Dawn Drain, Deep Ganguli, Dustin Li, Eli Tran-Johnson, Ethan Perez, Jamie Kerr, Jared Mueller, Jeffrey Ladish, Joshua Landau, Kamal Ndousse, Kamile Lukosuite, Liane Lovitt, Michael Sellitto, Nelson Elhage, Nicholas Schiefer, Noemi Mercado, Nova DasSarma, Robert Lasenby, Robin Larson, Sam Ringer, Scott Johnston, Shauna Kravec, Sheer El Showk, Stanislav Fort, Tamera Lanham, Timothy Telleen-Lawton, Tom Conerly, Tom Henighan, Tristan Hume, Samuel R. Bowman, Zac Hatfield-Dodds, Ben Mann, Dario Amodei, Nicholas Joseph, Sam McCandlish, Tom Brown, and Jared Kaplan. Constitutional AI: Harmlessness from AI feedback. 2022.
- Saibo Geng, Hudson Cooper, Michał Moskal, Samuel Jenkins, Julian Berman, Nathan Ranchin, Robert West, Eric Horvitz, and Harsha Nori. JSONSchemaBench: A rigorous benchmark of structured outputs for language models. 2025.
- Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegrefe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, Shashank Gupta, Bodhisattwa Prasad Majumder, Katherine Hermann, Sean Welleck, Amir Yazdanbakhsh, and Peter Clark. Self-Refine: Iterative refinement with self-feedback. In *Advances in Neural Information Processing Systems 36 (NeurIPS 2023)*, 2023.
- Noah Shinn, Federico Cassano, Edward Berman, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. In *Advances in Neural Information Processing Systems 36 (NeurIPS 2023)*, 2023.
- Junlin Wang, Jue Wang, Ben Athiwaratkun, Ce Zhang, and James Zou. Mixture-of-Agents enhances large language model capabilities. In *International Conference on Learning Representations (ICLR 2025)*, *Spotlight*, 2025.
- Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc V. Le, and Denny Zhou. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems 35 (NeurIPS 2022)*, 2022.
- Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena. In *Advances in Neural Information Processing Systems 36 (NeurIPS 2023)*, *Datasets and Benchmarks Track*, 2023.