

NATIONAL UNIVERSITY OF SINGAPORE

Special Semester, 2017/2018

TIC2001 Data Structure and Algorithm

Time Allowed: 2 Hours

INSTRUCTION TO CANDIDATES

1. This is NOT an open book assessment. You are allowed to bring one piece of A4 size cheat sheet only.
2. This assessment paper contains **EIGHT (8)** questions and comprises SEVEN (**7**) printed pages.
3. Answer *ALL* questions within the spaces provided in this booklet.
4. You are allowed to use the back of the paper but please remember to state "P.T.O."
5. *Cross out any draft* or otherwise we will mark the poorer answers.
6. Please write your student number below, but NOT your name.

TIDINESS COUNTS!

We will deduct marks if your writing is too messy.

STUDENT NUMBER: _____

(This portion is for examiner's use only)

Question	Max. Marks	Score	Check
Q1	10		
Q2	6		
Q3	4		
Q4	6		
Q5	8		
Q6	8		
Q7	4		
Q8	4		
Total	50		

Question 1 [10 marks]

You are given 10 statements below. State if each statement is True (T) or False (F) by writing your answer in the box provided. A correct answer will give you 1 mark. An empty answer will give you zero, but **wrong answer will result in -1 mark**. (Lowest mark for this question is 0)

T

We can say that the running time for MergeSort is $O(n^3)$
(Notes: L01d Page 12)

F

Quicksort is fast because its worst running time is $O(n \log n)$
(Among all the running time, expected, deterministic, worst is $O(n^2)$)

F

If we have a class template of linked list, it can be used as linked list of integers, doubles, or other classes. This feature of C++ is called polymorphism.
(Polymorphism is about how to find the right virtual functions for sub classes)

F

In C++, a child class can access the private member of its parent class.
(Only can access public or protected)

F

The Inverse Ackermann function $\alpha(n,n)$ is $\Theta(\sqrt{\log n})$.

T

You can find the successor of an item in a heap in $O(n)$ running time.
(You can find the successor of an item in any array in $O(n)$ time)

F

The shortest path between two nodes in a graph is always in the minimal spanning tree of the graph (Mentioned in the lecture)

T

If a graph has negative weighted edges, Dijkstra algorithm may not be able to find the shortest paths.

T

If a graph has n vertices and e edges and every edge does not cross each other, Dijkstra algorithm runs in worst case $O(n \log n)$ time. (A planar graph has $O(n)$ edges)

T

For any insertion of AVL tree, we need at most two rotations to balance the tree.

Question 2 (6 marks)

What is the time complexity of the function **f(n)** in each of the following boxes in terms of n for $n > 0$? Give your answer in the Big O notation. The functions `doOne()` and `do(n)` has time complexities of $O(1)$ and $O(n)$ respectively.

<pre>void f(int n) { do(n); if(n<1) return; for(int i=0; i<2; i++) f(n/2); }</pre>	Time complexity = $O(n \log n)$
<pre>int f(n) { for(int i=1; i<n; i++) for(int j=0; j<i; j+=i) doOne(); }</pre>	Time complexity = $O(n)$
<pre>void f(n) { if(n<1) return; g(n-1); } void g(n) { f(n/2) doOne(); }</pre>	Time complexity of $f(n)$ = $O(\log n)$

Question 3 (4 marks)

Here is the array after one round of pivoting by Quicksort

10	9	32	45	7	61	88	100	97	77
----	---	----	----	---	----	----	-----	----	----


Which number was the pivot for the last round? Answer: ____ **61** ____

Perform one more round of pivoting on the left and the right arrays of the pivot above by using the first element as the pivot of each array. Circle the two pivots.

9	7	10	32	45	61	77	88	97	100
----------	----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	------------


Question 4 (6 marks)

Here is an AVL tree after inserting one new node **before** balancing.



Which node is the newly inserted node? Answer: ____ **71** ____

Perform the necessary rotations according to AVL trees and show the final balanced tree below. Add/remove any bubble(s) if necessary.



Question 5 (8 marks)

You are given an array A of $n = 10$ unsorted integers as below:

5	1	2	9	8	7	4	3	6	10
---	---	---	---	---	---	---	---	---	----

Follow the algorithm in the lecture notes:

```
for (int i=(n-1); i>=0; i--)
    bubbleDown(i, A);
```

Your job is to heapify the unsorted array into a Maxheap. The first round, $i = 9$ is done for you as an example (the input i is the index of the array that starts with 0):

After bubbleDown(9,A):

5	1	2	9	8	7	4	3	6	10
---	---	---	---	---	---	---	---	---	----

After bubbleDown(8,A):

same									
------	--	--	--	--	--	--	--	--	--

After bubbleDown(7,A):

same									
------	--	--	--	--	--	--	--	--	--

After bubbleDown(6,A):

same									
------	--	--	--	--	--	--	--	--	--

After bubbleDown(5,A):

same									
------	--	--	--	--	--	--	--	--	--

After bubbleDown(4,A):

5	1	2	9	10	7	4	3	6	8
---	---	---	---	----	---	---	---	---	---

After bubbleDown(3,A):

5	1	2	9	10	7	4	3	6	8
---	---	---	---	----	---	---	---	---	---

After bubbleDown(2,A):

5	1	7	9	10	2	4	3	6	8
---	---	---	---	----	---	---	---	---	---

After bubbleDown(1,A):

5	10	7	9	8	2	4	3	6	1
---	----	---	---	---	---	---	---	---	---



After bubbleDown(0,A):

10	9	7	6	8	2	4	3	5	1
----	---	---	---	---	---	---	---	---	---

Last line wrong: 6, two lines wrong/min heap: 5

Question 6 (8 marks)

Here is a graph (left) and its adjacency list (right). In the adjacency list, each node will point to another node with the left entry is the vertex index and the right value is the weight of the edge.



Perform Dijkstra Algorithm of this graph to find all the shortest distance from the node 0. Each of the following table is a priority queue sorted by the shortest estimated distance, $\delta(0,v)$.

Node v	$\delta(0,v)$
0	0
1	∞
2	∞
3	∞
4	∞
5	∞
6	∞
7	∞

Extract

→

Node v	$\delta(0,v)$
2	6
1	∞
3	∞
4	∞
5	∞
6	∞
7	∞

Extract

→

Node v	$\delta(0,v)$
5	12
4	14
1	15
3	∞
6	∞
7	∞

Extract

→

Node v	$\delta(0,v)$
4	14
1	15
7	18
3	∞
6	∞

Extract

→

Node v	$\delta(0,v)$
1	15
7	15
3	∞
6	∞

Extract

→

Node v	$\delta(0,v)$
7	15
3	22
6	22

Extract

→

Node v	$\delta(0,v)$
3	22
6	22

Extract

→

Node v	$\delta(0,v)$
6	22

The shortest distance of each node from 0 is:

Node:	1	2	3	4	5	6	7
Distance:	15	6	22	14	12	22	15

Question 7 (4 marks)

It is World Cup time! We have a few hundreds of players in different team. Let's say there is about 600+ different players and we would like to store them into a hash table with size $m = 4096$. In order to avoid confusion if there are two players with the same name from different countries, we will hash the concatenation of a player name with his country. For example, if a player "RONALDO" is from "PORTUGAL", we will use the string "RONALDOPORTUGAL". Then we will convert this string into "binary" performing "mod 2" on the ASCII value of each character. Since the ASCII values of "RONALDOPORTUGAL" are:

82	79	78	65	76	68	79	80	79	82	84	85	71	65	76
		↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓		
0	1	0	1	0	0	1	0	1	0	0	1	1	1	0

After "mod 2" with each number, the binary number will be 010100101001110 = 10574 in decimal. And the final hash value is

$$h(21150) = 10574 \bmod m = 2382.$$

There will be a lot of players with even longer names and country names and they will produce more random and larger numbers. So we expect the hash function will work well.

Is this hashing method good or bad? Give reasons to support your answer.

There will be a lot of collisions and a lot of hash table entries are empty. Because after "mod 4096", it basically just use the least 12 significant digits that are all coming from the countries. E.g almost all players from Switzerland will be mapped into TWO slots in the hash table among all 4096 slots.

Question 8 (4 marks)

You are given a weighted graph $G = (V, E)$, with a source s and a destination d , where each node represents a city and each edge a cost to the travelling from one city to another one. There are altogether n cities. Among all these n cities, there are k cities that are very interesting. Your job is to find the **cheapest path** from s to d according to the cost, such that on the way, you will pass through at least one of the k interesting cities.

Propose a scheme to modify the graph G to solve this problem. (Your proposal cannot exceed 50 words). Your method should base on modifying the graph and run Dijkstra on it. You may draw some pictures to illustrate your idea. Finally, what is the time complexity of your algorithm according to $|V|$ and $|E|$? (This final answer will not gain any marks if your scheme/ideas was not right at all.)

Copy the graph into $G1$ and $G2$. For each interesting city, connect an edge from that city in $G1$ to that of $G2$ with a weight 0 edge. Compute the shortest path from s in $G1$ to d in $G2$.

$O(E \log V)$ by Dijkstra.

- End of Paper -