




IT615 – Data Base Management System

Dr. Manish Khare

Transactions



Outline

- 
-
- Transaction Concept
 - Transaction State
 - Concurrent Executions
 - Serializability
 - Recoverability
 - Implementation of Isolation
 - Transaction Definition in SQL
 - Testing for Serializability.

Transaction Concept

- A **transaction** is a *unit* of program execution that accesses and possibly updates various data items.
- E.g., transaction to transfer \$50 from account A to account B:
 1. **read**(A)
 2. $A := A - 50$
 3. **write**(A)
 4. **read**(B)
 5. $B := B + 50$
 6. **write**(B)
- Two main issues to deal with:
 - Failures of various kinds, such as hardware failures and system crashes
 - Concurrent execution of multiple transactions

Example of Fund Transfer

➤ Transaction to transfer \$50 from account A to account B:

1. **read**(A)
2. $A := A - 50$
3. **write**(A)
4. **read**(B)
5. $B := B + 50$
6. **write**(B)

➤ **Atomicity requirement**

- If the transaction fails after step 3 and before step 6, money will be “lost” leading to an inconsistent database state
 - Failure could be due to software or hardware
- The system should ensure that updates of a partially executed transaction are not reflected in the database

➤ **Durability requirement** — once the user has been notified that the transaction has completed (i.e., the transfer of the \$50 has taken place), the updates to the database by the transaction must persist even if there are software or hardware failures.

Example of Fund Transfer (Cont.)

➤ **Consistency requirement** in above example:

- The sum of A and B is unchanged by the execution of the transaction

➤ In general, consistency requirements include

- Explicitly specified integrity constraints such as primary keys and foreign keys
- Implicit integrity constraints
 - e.g., sum of balances of all accounts, minus sum of loan amounts must equal value of cash-in-hand
- A transaction must see a consistent database.
- During transaction execution the database may be temporarily inconsistent.
- When the transaction completes successfully the database must be consistent
 - Erroneous transaction logic can lead to inconsistency

Example of Fund Transfer (Cont.)

- **Isolation requirement** — if between steps 3 and 6, another transaction T2 is allowed to access the partially updated database, it will see an inconsistent database (the sum $A + B$ will be less than it should be).

T1

1. **read**(A)
2. $A := A - 50$
3. **write**(A)
4. **read**(B)
5. $B := B + 50$
6. **write**(B)

T2

read(A), read(B), print(A+B)

- Isolation can be ensured trivially by running transactions **serially**
 - That is, one after the other.
- However, executing multiple transactions concurrently has significant benefits, as we will see later.

ACID Properties


A **transaction** is a unit of program execution that accesses and possibly updates various data items. To preserve the integrity of data the database system must ensure:

- **Atomicity.** Either all operations of the transaction are properly reflected in the database or none are.
- **Consistency.** Execution of a transaction in isolation preserves the consistency of the database.
- **Isolation.** Although multiple transactions may execute concurrently, each transaction must be unaware of other concurrently executing transactions. Intermediate transaction results must be hidden from other concurrently executed transactions.
 - That is, for every pair of transactions T_i and T_j , it appears to T_i that either T_j finished execution before T_i started, or T_j started execution after T_i finished.
- **Durability.** After a transaction completes successfully, the changes it has made to the database persist, even if there are system failures.

Transaction State

- **Active** – the initial state; the transaction stays in this state while it is executing
- **Partially committed** – after the final statement has been executed.
- **Failed** -- after the discovery that normal execution can no longer proceed.
- **Aborted** – after the transaction has been rolled back and the database restored to its state prior to the start of the transaction. Two options after it has been aborted:
 - Restart the transaction
 - Can be done only if no internal logical error
 - Kill the transaction
- **Committed** – after successful completion.

Transaction State (Cont.)



Concurrent Executions

- Multiple transactions are allowed to run concurrently in the system.

Advantages are:

- **Increased processor and disk utilization**, leading to better transaction *throughput*
 - E.g., one transaction can be using the CPU while another is reading from or writing to the disk
- **Reduced average response time** for transactions: short transactions need not wait behind long ones.

- **Concurrency control schemes** – mechanisms to achieve isolation

- That is, to control the interaction among the concurrent transactions in order to prevent them from destroying the consistency of the database

Schedules

- **Schedule** – a sequences of instructions that specify the chronological order in which instructions of concurrent transactions are executed
 - A schedule for a set of transactions must consist of all instructions of those transactions
 - Must preserve the order in which the instructions appear in each individual transaction.
- A transaction that successfully completes its execution will have a commit instructions as the last statement
 - By default transaction assumed to execute commit instruction as its last step
- A transaction that fails to successfully complete its execution will have an abort instruction as the last statement

Schedule 1

- Let T_1 transfer \$50 from A to B , and T_2 transfer 10% of the balance from A to B .
- A **serial** schedule in which T_1 is followed by T_2 :

T_1	T_2
read (A) $A := A - 50$ write (A) read (B) $B := B + 50$ write (B) commit	read (A) $temp := A * 0.1$ $A := A - temp$ write (A) read (B) $B := B + temp$ write (B) commit

Schedule 2

➤ A serial schedule where T_2 is followed by T_1

T_1	T_2
read (A) $A := A - 50$ write (A) read (B) $B := B + 50$ write (B) commit	read (A) $temp := A * 0.1$ $A := A - temp$ write (A) read (B) $B := B + temp$ write (B) commit

Schedule 3

- Let T_1 and T_2 be the transactions defined previously. The following schedule is not a serial schedule, but it is *equivalent* to Schedule 1

T_1	T_2
read (A) $A := A - 50$ write (A)	read (A) $temp := A * 0.1$ $A := A - temp$ write (A)
read (B) $B := B + 50$ write (B) commit	read (B) $B := B + temp$ write (B) commit

- In Schedules 1, 2 and 3, the sum $A + B$ is preserved.

Schedule 4

- The following concurrent schedule does not preserve the value of $(A + B)$.

T_1	T_2
read (A) $A := A - 50$	read (A) $temp := A * 0.1$ $A := A - temp$ write (A) read (B)
write (A) read (B) $B := B + 50$ write (B) commit	 $B := B + temp$ write (B) commit

Serializability

- **Basic Assumption** – Each transaction preserves database consistency.
- Thus, serial execution of a set of transactions preserves database consistency.
- A (possibly concurrent) schedule is serializable if it is equivalent to a serial schedule. Different forms of schedule equivalence give rise to the notions of:
 1. **Conflict serializability**
 2. **View serializability**

Simplified view of transactions

- We ignore operations other than **read** and **write** instructions
- We assume that transactions may perform arbitrary computations on data in local buffers in between reads and writes.
- Our simplified schedules consist of only **read** and **write** instructions.

Conflicting Instructions

- Instructions l_i and l_j of transactions T_i and T_j respectively, **conflict** if and only if there exists some item Q accessed by both l_i and l_j , and at least one of these instructions wrote Q .
 1. $l_i = \mathbf{read}(Q)$, $l_j = \mathbf{read}(Q)$. l_i and l_j don't conflict.
 2. $l_i = \mathbf{read}(Q)$, $l_j = \mathbf{write}(Q)$. They conflict.
 3. $l_i = \mathbf{write}(Q)$, $l_j = \mathbf{read}(Q)$. They conflict
 4. $l_i = \mathbf{write}(Q)$, $l_j = \mathbf{write}(Q)$. They conflict
- Intuitively, a conflict between l_i and l_j forces a (logical) temporal order between them.
- If l_i and l_j are consecutive in a schedule and they do not conflict, their results would remain the same even if they had been interchanged in the schedule.

Conflict Serializability

- If a schedule S can be transformed into a schedule S' by a series of swaps of non-conflicting instructions, we say that S and S' are **conflict equivalent**.
- We say that a schedule S is **conflict serializable** if it is conflict equivalent to a serial schedule

Conflict Serializability (Cont.)

- Schedule 3 can be transformed into Schedule 6, a serial schedule where T_2 follows T_1 , by series of swaps of non-conflicting instructions. Therefore Schedule 3 is conflict serializable.

T_1	T_2
read (A) write (A)	
	read (A) write (A)
read (B) write (B)	
	read (B) write (B)

Schedule 3

T_1	T_2
read (A) write (A) read (B) write (B)	
	read (A) write (A) read (B) write (B)

Schedule 6

Conflict Serializability (Cont.)

- Example of a schedule that is not conflict serializable:

T_3	T_4
read (Q)	write (Q)
write (Q)	

- We are unable to swap instructions in the above schedule to obtain either the serial schedule $\langle T_3, T_4 \rangle$, or the serial schedule $\langle T_4, T_3 \rangle$.

View Serializability

- Let S and S' be two schedules with the same set of transactions. S and S' are **view equivalent** if the following three conditions are met, for each data item Q ,
 1. If in schedule S , transaction T_i reads the initial value of Q , then in schedule S' also transaction T_i must read the initial value of Q .
 2. If in schedule S transaction T_i executes **read**(Q), and that value was produced by transaction T_j (if any), then in schedule S' also transaction T_i must read the value of Q that was produced by the same **write**(Q) operation of transaction T_j .
 3. The transaction (if any) that performs the final **write**(Q) operation in schedule S must also perform the final **write**(Q) operation in schedule S' .
- As can be seen, view equivalence is also based purely on **reads** and **writes** alone.

View Serializability (Cont.)

- A schedule S is **view serializable** if it is view equivalent to a serial schedule.
- Every conflict serializable schedule is also view serializable.
- Below is a schedule which is view-serializable but *not* conflict serializable.

T_{27}	T_{28}	T_{29}
read (Q)	write (Q)	
write (Q)		write (Q)

- What serial schedule is above equivalent to?
- Every view serializable schedule that is not conflict serializable has **blind writes**.

Other Notions of Serializability


- The schedule below produces same outcome as the serial schedule $\langle T_1, T_5 \rangle$, yet is not conflict equivalent or view equivalent to it.

T_1	T_5
read (A) $A := A - 50$ write (A)	
	read (B) $B := B - 10$ write (B)
read (B) $B := B + 50$ write (B)	
	read (A) $A := A + 10$ write (A)

- Determining such equivalence requires analysis of operations other than read and write.




Testing for Serializability

- Consider some schedule of a set of transactions T_1, T_2, \dots, T_n
- **Precedence graph** — a direct graph where the vertices are the transactions (names).
- We draw an arc from T_i to T_j if the two transaction conflict, and T_i accessed the data item on which the conflict arose earlier.
- We may label the arc by the item that was accessed.
- Example of a precedence graph



Test for Conflict Serializability

- A schedule is conflict serializable if and only if its precedence graph is acyclic.
- Cycle-detection algorithms exist which take order n^2 time, where n is the number of vertices in the graph.
 - (Better algorithms take order $n + e$ where e is the number of edges.)
- If precedence graph is acyclic, the serializability order can be obtained by a *topological sorting* of the graph.
 - This is a linear order consistent with the partial order of the graph.
 - For example, a serializability order for Schedule A would be
$$T_5 \rightarrow T_1 \rightarrow T_3 \rightarrow T_2 \rightarrow T_4$$
 - Are there others?



Test for View Serializability

- The precedence graph test for conflict serializability cannot be used directly to test for view serializability.
 - Extension to test for view serializability has cost exponential in the size of the precedence graph.
- The problem of checking if a schedule is view serializable falls in the class of *NP*-complete problems.
 - Thus, existence of an efficient algorithm is *extremely* unlikely.
- However practical algorithms that just check some **sufficient conditions** for view serializability can still be used.

Recoverable Schedules

Need to address the effect of transaction failures on concurrently running transactions.

- **Recoverable schedule** — if a transaction T_j reads a data item previously written by a transaction T_i , then the commit operation of T_i appears before the commit operation of T_j .
- The following schedule (Schedule 11) is not recoverable

T_8	T_9
read (A)	
write (A)	
	read (A)
	commit
read (B)	

- If T_8 should abort, T_9 would have read (and possibly shown to the user) an inconsistent database state. Hence, database must ensure that schedules are recoverable.

Cascading Rollbacks

- **Cascading rollback** – a single transaction failure leads to a series of transaction rollbacks. Consider the following schedule where none of the transactions has yet committed (so the schedule is recoverable)

T_{10}	T_{11}	T_{12}
read (A) read (B) write (A)	read (A) write (A)	
abort		read (A)

If T_{10} fails, T_{11} and T_{12} must also be rolled back.

- Can lead to the undoing of a significant amount of work

Cascadeless Schedules

- **Cascadeless schedules** — cascading rollbacks cannot occur;
 - For each pair of transactions T_i and T_j such that T_j reads a data item previously written by T_i , the commit operation of T_i appears before the read operation of T_j .
- Every Cascadeless schedule is also recoverable
- It is desirable to restrict the schedules to those that are cascadeless

Concurrency Control

- A database must provide a mechanism that will ensure that all possible schedules are
 - either conflict or view serializable, and
 - are recoverable and preferably cascadeless
- A policy in which only one transaction can execute at a time generates serial schedules, but provides a poor degree of concurrency
 - Are serial schedules recoverable/cascadeless?
- Testing a schedule for serializability *after* it has executed is a little too late!
- **Goal** – to develop concurrency control protocols that will assure serializability.

Concurrency Control (Cont.)

- Schedules must be conflict or view serializable, and recoverable, for the sake of database consistency, and preferably cascadeless.
- A policy in which only one transaction can execute at a time generates serial schedules, but provides a poor degree of concurrency.
- Concurrency-control schemes tradeoff between the amount of concurrency they allow and the amount of overhead that they incur.
- Some schemes allow only conflict-serializable schedules to be generated, while others allow view-serializable schedules that are not conflict-serializable.

Concurrency Control vs. Serializability Tests

- Concurrency-control protocols allow concurrent schedules, but ensure that the schedules are conflict/view serializable, and are recoverable and cascadeless .
- Concurrency control protocols (generally) do not examine the precedence graph as it is being created
 - Instead a protocol imposes a discipline that avoids non-serializable schedules.
 - We study such protocols in Chapter 16.
- Different concurrency control protocols provide different tradeoffs between the amount of concurrency they allow and the amount of overhead that they incur.
- Tests for serializability help us understand why a concurrency control protocol is correct.

Weak Levels of Consistency

- Some applications are willing to live with weak levels of consistency, allowing schedules that are not serializable
 - E.g., a read-only transaction that wants to get an approximate total balance of all accounts
 - E.g., database statistics computed for query optimization can be approximate (why?)
 - Such transactions need not be serializable with respect to other transactions
- Tradeoff accuracy for performance

Levels of Consistency in SQL-92

- **Serializable** — default
- **Repeatable read** — only committed records to be read.
 - Repeated reads of same record must return same value.
 - However, a transaction may not be serializable – it may find some records inserted by a transaction but not find others.
- **Read committed** — only committed records can be read.
 - Successive reads of record may return different (but committed) values.
- **Read uncommitted** — even uncommitted records may be read.

Levels of Consistency

- Lower degrees of consistency useful for gathering approximate information about the database
- Warning: some database systems do not ensure serializable schedules by default
- E.g., Oracle (and PostgreSQL prior to version 9) by default support a level of consistency called snapshot isolation (not part of the SQL standard)

Transaction Definition in SQL

- In SQL, a transaction begins implicitly.
- A transaction in SQL ends by:
 - **Commit work** commits current transaction and begins a new one.
 - **Rollback work** causes current transaction to abort.
- In almost all database systems, by default, every SQL statement also commits implicitly if it executes successfully
 - Implicit commit can be turned off by a database directive
 - E.g., in JDBC -- `connection.setAutoCommit(false);`
- Isolation level can be set at database level
- Isolation level can be changed at start of transaction
 - E.g. In SQL **set transaction isolation level serializable**
 - E.g. in JDBC -- `connection.setTransactionIsolation(`
`Connection.TRANSACTION_SERIALIZABLE)`

Implementation of Isolation Levels

➤ Locking

- Lock on whole database vs lock on items
- How long to hold lock?
- Shared vs exclusive locks

➤ Timestamps

- Transaction timestamp assigned e.g. when a transaction begins
- Data items store two timestamps
 - Read timestamp
 - Write timestamp
- Timestamps are used to detect out of order accesses

➤ Multiple versions of each data item

- Allow transactions to read from a “snapshot” of the database

Transactions as SQL Statements

- E.g., Transaction 1:
select *ID, name* **from** *instructor* **where** *salary* > 90000
- E.g., Transaction 2:
insert into *instructor* **values** ('11111', 'James', 'Marketing', 100000)
- Suppose
 - T1 starts, finds tuples *salary* > 90000 using index and locks them
 - And then T2 executes.
 - Do T1 and T2 conflict? Does tuple level locking detect the conflict?
 - Instance of the **phantom phenomenon**
- Also consider T3 below, with Wu's salary = 90000
update *instructor*
set *salary* = *salary* * 1.1
where *name* = 'Wu'
- Key idea: Detect “**predicate**” conflicts, and use some form of “**predicate locking**”