

IT615 – Data Base Management System

Dr. Manish Khare




SQL



Introduction to SQL

Outline

- 
- Overview of The SQL Query Language
 - SQL Data Definition
 - Basic Query Structure of SQL Queries
 - Additional Basic Operations
 - Set Operations
 - Null Values
 - Aggregate Functions
 - Nested Subqueries
 - Modification of the Database

History

- IBM Sequel language developed as part of System R project at the IBM San Jose Research Laboratory
- Renamed Structured Query Language (SQL)
- ANSI and ISO standard SQL:
 - SQL-86
 - SQL-89
 - SQL-92
 - SQL:1999 (language name became Y2K compliant!)
 - SQL:2003
- Commercial systems offer most, if not all, SQL-92 features, plus varying feature sets from later standards and special proprietary features.
 - Not all examples here may work on your particular system.

SQL Parts

- DML -- provides the ability to query information from the database and to insert tuples into, delete tuples from, and modify tuples in the database.
- integrity – the DDL includes commands for specifying integrity constraints.
- View definition -- The DDL includes commands for defining views.
- Transaction control –includes commands for specifying the beginning and ending of transactions.
- Embedded SQL and dynamic SQL -- define how SQL statements can be embedded within general-purpose programming languages.
- Authorization – includes commands for specifying access rights to relations and views.

Data Definition Language

The SQL data-definition language (DDL) allows the specification of information about relations, including:

- The schema for each relation.
- The type of values associated with each attribute.
- The Integrity constraints
- The set of indices to be maintained for each relation.
- Security and authorization information for each relation.
- The physical storage structure of each relation on disk.

Domain Types in SQL

- **char(*n*)**. Fixed length character string, with user-specified length *n*.
- **varchar(*n*)**. Variable length character strings, with user-specified maximum length *n*.
- **int**. Integer (a finite subset of the integers that is machine-dependent).
- **smallint**. Small integer (a machine-dependent subset of the integer domain type).
- **numeric(*p*,*d*)**. Fixed point number, with user-specified precision of *p* digits, with *d* digits to the right of decimal point. (ex., **numeric**(3,1), allows 44.5 to be stored exactly, but not 444.5 or 0.32)
- **real, double precision**. Floating point and double-precision floating point numbers, with machine-dependent precision.
- **float(*n*)**. Floating point number, with user-specified precision of at least *n* digits.

Create Table Construct

- An SQL relation is defined using the **create table** command:

create table *r*

$(A_1 D_1, A_2 D_2, \dots, A_n D_n,$
 (integrity-constraint₁),
 ...,
 (integrity-constraint_k))

- *r* is the name of the relation
- each A_i is an attribute name in the schema of relation *r*
- D_i is the data type of values in the domain of attribute A_i

- Example:

```
create table instructor (  
    ID           char(5),  
    name        varchar(20),  
    dept_name varchar(20),  
    salary     numeric(8,2))
```


Integrity Constraints in Create Table

- Types of integrity constraints
 - **primary key** (A_1, \dots, A_n)
 - **foreign key** (A_m, \dots, A_n) **references** r
 - **not null**
- SQL prevents any update to the database that violates an integrity constraint.
- Example:


```
create table instructor (  
    ID          char(5),  
    name       varchar(20) not null,  
    dept_name varchar(20),  
    salary     numeric(8,2),  
    primary key (ID),  
    foreign key (dept_name) references department);
```

And a Few More Relation Definitions

- **create table** *student* (
 ID **varchar**(5),
 name **varchar**(20) not null,
 dept_name **varchar**(20),
 tot_cred **numeric**(3,0),
 primary key (*ID*),
 foreign key (*dept_name*) **references** *department*);

- **create table** *takes* (
 ID **varchar**(5),
 course_id **varchar**(8),
 sec_id **varchar**(8),
 semester **varchar**(6),
 year **numeric**(4,0),
 grade **varchar**(2),
 primary key (*ID*, *course_id*, *sec_id*, *semester*, *year*) ,
 foreign key (*ID*) **references** *student*,
 foreign key (*course_id*, *sec_id*, *semester*, *year*) **references** *section*);

And more still



```
➤ create table course (  
    course_id    varchar(8),  
    title        varchar(50),  
    dept_name    varchar(20),  
    credits      numeric(2,0),  
    primary key (course_id),  
    foreign key (dept_name) references department);
```

Updates to tables

➤ Insert

- **insert into** *instructor* **values** ('10211', 'Smith', 'Biology', 66000);

➤ Delete

- Remove all tuples from the *student* relation
 - **delete from** *student*

➤ Drop Table

- **drop table** *r*

➤ Alter

- **alter table** *r* **add** *A D*
 - where *A* is the name of the attribute to be added to relation *r* and *D* is the domain of *A*.
 - All exiting tuples in the relation are assigned *null* as the value for the new attribute.
- **alter table** *r* **drop** *A*
 - where *A* is the name of an attribute of relation *r*
 - Dropping of attributes not supported by many databases.