CUI DEVICES

date 10/28/2019

page 1 of 4

MODEL: PJ-036AH-SMT-TR | **DESCRIPTION:** DC POWER JACK

FEATURES

- 2.0mm center pin
- 5.0 A rating
- horizontal orientation
- surface mount (SMT)





SPECIFICATIONS

parameter	conditions/description	min	typ	max	units
rated input voltage			24		Vdc
rated input current				5	А
contact resistance ¹	between terminal and mating plug between terminal in a closed circuit			50 30	mΩ mΩ
insulation resistance	at 500 Vdc	100			MΩ
voltage withstand	for 1 minute			500	Vac
insertion/withdrawal force		0.3		3	kg
operating temperature		-25		85	°C
life	at a rate of 24 cycles/minute		5,000		cycles
flammability rating	UL94V-0				
RoHS	yes				

Note:


- 1. When measured at a current of less than 100 mA/1 kHz
- $2. \ \ \text{All specifications measured at } 10\sim35^{\circ}\text{C, humidity at } 45\sim85\%, \ under \ standard \ atmospheric \ pressure, \ unless \ otherwise \ noted.$

SOLDERABILITY

parameter	conditions/description	min	typ	max	units
reel storage	at relative humidity <80%			40	°C
reflow soldering ³	see reflow profile	255	260	265	°C
drying conditions ⁴	parts in reel: bake at 40° C $\pm 5^{\circ}$ C for 72 hours parts removed from reel: bake at 40° C $\pm 5^{\circ}$ C for 10 hours				


Note:

- 3. Must reflow solder within 72 hours from opening vacuum packaging at a temperature <30°C & relative humidity <60%.
- 4. When exceeding floor life by >72 hours.





MECHANICAL DRAWING


units: mm[inches] tolerance: $X.X \pm 0.2mm$ $X.XX \pm 0.1mm$ $X.XXX \pm 0.05mm$ PCB: ±0.05 mm



	MATERIAL	PLATING
center pin	copper	nickel
terminal 1	brass	silver
terminal 2	copper alloy	silver
terminal 3	brass	silver
plastic	PA6T or equivalent	








6.8 [0.268] (2 PLCS) 15.20 [0.598] 3 ±0.30 1.70 [0.067] 0.7 [0.028] 2 4.60 [0.181] (2 PLCS)

Recommended PCB Layout Top View



SCHEMATIC Model PJ-036AH-SMT Center Pin Ø2.0 mm

-01


-∘3

MATING PLUG Jack Insertion Depth: 9.15 mm

PACKAGING

units: mm

Reel Size: Ø381 mm Reel QTY: 200 pcs per reel



Additional Resources: Product Page | 3D Model | PCB Footprint

CUI Devices | MODEL: PJ-036AH-SMT-TR | DESCRIPTION: DC POWER JACK date 10/28/2019 | page 4 of 4

REVISION HISTORY

rev.	description	date
1.0	initial release	02/02/2007
1.01	added TR package option	11/07/2012
1.02	applied new spec template, updated center pin material	08/21/2013
1.03	increased voltage rating	04/14/2016
1.04	added storage and drying conditions, and tape and reel packaging details	10/17/2017
1.05	brand update	10/28/2019

The revision history provided is for informational purposes only and is believed to be accurate.

CUI DEVICES

CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

CUI Inc.:

PJ-036AH-SMT-TR