IF2130 – Organisasi dan Arsitektur Komputer

sumber: Greg Kesden, CMU 15-213, 2012

Representasi Informasi

Achmad Imam Kistijantoro (imam@staff.stei.itb.ac.id)
Robithoh Annur (robithoh@staff.stei.itb.ac.id)
Bara Timur (bara@staff.stei.itb.ac.id)
Monterico Adrian (monterico@staff.stei.itb.ac.id)

Representasi Biner



source: Slide CMU 15-213

Encoding Byte Values

- Byte = 8 bit
- 00000000_2 hingga 11111111_2
- Desimal 0 – 255
- Hexadesimal 00 – FF
  - 0xdeadbeef
  - 0xc0ffeeee

Organisasi Memori Berorientasi Byte



- Program mengakses lokasi berbasis virtual memori
- terdiri atas array byte yang sangat besar
- diimplementasikan sebagai hierarki dari beberapa jenis memori
- sistem menyediakan private address space ke proses
  - program dijalankan dan tidak saling mengganggu program lain
- Compiler + Runtime system mengontrol alokasi
  - dimana berbagai objek program harus disimpan
  - semua alokasi berada pada virtual address space yang tunggal

Machine Words

- **Mesin memiliki "Word Size"**
  - Ukuran nominal data bernilai integer
    - Termasuk addresses
  - Umumnya, mesin sekarang menggunakan 32 bits (4 bytes) words
    - Batas alamat 4GB
    - Terlalu kecil untuk aplikasi yang memerlukan memori intensif
  - High-end systems menggunakan 64 bits (8 bytes) words
    - Potential address space ≈ 1.8 X 1019 bytes
    - x86-64 machines support 48-bit addresses: 256 Terabytes
  - Machines support multiple data formats
    - Fractions or multiples of word size
    - Always integral number of bytes

Word Oriented Memory Organization

- **Addresses Specify Byte Locations**
  - Address of first byte in word
  - Addresses of successive words differ by 4 (32-bit) or 8 (64-bit)



Representasi Data

C Data Type	Typical 32-bit	Intel IA32	x86-64
char	1	1	1
short	2	2	2
int	4	4	4
long	4	4	8
long long	8	8	8
float	4	4	4
double	8	8	8
long double	8	10/12	10/16
pointer	4	4	8

Byte Ordering

- **How should bytes within a multi-byte word be ordered in memory?**
- **Conventions**
  - Big Endian: Sun, PPC Mac, Internet
    - Least significant byte has highest address
  - Little Endian: x86
    - Least significant byte has lowest address



Melihat representasi data

- Code untuk mencetak representasi data

```
typedef unsigned char *pointer;

void show_bytes(pointer start, int len){
  int i;
  for (i = 0; i < len; i++)
    printf(”%p\t0x%.2x\n",start+i, start[i]);
  printf("\n");
}
```

Printf directives:

%p: Print pointer

%x: Print Hexadecimal

```
int a = 15213;
printf("int a = 15213;\n");
show_bytes((pointer) &a, sizeof(int));
```

Result (Linux):

```
int a = 15213;
0x11ffffcb8 0x6d
0x11ffffcb9 0x3b
0x11ffffcba 0x00
0x11ffffcbb 0x00
```

Representing Integers

Decimal:	15213
Binary:	0011 1011 0110 1101
Hex:	3 B 6 D

int A = 15213;



long int C = 15213;



int B = -15213;



Two's complement representation

Representing Pointers

```
int B = -15213;
int *P = &B;
```



Different compilers & machines assign different locations to objects

Representing Strings

```
char S[6] = "18243";
```

- Strings in C
  - Represented by array of characters
  - Each character encoded in ASCII format
    - Standard 7-bit encoding of character set
    - Character "0" has code 0x30
      - Digit *i* has code 0x30+*i*
  - String should be null-terminated
    - Final character = 0
- Compatibility
  - Byte ordering not an issue



Boolean Algebra

- Developed by George Boole in 19th Century
  - Algebraic representation of logic
    - Encode "True" as 1 and "False" as 0

And

- **A&B = 1 when both A=1 and B=1**

&	0	1
0	0	0
1	0	1

Or

- **A|B = 1 when either A=1 or B=1**

|	0	1
0	0	1
1	1	1

Not

- **~A = 1 when A=0**

~	
0	1
1	0

Exclusive-Or (Xor)

- **A^B = 1 when either A=1 or B=1, but not both**

^	0	1
0	0	1
1	1	0

General Boolean Algebras

- Operate on Bit Vectors
  - Operations applied bitwise

```
  01101001     01101001     01101001
& 01010101   | 01010101   ^ 01010101   ~ 01010101
  --------     --------     --------     --------
  01000001     01111101     00111100     10101010
```

- All of the Properties of Boolean Algebra Apply

Example: Representing & Manipulating Sets

- Representation
  - Width w bit vector represents subsets of {0, …, w–1}
  - $a_j = 1$ if $j \in A$
    - 01101001 { 0, 3, 5, 6 }
    - *76543210*
    - 01010101 { 0, 2, 4, 6 }
    - *76543210*
- Operations

&	Intersection	01000001	{ 0, 6 }
|	Union	01111101	{ 0, 2, 3, 4, 5, 6 }
^	Symmetric difference	00111100	{ 2, 3, 4, 5 }
~	Complement	10101010	{ 1, 3, 5, 7 }

Bit-Level Operations in C

- Operations &, |, ~, ^ Available in C
  - Apply to any "integral" data type
    - long, int, short, char, unsigned
  - View arguments as bit vectors
  - Arguments applied bit-wise
- Examples (Char data type)
  - ~0x41 = 0xBE
    - $\sim 01000001_2 = 10111110_2$
  - ~0x00 = 0xFF
    - $\sim 00000000_2 = 11111111_2$
  - 0x69 & 0x55 = 0x41
    - $01101001_2 \;\&\; 01010101_2 = 01000001_2$
  - 0x69 | 0x55 = 0x7D
    - $01101001_2 \mid 01010101_2 = 01111101_2$

Contrast: Logic Operations in C

- Contrast to Logical Operators
  - &&, ||, !
    - View 0 as "False"
    - Anything nonzero as "True"
    - Always return 0 or 1
    - Early termination
- Examples (char data type)
  - !0x41 = 0x00
  - !0x00 = 0x01
  - !!0x41 = 0x01
  - 0x69 && 0x55 = 0x01
  - 0x69 || 0x55 = 0x01
  - p && *p (avoids null pointer access)

Contrast: Logic Operations in C

- Contrast to Logical Operators
  - &&, ||, !
    - View 0 as "Fa
    - Anything nonz ”
    - Alway
    - Early
- Example
  - !0x41 =
  - !0x00 =
  - !!0x41 =
  - 0x69 &&
  - 0x69 || 0x55 = 0x01
  - p && *p (avoids null pointer access)

Watch out for && vs. & (and || vs. |)…
one of the more common oopsies in C programming

Shift Operations

- Left Shift: x << y
  - Shift bit-vector x left y positions
    - Throw away extra bits on left
  - Fill with 0's on right
- Right Shift: x >> y
  - Shift bit-vector x right y positions
    - Throw away extra bits on right
  - Logical shift
    - Fill with 0's on left
  - Arithmetic shift
    - Replicate most significant bit on left
- Undefined Behavior
  - Shift amount < 0 or ≥ word size

Argument x	01100010
<< 3	00010000
Log. >> 2	00011000
Arith. >> 2	00011000

Argument x	10100010
<< 3	00010000
Log. >> 2	00101000
Arith. >> 2	11101000

Encoding Integers

Unsigned

$$B2U(X) = \sum_{i=0}^{w-1} x_i \cdot 2^i$$

Two's Complement

$$B2T(X) = -x_{w-1} \cdot 2^{w-1} + \sum_{i=0}^{w-2} x_i \cdot 2^i$$




```
short int x =  15213;
short int y = -15213;
```

- C `short` 2 bytes long

	Decimal	Hex	Binary
x	15213	**3B 6D**	**00111011 01101101**
y	-15213	**C4 93**	**11000100 10010011**

- Sign Bit
  - For 2's complement, most significant bit indicates sign
    - 0 for nonnegative
    - 1 for negative

Two-complement Encoding Example (Cont.)

```
x =      15213: 00111011 01101101
y =     -15213: 11000100 10010011
```

Weight	15213		-15213	
1	1	1	1	1
2	0	0	1	2
4	1	4	0	0
8	1	8	0	0
16	0	0	1	16
32	1	32	0	0
64	1	64	0	0
128	0	0	1	128
256	1	256	0	0
512	1	512	0	0
1024	0	0	1	1024
2048	1	2048	0	0
4096	1	4096	0	0
8192	1	8192	0	0
16384	0	0	1	16384
-32768	0	0	1	-32768
Sum		**15213**		**-15213**

Numeric Ranges

- Unsigned Values
  - *UMin* = 0
    000…0
  - *UMax* = $2^w - 1$
    111…1
- Two's Complement Values
  - *TMin* = -2^{w-1}
    100…0
  - *TMax* = $2^{w-1} - 1$
    011…1
- Other Values
  - Minus 1
    111…1

Values for $W = 16$

	Decimal	Hex	Binary
UMax	**65535**	**FF FF**	**11111111 11111111**
TMax	**32767**	**7F FF**	**01111111 11111111**
TMin	**-32768**	**80 00**	**10000000 00000000**
-1	**-1**	**FF FF**	**11111111 11111111**
0	**0**	**00 00**	**00000000 00000000**

Values for Different Word Sizes

	W			
	8	**16**	**32**	**64**
UMax	255	65,535	4,294,967,295	18,446,744,073,709,551,615
TMax	127	32,767	2,147,483,647	9,223,372,036,854,775,807
TMin	-128	-32,768	-2,147,483,648	-9,223,372,036,854,775,808

- Observations
  - $|TMin| = TMax + 1$
    - Asymmetric range
  - $UMax = 2 * TMax + 1$

- **C Programming**
  - #include <limits.h>
  - Declares constants, e.g.,
    - ULONG_MAX
    - LONG_MAX
    - LONG_MIN
  - Values platform specific

Unsigned & Signed Numeric Values

X	B2U(*X*)	B2T(*X*)
0000	0	0
0001	1	1
0010	2	2
0011	3	3
0100	4	4
0101	5	5
0110	6	6
0111	7	7
1000	8	–8
1001	9	–7
1010	10	–6
1011	11	–5
1100	12	–4
1101	13	–3
1110	14	–2
1111	15	–1

- Equivalence
  - Same encodings for nonnegative values
- Uniqueness
  - Every bit pattern represents unique integer value
  - Each representable integer has unique bit encoding
- $\Rightarrow$ Can Invert Mappings
  - $U2B(x) = B2U^{-1}(x)$
    - Bit pattern for unsigned integer
  - $T2B(x) = B2T^{-1}(x)$
    - Bit pattern for two's comp integer

Today: Bits, Bytes, and Integers

- Representing information as bits
- Bit-level manipulations
- Integers
  - Representation: unsigned and signed
  - **Conversion, casting**
  - Expanding, truncating
  - Addition, negation, multiplication, shifting
  - Summary
- Representations in memory, pointers, strings

Mapping Between Signed & Unsigned



- Mappings between unsigned and two's complement numbers: keep bit representations and reinterpret

Mapping Signed ↔ Unsigned

Bits	Signed	Unsigned
0000	0	0
0001	1	1
0010	2	2
0011	3	3
0100	4	4
0101	5	5
0110	6	6
0111	7	7
1000	-8	8
1001	-7	9
1010	-6	10
1011	-5	11
1100	-4	12
1101	-3	13
1110	-2	14
1111	-1	15



Mapping Signed ↔ Unsigned

Bits	Signed		Unsigned
0000	0		0
0001	1		1
0010	2		2
0011	3	=	3
0100	4		4
0101	5		5
0110	6		6
0111	7		7
1000	-8		8
1001	-7		9
1010	-6		10
1011	-5	+/- 16	11
1100	-4		12
1101	-3		13
1110	-2		14
1111	-1		15

Relation between Signed & Unsigned

Two's Complement

Unsigned



Maintain Same Bit Pattern



Large negative weight
becomes
Large positive weight

Conversion Visualized

- 2's Comp. → Unsigned
  - Ordering Inversion
  - Negative → Big Positive



Signed vs. Unsigned in C

- Constants
  - By default are considered to be signed integers
  - Unsigned if have "U" as suffix

    ```
    0U, 4294967259U
    ```
- Casting
  - Explicit casting between signed & unsigned same as U2T and T2U

    ```
    int tx, ty;
    unsigned ux, uy;
    tx = (int) ux;
    uy = (unsigned) ty;
    ```

  - Implicit casting also occurs via assignments and procedure calls

    ```
    tx = ux;
    uy = ty;
    ```

Casting Surprises

- Expression Evaluation
  - If there is a mix of unsigned and signed in single expression, ***signed values implicitly cast to unsigned***
  - Including comparison operations <, >, ==, <=, >=
  - Examples for *W* = 32: **TMIN = -2,147,483,648 , TMAX = 2,147,483,647**

Constant$_1$	Constant$_2$	Relation	Evaluation
0	0U	==	unsigned
-1	0	<	signed
-1	0U	>	unsigned
2147483647	(-2147483647)-1	>	signed
2147483647U	-2147483647-1	<	unsigned
-1	-2	>	signed
(unsigned)-1	-2	>	unsigned
2147483647	2147483648U	<	unsigned
2147483647	(int) 2147483648U	>	signed

Summary
Casting Signed ↔ Unsigned: Basic Rules

- Bit pattern is maintained
- But reinterpreted
- Can have unexpected effects: adding or subtracting 2^w

- Expression containing signed and unsigned int
  - `int` **is cast to** `unsigned`**!!**

Today: Bits, Bytes, and Integers

- Representing information as bits
- Bit-level manipulations
- Integers
  - Representation: unsigned and signed
  - Conversion, casting
  - **Expanding, truncating**
  - Addition, negation, multiplication, shifting
  - Summary
- Representations in memory, pointers, strings

Sign Extension

- Task:
  - Given *w*-bit signed integer *x*
  - Convert it to *w*+*k*-bit integer with same value
- Rule:
  - Make *k* copies of sign bit:
  - $X' = \underbrace{x_{w-1}, \ldots, x_{w-1}}, x_{w-1}, x_{w-2}, \ldots, x_0$



Sign Extension Example

```
short int x =  15213;
int       ix = (int) x;
short int y = -15213;
int       iy = (int) y;
```

	Decimal	Hex	Binary
x	15213	3B 6D	00111011 01101101
ix	15213	00 00 3B 6D	00000000 00000000 00111011 01101101
y	-15213	C4 93	11000100 10010011
iy	-15213	FF FF C4 93	11111111 11111111 11000100 10010011

- Converting from smaller to larger integer data type
- C automatically performs sign extension

Summary: Expanding, Truncating: Basic Rules

- Expanding (e.g., short int to int)
  - Unsigned: zeros added
  - Signed: sign extension
  - Both yield expected result
- Truncating (e.g., unsigned to unsigned short)
  - Unsigned/signed: bits are truncated
  - Result reinterpreted
  - Unsigned: mod operation
  - Signed: similar to mod
  - For small numbers yields expected behaviour

Today: Bits, Bytes, and Integers

- Representing information as bits
- Bit-level manipulations
- Integers
  - Representation: unsigned and signed
  - Conversion, casting
  - Expanding, truncating
  - **Addition, negation, multiplication, shifting**
- Representations in memory, pointers, strings
- Summary

Unsigned Addition

Operands: *w* bits

True Sum: *w*+1 bits

Discard Carry: *w* bits



- Standard Addition Function
  - Ignores carry output
- Implements Modular Arithmetic

  $s = \mathrm{UAdd}_w(u , v) = u + v \mod 2^w$

Visualizing (Mathematical) Integer Addition

- Integer Addition
  - 4-bit integers *u*, *v*
  - Compute true sum $\text{Add}_4(u , v)$
  - Values increase linearly with *u* and *v*
  - Forms planar surface

$\text{Add}_4(u , v)$



Visualizing Unsigned Addition

- Wraps Around
  - If true sum ≥ 2^w
  - At most once





Two's Complement Addition



- TAdd and UAdd have Identical Bit-Level Behavior
  - Signed vs. unsigned addition in C:

```
int s, t, u, v;
s = (int) ((unsigned) u + (unsigned) v);
t = u + v
```

  - Will give `s == t`

TAdd Overflow

- Functionality
  - True sum requires $w+1$ bits
  - Drop off MSB
  - Treat remaining bits as 2's comp. integer



Visualizing 2's Complement Addition

- Values
  - 4-bit two's comp.
  - Range from -8 to +7
- Wraps Around
  - If sum $\geq 2^{w-1}$
    - Becomes negative
    - At most once
  - If sum $< -2^{w-1}$
    - Becomes positive
    - At most once



Multiplication

- Goal: Computing Product of *w*-bit numbers *x*, *y*
  - Either signed or unsigned
- But, exact results can be bigger than *w* bits
  - Unsigned: up to 2*w* bits
    - Result range: $0 \le x * y \le (2^w - 1)^2 = 2^{2w} - 2^{w+1} + 1$
  - Two's complement min (negative): Up to 2*w*-1 bits
    - Result range: $x * y \ge (-2^{w-1})*(2^{w-1}-1) = -2^{2w-2} + 2^{w-1}$
  - Two's complement max (positive): Up to 2*w* bits, but only for $(TMin_w)^2$
    - Result range: $x * y \le (-2^{w-1})^2 = 2^{2w-2}$
- So, maintaining exact results…
  - would need to keep expanding word size with each product computed
  - is done in software, if needed
    - e.g., by "arbitrary precision" arithmetic packages

Unsigned Multiplication in C



- Standard Multiplication Function
  - Ignores high order w bits
- Implements Modular Arithmetic

  $\text{UMult}_w(u , v) = u \cdot v \mod 2^w$

Signed Multiplication in C



- Standard Multiplication Function
  - Ignores high order *w* bits
  - Some of which are different for signed vs. unsigned multiplication
  - Lower bits are the same

Power-of-2 Multiply with Shift

- Operation
  - `u << k` gives `u * 2^k`
  - Both signed and unsigned



- Examples
  - `u << 3 == u * 8`
  - `u << 5 - u << 3 == u * 24`
  - Most machines shift and add faster than multiply
    - Compiler generates this code automatically

Unsigned Power-of-2 Divide with Shift

- Quotient of Unsigned by Power of 2
  - `u >> k` gives $\lfloor$ `u / 2`^{k} $\rfloor$
  - Uses logical shift



	Division	Computed	Hex	Binary
`x`	15213	15213	`3B 6D`	`00111011 01101101`
`x >> 1`	7606.5	7606	`1D B6`	`00011101 10110110`
`x >> 4`	950.8125	950	`03 B6`	`00000011 10110110`
`x >> 8`	59.4257813	59	`00 3B`	`00000000 00111011`

Signed Power-of-2 Divide with Shift

- Quotient of Signed by Power of 2
  - `x >> k` gives $\lfloor x / 2^k \rfloor$
  - Uses arithmetic shift
  - Rounds wrong direction when `u < 0`



	Division	Computed	Hex	Binary
y	-15213	-15213	C4 93	11000100 10010011
y >> 1	-7606.5	-7607	E2 49	11100010 01001001
y >> 4	-950.8125	-951	FC 49	11111100 01001001
y >> 8	-59.4257813	-60	FF C4	11111111 11000100

Correct Power-of-2 Divide

- Quotient of Negative Number by Power of 2
  - Want $\lceil$ **x / 2^k** $\rceil$ (Round Toward 0)
  - Compute as $\lfloor$ **(x+2^k−1) / 2^k** $\rfloor$
    - In C: **(x + (1<<k)-1) >> k**
    - Biases dividend toward 0

Case 1: No rounding



Biasing has no effect

Correct Power-of-2 Divide (Cont.)

Case 2: Rounding



Biasing adds 1 to final result

Today: Bits, Bytes, and Integers

- Representing information as bits
- Bit-level manipulations
- Integers
  - Representation: unsigned and signed
  - Conversion, casting
  - Expanding, truncating
  - Addition, negation, multiplication, shifting
  - **Summary**
- Representations in memory, pointers, strings

Arithmetic: Basic Rules

- Addition:
  - Unsigned/signed: Normal addition followed by truncate, same operation on bit level
  - Unsigned: addition mod 2^w
    - Mathematical addition + possible subtraction of 2^w
  - Signed: modified addition mod 2^w (result in proper range)
    - Mathematical addition + possible addition or subtraction of 2^w

- Multiplication:
  - Unsigned/signed: Normal multiplication followed by truncate, same operation on bit level
  - Unsigned: multiplication mod 2^w
  - Signed: modified multiplication mod 2^w (result in proper range)

Why Should I Use Unsigned?

- *Don't* Use Just Because Number Nonnegative
  - Easy to make mistakes

```
unsigned i;
for (i = cnt-2; i >= 0; i--)
  a[i] += a[i+1];
```

  - Can be very subtle

```
#define DELTA sizeof(int)
int i;
for (i = CNT; i-DELTA >= 0; i-= DELTA)
  . . .
```

- *Do* Use When Performing Modular Arithmetic
  - Multiprecision arithmetic
- *Do* Use When Using Bits to Represent Sets
  - Logical right shift, no sign extension