IF2130 – Organisasi dan Arsitektur Komputer

sumber: Greg Kesden, CMU 15-213, 2012

Representasi Informasi: Floating Point

Today: Floating Point

- Background: Fractional binary numbers
- IEEE floating point standard: Definition
- Example and properties
- Rounding, addition, multiplication
- Floating point in C
- Summary

Fractional binary numbers

- What is 1011.101_2?

Fractional Binary Numbers



- Representation
  - Bits to right of "binary point" represent fractional powers of 2
  - Represents rational number: $$\sum_{k=-j}^{i} b_k \times 2^k$$

Fractional Binary Numbers: Examples

- **Value** **Representation**

Value	Representation
5 3/4	101.11_2
2 7/8	10.111_2
1 7/16	1.0111_2

- **Observations**
  - Divide by 2 by shifting right (unsigned)
  - Multiply by 2 by shifting left
  - Numbers of form $0.111111\ldots_2$ are just below 1.0
    - $1/2 + 1/4 + 1/8 + \ldots + 1/2^i + \ldots \rightarrow 1.0$
    - Use notation $1.0 - \varepsilon$

Representable Numbers

- Limitation #1
  - Can only exactly represent numbers of the form $x/2^k$
    - Other rational numbers have repeating bit representations
  - Value Representation
    - 1/3 $0.0101010101[01]\ldots_2$
    - 1/5 $0.001100110011[0011]\ldots_2$
    - 1/10 $0.0001100110011[0011]\ldots_2$

- Limitation #2
  - Just one setting of decimal point within the *w* bits
    - Limited range of numbers (very small values? very large?)

Today: Floating Point

- Background: Fractional binary numbers
- IEEE floating point standard: Definition
- Example and properties
- Rounding, addition, multiplication
- Floating point in C
- Summary

IEEE Floating Point

- IEEE Standard 754
  - Established in 1985 as uniform standard for floating point arithmetic
    - Before that, many idiosyncratic formats
  - Supported by all major CPUs

- Driven by numerical concerns
  - Nice standards for rounding, overflow, underflow
  - Hard to make fast in hardware
    - Numerical analysts predominated over hardware designers in defining standard

Floating Point Representation

- Numerical Form:

$$(-1)^s \, M \; 2^E$$

  - **Sign bit *s*** determines whether number is negative or positive
  - **Significand *M*** normally a fractional value in range [1.0,2.0).
  - **Exponent *E*** weights value by power of two

- Encoding
  - MSB s is sign bit ***s***
  - exp field encodes ***E*** (but is not equal to E)
  - frac field encodes ***M*** (but is not equal to M)



Precision options

- Single precision: 32 bits

s	exp	frac
1	8-bits	23-bits

- Double precision: 64 bits

s	exp	frac
1	11-bits	52-bits

- Extended precision: 80 bits (Intel only)

s	exp	frac
1	15-bits	63 or 64-bits

"Normalized" Values

- When: exp ≠ 000…0 and exp ≠ 111…1
- Exponent coded as a ***biased*** value: ***E* = *Exp* – *Bias***
  - *Exp*: unsigned value exp
  - *Bias* = $2^{k-1} - 1$, where *k* is number of exponent bits
    - Single precision: 127 (Exp: 1…254, E: -126…127)
    - Double precision: 1023 (Exp: 1…2046, E: -1022…1023)
- Significand coded with implied leading 1: ***M*** = $1.xxx...x_2$
  - xxx…x: bits of frac
  - Minimum when frac=000…0 (*M* = 1.0)
  - Maximum when frac=111…1 (*M* = 2.0 – ε)
  - Get extra leading bit for "free"

Normalized Encoding Example

- Value: `Float F = 15213.0;`
  - $15213_{10} = 11101101101101_2$
    $= 1.1101101101101_2 \times 2^{13}$

- Significand
  $M = 1.\underline{1101101101101}_2$
  `frac` $= \underline{1101101101101}0000000000_2$

- Exponent
  $E = 13$
  $Bias = 127$
  $Exp = 140 = 10001100_2$

- Result:

0	10001100	11011011011010000000000
s	**exp**	**frac**

Denormalized Values

- Condition: exp = 000…0

- Exponent value: $E = -Bias + 1$ (instead of $E = 0 - Bias$)
- Significand coded with implied leading 0: $M = 0.xxx\ldots x_2$
  - `xxx…x`: bits of `frac`
- Cases
  - `exp` = 000…0, `frac` = 000…0
    - Represents zero value
    - Note distinct values: +0 and –0 (why?)
  - `exp` = 000…0, `frac` ≠ 000…0
    - Numbers closest to 0.0
    - Equispaced

Special Values

- Condition: **`exp`** = 111…1

- Case: **`exp`** = 111…1, **`frac`** = 000…0
  - Represents value ∞ (infinity)
  - Operation that overflows
  - Both positive and negative
  - E.g., $1.0/0.0 = -1.0/-0.0 = +\infty$, $1.0/-0.0 = -\infty$

- Case: **`exp`** = 111…1, **`frac`** $\neq$ 000…0
  - Not-a-Number (NaN)
  - Represents case when no numeric value can be determined
  - E.g., sqrt(–1), $\infty - \infty$, $\infty \times 0$

Visualization: Floating Point Encodings



Today: Floating Point

- Background: Fractional binary numbers
- IEEE floating point standard: Definition
- Example and properties
- Rounding, addition, multiplication
- Floating point in C
- Summary

Tiny Floating Point Example

s	exp	frac
1	4-bits	3-bits

- 8-bit Floating Point Representation
  - the sign bit is in the most significant bit
  - the next four bits are the exponent, with a bias of 7
  - the last three bits are the **`frac`**

- Same general form as IEEE Format
  - normalized, denormalized
  - representation of 0, NaN, infinity

Dynamic Range (Positive Only)

	s	exp	frac	E	Value	
	0	0000	000	-6	0	
	0	0000	001	-6	1/8*1/64 = 1/512	closest to zero
Denormalized numbers	0	0000	010	-6	2/8*1/64 = 2/512	
	…					
	0	0000	110	-6	6/8*1/64 = 6/512	
	0	0000	111	-6	7/8*1/64 = 7/512	largest denorm
	0	0001	000	-6	8/8*1/64 = 8/512	smallest norm
	0	0001	001	-6	9/8*1/64 = 9/512	
	…					
	0	0110	110	-1	14/8*1/2 = 14/16	
	0	0110	111	-1	15/8*1/2 = 15/16	closest to 1 below
Normalized numbers	0	0111	000	0	8/8*1 = 1	
	0	0111	001	0	9/8*1 = 9/8	closest to 1 above
	0	0111	010	0	10/8*1 = 10/8	
	…					
	0	1110	110	7	14/8*128 = 224	
	0	1110	111	7	15/8*128 = 240	largest norm
	0	1111	000	n/a	inf	

Distribution of Values

- 6-bit IEEE-like format
  - e = 3 exponent bits
  - f = 2 fraction bits
  - Bias is $2^{3-1}-1 = 3$



- Notice how the distribution gets denser toward zero.



Distribution of Values (close-up view)

- 6-bit IEEE-like format
  - e = 3 exponent bits
  - f = 2 fraction bits
  - Bias is 3





Special Properties of the IEEE Encoding

- FP Zero Same as Integer Zero
  - All bits = 0
- Can (Almost) Use Unsigned Integer Comparison
  - Must first compare sign bits
  - Must consider −0 = 0
  - NaNs problematic
    - Will be greater than any other values
    - What should comparison yield?
  - Otherwise OK
    - Denorm vs. normalized
    - Normalized vs. infinity

Today: Floating Point

- Background: Fractional binary numbers
- IEEE floating point standard: Definition
- Example and properties
- Rounding, addition, multiplication
- Floating point in C
- Summary

Floating Point Operations: Basic Idea

- $\mathbf{x} +_f \mathbf{y} = \mathrm{Round}(\mathbf{x} + \mathbf{y})$

- $\mathbf{x} \times_f \mathbf{y} = \mathrm{Round}(\mathbf{x} \times \mathbf{y})$

- Basic idea
  - First compute exact result
  - Make it fit into desired precision
    - Possibly overflow if exponent too large
    - Possibly round to fit into `frac`

Rounding

- Rounding Modes (illustrate with $ rounding)

	\$1.40	\$1.60	\$1.50	\$2.50	–\$1.50
Towards zero	\$1	\$1	\$1	\$2	–\$1
Round down ($-\infty$)	\$1	\$1	\$1	\$2	–\$2
Round up ($+\infty$)	\$2	\$2	\$2	\$3	–\$1
Nearest Even(default)	\$1	\$2	\$2	\$2	–\$2

Closer Look at Round-To-Even

- Default Rounding Mode
  - Hard to get any other kind without dropping into assembly
  - All others are statistically biased
    - Sum of set of positive numbers will consistently be over- or under-estimated
- Applying to Other Decimal Places / Bit Positions
  - When exactly halfway between two possible values
    - Round so that least significant digit is even
  - E.g., round to nearest hundredth

1.2349999	1.23	(Less than half way)
1.2350001	1.24	(Greater than half way)
1.2350000	1.24	(Half way—round up)
1.2450000	1.24	(Half way—round down)

Rounding Binary Numbers

- Binary Fractional Numbers
  - "Even" when least significant bit is 0
  - "Half way" when bits to right of rounding position = $100\ldots_2$
- Examples
  - Round to nearest 1/4 (2 bits right of binary point)

Value	Binary	Rounded	Action	Rounded Value
2 3/32	10.00011_2	10.00_2	(<1/2—down)	2
2 3/16	10.00110_2	10.01_2	(>1/2—up)	2 1/4
2 7/8	10.11100_2	11.00_2	(1/2—up)	3
2 5/8	10.10100_2	10.10_2	(1/2—down)	2 1/2

FP Multiplication

- $(-1)^{s1}\ M1\ \ 2^{E1}\quad \times\quad (-1)^{s2}\ M2\ \ 2^{E2}$
- Exact Result: $(-1)^{s}\ M\ \ 2^{E}$
  - Sign s: $s1$ ^ $s2$
  - Significand M: $M1 \times M2$
  - Exponent E: $E1 + E2$

- Fixing
  - If $M \geq 2$, shift M right, increment E
  - If E out of range, overflow
  - Round M to fit `frac` precision

- Implementation
  - Biggest chore is multiplying significands

Floating Point Addition

- $(-1)^{s1}\ M1\ \ 2^{E1}\ \ +\ \ (-1)^{s2}\ M2\ \ 2^{E2}$
  - Assume $E1 > E2$
- Exact Result: $(-1)^{s}\ M\ \ 2^{E}$
  - Sign s, significand M:
    - Result of signed align & add
  - Exponent E: $E1$



- Fixing
  - If $M \geq 2$, shift M right, increment E
  - if $M < 1$, shift M left k positions, decrement E by k
  - Overflow if E out of range
  - Round M to fit `frac` precision

Today: Floating Point

- Background: Fractional binary numbers
- IEEE floating point standard: Definition
- Example and properties
- Rounding, addition, multiplication
- Floating point in C
- Summary

Floating Point in C

- C Guarantees Two Levels
  - **`float`** single precision
  - **`double`** double precision

- Conversions/Casting
  - Casting between **`int`**, **`float`**, and **`double`** changes bit representation
  - **`double`/`float`** → **`int`**
    - Truncates fractional part
    - Like rounding toward zero
    - Not defined when out of range or NaN: Generally sets to TMin
  - **`int`** → **`double`**
    - Exact conversion, as long as **`int`** has ≤ 53 bit word size
  - **`int`** → **`float`**
    - Will round according to rounding mode

Summary

- IEEE Floating Point has clear mathematical properties
- Represents numbers of form M x 2^E
- One can reason about operations independent of implementation
  - As if computed with perfect precision and then rounded
- Not the same as real arithmetic
  - Violates associativity/distributivity
  - Makes life difficult for compilers & serious numerical applications programmers

Floating Point Puzzles

- For each of the following C expressions, either:
  - Argue that it is true for all argument values
  - Explain why not true

```
int x = …;
float f = …;
double d = …;
```

Assume neither **d** nor **f** is NaN

- x == (int)(float) x
- x == (int)(double) x
- f == (float)(double) f
- d == (float) d
- f == -(-f);
- 2/3 == 2/3.0
- d < 0.0 ⇒ ((d*2) < 0.0)
- d > f ⇒ -f > -d
- d * d >= 0.0
- (d+f)-d == f

Interesting Numbers `{single,double}`

Description	*exp*	*frac*	*Numeric Value*
Zero	00…00	00…00	0.0
Smallest Pos. Denorm.	00…00	00…01	$2^{-\{23,52\}} \times 2^{-\{126,1022\}}$
Largest Denormalized	00…00	11…11	$(1.0 - \varepsilon) \times 2^{-\{126,1022\}}$
Smallest Pos. Normalized	00…01	00…00	$1.0 \times 2^{-\{126,1022\}}$
One	01…11	00…00	1.0
Largest Normalized	11…10	11…11	$(2.0 - \varepsilon) \times 2^{\{127,1023\}}$

- Smallest Pos. Denorm.
  - Single ≈ 1.4×10^{-45}
  - Double ≈ 4.9×10^{-324}
- Largest Denormalized
  - Single ≈ 1.18×10^{-38}
  - Double ≈ 2.2×10^{-308}
- Smallest Pos. Normalized
  - Just larger than largest denormalized
- Largest Normalized
  - Single ≈ 3.4×10^{38}
  - Double ≈ 1.8×10^{308}

Creating Floating Point Number

- Steps
  - Normalize to have leading 1
  - Round to fit within fraction
  - Postnormalize to deal with effects of rounding

s	exp	frac
1	4-bits	3-bits

- Case Study
  - Convert 8-bit unsigned numbers to tiny floating point format

Example Numbers

128	10000000
15	00001111
17	00010001
19	00010011
33	00100001
35	00100011
138	10001010
63	00111111

Rounding

1.BBGRXXX

Guard bit: LSB of result

Sticky bit: OR of remaining bits

Round bit: 1st bit removed

- Round up conditions
  - Round = 1, Sticky = 1 → > 0.5
  - Guard = 1, Round = 1, Sticky = 0 → Round to even

Value	***Fraction***	***GRS***	***Incr?***	***Rounded***
128	1.0000000	000	N	1.000
15	1.1110000	100	N	1.111
17	1.0001000	010	N	1.000
19	1.0011000	110	Y	1.010
138	1.0001010	011	Y	1.001
63	1.1111100	111	Y	10.000

More Slides

Today: Floating Point

- Background: Fractional binary numbers
- IEEE floating point standard: Definition
- Example and properties
- Rounding, addition, multiplication
- Floating point in C
- Summary

Mathematical Properties of FP Add

- Compare to those of Abelian Group
  - Closed under addition?
    - But may generate infinity or NaN
  - Commutative?
  - Associative?
    - Overflow and inexactness of rounding
  - 0 is additive identity?
  - Every element has additive inverse
    - Except for infinities & NaNs
- Monotonicity
  - $a \geq b \Rightarrow a+c \geq b+c$?
    - Except for infinities & NaNs

Mathematical Properties of FP Mult

- Compare to Commutative Ring
  - Closed under multiplication?
    - But may generate infinity or NaN
  - Multiplication Commutative?
  - Multiplication is Associative?
    - Possibility of overflow, inexactness of rounding
  - 1 is multiplicative identity?
  - Multiplication distributes over addition?
    - Possibility of overflow, inexactness of rounding

- Monotonicity
  - $a \geq b \;\; \& \; c \geq 0 \;\; \Rightarrow a * c \geq b * c$?
    - Except for infinities & NaNs

Normalize

s	exp	frac
1	4-bits	3-bits

- **Requirement**
  - Set binary point so that numbers of form 1.xxxxx
  - Adjust all to have leading one
    - Decrement exponent as shift left

Value	*Binary*	*Fraction*	*Exponent*
128	10000000	1.0000000	7
15	00001101	1.1010000	3
17	00010001	1.0001000	4
19	00010011	1.0011000	4
138	10001010	1.0001010	7
63	00111111	1.1111100	5

Postnormalize

- Issue
  - Rounding may have caused overflow
  - Handle by shifting right once & incrementing exponent

Value	*Rounded*	*Exp*	*Adjusted*	*Result*
128	1.000	7		128
15	1.101	3		15
17	1.000	4		16
19	1.010	4		20
138	1.001	7		134
63	10.000	5	1.000/6	64