



Pilares			
Nome	Seção (cm)	Elevação (cm)	Nível (cm)
P7	15x25	0	455
P8	15x25	0	455
P9	15x25	0	455
P10	15x25	0	455

Legenda dos pilares	
	Pilar que morre

Legenda das vigas e paredes	
	Viga

Technical drawing of a roof structure showing dimensions and components:

- Top edge: 2 N3 ø8.0 C=359
- Bottom edge: 2 N2 ø8.0 C=337
- Horizontal dimensions:
 - Top: 337 (between corner markers), 455 (from left edge to start of 337 segment)
 - Bottom: 315.1 (between vertical lines), 46 N1 c/7 (total width)
- Vertical dimensions: 15 (from top/bottom edges to horizontal lines), 315.1 (between horizontal lines), 15 x 20 (height of central section)
- Labels: A (corner markers), P7 (left vertical support), A (right vertical support)

SEÇÃO A-A
ESC 1:25

Technical drawing of a beam cross-section. The drawing shows a rectangular beam with a width of 43 N1 c/7 and a height of 15 x 20. The top reinforcement consists of 2 N3 ø8.0 C=359, and the bottom reinforcement consists of 2 N2 ø8.0 C=337. The drawing includes dimensions for the beam width (43 N1 c/7), height (15 x 20), and reinforcement spacing (C=359, C=337). Section lines A-A are indicated on the top and bottom reinforcement.

SEÇÃO A-A
ESC 1:25

2 N5 $\varnothing$ 8.0 C=233

12

212

455

A

P9

A

P7

15

190

25

15 x 20

205

30 N1 c/7

212

10

2 N4 $\varnothing$ 8.0 C=220

ESC 1:20

12

7

30 N1 $\varnothing$ 5.0 C=...

SEÇÃO A-A
ESC 1:25

Technical drawing of a reinforced concrete slab (P10) showing dimensions and reinforcement details. The drawing includes a plan view and a cross-section view.

Plan View Dimensions:

- Overall width: 212
- Overall length: 205
- Internal width: 180
- Internal length: 150
- Left edge offset: 15
- Right edge offset: 25
- Bottom edge offset: 10

Reinforcement Details:

- Top reinforcement: 2 N5 $\varnothing 8.0$ C=233
- Bottom reinforcement: 2 N4 $\varnothing 8.0$ C=220
- Internal reinforcement: 30 N1 $\varnothing 5.0$ C=49
- Internal reinforcement: 30 N1 $\varnothing 7.0$ C=7
- Internal reinforcement: 30 N1 $\varnothing 5.0$ C=49

Section View Details:

- Section line: A-A
- Section width: 20
- Section height: 15
- Section reinforcement: 2 N5 $\varnothing 8.0$ C=233
- Section reinforcement: 2 N4 $\varnothing 8.0$ C=220
- Section reinforcement: 30 N1 $\varnothing 5.0$ C=49
- Section reinforcement: 30 N1 $\varnothing 7.0$ C=7

V301	V302	V303
V304		

AÇO	N	DIAM (mm)	QUANT	C.UNIT (cm)	C.TOTAL (cm)
CA60	1	5.0	149	49	7301
CA50	2	8.0	4	337	1348
	3	8.0	4	359	1436
	4	8.0	4	220	880
	5	8.0	4	233	932

AÇO	DIAM (mm)	C.TOTAL (m)	PESO + 0% (kg)
CA50	8.0	46	18.1
CA60	5.0	73	11.3
PESO TOTAL (kg)			
CA50	18.1		
CA60	11.3		

Volume de concreto (C-25) = 0.34 m³
Área de forma = 6.22 m²

PLATIBANDA - L4

SEÇÃO
ESC 1:20

VISTA B

VISTA H

VISTA B

7 N1 $\varnothing 5.0$ C=59

455

390

VISTA H
ESC 1:5

VISTA B
ESC 1:5

61

4 N2 $\varnothing 10.0$ C=61

65

7 N1 $\varnothing 10$

4xP7

AÇO	N	DIAM (mm)	QUANT	C.UNIT (cm)	C.TOTAL (cm)
CA60	1	5.0	28	59	1652
CA50	2	10.0	16	61	976

AÇO	DIAM (mm)	C.TOTAL (m)	PESO + 0% (kg)
CA50	10.0	9.8	6
CA60	5.0	16.5	2.5
PESO TOTAL (kg)			
CA50	6		
CA60	2.5		

Volume de concreto (C-25) = 0.10 m³
Área de forma = 2.08 m²

CONSTRUÇÃO:

FOLHA		PROJETO: CONSTRUÇÃO DE GINÁSIO POLIESPORTIVO	
12/12		CONVENIENTE: PREFEITURA MUNICIPAL DE COREMAS - PB	
		CONVENIADO: MUNICÍPIO DE COREMAS - PB	
		LOCALIDADE: COREMAS - PB	
DATA	RESPONSÁVEL	RUBRICA	DADOS
DESENHO	AGO/2025	LINCOLN CARTAXO	
CÓPIA			
VISTO			
ESCALAS		CONVÊNIO	
Indicada	DESENHOS - Forma Tampa Caixa D'água - Vigas Tampa Caixa D'água - Pilares Tampa Caixa D'água		GOVERNO DO ESTADO
			ARQUIVO

Aprovações