

1. 48 Bit Ethernet Address of the host computer:
 - a. Ethernet II, Src: 0e:74:38:9c:58:cb (0e:74:38:9c:58:cb)
2. 48 Bit Ethernet Address of the destination.
 - a. Ethernet II, Dst: PaloAltoNetw_e0:80:10 (b4:0c:25:e0:80:10)
Destination: PaloAltoNetw_e0:80:10 (b4:0c:25:e0:80:10)

So, no it is not. It is being routed to the gateway (router) first, before a request is made to OPENMANIAK.

3. Frame Type:
 - a. IPv4 (0x0800)
4. 160 Bytes → Byte 47 + Offset
5. Source Destination: (*Response*)
 - a. 128.65.195.155 (b4:0c:25:e0:80:10)

Again, it is not. It gets sent to the router and then to the computer. At the ethernet Layer, it shows Palo Alto Networks is where the response was received before forwarding to the host computer.

6. Destination:
 - a. 0e:74:38:9c:58:cb (0e:74:38:9c:58:cb)
(This is the ethernet address of the computer)
7. Frame Type:
 - a. IPv4 (0x0800)
8. 220 Bytes

```
base ~/Desktop (0.469s)
arp
Address          HWtype  HWAddress      Flags Mask      Iface
192.168.68.66    ether   38:e7:c0:e9:33:84 C              wlp0s20f3
192.168.68.59    ether   50:dc:e7:0b:81:d4 C              wlp0s20f3
192.168.68.81    ether   5a:91:94:ce:22:cf C              wlp0s20f3
192.168.68.71    ether   28:cd:c4:db:a8:d7 C              wlp0s20f3
_gateway         ether   74:fe:ce:80:bc:f4 C              wlp0s20f3
192.168.68.86    ether   ac:d5:64:ae:4f:d5 C              wlp0s20f3
172.19.0.2        ether   be:a2:80:98:05:e3 C              br-afa04f0f2c68
```

9.
 - a. Address: the IP Address of each device on the network my computer knows about.
 - b. HWtype: the hardware type of the link layer protocol (Wi-Fi here).
 - c. HWAddress: the ethernet address
 - d. Mask; the validity of the address
 - e. Iface: the interface that is doing the mapping (where it was seen)
10. Ethernet II
 - a. Src: Commscope_a7:40:a7 (10:86:8c:a7:40:a7), Dst: Intel_17:0a:7a (f8:63:3f:17:0a:7a)
 - b. Destination: Intel_17:0a:7a (f8:63:3f:17:0a:7a)
11. Frame Type:
 - a. Type: ARP (0x0806)

12. ARP Request

- a. 20 Bytes
- b. 0x001
- c. Yes contains senders IP Address

13. ARP Reply

- a. 20 bytes
- b. 0x002
- c. Source MAC: 10:86:8c:47:40:a7
- d. Destination MAC: f8:63:3f:17:0a:7a