

1-5 Common Motor Standard

Item	Specifications
Power Supply	The motor is equipped with a 380V three-phase motor drive. The input voltage of the motor drive cannot be lower than 380V, and the maximum cannot be higher than the allowable maximum input value of the motor drive. The rated output current of the motor drive cannot be lower than the rated current of the motor. The carrier frequency of the motor drive cannot be lower than 4kHz.
Rotation Direction	Clockwise direction when observing from the shaft end.
Working Environment	Temperature: -15°C–40°C; altitude below 1000m; humidity <95%TGen
Electrical Operating Conditions	During the operation of the motor, the deviation of the power supply voltage and the rated frequency should be in accordance with the regulations of IEC60034-1 (GB755).
Motor Work Mode	Motor is of continuous duty (S1).
Protection Level	IP55
Motor Thermal Protection	KTY84-130/PTC-130
Shaft Type	F80-F160: Deep groove ball bearing with seals or shields
	F180-F225: Deep groove ball bearing
Insulation Class	Class F
Temperature Rise Class	Class B for general series
Painting	Anti-rust treatment, Phenolic Resin, Black topcoat (Munsell N/1.5), thickness of painting: above 60um.
Operation Environment	Indoor only
Driving Method	(1) Standard model and direct coupling only (FPC connector) (2) Pulley applications: Enlarged front bearing is required (See code 9= A) and follow table 3-2 to apply forces.
Encoder	N/A
Overload Capacity	Take 120% overload capacity for 60 seconds at rated rotation speed.
International Certificates	CE, UKCA