

2-3 Transportation

2-3-1 Model of Lifting Eye Bolts

	H80	H90	H100	H112	H132	H160	H180	H200	H225
Cast Iron Enclosure	-	-	-	M8x1	M10X1	M12x1	M12x1	M16x1	M16x1
Aluminum Enclosure	-	-	M8x2	M8x2	M10x2	-	-	-	-

NOTE: Refer to DIN 580 regulations for dimension of stainless steel lifting eye bolts.

2-3-2 Hoisting (Vertical Loading) and Transportation

Considering the possibility of hoisting and transporting the motor and the rotary screw compressor together after integrated installation, it is necessary to limit the usage of the lifting eye bolts on both sides of the motor. The lifting eye bolts on both sides of the casing are only able to support the weight of the motor stator assembly and cannot support the combined weight of the rotary screw compressor and the whole machine. If you need to install the lifting eye bolts in the motor that are capable to support the weight of the entire motor and rotary screw compressor, reinstall these eye screws at the two holes of the rear end cover. The two lifting eye bolts of the rear end cover are able to support the weight when hoisting.

Motor Model Name	Lifting Eye Bolts		Maximum Allowable Combined Weight of the Motor and the Rotary Screw Compressor
	Part Number	Q'ty	
MSI15D-56CCXO7F0AC MSI15D-56CDXO7F0AC MSI22D-32CCXO7F0AC MSI22D-32CDXO7F0AC	GBT825-M8	2	≤160Kg
MSI37D-38CCXO7F0AC MSI37D-38CDXO7F0AC MSI37D-38CCXO7Z0AC MSI37D-38CDXO7Z0AC	GBT825-M12	2	≤400Kg
MSI75D-25CCXO7F0AC MSI75D-25CDXO7F0AC	GBT825-M12	2	≤400Kg