

No.	Item	Description
①	DC Fan	DC fan for ventilation.
②	CT	CT signal terminals.
③	COM (Communication Terminals)	Communication terminals between the display and the module.
④	LED Indicators	Module status indicator: - Green (Normal): The module operates normally. - Yellow (Standby): The module is in standby mode. - Red (Fault): The module is malfunctioning.
⑤	ID (DIP Switch)	Setup of the module ID and the terminal resistor.
⑥	Main Power Input Terminals	Main power wiring terminals for R/ S/ T/ N/ PE.



NOTE:

1. The communication port is insulated. Contacting the port does not present the risk of electric shock.
2. The CT wire shall be fastened to avoid open circuit, which will lead to high-voltage risk and secondary circuit burning.

Table 2-10: SVG Module Dimensions and Weights

Model	Dimensions (W × D × H)	Weights (kg)
PQCS-400-50-50MM4	484 × 641.5 × 190 mm	34 kg
PQCS-400-50-50MM3	484 × 641.5 × 190 mm	33 kg
PQCS-400-100-100MM4	484 × 731.5 × 190 mm	47 kg
PQCS-400-100-100MM3	484 × 731.5 × 190 mm	46 kg
PQCS-400-150-150MM4	484 × 701.5 × 270 mm	63 kg
PQCS-400-150-150MM3	484 × 701.5 × 270 mm	62 kg