

1-7 Motor Parameters

1-7-1 Standard 3000rpm Series

Model Name	Frame	Rated Power	Rated Current	Rated Torque	Rated Efficiency	Noise
Unit	(mm)	(kW)	(A)	(Nm)	(%)	(dB)
MSI75B-30CDXS2□1A	80	0.75	1.5	2.4	86.3	67
MSI11C-30CDXS2□1A		1.1	2.3	3.5	87.8	67
MSI15C-30CDXS2□1A		1.5	3.1	4.8	88.9	72
MSI22C-30CDXS2□1A		2.2	4.4	7	90.2	72

NOTE: □ represents the installation method: A (IM B3 installation), B (IM V1/B5 installation), D (IM V18/B14 installation), H (IM V15/ B35 installation)

Model Name	Frame	Rated Power	Rated Current	Rated Torque	Rated Efficiency	Noise
Unit	(mm)	(kW)	(A)	(Nm)	(%)	(dB)
MSI30C-30CDXS2□1A	90	3	5.8	9.6	91.1	76
MSI40C-30CDXS2□1A		4	8	12.7	91.8	77
MSI55C-30CDXS2□1A	100	5.5	11	17.5	92.6	80
MSI75C-30CDXS2□1A		7.5	14.7	23.9	93.3	80

NOTE: □ represents the installation method: A (IM B3 installation), B (IM V1/B5 installation), D (IM V18/B14 installation), H (IM V15/ B35 installation)

Model Name	Frame	Rated Power	Rated Current	Rated Torque	Rated Efficiency	Noise
Unit	(mm)	(kW)	(A)	(Nm)	(%)	(dB)
MSI11D-30CDXS2□1A	112	11	23	35	94.0	68
MSI15D-30CDXS2□1A		15	30	47.8	94.5	68
MSI18D-30CDXS2□1A	132	18.5	37	58.7	94.9	70
MSI22D-30CDXS2□1A		22	43	70	95.1	70
MSI30D-30CDXS2□1B	160	30	58.2	95.5	95.5	92
MSI37D-30CDXS2□1B		37	73.7	117.8	95.8	92

NOTE: □ represents the installation method: A (IM B3 installation), B (IM V1/B5 installation)