

Model Name	Type	Frame	Dimensions and Tolerances / mm														
			A	B	C		D		E	js14	ED	F	h8	GA		H	
MSI55C-15CDXS2H1B MSI75C-15CDXS2H1B	Iron case	112	190	140	88±2		38	+0.018 -0.002	80	±0.370	70	10 ⁰ -0.022	41 ⁰ -0.2	112 ⁰ -0.5			
			K		M	N	j6		P		Holes	S	H14	T	h12	AB	AC
			12	+0.43 0	265	230	+0.016 -0.013	300±5		4	14.5	+0.43 0	4 ⁰ -0.12	226	217		
			HD			L			DHTAP			Front Bearing			Rear Bearing		
			295±5			500±10			M12×24L			6309 ZZ/C3			6206 ZZ/C3		

Model Name	Type	Frame	Dimensions and Tolerances / mm													
			A	B	C		D		E	js14	ED	F	h8	GA		H
MSI11D-15CDXS2H1B MSI15D-15CDXS2H1B	Iron case	132	216	178	100±3		42	+0.018 -0.002	110	±0.435	90	12 ⁰ -0.027	45 ⁰ -0.2	132 ⁰ -0.5		
			K		M	N	j6		P	Holes	S	H14	T	h12	AB	AC
			12	+0.43 0	300	250	+0.016 -0.013	350±5		4	18.5	+0.52 0	5 ⁰ -0.12	262	259	
			HD			L			DHTAP			Front Bearing			Rear Bearing	
			333±5			580±10			M16×32L			6310 ZZ/C3			6208 ZZ/C3	

Model Name	Type	Frame	Dimensions and Tolerances / mm													
			A	B	C		D		E	js14	ED	F	h8	GA		H
MSI18D-15CDXS2H1B MSI22D-15CDXS2H1B	Iron case	160	254	254	95±2		48	+0.018 -0.002	110	±0.435	100	14 ⁰ -0.027	51.5 ⁰ -0.2	160 ⁰ -0.5		
			K		M	N	j6		P	Holes	S	H14	T	h12	AB	AC
			14.5 ^{+0.43} 0	300	250	+0.016 -0.013	350±5		4	18.5 ^{+0.52} 0	5 ⁰ -0.12	314	314			
			HD			L			DHTAP			Front Bearing			Rear Bearing	
			416±5			669±10			M16×32L			6310 ZZ/C3			6209 ZZ/C3	

Model Name	Type	Frame	Dimensions and Tolerances / mm														
			A	B	C		D		E	js14	ED	F	h8	GA		H	
MSI30D-15CDXS2H1B	Iron case	180	279	279	135±3		55	+0.030 -0.011	110	±0.435	100	16 ⁰ -0.027	59 ⁰ -0.2	180 ⁰ -0.5			
			K		M	N	j6	P		Holes		S	H14	T	h12	AB	AC
			14.5	+0.43 0	350	300	±0.016	400±5		4	18.5	+0.52 0	5 ⁰ -0.12	349	355		
			HD			L			DHTAP			Front Bearing			Rear Bearing		
			447±5			740±10			M20×40L			6313/C3			6211/C3		

Model Name	Type	Frame	Dimensions and Tolerances / mm													
			A	B	C		D		E	js14	ED	F	h8	GA		H
MSI37D-15CDXS2H1B	Iron case	180	279	279	135±3		60	+0.030 -0.011	140	±0.500	125	18 ⁰ -0.027	64 ⁰ -0.2	180 ⁰ -0.5		
			K		M	N	j6	P		Holes	S	H14	T	h12	AB	AC
			14.5	+0.43 0	400	350	±0.018	450±5		8	18.5	+0.52 0	5 ⁰ -0.12	349	355	
			HD			L			DHTAP			Front Bearing			Rear Bearing	
			447±5			770±10			M20×40L			6313/C3			6211/C3	