

5-2 Motor Exterior Cleaning

	☒ When the motor is running, do not clean the outside of the motor or remove the rear air hood to prevent flowing dust or broken objects from being directly sucked into the motor.
---	---

The operating environment should always be kept dry. The surface of the motor should be kept clean, and the air inlet of the wind cover should be clear and unobstructed.

If any abnormalities or abnormal sounds are found while the motor is running, stop immediately for inspection. Do not try to start again until the fault is identified and eliminated.

It is necessary to keep the motor well lubricated during operation.

When the bearings have been filled with grease, no more grease is added within the allowed period. After 5,000 hours of continuous rotation, the motor should be disassembled and inspected to refill the grease (except for sealed bearings). The bearing temperature should not exceed 95°C, otherwise the grease should be replaced (grease according to the motor refueling mark).

- ① Semi-enclosed motors are suitable for clean, dry, well-ventilated and non-corrosive environments. The air inlet window at the air inlet should not be filled with dirt, dust, lint and other debris, or it may block the air flow path and cause the air not able to flow freely.
- ② If the motor is equipped with filter consumables, they must be replaced regularly (replaceable filter consumables), or the filter (permanent type) must be cleaned and maintained according to on-site usage conditions. If the filter is not cleaned for a long time, the filter will lose its filtering effect. Therefore, users must be reminded to replace or clean the filter regularly.
- ③ For fully sealed air-cooling methods and fully sealed external fan cooling methods, special cleaning considerations are required for the motor. The outer fan must be cleaned of dust and dirt, because the dust accumulated on the outer fan will cause imbalance and vibration. The heat exchange tubes inside the motor's air duct cold box must be cleaned with an appropriate tube brush. The material of the tube brush is rigid artificial fiber (do NOT use metal steel brushes).