



## Chapter 7: Specifications

| Item                                  | Model No.                 |                                                      | Part No.      |
|---------------------------------------|---------------------------|------------------------------------------------------|---------------|
|                                       | HC5990                    |                                                      | HC5990AADU0XX |
| 1. Input/ Output                      |                           |                                                      |               |
| 1.1 Input Voltage                     | 100-240 Vac; 47~63 Hz     |                                                      |               |
| 1.2 Rated Current                     | 2.5A                      |                                                      |               |
| 1.3 Input Power                       | 210W                      |                                                      |               |
| 1.4 Input Plug/ Connector             | UL                        | Male Plug-NEMA 5-15P;<br>Female Connector-IEC320 C13 |               |
|                                       | CE                        | Male Plug-IEC320 C14;<br>Female Connector-IEC320 C13 |               |
| 2. Dimensions/ Weight                 |                           |                                                      |               |
| 2.1 Dimensions (W x D x H)            | 430 x 400 x 54 mm         |                                                      |               |
| 2.2 Unit Weight                       | 5.62 Kg                   |                                                      |               |
| 2.3 Shipping Weight                   | 7.52 Kg                   |                                                      |               |
| 3. Airflow<br>(with the Raised Floor) |                           |                                                      |               |
| 3.1 Air Supply Volume                 | 1000CFM (0.464 m³/s) ± 5% |                                                      |               |
| 3.2 FAR (The Raised Floor)            | > 50%                     |                                                      |               |
| 4. Environment                        |                           |                                                      |               |
| 4.1 Operating temperature             | 0°C~45°C                  |                                                      |               |
| 4.2 Storage temperature               | -20°C~60°C                |                                                      |               |
| 4.3 Operating relative humidity       | 20%~90% (non-condensing)  |                                                      |               |
| 4.4 Storage relative humidity         | 0%~90% (non-condensing)   |                                                      |               |



### NOTE:

- ※ Refer to the rating label for the safety rating.
- ※ All specifications are subject to change without prior notice.