

No.	Item	Description	Default
[f]	System Location	The System Location information.	
[g]	Ethernet PHY Mode	Switch to the speed (10/ 100 Mbps) and duplex or auto negotiation.	Auto Negotiation
[h]	Status Stable	Status change confirmation (number of times).	3
[i]	Telnet Idle Time	Telnet connection time-out setting.	60 Seconds

● Network Parameter

```

*****
Network Parameter
*****
1. HTTP Server:      Enable
2. HTTPS Server:    Enable
3. Telnet Server:    Enable
4. SSH/SFTP Server:  Enable
5. FTP Server:       Disable
6. Syslog:           Disable
7. HTTP Server Port: 80
8. HTTPS Server Port: 443
9. Telnet Server Port: 23
a. SSH Server Port:  22
b. FTP Server Port:   21
c. Syslog Server1:
d. Syslog Server2:
e. Syslog Server3:
f. Syslog Server4:
g. SNMP Get/Set Port: 161
0. Back To Previous Menu
Mini>

```

No.	Item	Description	Default
[1]	HTTP Server	Enable/ Disable HTTP protocol.	Enable
[2]	HTTPS Server	Enable/ Disable HTTPS protocol.	Enable
[3]	Telnet Server	Enable/ Disable Telnet protocol.	Disable
[4]	SSH/ SFTP Server	Enable/ Disable SSH/ SFTP protocol.	Enable
[5]	FTP Server	Enable/ Disable FTP protocol.	Disable
[6]	Syslog	Enable/ Disable remote Syslog.	Disable
[7]	HTTP Server Port	HTTP port.	80
[8]	HTTPS Server Port	HTTPS port.	443
[9]	Telnet Server Port	Telnet port.	23
[a]	SSH Server Port	SSH port.	22
[b]	FTP Server Port	FTP port.	21