

RenE-InD 17400-48



GOAEEM-01-ZL

INPUT GRID SECTION

Voltage (nominal)	3 x 230V _{AC} (L-N); 3L, N, PE
Voltage (range)	88 - 300V _{AC}
AC SPD	Optional
Frequency	45 - 66Hz

INPUT GENERATOR SECTION

Voltage (nominal)	3 x 230V _{AC} (L-N); 3L, N, PE
Current Nominal / Phase	32 A _{RMS}
Automatic Transfer Switch	Voltage relay monitoring, Mechanical interlocking
Mains Terminal	Terminal blocks, or Main breaker
Input Protection	Optional

INPUT RENEWABLE POWER SECTION

Renewable DC connection	6 feeds 50A
Voltage Range	60-150V _{DC}
Current Max / Pole	48A _{DC}
Input Terminal	Circuit breakers
Input Protection	6 x 50A 2P
Transient Protection	1000 DC/2+V optional

OUTPUT POWER SECTION

Rectifier Power	17.4kW max
Solar Power	6 x 4.3kW peak
Voltage Range	42 - 58V _{DC} ; 53.5V _{DC} nom
Battery MCB	1 - 4 x 80 - 300A
LVD 300A	Option
Batt-capacity Expansion Cab.	1200Ah
Max. Batt Expansion Cab.	3600Ah
MCB	18 pcs / 1 - 63A
PLD 150A	Option

ENERGY MANAGEMENT SECTION

Energy Management	Configurable, depending on the OPEX saving targets
AC & Genset Management	Automatic, configurable
Energy Meter	AC and DC power

GENERAL

Ambient Temperature	-45 to +45 °C (-49 to + 113 °F)
Safety	IEC/EN 60950
EMC	EN 300 386
Protection	ETS 300 019 Part 1-4
Environment	RoHS

* All specifications are subject to change without prior notice.