

2.2 PQC Series Mixed Fixed type SVG Product Category

The Delta PQC Series Mixed Fixed type SVG is categorized by the capacity and wiring system. **Table 2-1** lists the information regarding the SVG module products.

Table 2-1: PQC Series Mixed Fixed Type SVG Specifications

Product	Model	Capacity	Wiring System
SVG Module	PQCS-400-50-50MM4	50 kvar	3P4W
	PQCS-400-50-50MM3	50 kvar	3P3W
	PQCS-400-100-100MM4	100 kvar	3P4W
	PQCS-400-100-100MM3	100 kvar	3P3W
	PQCS-400-150-150MM4	150 kvar	3P4W
	PQCS-400-150-150MM3	150 kvar	3P3W
SVG Module (Maintained from the Front)	SVG Module + Pluggable terminals(50/100kvar)		
HMI Display	PQC-HMI-F (7")	N/A	N/A
	PQC-HMI-F10 (10")	N/A	N/A
Accessories	Pluggable terminals(50/100kvar)	N/A	N/A



NOTE:

Only 50kvar and 100kvar SVG can be used with pluggable terminals, For detailed information regarding the Pluggable terminals, please see **Chapter 3.5.2**.

- **SVG Module**

The SVG module is available in two wiring modes, i.e. 3P3W and 3P4W, and is available in the following output capacity: 50kvar and 100kvar.

The 3P4W module shall be connected to a neutral line, which in turn will improve its ability of compensating the zero sequence current. The 3P3W model is not required to connect to the neutral line; as a result, it is not able to compensate the zero sequence current. **Figure 2-2** shows the SVG module appearance.