

Design and Analysis of Algorithms

Part I: Divide and Conquer

Lecture 4: The Polynomial Multiplication Problem and Quicksort Problem



Yongxin Tong (童咏昕)

School of CSE, Beihang University

yxtong@buaa.edu.cn

Outline

- Review to Divide-and-Conquer Paradigm
- Polynomial Multiplication Problem
 - Problem definition
 - A brute force algorithm
 - A first divide-and-conquer algorithm
 - An improved divide-and-conquer algorithm
 - Analysis of the divide-and-conquer algorithm
- Quicksort Problem
 - Basic partition
 - Randomized partition and randomized quicksort
 - Analysis of the randomized quicksort

Outline

- Review to Divide-and-Conquer Paradigm
- Polynomial Multiplication Problem
 - Problem definition
 - A brute force algorithm
 - A first divide-and-conquer algorithm
 - An improved divide-and-conquer algorithm
 - Analysis of the divide-and-conquer algorithm
- Quicksort Problem
 - Basic partition
 - Randomized partition and randomized quicksort
 - Analysis of the randomized quicksort

Review to Divide-and-Conquer Paradigm

- **Divide-and-conquer** (D&C) is an important algorithm design paradigm.
 - **Divide**
Dividing a given problem into two or more subproblems (ideally of approximately equal size)
 - **Conquer**
Solving each subproblem (directly if small enough or **recursively**)
 - **Combine**
Combining the solutions of the subproblems into a global solution

Review to Divide-and-Conquer Paradigm

- In Part I, we will illustrate Divide-and-Conquer using several examples:
 - Maximum Contiguous Subarray (最大子数组)
 - Counting Inversions (逆序计数)
 - Polynomial Multiplication (多项式乘法)
 - QuickSort and Partition (快速排序与划分)
 - Lower Bound for Sorting (基于比较的排序下界)

Review to Divide-and-Conquer Paradigm

- In Part I, we will illustrate Divide-and-Conquer using several examples:
 - Maximum Contiguous Subarray (最大子数组)
 - Counting Inversions (逆序计数)
 - Polynomial Multiplication (多项式乘法)
 - QuickSort and Partition (快速排序与划分)
 - Lower Bound for Sorting (基于比较的排序下界)

Outline

- Review to Divide-and-Conquer Paradigm
- Polynomial Multiplication Problem
 - Problem definition
 - A brute force algorithm
 - A first divide-and-conquer algorithm
 - An improved divide-and-conquer algorithm
 - Analysis of the divide-and-conquer algorithm
- Quicksort Problem
 - Basic partition
 - Randomized partition and randomized quicksort
 - Analysis of the randomized quicksort

The Polynomial Multiplication Problem

Definition (Polynomial Multiplication Problem)

Given two polynomials

$$A(x) = a_0 + a_1x + \cdots + a_nx^n$$

$$B(x) = b_0 + b_1x + \cdots + b_mx^m$$

Compute the **product** $A(x)B(x)$

The Polynomial Multiplication Problem

Definition (Polynomial Multiplication Problem)

Given two polynomials

$$A(x) = a_0 + a_1x + \cdots + a_nx^n$$

$$B(x) = b_0 + b_1x + \cdots + b_mx^m$$

Compute the **product** $A(x)B(x)$

Example

$$A(x) = 1 + 2x + 3x^2$$

$$B(x) = 3 + 2x + 2x^2$$

$$A(x)B(x) = 3 + 8x + 15x^2 + 10x^3 + 6x^4$$

The Polynomial Multiplication Problem

Definition (Polynomial Multiplication Problem)

Given two polynomials

$$A(x) = a_0 + a_1x + \cdots + a_nx^n$$

$$B(x) = b_0 + b_1x + \cdots + b_mx^m$$

Compute the **product** $A(x)B(x)$

Example

$$A(x) = 1 + 2x + 3x^2$$

$$B(x) = 3 + 2x + 2x^2$$

$$A(x)B(x) = 3 + 8x + 15x^2 + 10x^3 + 6x^4$$

- Assume that the coefficients a_i and b_i are stored in arrays $A[0..n]$ and $B[0..m]$

The Polynomial Multiplication Problem

Definition (Polynomial Multiplication Problem)

Given two polynomials

$$A(x) = a_0 + a_1x + \cdots + a_nx^n$$

$$B(x) = b_0 + b_1x + \cdots + b_mx^m$$

Compute the **product** $A(x)B(x)$

Example

$$A(x) = 1 + 2x + 3x^2$$

$$B(x) = 3 + 2x + 2x^2$$

$$A(x)B(x) = 3 + 8x + 15x^2 + 10x^3 + 6x^4$$

- Assume that the coefficients a_i and b_i are stored in arrays $A[0..n]$ and $B[0..m]$
- **Cost**: number of scalar multiplications and additions

What do we need to compute exactly?

Define

- $A(x) = \sum_{i=0}^n a_i x^i$
- $B(x) = \sum_{i=0}^m b_i x^i$

What do we need to compute exactly?

Define

- $A(x) = \sum_{i=0}^n a_i x^i$
- $B(x) = \sum_{i=0}^m b_i x^i$
- $C(x) = A(x)B(x) = \sum_{k=0}^{n+m} c_k x^k$

What do we need to compute exactly?

Define

- $A(x) = \sum_{i=0}^n a_i x^i$
- $B(x) = \sum_{i=0}^m b_i x^i$
- $C(x) = A(x)B(x) = \sum_{k=0}^{n+m} c_k x^k$

Then

- $c_k = \sum_{0 \leq i \leq n, 0 \leq j \leq m, i+j=k} a_i b_j$, for all $0 \leq k \leq m+n$

What do we need to compute exactly?

Define

- $A(x) = \sum_{i=0}^n a_i x^i$
- $B(x) = \sum_{i=0}^m b_i x^i$
- $C(x) = A(x)B(x) = \sum_{k=0}^{n+m} c_k x^k$

Then

- $c_k = \sum_{0 \leq i \leq n, 0 \leq j \leq m, i+j=k} a_i b_j$, for all $0 \leq k \leq m+n$

Definition

The vector $(c_0, c_1, \dots, c_{m+n})$ is the **convolution** of the vectors (a_0, a_1, \dots, a_n) and (b_0, b_1, \dots, b_m)

What do we need to compute exactly?

Define

- $A(x) = \sum_{i=0}^n a_i x^i$
- $B(x) = \sum_{i=0}^m b_i x^i$
- $C(x) = A(x)B(x) = \sum_{k=0}^{n+m} c_k x^k$

Then

- $c_k = \sum_{0 \leq i \leq n, 0 \leq j \leq m, i+j=k} a_i b_j$, for all $0 \leq k \leq m+n$

Definition

The vector $(c_0, c_1, \dots, c_{m+n})$ is the **convolution** of the vectors (a_0, a_1, \dots, a_n) and (b_0, b_1, \dots, b_m)

- We need to calculate convolutions. This is a major problem in digital signal processing

Outline

- Review to Divide-and-Conquer Paradigm
- **Polynomial Multiplication Problem**
 - Problem definition
 - **A brute force algorithm**
 - A first divide-and-conquer algorithm
 - An improved divide-and-conquer algorithm
 - Analysis of the divide-and-conquer algorithm
- **Quicksort Problem**
 - Basic partition
 - Randomized partition and randomized quicksort
 - Analysis of the randomized quicksort

Direct (Brute Force) Approach

To ease analysis, assume $n = m$.

Direct (Brute Force) Approach

To ease analysis, assume $n = m$.

- $A(x) = \sum_{i=0}^n a_i x^i$
- $B(x) = \sum_{i=0}^m b_i x^i$

Direct (Brute Force) Approach

To ease analysis, assume $n = m$.

- $A(x) = \sum_{i=0}^n a_i x^i$
- $B(x) = \sum_{i=0}^m b_i x^i$
- $C(x) = A(x)B(x) = \sum_{k=0}^{2n} c_k x^k$ with

$$c_k = \sum_{0 \leq i, j \leq n, i+j=k} a_i b_j, \text{ for all } 0 \leq k \leq 2n$$

Direct (Brute Force) Approach

To ease analysis, assume $n = m$.

- $A(x) = \sum_{i=0}^n a_i x^i$
- $B(x) = \sum_{i=0}^m b_i x^i$
- $C(x) = A(x)B(x) = \sum_{k=0}^{2n} c_k x^k$ with

$$c_k = \sum_{0 \leq i, j \leq n, i+j=k} a_i b_j, \text{ for all } 0 \leq k \leq 2n$$

Direct approach:

Direct (Brute Force) Approach

To ease analysis, assume $n = m$.

- $A(x) = \sum_{i=0}^n a_i x^i$
- $B(x) = \sum_{i=0}^m b_i x^i$
- $C(x) = A(x)B(x) = \sum_{k=0}^{2n} c_k x^k$ with

$$c_k = \sum_{0 \leq i, j \leq n, i+j=k} a_i b_j, \text{ for all } 0 \leq k \leq 2n$$

Direct approach: Compute all c_k 's using the formula above.

Direct (Brute Force) Approach

To ease analysis, assume $n = m$.

- $A(x) = \sum_{i=0}^n a_i x^i$
- $B(x) = \sum_{i=0}^m b_i x^i$
- $C(x) = A(x)B(x) = \sum_{k=0}^{2n} c_k x^k$ with

$$c_k = \sum_{0 \leq i, j \leq n, i+j=k} a_i b_j, \text{ for all } 0 \leq k \leq 2n$$

Direct approach: Compute all c_k 's using the formula above.

- Total number of multiplications: $O(n^2)$

Direct (Brute Force) Approach

To ease analysis, assume $n = m$.

- $A(x) = \sum_{i=0}^n a_i x^i$
- $B(x) = \sum_{i=0}^m b_i x^i$
- $C(x) = A(x)B(x) = \sum_{k=0}^{2n} c_k x^k$ with

$$c_k = \sum_{0 \leq i, j \leq n, i+j=k} a_i b_j, \text{ for all } 0 \leq k \leq 2n$$

Direct approach: Compute all c_k 's using the formula above.

- Total number of multiplications: $O(n^2)$
- Total number of additions: $O(n^2)$

Direct (Brute Force) Approach

To ease analysis, assume $n = m$.

- $A(x) = \sum_{i=0}^n a_i x^i$
- $B(x) = \sum_{i=0}^m b_i x^i$
- $C(x) = A(x)B(x) = \sum_{k=0}^{2n} c_k x^k$ with

$$c_k = \sum_{0 \leq i, j \leq n, i+j=k} a_i b_j, \text{ for all } 0 \leq k \leq 2n$$

Direct approach: Compute all c_k 's using the formula above.

- Total number of multiplications: $O(n^2)$
- Total number of additions: $O(n^2)$
- Complexity: $O(n^2)$

Outline

- Review to Divide-and-Conquer Paradigm
- **Polynomial Multiplication Problem**
 - Problem definition
 - A brute force algorithm
 - **A first divide-and-conquer algorithm**
 - An improved divide-and-conquer algorithm
 - Analysis of the divide-and-conquer algorithm
- Quicksort Problem
 - Basic partition
 - Randomized partition and randomized quicksort
 - Analysis of the randomized quicksort

The First Divide-and-Conquer: Divide

Assume n is a power of 2

Define

$$A_0(x) = a_0 + a_1x + \cdots + a_{\frac{n}{2}-1}x^{\frac{n}{2}-1}$$

$$A_1(x) = a_{\frac{n}{2}} + a_{\frac{n}{2}+1}x + \cdots + a_nx^{\frac{n}{2}}$$

$$A(x) =$$

The First Divide-and-Conquer: Divide

Assume n is a power of 2

Define

$$A_0(x) = a_0 + a_1x + \cdots + a_{\frac{n}{2}-1}x^{\frac{n}{2}-1}$$

$$A_1(x) = a_{\frac{n}{2}} + a_{\frac{n}{2}+1}x + \cdots + a_nx^{\frac{n}{2}}$$

$$A(x) = A_0(x) +$$

The First Divide-and-Conquer: Divide

Assume n is a power of 2

Define

$$A_0(x) = a_0 + a_1x + \cdots + a_{\frac{n}{2}-1}x^{\frac{n}{2}-1}$$

$$A_1(x) = a_{\frac{n}{2}} + a_{\frac{n}{2}+1}x + \cdots + a_nx^{\frac{n}{2}}$$

$$A(x) = A_0(x) + A_1(x)x^{\frac{n}{2}}$$

The First Divide-and-Conquer: Divide

Assume n is a power of 2

Define

$$A_0(x) = a_0 + a_1x + \cdots + a_{\frac{n}{2}-1}x^{\frac{n}{2}-1}$$

$$A_1(x) = a_{\frac{n}{2}} + a_{\frac{n}{2}+1}x + \cdots + a_nx^{\frac{n}{2}}$$

$$A(x) = A_0(x) + A_1(x)x^{\frac{n}{2}}$$

Similarly, define $B_0(x)$ and $B_1(x)$ such that

$$B(x) = B_0(x) + B_1(x)x^{\frac{n}{2}}$$

The First Divide-and-Conquer: Divide

Assume n is a power of 2

Define

$$A_0(x) = a_0 + a_1x + \cdots + a_{\frac{n}{2}-1}x^{\frac{n}{2}-1}$$

$$A_1(x) = a_{\frac{n}{2}} + a_{\frac{n}{2}+1}x + \cdots + a_nx^{\frac{n}{2}}$$

$$A(x) = A_0(x) + A_1(x)x^{\frac{n}{2}}$$

Similarly, define $B_0(x)$ and $B_1(x)$ such that

$$B(x) = B_0(x) + B_1(x)x^{\frac{n}{2}}$$

$$A(x)B(x) =$$

The First Divide-and-Conquer: Divide

Assume n is a power of 2

Define

$$A_0(x) = a_0 + a_1x + \cdots + a_{\frac{n}{2}-1}x^{\frac{n}{2}-1}$$

$$A_1(x) = a_{\frac{n}{2}} + a_{\frac{n}{2}+1}x + \cdots + a_nx^{\frac{n}{2}}$$

$$A(x) = A_0(x) + A_1(x)x^{\frac{n}{2}}$$

Similarly, define $B_0(x)$ and $B_1(x)$ such that

$$B(x) = B_0(x) + B_1(x)x^{\frac{n}{2}}$$

$$A(x)B(x) = A_0(x)B_0(x) +$$

The First Divide-and-Conquer: Divide

Assume n is a power of 2

Define

$$A_0(x) = a_0 + a_1x + \cdots + a_{\frac{n}{2}-1}x^{\frac{n}{2}-1}$$

$$A_1(x) = a_{\frac{n}{2}} + a_{\frac{n}{2}+1}x + \cdots + a_nx^{\frac{n}{2}}$$

$$A(x) = A_0(x) + A_1(x)x^{\frac{n}{2}}$$

Similarly, define $B_0(x)$ and $B_1(x)$ such that

$$B(x) = B_0(x) + B_1(x)x^{\frac{n}{2}}$$

$$A(x)B(x) = A_0(x)B_0(x) + A_0(x)B_1(x)x^{\frac{n}{2}} +$$

The First Divide-and-Conquer: Divide

Assume n is a power of 2

Define

$$A_0(x) = a_0 + a_1x + \cdots + a_{\frac{n}{2}-1}x^{\frac{n}{2}-1}$$

$$A_1(x) = a_{\frac{n}{2}} + a_{\frac{n}{2}+1}x + \cdots + a_nx^{\frac{n}{2}}$$

$$A(x) = A_0(x) + A_1(x)x^{\frac{n}{2}}$$

Similarly, define $B_0(x)$ and $B_1(x)$ such that

$$B(x) = B_0(x) + B_1(x)x^{\frac{n}{2}}$$

$$\begin{aligned} A(x)B(x) &= A_0(x)B_0(x) + A_0(x)B_1(x)x^{\frac{n}{2}} \\ &\quad + A_1(x)B_0(x)x^{\frac{n}{2}} + \end{aligned}$$

The First Divide-and-Conquer: Divide

Assume n is a power of 2

Define

$$A_0(x) = a_0 + a_1x + \cdots + a_{\frac{n}{2}-1}x^{\frac{n}{2}-1}$$

$$A_1(x) = a_{\frac{n}{2}} + a_{\frac{n}{2}+1}x + \cdots + a_nx^{\frac{n}{2}}$$

$$A(x) = A_0(x) + A_1(x)x^{\frac{n}{2}}$$

Similarly, define $B_0(x)$ and $B_1(x)$ such that

$$B(x) = B_0(x) + B_1(x)x^{\frac{n}{2}}$$

$$\begin{aligned} A(x)B(x) &= A_0(x)B_0(x) + A_0(x)B_1(x)x^{\frac{n}{2}} \\ &\quad + A_1(x)B_0(x)x^{\frac{n}{2}} + A_1(x)B_1(x)x^n \end{aligned}$$

The First Divide-and-Conquer: Divide

Assume n is a power of 2

Define

$$A_0(x) = a_0 + a_1x + \cdots + a_{\frac{n}{2}-1}x^{\frac{n}{2}-1}$$

$$A_1(x) = a_{\frac{n}{2}} + a_{\frac{n}{2}+1}x + \cdots + a_nx^{\frac{n}{2}}$$

$$A(x) = A_0(x) + A_1(x)x^{\frac{n}{2}}$$

Similarly, define $B_0(x)$ and $B_1(x)$ such that

$$B(x) = B_0(x) + B_1(x)x^{\frac{n}{2}}$$

$$\begin{aligned} A(x)B(x) &= A_0(x)B_0(x) + A_0(x)B_1(x)x^{\frac{n}{2}} \\ &\quad + A_1(x)B_0(x)x^{\frac{n}{2}} + A_1(x)B_1(x)x^n \end{aligned}$$

The original problem (of size n) is divided into 4 problems of input size $n/2$

Example

$$A(x) = 2 + 5x + 3x^2 + x^3 - x^4$$

$$B(x) = 1 + 2x + 2x^2 + 3x^3 + 6x^4$$

$$A(x)B(x) = 2 + 9x + 17x^2 + 23x^3 + 34x^4 \\ + 39x^5 + 19x^6 + 3x^7 - 6x^8$$

$$A_0(x) = 2 + 5x, A_1(x) = 3 + x - x^2$$

$$A(x) = A_0(x) + A_1(x)x^2$$

Example

$$A(x) = 2 + 5x + 3x^2 + x^3 - x^4$$

$$B(x) = 1 + 2x + 2x^2 + 3x^3 + 6x^4$$

$$A(x)B(x) = 2 + 9x + 17x^2 + 23x^3 + 34x^4 + 39x^5 + 19x^6 + 3x^7 - 6x^8$$

$$A_0(x) = 2 + 5x, A_1(x) = 3 + x - x^2$$

$$A(x) = A_0(x) + A_1(x)x^2$$

$$B_0(x) = 1 + 2x, B_1(x) = 2 + 3x + 6x^2$$

$$B(x) = B_0(x) + B_1(x)x^2$$

Example

$$A(x) = 2 + 5x + 3x^2 + x^3 - x^4$$

$$B(x) = 1 + 2x + 2x^2 + 3x^3 + 6x^4$$

$$A(x)B(x) = 2 + 9x + 17x^2 + 23x^3 + 34x^4 + 39x^5 + 19x^6 + 3x^7 - 6x^8$$

$$A_0(x) = 2 + 5x, A_1(x) = 3 + x - x^2$$

$$A(x) = A_0(x) + A_1(x)x^2$$

$$B_0(x) = 1 + 2x, B_1(x) = 2 + 3x + 6x^2$$

$$B(x) = B_0(x) + B_1(x)x^2$$

$$A_0(x)B_0(x) = 2 + 9x + 10x^2$$

$$A_1(x)B_1(x) = 6 + 11x + 19x^2 + 3x^3 - 6x^4$$

$$A_0(x)B_1(x) = 4 + 16x + 27x^2 + 30x^3$$

$$A_1(x)B_0(x) = 3 + 7x + x^2 - 2x^3$$

Example

$$A(x) = 2 + 5x + 3x^2 + x^3 - x^4$$

$$B(x) = 1 + 2x + 2x^2 + 3x^3 + 6x^4$$

$$A(x)B(x) = 2 + 9x + 17x^2 + 23x^3 + 34x^4 + 39x^5 + 19x^6 + 3x^7 - 6x^8$$

$$A_0(x) = 2 + 5x, A_1(x) = 3 + x - x^2$$

$$A(x) = A_0(x) + A_1(x)x^2$$

$$B_0(x) = 1 + 2x, B_1(x) = 2 + 3x + 6x^2$$

$$B(x) = B_0(x) + B_1(x)x^2$$

$$A_0(x)B_0(x) = 2 + 9x + 10x^2$$

$$A_1(x)B_1(x) = 6 + 11x + 19x^2 + 3x^3 - 6x^4$$

$$A_0(x)B_1(x) = 4 + 16x + 27x^2 + 30x^3$$

$$A_1(x)B_0(x) = 3 + 7x + x^2 - 2x^3$$

$$A_0(x)B_1(x) + A_1(x)B_0(x) = 7 + 23x + 28x^2 + 28x^3$$

$$A_0(x)B_0(x) + (A_0(x)B_1(x) + A_1(x)B_0(x))x^2 + A_1(x)B_1(x)x^4$$

Example

$$A(x) = 2 + 5x + 3x^2 + x^3 - x^4$$

$$B(x) = 1 + 2x + 2x^2 + 3x^3 + 6x^4$$

$$A(x)B(x) = 2 + 9x + 17x^2 + 23x^3 + 34x^4 + 39x^5 + 19x^6 + 3x^7 - 6x^8$$

$$A_0(x) = 2 + 5x, A_1(x) = 3 + x - x^2$$

$$A(x) = A_0(x) + A_1(x)x^2$$

$$B_0(x) = 1 + 2x, B_1(x) = 2 + 3x + 6x^2$$

$$B(x) = B_0(x) + B_1(x)x^2$$

$$A_0(x)B_0(x) = 2 + 9x + 10x^2$$

$$A_1(x)B_1(x) = 6 + 11x + 19x^2 + 3x^3 - 6x^4$$

$$A_0(x)B_1(x) = 4 + 16x + 27x^2 + 30x^3$$

$$A_1(x)B_0(x) = 3 + 7x + x^2 - 2x^3$$

$$A_0(x)B_1(x) + A_1(x)B_0(x) = 7 + 23x + 28x^2 + 28x^3$$

$$\begin{aligned} & A_0(x)B_0(x) + (A_0(x)B_1(x) + A_1(x)B_0(x))x^2 + A_1(x)B_1(x)x^4 \\ &= 2 + 9x + 17x^2 + 23x^3 + 34x^4 + 39x^5 + 19x^6 + 3x^7 - 6x^8 \end{aligned}$$

The First Divide-and-Conquer: Conquer

Conquer: Solve the four subproblems

- Compute

$$A_0(x)B_0(x), A_0(x)B_1(x), A_1(x)B_0(x), A_1(x)B_1(x)$$

The First Divide-and-Conquer: Conquer

Conquer: Solve the four subproblems

- Compute

$A_0(x)B_0(x), A_0(x)B_1(x), A_1(x)B_0(x), A_1(x)B_1(x)$

by recursively calling the algorithm **4 times**

The First Divide-and-Conquer: Conquer

Conquer: Solve the four subproblems

- Compute

$A_0(x)B_0(x), A_0(x)B_1(x), A_1(x)B_0(x), A_1(x)B_1(x)$

by recursively calling the algorithm **4 times**

Combine

The First Divide-and-Conquer: Conquer

Conquer: Solve the four subproblems

- Compute

$$A_0(x)B_0(x), A_0(x)B_1(x), A_1(x)B_0(x), A_1(x)B_1(x)$$

by recursively calling the algorithm **4 times**

Combine

- Add the following four polynomials

$$\begin{aligned} &A_0(x)B_0(x) + A_0(x)B_1(x)x^{\frac{n}{2}} \\ &\quad + A_1(x)B_0(x)x^{\frac{n}{2}} \\ &\quad + A_1(x)B_1(x)x^n \end{aligned}$$

The First Divide-and-Conquer: Conquer

Conquer: Solve the four subproblems

- Compute
 $A_0(x)B_0(x), A_0(x)B_1(x), A_1(x)B_0(x), A_1(x)B_1(x)$
 by recursively calling the algorithm **4 times**

Combine

- Add the following four polynomials

$$\begin{aligned}
 &A_0(x)B_0(x) + A_0(x)B_1(x)x^{\frac{n}{2}} \\
 &\quad + A_1(x)B_0(x)x^{\frac{n}{2}} \\
 &\quad + A_1(x)B_1(x)x^n
 \end{aligned}$$

- Takes **$O(\)$** operations

The First Divide-and-Conquer: Conquer

Conquer: Solve the four subproblems

- Compute
 $A_0(x)B_0(x), A_0(x)B_1(x), A_1(x)B_0(x), A_1(x)B_1(x)$
 by recursively calling the algorithm **4 times**

Combine

- Add the following four polynomials

$$\begin{aligned}
 &A_0(x)B_0(x) + A_0(x)B_1(x)x^{\frac{n}{2}} \\
 &\quad + A_1(x)B_0(x)x^{\frac{n}{2}} \\
 &\quad + A_1(x)B_1(x)x^n
 \end{aligned}$$

- Takes **$O(n)$** operations

The First Divide-and-Conquer Algorithm

PolyMulti1($A(x), B(x)$)

Input: $A(x), B(x)$

Output: $A(x) \times B(x)$

$$A_0(x) \leftarrow a_0 + a_1x + \cdots + a_{\frac{n}{2}-1}x^{\frac{n}{2}-1};$$

$$A_1(x) \leftarrow a_{\frac{n}{2}} + a_{\frac{n}{2}+1}x + \cdots + a_nx^{\frac{n}{2}};$$

$$B_0(x) \leftarrow b_0 + b_1x + \cdots + b_{\frac{n}{2}-1}x^{\frac{n}{2}-1};$$

$$B_1(x) \leftarrow b_{\frac{n}{2}} + b_{\frac{n}{2}+1}x + \cdots + b_nx^{\frac{n}{2}};$$

The First Divide-and-Conquer Algorithm

PolyMulti1($A(x), B(x)$)

Input: $A(x), B(x)$

Output: $A(x) \times B(x)$

$A_0(x) \leftarrow a_0 + a_1x + \cdots + a_{\frac{n}{2}-1}x^{\frac{n}{2}-1};$

$A_1(x) \leftarrow a_{\frac{n}{2}} + a_{\frac{n}{2}+1}x + \cdots + a_nx^{\frac{n}{2}};$

$B_0(x) \leftarrow b_0 + b_1x + \cdots + b_{\frac{n}{2}-1}x^{\frac{n}{2}-1};$

$B_1(x) \leftarrow b_{\frac{n}{2}} + b_{\frac{n}{2}+1}x + \cdots + b_nx^{\frac{n}{2}};$

$U(x) \leftarrow \text{PolyMulti1}(A_0(x), B_0(x)); // T(n/2)$

$V(x) \leftarrow \text{PolyMulti1}(A_0(x), B_1(x)); // T(n/2)$

$W(x) \leftarrow \text{PolyMulti1}(A_1(x), B_0(x)); // T(n/2)$

$Z(x) \leftarrow \text{PolyMulti1}(A_1(x), B_1(x)); // T(n/2)$

The First Divide-and-Conquer Algorithm

PolyMulti1($A(x), B(x)$)

Input: $A(x), B(x)$

Output: $A(x) \times B(x)$

$A_0(x) \leftarrow a_0 + a_1x + \cdots + a_{\frac{n}{2}-1}x^{\frac{n}{2}-1};$

$A_1(x) \leftarrow a_{\frac{n}{2}} + a_{\frac{n}{2}+1}x + \cdots + a_nx^{\frac{n}{2}};$

$B_0(x) \leftarrow b_0 + b_1x + \cdots + b_{\frac{n}{2}-1}x^{\frac{n}{2}-1};$

$B_1(x) \leftarrow b_{\frac{n}{2}} + b_{\frac{n}{2}+1}x + \cdots + b_nx^{\frac{n}{2}};$

$U(x) \leftarrow \text{PolyMulti1}(A_0(x), B_0(x)); // T(n/2)$

$V(x) \leftarrow \text{PolyMulti1}(A_0(x), B_1(x)); // T(n/2)$

$W(x) \leftarrow \text{PolyMulti1}(A_1(x), B_0(x)); // T(n/2)$

$Z(x) \leftarrow \text{PolyMulti1}(A_1(x), B_1(x)); // T(n/2)$

return $(U(x) + [V(x) + W(x)]x^{\frac{n}{2}} + Z(x)x^n); // O(n)$

The First Divide-and-Conquer Algorithm

PolyMulti1($A(x), B(x)$)

Input: $A(x), B(x)$

Output: $A(x) \times B(x)$

$A_0(x) \leftarrow a_0 + a_1x + \cdots + a_{\frac{n}{2}-1}x^{\frac{n}{2}-1};$

$A_1(x) \leftarrow a_{\frac{n}{2}} + a_{\frac{n}{2}+1}x + \cdots + a_nx^{\frac{n}{2}};$

$B_0(x) \leftarrow b_0 + b_1x + \cdots + b_{\frac{n}{2}-1}x^{\frac{n}{2}-1};$

$B_1(x) \leftarrow b_{\frac{n}{2}} + b_{\frac{n}{2}+1}x + \cdots + b_nx^{\frac{n}{2}};$

$U(x) \leftarrow \text{PolyMulti1}(A_0(x), B_0(x)); // T(n/2)$

$V(x) \leftarrow \text{PolyMulti1}(A_0(x), B_1(x)); // T(n/2)$

$W(x) \leftarrow \text{PolyMulti1}(A_1(x), B_0(x)); // T(n/2)$

$Z(x) \leftarrow \text{PolyMulti1}(A_1(x), B_1(x)); // T(n/2)$

return $(U(x) + [V(x) + W(x)]x^{\frac{n}{2}} + Z(x)x^n); // O(n)$

$$T(n) = \begin{cases} 4T(n/2) + n, & \text{if } n > 1, \\ 1, & \text{if } n = 1. \end{cases}$$

Analysis of Running Time


Assume that n is a power of 2

$$T(n) = \begin{cases} 4T(n/2) + n, & \text{if } n > 1, \\ 1, & \text{if } n = 1. \end{cases}$$

Analysis of Running Time

Assume that n is a power of 2

$$T(n) = \begin{cases} 4T(n/2) + n, & \text{if } n > 1, \\ 1, & \text{if } n = 1. \end{cases}$$




$$4^{\log n} = n^{\log 4} = n^2$$

$$\text{Total} = O(n^2)$$

Analysis of Running Time

Assume that n is a power of 2

$$T(n) = \begin{cases} 4T(n/2) + n, & \text{if } n > 1, \\ 1, & \text{if } n = 1. \end{cases}$$




Same order as the brute force approach!

Analysis of Running Time

Assume that n is a power of 2

$$T(n) = \begin{cases} 4T(n/2) + n, & \text{if } n > 1, \\ 1, & \text{if } n = 1. \end{cases}$$



Same order as the brute force approach! No improvement!

Outline

- Review to Divide-and-Conquer Paradigm
- **Polynomial Multiplication Problem**
 - Problem definition
 - A brute force algorithm
 - A first divide-and-conquer algorithm
 - **An improved divide-and-conquer algorithm**
 - Analysis of the divide-and-conquer algorithm
- Quicksort Problem
 - Basic partition
 - Randomized partition and randomized quicksort
 - Analysis of the randomized quicksort

Two Observations

Observation 1:

What we really need are the following 3 terms:

$$A_0B_0, A_0B_1 + A_1B_0, A_1B_1?$$

Instead of the following 4 terms:

$$A_0B_0, A_0B_1, A_1B_0, A_1B_1?$$

Two Observations

Observation 1:

What we really need are the following 3 terms:

$$A_0B_0, A_0B_1 + A_1B_0, A_1B_1?$$

Instead of the following 4 terms:

$$A_0B_0, A_0B_1, A_1B_0, A_1B_1?$$

Observation 2:

The three terms can be obtained using only 3 multiplications:

Two Observations

Observation 1:

What we really need are the following 3 terms:

$$A_0B_0, A_0B_1 + A_1B_0, A_1B_1?$$

Instead of the following 4 terms:

$$A_0B_0, A_0B_1, A_1B_0, A_1B_1?$$

Observation 2:

The three terms can be obtained using only 3 multiplications:

$$Y = (A_0 + A_1)(B_0 + B_1)$$

$$U = A_0B_0$$

$$Z = A_1B_1$$

Two Observations

Observation 1:

What we really need are the following 3 terms:

$$A_0B_0, A_0B_1 + A_1B_0, A_1B_1?$$

Instead of the following 4 terms:

$$A_0B_0, A_0B_1, A_1B_0, A_1B_1?$$

Observation 2:

The three terms can be obtained using only 3 multiplications:

$$Y = (A_0 + A_1)(B_0 + B_1)$$

$$U = A_0B_0$$

$$Z = A_1B_1$$

- *U and Z are what we originally wanted*

Two Observations

Observation 1:

What we really need are the following 3 terms:

$$A_0B_0, A_0B_1 + A_1B_0, A_1B_1?$$

Instead of the following 4 terms:

$$A_0B_0, A_0B_1, A_1B_0, A_1B_1?$$

Observation 2:

The three terms can be obtained using only 3 multiplications:

$$Y = (A_0 + A_1)(B_0 + B_1)$$

$$U = A_0B_0$$

$$Z = A_1B_1$$

- U and Z are what we originally wanted
- $A_0B_1 + A_1B_0 =$

Two Observations

Observation 1:

What we really need are the following 3 terms:

$$A_0B_0, A_0B_1 + A_1B_0, A_1B_1?$$

Instead of the following 4 terms:

$$A_0B_0, A_0B_1, A_1B_0, A_1B_1?$$

Observation 2:

The three terms can be obtained using only 3 multiplications:

$$Y = (A_0 + A_1)(B_0 + B_1)$$

$$U = A_0B_0$$

$$Z = A_1B_1$$

- U and Z are what we originally wanted
- $A_0B_1 + A_1B_0 = Y - U - Z$

The improved Divide-and-Conquer Algorithm

PolyMulti2($A(x), B(x)$)

Input: $A(x), B(x)$

Output: $A(x) \times B(x)$

$$A_0(x) \leftarrow a_0 + a_1x + \cdots + a_{\frac{n}{2}-1}x^{\frac{n}{2}-1};$$

$$A_1(x) \leftarrow a_{\frac{n}{2}} + a_{\frac{n}{2}+1}x + \cdots + a_nx^{n-\frac{n}{2}};$$

$$B_0(x) \leftarrow b_0 + b_1x + \cdots + b_{\frac{n}{2}-1}x^{\frac{n}{2}-1};$$

$$B_1(x) \leftarrow b_{\frac{n}{2}} + b_{\frac{n}{2}+1}x + \cdots + b_nx^{n-\frac{n}{2}};$$

The improved Divide-and-Conquer Algorithm

PolyMulti2($A(x), B(x)$)

Input: $A(x), B(x)$

Output: $A(x) \times B(x)$

$$A_0(x) \leftarrow a_0 + a_1x + \cdots + a_{\frac{n}{2}-1}x^{\frac{n}{2}-1};$$

$$A_1(x) \leftarrow a_{\frac{n}{2}} + a_{\frac{n}{2}+1}x + \cdots + a_nx^{n-\frac{n}{2}};$$

$$B_0(x) \leftarrow b_0 + b_1x + \cdots + b_{\frac{n}{2}-1}x^{\frac{n}{2}-1};$$

$$B_1(x) \leftarrow b_{\frac{n}{2}} + b_{\frac{n}{2}+1}x + \cdots + b_nx^{n-\frac{n}{2}};$$

$$Y(x) \leftarrow \text{PolyMulti2}(A_0(x) + A_1(x), B_0(x) + B_1(x)); // T(n/2)$$

$$U(x) \leftarrow \text{PolyMulti2}(A_0(x), B_0(x)); // T(n/2)$$

$$Z(x) \leftarrow \text{PolyMulti2}(A_1(x), B_1(x)); // T(n/2)$$

The Second Divide-and-Conquer Algorithm

PolyMulti2($A(x), B(x)$)

Input: $A(x), B(x)$

Output: $A(x) \times B(x)$

$A_0(x) \leftarrow a_0 + a_1x + \cdots + a_{\frac{n}{2}-1}x^{\frac{n}{2}-1};$

$A_1(x) \leftarrow a_{\frac{n}{2}} + a_{\frac{n}{2}+1}x + \cdots + a_nx^{n-\frac{n}{2}};$

$B_0(x) \leftarrow b_0 + b_1x + \cdots + b_{\frac{n}{2}-1}x^{\frac{n}{2}-1};$

$B_1(x) \leftarrow b_{\frac{n}{2}} + b_{\frac{n}{2}+1}x + \cdots + b_nx^{n-\frac{n}{2}};$

$Y(x) \leftarrow \text{PolyMulti2}(A_0(x) + A_1(x), B_0(x) + B_1(x)); // T(n/2)$

$U(x) \leftarrow \text{PolyMulti2}(A_0(x), B_0(x)); // T(n/2)$

$Z(x) \leftarrow \text{PolyMulti2}(A_1(x), B_1(x)); // T(n/2)$

return $(U(x) + [Y(x) - U(x) - Z(x)]x^{\frac{n}{2}} + Z(x)x^{2\frac{n}{2}}); // O(n)$

The improved Divide-and-Conquer Algorithm

PolyMulti2($A(x), B(x)$)

Input: $A(x), B(x)$

Output: $A(x) \times B(x)$

$A_0(x) \leftarrow a_0 + a_1x + \cdots + a_{\frac{n}{2}-1}x^{\frac{n}{2}-1};$

$A_1(x) \leftarrow a_{\frac{n}{2}} + a_{\frac{n}{2}+1}x + \cdots + a_nx^{n-\frac{n}{2}};$

$B_0(x) \leftarrow b_0 + b_1x + \cdots + b_{\frac{n}{2}-1}x^{\frac{n}{2}-1};$

$B_1(x) \leftarrow b_{\frac{n}{2}} + b_{\frac{n}{2}+1}x + \cdots + b_nx^{n-\frac{n}{2}};$

$Y(x) \leftarrow \text{PolyMulti2}(A_0(x) + A_1(x), B_0(x) + B_1(x)); // T(n/2)$

$U(x) \leftarrow \text{PolyMulti2}(A_0(x), B_0(x)); // T(n/2)$

$Z(x) \leftarrow \text{PolyMulti2}(A_1(x), B_1(x)); // T(n/2)$

return $(U(x) + [Y(x) - U(x) - Z(x)]x^{\frac{n}{2}} + Z(x)x^{2\frac{n}{2}}); // O(n)$


$$T(n) = \begin{cases} 3T(n/2) + n, & \text{if } n > 1, \\ 1, & \text{if } n = 1. \end{cases}$$

Running Time of the Improved Algorithm

$$T(n) = \begin{cases} 3T(n/2) + n, & \text{if } n > 1, \\ 1, & \text{if } n = 1. \end{cases}$$

Running Time of the Improved Algorithm

$$T(n) = \begin{cases} 3T(n/2) + n, & \text{if } n > 1, \\ 1, & \text{if } n = 1. \end{cases}$$




$$3^{\log n} = n^{\log 3}$$

$$\text{Total} = O(n^{\log 3})$$

Running Time of the Improved Algorithm

$$T(n) = \begin{cases} 3T(n/2) + n, & \text{if } n > 1, \\ 1, & \text{if } n = 1. \end{cases}$$



Outline

- Review to Divide-and-Conquer Paradigm
- **Polynomial Multiplication Problem**
 - Problem definition
 - A brute force algorithm
 - A first divide-and-conquer algorithm
 - An improved divide-and-conquer algorithm
 - **Analysis of the divide-and-conquer algorithm**
- **Quicksort Problem**
 - Basic partition
 - Randomized partition and randomized quicksort
 - Analysis of the randomized quicksort

Analysis of the D&C algorithm

- The divide-and-conquer approach does not always give you the best solution
 - Our original algorithm was just as bad as brute force

Analysis of the D&C algorithm

- The divide-and-conquer approach does not always give you the best solution
 - Our original algorithm was just as bad as brute force
- There is actually an $O(n \log n)$ solution to the polynomial multiplication problem

Analysis of the D&C algorithm

- The divide-and-conquer approach does not always give you the best solution
 - Our original algorithm was just as bad as brute force
- There is actually an $O(n \log n)$ solution to the polynomial multiplication problem
 - It involves using the **Fast Fourier Transform** algorithm as a subroutine
 - The FFT is another classic divide-and-conquer algorithm(check Chapt 30 in CLRS if interested)

Analysis of the D&C algorithm

- The divide-and-conquer approach does not always give you the best solution
 - Our original algorithm was just as bad as brute force
- There is actually an $O(n \log n)$ solution to the polynomial multiplication problem
 - It involves using the **Fast Fourier Transform** algorithm as a subroutine
 - The FFT is another classic divide-and-conquer algorithm(check Chapt 30 in CLRS if interested)
- The idea of using 3 multiplications instead of 4 is used in large-integer multiplications
 - A similar idea is the basis of the classic **Strassen matrix multiplication algorithm** (CLRS 4.2)

Outline


- Review to Divide-and-Conquer Paradigm
- Polynomial Multiplication Problem
 - Problem definition
 - A brute force algorithm
 - A first divide-and-conquer algorithm
 - An improved divide-and-conquer algorithm
 - Analysis of the divide-and-conquer algorithm
- **Quicksort Problem**
 - **Basic partition**
 - Randomized partition and randomized quicksort
 - Analysis of the randomized quicksort

Partition

- Partition

- **Given:** An array of numbers
- **Partition:** Rearrange the array $A[p..r]$ **in place** into two (possibly empty) subarrays $A[p..q-1]$ and $A[q+1..r]$ such that

$A[u] < A[q] < A[v]$ for any $p \leq u \leq q-1$ and $q+1 \leq v \leq r$




$$x = A[r]$$

Partition

- Partition

- **Given:** An array of numbers
- **Partition:** Rearrange the array $A[p..r]$ **in place** into two (possibly empty) subarrays $A[p..q-1]$ and $A[q+1..r]$ such that

$A[u] < A[q] < A[v]$ for any $p \leq u \leq q-1$ and $q+1 \leq v \leq r$



$$x = A[r]$$


- x is called the **pivot**. Assume $x = A[r]$; if not, swap first

Partition

- Partition

- **Given**: An array of numbers
- **Partition**: Rearrange the array $A[p..r]$ **in place** into two (possibly empty) subarrays $A[p..q-1]$ and $A[q+1..r]$ such that

$A[u] < A[q] < A[v]$ for any $p \leq u \leq q-1$ and $q+1 \leq v \leq r$



$$x = A[r]$$


- x is called the **pivot**. Assume $x = A[r]$; if not, swap first
- **Quicksort** works by:

Partition

- Partition

- **Given:** An array of numbers
- **Partition:** Rearrange the array $A[p..r]$ **in place** into two (possibly empty) subarrays $A[p..q-1]$ and $A[q+1..r]$ such that

$A[u] < A[q] < A[v]$ for any $p \leq u \leq q-1$ and $q+1 \leq v \leq r$



$$x = A[r]$$


- x is called the **pivot**. Assume $x = A[r]$; if not, swap first
- **Quicksort** works by:
 - calling partition first

Partition

- Partition

- Given: An array of numbers
- Partition: Rearrange the array $A[p..r]$ **in place** into two (possibly empty) subarrays $A[p..q-1]$ and $A[q+1..r]$ such that

$A[u] < A[q] < A[v]$ for any $p \leq u \leq q-1$ and $q+1 \leq v \leq r$



$$x = A[r]$$


- x is called the **pivot**. Assume $x = A[r]$; if not, swap first
- Quicksort works by:
 - calling partition first
 - recursively sorting $A[p..q-1]$ and $A[q+1..r]$

Partition

- Partition

- **Given:** An array of numbers
- **Partition:** Rearrange the array $A[p..r]$ **in place** into two (possibly empty) subarrays $A[p..q-1]$ and $A[q+1..r]$ such that

$A[u] < A[q] < A[v]$ for any $p \leq u \leq q-1$ and $q+1 \leq v \leq r$



$$x = A[r]$$


- x is called the **pivot**. Assume $x = A[r]$; if not, swap first
- **Quicksort** works by:
 - calling partition first
 - recursively sorting $A[p..q-1]$ and $A[q+1..r]$

Partition

- Partition

- **Given:** An array of numbers
- **Partition:** Rearrange the array $A[p..r]$ **in place** into two (possibly empty) subarrays $A[p..q-1]$ and $A[q+1..r]$ such that

$A[u] < A[q] < A[v]$ for any $p \leq u \leq q-1$ and $q+1 \leq v \leq r$




$$x = A[r]$$

- x is called the **pivot**. Assume $x = A[r]$; if not, swap first
- **Quicksort** works by:
 - calling partition first
 - recursively sorting $A[p..q-1]$ and $A[q+1..r]$


Partition

- The idea of Partition(A, p, r)
 - Use A[r] as the pivot, and grow partition from left to right



Partition

- The idea of Partition(A, p, r)
 - Use $A[r]$ as the pivot, and grow partition from left to right



- Initially $(i, j) = (p-1, p)$
- Increase j by 1 each time to find a place for $A[j]$
 - At the same time increase i when necessary
- Stops when $j = r$


Partition

- One Iteration of the Procedure Partition
 - Increase j by 1 each time to find a place for $A[j]$
At the same time increase i when necessary

Partition

- One Iteration of the Procedure Partition
 - Increase j by 1 each time to find a place for $A[j]$


At the same time increase i when necessary



Partition

- One Iteration of the Procedure Partition
 - Increase j by 1 each time to find a place for $A[j]$

At the same time increase i when necessary




- Case (A): Only increase j by 1

Partition

- One Iteration of the Procedure Partition
 - Increase j by 1 each time to find a place for $A[j]$


At the same time increase i when necessary



- Case (A): Only increase j by 1
- Case (B): $i = i + 1$; $A[i] \leftrightarrow A[j]$; $j = j + 1$.


Partition-Example

- The Operation of Partition(A , p , r)



Partition-Example


- The Operation of Partition(A , p , r)



$$A[j] < A[r]$$

Partition-Example

- The Operation of Partition(A, p, r)



$$i = i + 1, A[i] \leftrightarrow A[j], j = j + 1$$

Partition-Example


- The Operation of Partition(A , p , r)

p,i	j						r
2	8	7	1	3	5	6	4

$$A[j] > A[r]$$

Partition-Example


- The Operation of Partition(A, p, r)



Increase j by 1

Partition-Example


- The Operation of Partition(A , p , r)



$$A[j] > A[r]$$

Partition-Example


- The Operation of Partition(A, p, r)



Increase j by 1

Partition-Example


- The Operation of Partition(A , p , r)



$$A[j] < A[r]$$

Partition-Example


- The Operation of Partition(A, p, r)



$$i = i + 1, A[i] \leftrightarrow A[j], j = j + 1$$

Partition-Example


- The Operation of Partition(A , p , r)



$$A[j] < A[r]$$

Partition-Example


- The Operation of Partition(A, p, r)



$$i = i + 1, A[i] \leftrightarrow A[j], j = j + 1$$

Partition-Example


- The Operation of Partition(A , p , r)



$$A[j] > A[r]$$

Partition-Example


- The Operation of Partition(A , p , r)



Increase j by 1

Partition-Example


- The Operation of Partition(A , p , r)



$$A[j] > A[r]$$

Partition-Example


- The Operation of Partition(A , p , r)



Increase j by 1

Partition-Example

- The Operation of Partition(A, p, r)



Partition-Example

- The Operation of Partition(A , p , r)



$$A[i + 1] \leftrightarrow A[r]$$

Partition - Pseudocode

Partition(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: Index of the pivot after partition

$x \leftarrow A[r]$; // $A[r]$ is the pivot element

Partition - Pseudocode

Partition(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: Index of the pivot after partition

$x \leftarrow A[r]$; // $A[r]$ is the pivot element

$i \leftarrow p - 1$;

Partition - Pseudocode

Partition(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: Index of the pivot after partition

$x \leftarrow A[r]$; // $A[r]$ is the pivot element

$i \leftarrow p - 1$;

for $j \leftarrow p$ *to* $r - 1$ **do**

|

end

Partition - Pseudocode

Partition(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: Index of the pivot after partition

$x \leftarrow A[r]$; // $A[r]$ is the pivot element

$i \leftarrow p - 1$;

for $j \leftarrow p$ *to* $r - 1$ **do**

if $A[j] \leq x$ **then**

 |

end

end

Partition - Pseudocode

Partition(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: Index of the pivot after partition

$x \leftarrow A[r]$; // $A[r]$ is the pivot element

$i \leftarrow p - 1$;

for $j \leftarrow p$ *to* $r - 1$ **do**

if $A[j] \leq x$ **then**

$i \leftarrow i + 1$;

 exchange $A[i]$ and $A[j]$;

end

end

Partition - Pseudocode

Partition(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: Index of the pivot after partition

$x \leftarrow A[r]$; // $A[r]$ is the pivot element

$i \leftarrow p - 1$;

for $j \leftarrow p$ *to* $r - 1$ **do**

if $A[j] \leq x$ **then**

$i \leftarrow i + 1$;

 exchange $A[i]$ and $A[j]$;

end

end

exchange $A[i + 1]$ and $A[r]$; // Put pivot in position

Partition - Pseudocode

Partition(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: Index of the pivot after partition

$x \leftarrow A[r]$; // $A[r]$ is the pivot element

$i \leftarrow p - 1$;

for $j \leftarrow p$ *to* $r - 1$ **do**

if $A[j] \leq x$ **then**

$i \leftarrow i + 1$;

 exchange $A[i]$ and $A[j]$;

end

end

exchange $A[i + 1]$ and $A[r]$; // Put pivot in position

return

Partition - Pseudocode

Partition(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: Index of the pivot after partition

$x \leftarrow A[r]$; // $A[r]$ is the pivot element

$i \leftarrow p - 1$;

for $j \leftarrow p$ *to* $r - 1$ **do**

if $A[j] \leq x$ **then**

$i \leftarrow i + 1$;

 exchange $A[i]$ and $A[j]$;

end

end

exchange $A[i + 1]$ and $A[r]$; // Put pivot in position

return $i + 1$; // $q \leftarrow i + 1$

Partition - Pseudocode

Partition(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: Index of the pivot after partition

$x \leftarrow A[r]$; // $A[r]$ is the pivot element

$i \leftarrow p - 1$;

for $j \leftarrow p$ *to* $r - 1$ **do**

if $A[j] \leq x$ **then**

$i \leftarrow i + 1$;

 exchange $A[i]$ and $A[j]$;

end

end

exchange $A[i + 1]$ and $A[r]$; // Put pivot in position

return $i + 1$; // $q \leftarrow i + 1$

- Running time is $O(\quad)$

Partition - Pseudocode

Partition(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: Index of the pivot after partition

$x \leftarrow A[r]$; // $A[r]$ is the pivot element

$i \leftarrow p - 1$;

for $j \leftarrow p$ *to* $r - 1$ **do**

if $A[j] \leq x$ **then**

$i \leftarrow i + 1$;

 exchange $A[i]$ and $A[j]$;

end

end

exchange $A[i + 1]$ and $A[r]$; // Put pivot in position

return $i + 1$; // $q \leftarrow i + 1$

- Running time is $O(r - p)$

Partition - Pseudocode

Partition(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: Index of the pivot after partition

$x \leftarrow A[r]$; // $A[r]$ is the pivot element

$i \leftarrow p - 1$;

for $j \leftarrow p$ *to* $r - 1$ **do**

if $A[j] \leq x$ **then**

$i \leftarrow i + 1$;

 exchange $A[i]$ and $A[j]$;

end

end

exchange $A[i + 1]$ and $A[r]$; // Put pivot in position

return $i + 1$; // $q \leftarrow i + 1$

- Running time is $O(r - p)$
 - linear in the length of the array $A[p..r]$

Quicksort

Quicksort(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: Sorted array A

if $p < r$ **then**

$q \leftarrow \text{Partition}(A, p, r);$

 Quicksort($A, \quad \quad$);

 Quicksort($A, \quad \quad$);

end

return A ;

Quicksort

Quicksort(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: Sorted array A

if $p < r$ **then**

$q \leftarrow \text{Partition}(A, p, r);$

 Quicksort($A, p, q - 1$);

 Quicksort(A, q, r);

end

return A ;

Quicksort

Quicksort(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: Sorted array A

if $p < r$ **then**

$q \leftarrow \text{Partition}(A, p, r);$

 Quicksort($A, p, q - 1$);

 Quicksort($A, q + 1, r$);

end

return A ;

A Divide-and-Conquer Framework

Quicksort

Quicksort(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: Sorted array A

if $p < r$ **then**

$q \leftarrow \text{Partition}(A, p, r);$

 Quicksort($A, p, q - 1$);

 Quicksort($A, q + 1, r$);

end

return A ;

A Divide-and-Conquer Framework

- If we could always partition the array into halves, then we have the recurrence $T(n) \leq 2T(n/2) + O(n)$, hence $T(n) = O(n \log n)$.

Quicksort

Quicksort(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: Sorted array A

if $p < r$ **then**

$q \leftarrow \text{Partition}(A, p, r);$

 Quicksort($A, p, q - 1$);

 Quicksort($A, q + 1, r$);

end

return A ;

A Divide-and-Conquer Framework

- If we could always partition the array into halves, then we have the recurrence $T(n) \leq 2T(n/2) + O(n)$, hence $T(n) = O(n \log n)$.
- However, if we always get unlucky with very unbalanced partitions, then $T(n) \leq T(n - 1) + O(n)$, hence $T(n) = O(n^2)$.

Outline

- Review to Divide-and-Conquer Paradigm
- Polynomial Multiplication Problem
 - Problem definition
 - A brute force algorithm
 - A first divide-and-conquer algorithm
 - An improved divide-and-conquer algorithm
 - Analysis of the divide-and-conquer algorithm
- Quicksort Problem
 - Basic partition
 - Randomized partition and randomized quicksort
 - Analysis of the randomized quicksort

Randomized-Partition(A, p, r)

- Idea

- In the algorithm Partition(A, p, r), $A[r]$ is always used as the pivot x to partition the array $A[p..r]$.



Randomized-Partition(A, p, r)

- Idea

- In the algorithm Partition(A, p, r), $A[r]$ is always used as the pivot x to partition the array $A[p..r]$.
- In the algorithm **Randomized**-Partition(A, p, r), we **randomly** choose an j , $p \leq j \leq r$, and use $A[j]$ as pivot.



Randomized-Partition(A, p, r)

- Idea

- In the algorithm Partition(A, p, r), $A[r]$ is always used as the pivot x to partition the array $A[p..r]$.
- In the algorithm **Randomized**-Partition(A, p, r), we **randomly** choose an j , $p \leq j \leq r$, and use $A[j]$ as pivot.
- Idea is that if we choose randomly, then the chance that we get unlucky every time is extremely low.



Randomized-Partition(A, p, r)

- Pseudocode of Randomized-Partition
 - Let `random(p, r)` be a pseudorandom-number generator that returns a random number between p and r.

Randomized-Partition(A, p, r)

- Pseudocode of Randomized-Partition
 - Let $\text{random}(p, r)$ be a pseudorandom-number generator that returns a random number between p and r .

Randomized-Partition(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: A random index in $[p..j]$

Partition(A, p, r);

return j ;

Randomized-Partition(A, p, r)

- Pseudocode of Randomized-Partition
 - Let $\text{random}(p, r)$ be a pseudorandom-number generator that returns a random number between p and r .

Randomized-Partition(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: A random index in $[p..r]$

$j \leftarrow \text{random}(p, r);$

Partition(A, p, r);

return j ;

Randomized-Partition(A, p, r)

- Pseudocode of Randomized-Partition
 - Let **random**(p, r) be a pseudorandom-number generator that returns a random number between p and r .

Randomized-Partition(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: A random index in $[p..r]$

$j \leftarrow \text{random}(p, r);$

exchange $A[r]$ and $A[j];$

Partition(A, p, r);

return j ;

Randomized-Partition(A, p, r)

- Pseudocode of Randomized-Quicksort
 - We make use of the Randomized-Partition idea to develop a new version of quicksort.

Randomized-Partition(A, p, r)

- Pseudocode of Randomized-Quicksort
 - We make use of the Randomized-Partition idea to develop a new version of quicksort.

Randomized-Quicksort(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: Sorted array A

```

if  $p < r$  then
     $q \leftarrow$  Randomized-Partition( $A, p, r$ );
    Randomized-Quicksort( $A, \quad$ );
    Randomized-Quicksort( $A, \quad$ );
end
return  $A$ ;
  
```

Randomized-Partition(A, p, r)

- Pseudocode of Randomized-Quicksort
 - We make use of the Randomized-Partition idea to develop a new version of quicksort.

Randomized-Quicksort(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: Sorted array A

```

if  $p < r$  then
     $q \leftarrow$  Randomized-Partition( $A, p, r$ );
    Randomized-Quicksort( $A, p, q - 1$ );
    Randomized-Quicksort( $A, q, r$ );
end
return  $A$ ;
  
```

Randomized-Partition(A, p, r)

- Pseudocode of Randomized-Quicksort
 - We make use of the Randomized-Partition idea to develop a new version of quicksort.

Randomized-Quicksort(A, p, r)

Input: An array A waiting to be sorted, the range of index p, r

Output: Sorted array A

```

if  $p < r$  then
     $q \leftarrow$  Randomized-Partition( $A, p, r$ );
    Randomized-Quicksort( $A, p, q - 1$ );
    Randomized-Quicksort( $A, q + 1, r$ );
end
return  $A$ ;
  
```


Quicksort - Example

2	8	7	1	3	5	6	4
---	---	---	---	---	---	---	---

Quicksort - Example

Divide

2	8	7	1	3	5	6	4
---	---	---	---	---	---	---	---



Quicksort - Example

Divide

2	8	7	1	3	5	6	4
---	---	---	---	---	---	---	---



Quicksort - Example

Divide


2	8	7	1	3	5	6	4
---	---	---	---	---	---	---	---



2	1	3	4	7	5	6	8
---	---	---	---	---	---	---	---

Quicksort - Example

Divide




Quicksort - Example

Divide

2	8	7	1	3	5	6	4
---	---	---	---	---	---	---	---




2	1	3	4	7	5	6	8
---	---	---	---	---	---	---	---




Quicksort - Example

Divide




Quicksort - Example

Divide




Quicksort - Example

Divide




Quicksort - Example

Divide




Quicksort - Example

Divide




Quicksort - Example

Divide




Quicksort - Example

Divide




Quicksort - Example

Divide




Quicksort - Example

Divide




Quicksort - Example

Divide




Quicksort - Example

Divide




Quicksort - Example

Divide




Quicksort - Example

Divide




Quicksort - Example

Divide




Quicksort - Example

Divide




Quicksort - Example

Divide




Quicksort - Example

Divide



Quicksort - Example

Divide




Quicksort - Example

Conquer




Quicksort - Example

Conquer




Quicksort - Example

Conquer




Quicksort - Example

Conquer




Quicksort - Example

Conquer




Quicksort - Example

Conquer



Quicksort - Example

Conquer



Outline

- Review to Divide-and-Conquer Paradigm
- Polynomial Multiplication Problem
 - Problem definition
 - A brute force algorithm
 - A first divide-and-conquer algorithm
 - An improved divide-and-conquer algorithm
 - Analysis of the divide-and-conquer algorithm
- Quicksort Problem
 - Basic partition
 - Randomized partition and randomized quicksort
 - Analysis of the randomized quicksort

Running Time of the Quicksort

- Measuring running time:

Running Time of the Quicksort

- Measuring running time:
 - The running time is dominated by the time spent in partition.

Running Time of the Quicksort

- Measuring running time:
 - The running time is dominated by the time spent in partition.
 - The running time of the partition procedure can be measured by the **number of key comparisons**.

Running Time of the Quicksort

- Measuring running time:
 - The running time is dominated by the time spent in partition.
 - The running time of the partition procedure can be measured by the **number of key comparisons**.
- $T(n)$: running time on array of size n .
- Recurrence: $T(n) =$

Running Time of the Quicksort

- Measuring running time:
 - The running time is dominated by the time spent in partition.
 - The running time of the partition procedure can be measured by the **number of key comparisons**.
- $T(n)$: running time on array of size n .
- Recurrence: $T(n) = T(m) +$

Running Time of the Quicksort

- Measuring running time:
 - The running time is dominated by the time spent in partition.
 - The running time of the partition procedure can be measured by the **number of key comparisons**.
- $T(n)$: running time on array of size n .
- Recurrence: $T(n) = T(m) + T(n - m - 1) +$

Running Time of the Quicksort

- Measuring running time:
 - The running time is dominated by the time spent in partition.
 - The running time of the partition procedure can be measured by the **number of key comparisons**.
- $T(n)$: running time on array of size n .
- Recurrence: $T(n) = T(m) + T(n - m - 1) + O(n)$

Running Time of the Quicksort

- Measuring running time:
 - The running time is dominated by the time spent in partition.
 - The running time of the partition procedure can be measured by the **number of key comparisons**.
- $T(n)$: running time on array of size n .
- Recurrence: $T(n) = T(m) + T(n - m - 1) + O(n)$
- **Worst Case:**

Running Time of the Quicksort

- Measuring running time:
 - The running time is dominated by the time spent in partition.
 - The running time of the partition procedure can be measured by the **number of key comparisons**.
- $T(n)$: running time on array of size n .
- Recurrence: $T(n) = T(m) + T(n - m - 1) + O(n)$
- **Worst Case:**

$$T(n) = T(0) + T(n - 1) + O(n)$$

Running Time of the Quicksort

- Measuring running time:
 - The running time is dominated by the time spent in partition.
 - The running time of the partition procedure can be measured by the **number of key comparisons**.
- $T(n)$: running time on array of size n .
- Recurrence: $T(n) = T(m) + T(n - m - 1) + O(n)$
- **Worst Case:**

$$T(n) = T(0) + T(n - 1) + O(n)$$

$$T(n) = O(n^2)$$

Running Time of the Quicksort

- Measuring running time:
 - The running time is dominated by the time spent in partition.
 - The running time of the partition procedure can be measured by the **number of key comparisons**.
- $T(n)$: running time on array of size n .
- Recurrence: $T(n) = T(m) + T(n - m - 1) + O(n)$
- **Worst Case:**

$$T(n) = T(0) + T(n - 1) + O(n)$$
$$T(n) = O(n^2)$$

Running Time of the Quicksort

- Measuring running time:
 - The running time is dominated by the time spent in partition.
 - The running time of the partition procedure can be measured by the **number of key comparisons**.
- $T(n)$: running time on array of size n .
- Recurrence: $T(n) = T(m) + T(n - m - 1) + O(n)$
- **Worst Case:**
$$T(n) = T(0) + T(n - 1) + O(n)$$
$$T(n) = O(n^2)$$
- What inputs give worst case performance?

Running Time of the Quicksort

- Measuring running time:
 - The running time is dominated by the time spent in partition.
 - The running time of the partition procedure can be measured by the **number of key comparisons**.
- $T(n)$: running time on array of size n .
- Recurrence: $T(n) = T(m) + T(n - m - 1) + O(n)$
- **Worst Case:**
$$T(n) = T(0) + T(n - 1) + O(n)$$
$$T(n) = O(n^2)$$
- What inputs give worst case performance?
 - Whether performance is the worst is not determined by input.

Running Time of the Quicksort

- Measuring running time:
 - The running time is dominated by the time spent in partition.
 - The running time of the partition procedure can be measured by the **number of key comparisons**.
- $T(n)$: running time on array of size n .
- Recurrence: $T(n) = T(m) + T(n - m - 1) + O(n)$
- **Worst Case:**
$$T(n) = T(0) + T(n - 1) + O(n)$$
$$T(n) = O(n^2)$$
- What inputs give worst case performance?
 - Whether performance is the worst is not determined by input.
 - An important property of randomized algorithms.

Running Time of the Quicksort

- Measuring running time:
 - The running time is dominated by the time spent in partition.
 - The running time of the partition procedure can be measured by the **number of key comparisons**.
- $T(n)$: running time on array of size n .
- Recurrence: $T(n) = T(m) + T(n - m - 1) + O(n)$
- **Worst Case:**
$$T(n) = T(0) + T(n - 1) + O(n)$$
$$T(n) = O(n^2)$$
- What inputs give worst case performance?
 - Whether performance is the worst is not determined by input.
 - An important property of randomized algorithms.
 - Worst case performance results only if the random number generator always produces the worst choice.

Randomized Algorithms

- Analysis for Randomized Algorithms:
 - Worst-case doesn't make sense: for any given input, the worst case is very unlikely to happen.

Randomized Algorithms

- Analysis for Randomized Algorithms:
 - Worst-case doesn't make sense: for any given input, the worst case is very unlikely to happen.
 - Use **expected running time** analysis for randomized algorithms!

Randomized Algorithms

- Analysis for Randomized Algorithms:
 - Worst-case doesn't make sense: for any given input, the worst case is very unlikely to happen.
 - Use **expected running time** analysis for randomized algorithms!

Average case analysis

- Used for deterministic algorithms

Expected case analysis

- Used for randomized algorithms

Randomized Algorithms

- Analysis for Randomized Algorithms:
 - Worst-case doesn't make sense: for any given input, the worst case is very unlikely to happen.
 - Use **expected running time** analysis for randomized algorithms!

Average case analysis

- Used for deterministic algorithms
- Assume the input is chosen randomly from some distribution

Expected case analysis

- Used for randomized algorithms
- Need to work for **any** given input

Randomized Algorithms

- Analysis for Randomized Algorithms:
 - Worst-case doesn't make sense: for any given input, the worst case is very unlikely to happen.
 - Use **expected running time** analysis for randomized algorithms!

Average case analysis

- Used for deterministic algorithms
- Assume the input is chosen randomly from some distribution
- Depends on assumptions on the input, weaker

Expected case analysis

- Used for randomized algorithms
- Need to work for **any** given input
- Randomization is inherent within the algorithm, stronger

Randomized Algorithms

- Analysis for Randomized Algorithms:
 - Worst-case doesn't make sense: for any given input, the worst case is very unlikely to happen.
 - Use **expected running time** analysis for randomized algorithms!

Average case analysis

- Used for deterministic algorithms
- Assume the input is chosen randomly from some distribution
- Depends on assumptions on the input, weaker
- Not required in this course

Expected case analysis

- Used for randomized algorithms
- Need to work for **any** given input
- Randomization is inherent within the algorithm, stronger
- Required in this course

Expected Case

- Two methods to analyze the expected running time of a divide-and-conquer randomized algorithm:
 - Old fashioned: Write out a recurrence on $T(n)$, where $T(n)$ is the **expected** running time of the algorithm on an input of size n , and solve it.
 - — (Almost) always works but needs complicated maths.

Expected Case

- Two methods to analyze the expected running time of a divide-and-conquer randomized algorithm:
 - Old fashioned: Write out a recurrence on $T(n)$, where $T(n)$ is the **expected** running time of the algorithm on an input of size n , and solve it.
 - (Almost) always works but needs complicated maths.
 - New: Indicator variables.
 - Simple and elegant, but needs practice to master.

Expected Case

- Two facts about key comparisons:


Expected Case

- Two facts about key comparisons:
 - When a pivot is selected, the pivot is compared with **every** other elements, then the elements are partitioned into two parts accordingly

Expected Case


- Two facts about key comparisons:
 - When a pivot is selected, the pivot is compared with **every** other elements, then the elements are partitioned into two parts accordingly
 - Elements in **different** partitions are **never** compared with each other in **all** operations

Expected Case




$\leq x$ $> x$

(A) $A[j] > x$




$\leq x$ $> x$



$\leq x$ $> x$

(B) $A[j] \leq x$



$\leq x$ $> x$

Expected Running Time

- Expected Running Time of Randomized-Quicksort:
 - Let $z_1 < z_2 < \dots < z_n$ be the n elements in sorted order

Expected Running Time

- Expected Running Time of Randomized-Quicksort:
 - Let $z_1 < z_2 < \dots < z_n$ be the n elements in sorted order
 - X : total number of comparisons performed in **all** calls to randomized-partition

Expected Running Time

- Expected Running Time of Randomized-Quicksort:
 - Let $z_1 < z_2 < \dots < z_n$ be the n elements in sorted order
 - X : total number of comparisons performed in **all** calls to randomized-partition
 - X_{ij} : number of comparisons between z_i and z_j

Expected Running Time

- Expected Running Time of Randomized-Quicksort:
 - Let $z_1 < z_2 < \dots < z_n$ be the n elements in sorted order
 - X : total number of comparisons performed in **all** calls to randomized-partition
 - X_{ij} : number of comparisons between z_i and z_j
 - can only be **0 or 1**

Expected Running Time

- Expected Running Time of Randomized-Quicksort:
 - Let $z_1 < z_2 < \dots < z_n$ be the n elements in sorted order
 - X : total number of comparisons performed in **all** calls to randomized-partition
 - X_{ij} : number of comparisons between z_i and z_j
 - can only be **0 or 1**

$$E[X] =$$

Expected Running Time

- Expected Running Time of Randomized-Quicksort:
 - Let $z_1 < z_2 < \dots < z_n$ be the n elements in sorted order
 - X : total number of comparisons performed in **all** calls to randomized-partition
 - X_{ij} : number of comparisons between z_i and z_j
 - can only be **0 or 1**

$$E[X] = E \left[\sum_{i=1}^{n-1} \sum_{j=i+1}^n X_{ij} \right] =$$

Expected Running Time

- Expected Running Time of Randomized-Quicksort:
 - Let $z_1 < z_2 < \dots < z_n$ be the n elements in sorted order
 - X : total number of comparisons performed in **all** calls to randomized-partition
 - X_{ij} : number of comparisons between z_i and z_j
 - can only be **0 or 1**

$$E[X] = E \left[\sum_{i=1}^{n-1} \sum_{j=i+1}^n X_{ij} \right] = \sum_{i=1}^{n-1} \sum_{j=i+1}^n E[X_{ij}]$$

$$=$$

Expected Running Time

- Expected Running Time of Randomized-Quicksort:
 - Let $z_1 < z_2 < \dots < z_n$ be the n elements in sorted order
 - X : total number of comparisons performed in **all** calls to randomized-partition
 - X_{ij} : number of comparisons between z_i and z_j
 - can only be **0 or 1**

$$\begin{aligned}
 E[X] &= E \left[\sum_{i=1}^{n-1} \sum_{j=i+1}^n X_{ij} \right] = \sum_{i=1}^{n-1} \sum_{j=i+1}^n E[X_{ij}] \\
 &= \sum_{i=1}^{n-1} \sum_{j=i+1}^n [\Pr\{
 \end{aligned}$$

Expected Running Time

- Expected Running Time of Randomized-Quicksort:
 - Let $z_1 < z_2 < \dots < z_n$ be the n elements in sorted order
 - X : total number of comparisons performed in **all** calls to randomized-partition
 - X_{ij} : number of comparisons between z_i and z_j
 - can only be **0 or 1**

$$\begin{aligned}
 E[X] &= E \left[\sum_{i=1}^{n-1} \sum_{j=i+1}^n X_{ij} \right] = \sum_{i=1}^{n-1} \sum_{j=i+1}^n E[X_{ij}] \\
 &= \sum_{i=1}^{n-1} \sum_{j=i+1}^n [\Pr\{z_i \text{ is compared with } z_j\} \times 1 \\
 &\quad + \Pr\{z_i \text{ is not compared with } z_j\} \times \mathbf{0}]
 \end{aligned}$$

Expected Running Time

- Expected Running Time of Randomized-Quicksort:
 - Let $z_1 < z_2 < \dots < z_n$ be the n elements in sorted order
 - X : total number of comparisons performed in **all** calls to randomized-partition
 - X_{ij} : number of comparisons between z_i and z_j
 - can only be **0 or 1**

$$\begin{aligned}
 E[X] &= E \left[\sum_{i=1}^{n-1} \sum_{j=i+1}^n X_{ij} \right] = \sum_{i=1}^{n-1} \sum_{j=i+1}^n E[X_{ij}] \\
 &= \sum_{i=1}^{n-1} \sum_{j=i+1}^n [\Pr\{z_i \text{ is compared with } z_j\} \times 1 \\
 &\quad + \Pr\{z_i \text{ is not compared with } z_j\} \times \mathbf{0}] \\
 &=
 \end{aligned}$$

Expected Running Time

- Expected Running Time of Randomized-Quicksort:
 - Let $z_1 < z_2 < \dots < z_n$ be the n elements in sorted order
 - X : total number of comparisons performed in **all** calls to randomized-partition
 - X_{ij} : number of comparisons between z_i and z_j
 - can only be **0 or 1**

$$\begin{aligned}
 E[X] &= E \left[\sum_{i=1}^{n-1} \sum_{j=i+1}^n X_{ij} \right] = \sum_{i=1}^{n-1} \sum_{j=i+1}^n E[X_{ij}] \\
 &= \sum_{i=1}^{n-1} \sum_{j=i+1}^n [\Pr\{z_i \text{ is compared with } z_j\} \times 1 \\
 &\quad + \Pr\{z_i \text{ is not compared with } z_j\} \times \mathbf{0}] \\
 &= \sum_{i=1}^{n-1} \sum_{j=i+1}^n \Pr\{z_i \text{ is compared with } z_j\}
 \end{aligned}$$

Observations

For $1 \leq i \leq j \leq n$, let $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$

- remember $z_i < z_{i+1} < \dots < z_j$

Observations

For $1 \leq i \leq j \leq n$, let $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$

- remember $z_i < z_{i+1} < \dots < z_j$

Observations:

- Partition divides an array into three segments, left, pivot, and Right.
- When z_i and z_j are first placed in DIFFERENT segments of the array by partitioning, the pivot is one of the elements in Z_{ij}

Observations

For $1 \leq i \leq j \leq n$, let $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$

- remember $z_i < z_{i+1} < \dots < z_j$

Observations:

- Partition divides an array into three segments, left, pivot, and Right.
- When z_i and z_j are first placed in DIFFERENT segments of the array by partitioning, the pivot is one of the elements in Z_{ij}
- If the pivot is either z_i or z_j

Observations

For $1 \leq i \leq j \leq n$, let $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$

- remember $z_i < z_{i+1} < \dots < z_j$

Observations:

- Partition divides an array into three segments, left, pivot, and Right.
- When z_i and z_j are first placed in DIFFERENT segments of the array by partitioning, the pivot is one of the elements in Z_{ij}
- If the pivot is either z_i or z_j
 - z_i and z_j will be compared

Observations

For $1 \leq i \leq j \leq n$, let $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$

- remember $z_i < z_{i+1} < \dots < z_j$

Observations:

- Partition divides an array into three segments, left, pivot, and Right.
- When z_i and z_j are first placed in DIFFERENT segments of the array by partitioning, the pivot is one of the elements in Z_{ij}
- If the pivot is either z_i or z_j
 - z_i and z_j will be compared
- If the pivot is any element in Z_{ij} other than z_i or z_j
 - z_i and z_j are not compared with each other in all randomized-partition calls

How to Find $\Pr\{z_i \text{ is compared with } z_j\}$?

$\Pr\{z_i \text{ is compared with } z_j\}$

=

How to Find $\Pr\{z_i \text{ is compared with } z_j\}$?

$\Pr\{z_i \text{ is compared with } z_j\}$

$= \Pr\{z_i \text{ or } z_j \text{ is the first pivot chosen from } Z_{ij}\}$

$=$

How to Find $\Pr\{z_i \text{ is compared with } z_j\}$?

$\Pr\{z_i \text{ is compared with } z_j\}$

$= \Pr\{z_i \text{ or } z_j \text{ is the first pivot chosen from } Z_{ij}\}$

$= \Pr\{z_i \text{ is the first pivot chosen from } Z_{ij}\}$

+

How to Find $\Pr\{z_i \text{ is compared with } z_j\}$?

$\Pr\{z_i \text{ is compared with } z_j\}$

$= \Pr\{z_i \text{ or } z_j \text{ is the first pivot chosen from } Z_{ij}\}$

$= \Pr\{z_i \text{ is the first pivot chosen from } Z_{ij}\}$

$+ \Pr\{z_j \text{ is the first pivot chosen from } Z_{ij}\}$

$= \frac{1}{j - i + 1} +$

How to Find $\Pr\{z_i \text{ is compared with } z_j\}$?

$\Pr\{z_i \text{ is compared with } z_j\}$

$= \Pr\{z_i \text{ or } z_j \text{ is the first pivot chosen from } Z_{ij}\}$

$= \Pr\{z_i \text{ is the first pivot chosen from } Z_{ij}\}$

$+ \Pr\{z_j \text{ is the first pivot chosen from } Z_{ij}\}$

$$= \frac{1}{j-i+1} + \frac{1}{j-i+1} =$$

How to Find $\Pr\{z_i \text{ is compared with } z_j\}$?

$\Pr\{z_i \text{ is compared with } z_j\}$

$= \Pr\{z_i \text{ or } z_j \text{ is the first pivot chosen from } Z_{ij}\}$

$= \Pr\{z_i \text{ is the first pivot chosen from } Z_{ij}\}$

$+ \Pr\{z_j \text{ is the first pivot chosen from } Z_{ij}\}$

$$= \frac{1}{j-i+1} + \frac{1}{j-i+1} = \frac{2}{j-i+1}$$

How to Find $\Pr\{z_i \text{ is compared with } z_j\}$?

$$\Pr\{z_i \text{ is compared with } z_j\}$$

$$= \Pr\{z_i \text{ or } z_j \text{ is the first pivot chosen from } Z_{ij}\}$$

$$= \Pr\{z_i \text{ is the first pivot chosen from } Z_{ij}\}$$

$$+ \Pr\{z_j \text{ is the first pivot chosen from } Z_{ij}\}$$

$$= \frac{1}{j-i+1} + \frac{1}{j-i+1} = \frac{2}{j-i+1}$$

$$E[X] = \sum_{i=1}^{n-1} \sum_{j=i+1}^n \Pr\{z_i \text{ is compared with } z_j\} =$$

How to Find $\Pr\{z_i \text{ is compared with } z_j\}$?

$$\Pr\{z_i \text{ is compared with } z_j\}$$

$$= \Pr\{z_i \text{ or } z_j \text{ is the first pivot chosen from } Z_{ij}\}$$

$$= \Pr\{z_i \text{ is the first pivot chosen from } Z_{ij}\}$$

$$+ \Pr\{z_j \text{ is the first pivot chosen from } Z_{ij}\}$$

$$= \frac{1}{j-i+1} + \frac{1}{j-i+1} = \frac{2}{j-i+1}$$

$$E[X] = \sum_{i=1}^{n-1} \sum_{j=i+1}^n \Pr\{z_i \text{ is compared with } z_j\} = \sum_{i=1}^{n-1} \sum_{j=i+1}^n \frac{2}{j-i+1}$$

=

How to Find $\Pr\{z_i \text{ is compared with } z_j\}$?

$$\Pr\{z_i \text{ is compared with } z_j\}$$

$$= \Pr\{z_i \text{ or } z_j \text{ is the first pivot chosen from } Z_{ij}\}$$

$$= \Pr\{z_i \text{ is the first pivot chosen from } Z_{ij}\}$$

$$+ \Pr\{z_j \text{ is the first pivot chosen from } Z_{ij}\}$$

$$= \frac{1}{j-i+1} + \frac{1}{j-i+1} = \frac{2}{j-i+1}$$

$$\begin{aligned} E[X] &= \sum_{i=1}^{n-1} \sum_{j=i+1}^n \Pr\{z_i \text{ is compared with } z_j\} = \sum_{i=1}^{n-1} \sum_{j=i+1}^n \frac{2}{j-i+1} \\ &= \sum_{i=1}^{n-1} \sum_{k=1}^{n-i} \frac{2}{k+1} \end{aligned}$$

How to Find $\Pr\{z_i \text{ is compared with } z_j\}$?

$$\Pr\{z_i \text{ is compared with } z_j\}$$

$$= \Pr\{z_i \text{ or } z_j \text{ is the first pivot chosen from } Z_{ij}\}$$

$$= \Pr\{z_i \text{ is the first pivot chosen from } Z_{ij}\}$$

$$+ \Pr\{z_j \text{ is the first pivot chosen from } Z_{ij}\}$$

$$= \frac{1}{j-i+1} + \frac{1}{j-i+1} = \frac{2}{j-i+1}$$

$$E[X] = \sum_{i=1}^{n-1} \sum_{j=i+1}^n \Pr\{z_i \text{ is compared with } z_j\} = \sum_{i=1}^{n-1} \sum_{j=i+1}^n \frac{2}{j-i+1}$$

$$= \sum_{i=1}^{n-1} \sum_{k=1}^{n-i} \frac{2}{k+1} < \sum_{i=1}^{n-1} \sum_{k=1}^n \frac{2}{k}$$

How to Find $\Pr\{z_i \text{ is compared with } z_j\}$?

$$\Pr\{z_i \text{ is compared with } z_j\}$$

$$= \Pr\{z_i \text{ or } z_j \text{ is the first pivot chosen from } Z_{ij}\}$$

$$= \Pr\{z_i \text{ is the first pivot chosen from } Z_{ij}\}$$

$$+ \Pr\{z_j \text{ is the first pivot chosen from } Z_{ij}\}$$

$$= \frac{1}{j-i+1} + \frac{1}{j-i+1} = \frac{2}{j-i+1}$$

$$E[X] = \sum_{i=1}^{n-1} \sum_{j=i+1}^n \Pr\{z_i \text{ is compared with } z_j\} = \sum_{i=1}^{n-1} \sum_{j=i+1}^n \frac{2}{j-i+1}$$

$$= \sum_{i=1}^{n-1} \sum_{k=1}^{n-i} \frac{2}{k+1} < \sum_{i=1}^{n-1} \sum_{k=1}^n \frac{2}{k} = \sum_{i=1}^{n-1} O(\log n)$$

Note: $\sum_{k=1}^n \frac{1}{k} \leq \log(n)$

How to Find $\Pr\{z_i \text{ is compared with } z_j\}$?

$$\Pr\{z_i \text{ is compared with } z_j\}$$

$$= \Pr\{z_i \text{ or } z_j \text{ is the first pivot chosen from } Z_{ij}\}$$

$$= \Pr\{z_i \text{ is the first pivot chosen from } Z_{ij}\}$$

$$+ \Pr\{z_j \text{ is the first pivot chosen from } Z_{ij}\}$$

$$= \frac{1}{j-i+1} + \frac{1}{j-i+1} = \frac{2}{j-i+1}$$

$$E[X] = \sum_{i=1}^{n-1} \sum_{j=i+1}^n \Pr\{z_i \text{ is compared with } z_j\} = \sum_{i=1}^{n-1} \sum_{j=i+1}^n \frac{2}{j-i+1}$$

$$= \sum_{i=1}^{n-1} \sum_{k=1}^{n-i} \frac{2}{k+1} < \sum_{i=1}^{n-1} \sum_{k=1}^n \frac{2}{k} = \sum_{i=1}^{n-1} O(\log n) = O(n \log n)$$

Note: $\sum_{k=1}^n \frac{1}{k} \leq \log(n)$

How to Find $\Pr\{z_i \text{ is compared with } z_j\}$?

$$\Pr\{z_i \text{ is compared with } z_j\}$$

$$= \Pr\{z_i \text{ or } z_j \text{ is the first pivot chosen from } Z_{ij}\}$$

$$= \Pr\{z_i \text{ is the first pivot chosen from } Z_{ij}\}$$

$$+ \Pr\{z_j \text{ is the first pivot chosen from } Z_{ij}\}$$

$$= \frac{1}{j-i+1} + \frac{1}{j-i+1} = \frac{2}{j-i+1}$$

$$E[X] = \sum_{i=1}^{n-1} \sum_{j=i+1}^n \Pr\{z_i \text{ is compared with } z_j\} = \sum_{i=1}^{n-1} \sum_{j=i+1}^n \frac{2}{j-i+1}$$

$$= \sum_{i=1}^{n-1} \sum_{k=1}^{n-i} \frac{2}{k+1} < \sum_{i=1}^{n-1} \sum_{k=1}^n \frac{2}{k} = \sum_{i=1}^{n-1} O(\log n) = O(n \log n)$$

Note: $\sum_{k=1}^n \frac{1}{k} \leq \log(n)$

Hence, the expected number of comparisons is $O(n \log n)$, which is the expected running time of Randomized-Quicksort

dank u
 Tack ju faleminderit
 Asante 谢谢 Tak mulțumesc
 kiitos Gracias
 Salammat! Terima kasih Aliquam
 Merci Dankie Obrigado
 ありがとう köszönöm grazie
 Aliquam Go raibh maith agat
 děkuji Thank you