

# Design and Analysis of Algorithms

## Part IV: Graph Algorithms

### Lecture 12: Single-Source Shortest Paths Problem



**Yongxin Tong (童咏昕)**

School of CSE, Beihang University

[yxtong@buaa.edu.cn](mailto:yxtong@buaa.edu.cn)

# Outline

---

- Review to Part IV
- Single-Source Shortest Paths Problem
- Dijkstra's Algorithm
  - The idea
  - The algorithm
  - Analysis of Dijkstra's algorithm
- The Bellman-Ford Algorithm
  - The algorithm
  - Analysis of Bellman-Ford algorithm

# Outline

---

- Review to Part IV
- Single-Source Shortest Paths Problem
- Dijkstra's Algorithm
  - The idea
  - The algorithm
  - Analysis of Dijkstra's algorithm
- The Bellman-Ford Algorithm
  - The algorithm
  - Analysis of Bellman-Ford algorithm

# Introduction to Part IV

---

- In Part IV, we will illustrate several graph algorithm problems using several examples:
  - Basic Concepts of Graphs (图的基本概念)
  - Breadth-First Search [BFS] (广度优先搜索)
  - Depth-First Search [DFS] (深度优先搜索)
  - Topological Sort (拓扑排序)
  - Strongly Connected Components (强联通分量)
  - Minimum Spanning Trees (最小生成树)
  - **Single-Source Shortest Paths (单源最短路径)**
  - All-Pairs Shortest Paths (所有结点对的最短路径)
  - Maximum/Network Flows (最大流/网络流)


# Outline

---

- Review to Part IV
- Single-Source Shortest Paths Problem
- Dijkstra's Algorithm
  - The idea
  - The algorithm
  - Analysis of Dijkstra's algorithm
- The Bellman-Ford Algorithm
  - The algorithm
  - Analysis of Bellman-Ford algorithm



# Single-Source Shortest Paths Problem



# Shortest Path Problem for Weighted Graphs

---

- Let  $G = (V, E)$  be a **weighted** digraph (directed graph),

# Shortest Path Problem for Weighted Graphs

---

- Let  $G = (V, E)$  be a **weighted** digraph (directed graph), with weight function  $w: E \mapsto \mathbb{R}$  mapping edges to real-valued weights



# Shortest Path Problem for Weighted Graphs

---

- Let  $G = (V, E)$  be a **weighted** digraph (directed graph), with weight function  $w: E \mapsto \mathbb{R}$  mapping edges to real-valued weights
- If  $e = (u, v)$ , we write  $w(u, v)$  for  $w(e)$ .

# Shortest Path Problem for Weighted Graphs

- Let  $G = (V, E)$  be a **weighted** digraph (directed graph), with weight function  $w: E \mapsto \mathbb{R}$  mapping edges to real-valued weights
- If  $e = (u, v)$ , we write  $w(u, v)$  for  $w(e)$ .

## Definition

The **length** of a path  $p = \langle v_0, v_1, \dots, v_k \rangle$  is the **sum** of the weights of its constituent edges:

$$\text{length}(p) = \sum_{i=1}^k w(v_{i-1}, v_i).$$

# Distance

---

## Definition

The **distance** from  $u$  to  $v$ , denoted  $\delta(u, v)$ , is the length of the **minimum length path** if there is a path from  $u$  to  $v$ ;

# Distance

---

## Definition


The **distance** from  $u$  to  $v$ , denoted  $\delta(u, v)$ , is the length of the **minimum length path** if there is a path from  $u$  to  $v$ ; and is  $\infty$  otherwise.

# Distance

## Definition

The **distance** from  $u$  to  $v$ , denoted  $\delta(u, v)$ , is the length of the **minimum length path** if there is a path from  $u$  to  $v$ ; and is  $\infty$  otherwise.

## Example




- $\text{length}(\langle a, b, c, e \rangle) =$

# Distance

## Definition

The **distance** from  $u$  to  $v$ , denoted  $\delta(u, v)$ , is the length of the **minimum length path** if there is a path from  $u$  to  $v$ ; and is  $\infty$  otherwise.

## Example



- $\text{length}(\langle a, b, c, e \rangle) = 6$ ; distance from  $a$  to  $e$  is 6



# Single-Source Shortest-Paths Problem

---

- Definition: Single-source shortest-paths problem
  - Given a digraph  $G = (V, E)$  with **no-negative edge weights**  $w$  and a designated **source vertex**  $s \in V$ , determine the **distance** and a **shortest path** from the source vertex to **every** vertex in the digraph.

# Single-Source Shortest-Paths Problem

---

- Definition: Single-source shortest-paths problem
  - Given a digraph  $G = (V, E)$  with **no-negative edge weights**  $w$  and a designated **source vertex**  $s \in V$ , determine the **distance** and a **shortest path** from the source vertex to **every** vertex in the digraph.
  - Note: Weight between two vertices  $u, v$  can actually be **negative**.

# Single-Source Shortest-Paths Problem

---

- Definition: Single-source shortest-paths problem
  - Given a digraph  $G = (V, E)$  with **no-negative edge weights**  $w$  and a designated **source vertex**  $s \in V$ , determine the **distance** and a **shortest path** from the source vertex to **every** vertex in the digraph.
  - Note: Weight between two vertices  $u, v$  can actually be **negative**.

## Question

How do you design an efficient algorithm for this problem?

# Outline

---

- Review to Part IV
- Single-Source Shortest Paths Problem
- **Dijkstra's Algorithm**
  - The idea
  - The algorithm
  - Analysis of Dijkstra's algorithm
- The Bellman-Ford Algorithm
  - The algorithm
  - Analysis of Bellman-Ford algorithm

# The Rough Idea of Dijkstra's Algorithm

---

- Maintain  $d[v]$  and  $S$ :
  - $d[v]$  is an upper bound of the length  $\delta(s, v)$  of the shortest path for each vertex  $v$ .

# The Rough Idea of Dijkstra's Algorithm

---

- Maintain  $d[v]$  and  $S$ :
  - $d[v]$  is an upper bound of the length  $\delta(s, v)$  of the shortest path for each vertex  $v$ .
  - $S \subseteq V$  is a subset of vertices for which we know the true distance, that is  $d[v] = \delta(s, v)$ .



# The Rough Idea of Dijkstra's Algorithm

---

- Maintain  $d[v]$  and  $S$ :
  - $d[v]$  is an upper bound of the length  $\delta(s, v)$  of the shortest path for each vertex  $v$ .
  - $S \subseteq V$  is a subset of vertices for which we know the true distance, that is  $d[v] = \delta(s, v)$ .
- Initially
  - $S =$

# The Rough Idea of Dijkstra's Algorithm

---

- Maintain  $d[v]$  and  $S$ :
  - $d[v]$  is an upper bound of the length  $\delta(s, v)$  of the shortest path for each vertex  $v$ .
  - $S \subseteq V$  is a subset of vertices for which we know the true distance, that is  $d[v] = \delta(s, v)$ .
- Initially
  - $S = \emptyset$
  - $d[s] =$

# The Rough Idea of Dijkstra's Algorithm

---

- Maintain  $d[v]$  and  $S$ :
  - $d[v]$  is an upper bound of the length  $\delta(s, v)$  of the shortest path for each vertex  $v$ .
  - $S \subseteq V$  is a subset of vertices for which we know the true distance, that is  $d[v] = \delta(s, v)$ .
- Initially
  - $S = \emptyset$
  - $d[s] = 0$  and  $d[v] = \infty$  for all others vertices  $v$ .

# The Rough Idea of Dijkstra's Algorithm

---

- Maintain  $d[v]$  and  $S$ :
  - $d[v]$  is an upper bound of the length  $\delta(s, v)$  of the shortest path for each vertex  $v$ .
  - $S \subseteq V$  is a subset of vertices for which we know the true distance, that is  $d[v] = \delta(s, v)$ .
- Initially
  - $S = \emptyset$
  - $d[s] = 0$  and  $d[v] = \infty$  for all others vertices  $v$ .
- One by one we select vertices from  $V \setminus S$  to add to  $S$ .

# The Rough Idea of Dijkstra's Algorithm

---

- Maintain  $d[v]$  and  $S$ :
  - $d[v]$  is an upper bound of the length  $\delta(s, v)$  of the shortest path for each vertex  $v$ .
  - $S \subseteq V$  is a subset of vertices for which we know the true distance, that is  $d[v] = \delta(s, v)$ .
- Initially
  - $S = \emptyset$
  - $d[s] = 0$  and  $d[v] = \infty$  for all others vertices  $v$ .
- One by one we select vertices from  $V \setminus S$  to add to  $S$ .
- Questions to answer at each step:

# The Rough Idea of Dijkstra's Algorithm

---

- Maintain  $d[v]$  and  $S$ :
  - $d[v]$  is an upper bound of the length  $\delta(s, v)$  of the shortest path for each vertex  $v$ .
  - $S \subseteq V$  is a subset of vertices for which we know the true distance, that is  $d[v] = \delta(s, v)$ .
- Initially
  - $S = \emptyset$
  - $d[s] = 0$  and  $d[v] = \infty$  for all others vertices  $v$ .
- One by one we select vertices from  $V \setminus S$  to add to  $S$ .
- Questions to answer at each step:
  - Which vertex do we select?
  - How do we update the distance upper bounds after a vertex is added to  $S$ ?



# Selection of Vertex

---

## Question

How does the algorithm **select** which vertex among the vertices of  $V \setminus S$  to process next?

# Selection of Vertex

---

## Question

How does the algorithm **select** which vertex among the vertices of  $V \setminus S$  to process next?

**Answer:** We use a **greedy** algorithm.

# Selection of Vertex

---

## Question

How does the algorithm **select** which vertex among the vertices of  $V \setminus S$  to process next?

**Answer:** We use a **greedy** algorithm.

- For each vertex in  $u \in V \setminus S$ , we have computed a distance upper bound  $d[u]$ .

# Selection of Vertex

---

## Question

How does the algorithm **select** which vertex among the vertices of  $V \setminus S$  to process next?

**Answer:** We use a **greedy** algorithm.

- For each vertex in  $u \in V \setminus S$ , we have computed a distance upper bound  $d[u]$ .
- The next vertex processed is always a vertex  $u \in V \setminus S$  for which  $d[u]$  is **minimum**

# Selection of Vertex

---

## Question

How does the algorithm **select** which vertex among the vertices of  $V \setminus S$  to process next?

**Answer:** We use a **greedy** algorithm.

- For each vertex in  $u \in V \setminus S$ , we have computed a distance upper bound  $d[u]$ .
- The next vertex processed is always a vertex  $u \in V \setminus S$  for which  $d[u]$  is **minimum**
  - that is, we take the unprocessed vertex that is **closest** (by our estimate) to  $s$ .

# Updating Distance Estimates

---

- Current distance upper bound for  $v$ :  $d[v]$ .




# Updating Distance Estimates

---

- Current distance upper bound for  $v$ :  $d[v]$ .
- Vertex  $u$  just added to  $S$ . Edge  $(u, v)$  with weight  $w(u, v)$ .

# Updating Distance Estimates


- Current distance upper bound for  $v$ :  $d[v]$ .
- Vertex  $u$  just added to  $S$ . Edge  $(u, v)$  with weight  $w(u, v)$ .
- How do we update  $d[v]$ ?



- Current shortest path to  $v$ :  $\langle s, \dots, w, v \rangle$ , length  $d[v]$ .

# Updating Distance Estimates


- Current distance upper bound for  $v$ :  $d[v]$ .
- Vertex  $u$  just added to  $S$ . Edge  $(u, v)$  with weight  $w(u, v)$ .
- How do we update  $d[v]$ ?



- Current shortest path to  $v$ :  $\langle s, \dots, w, v \rangle$ , length  $d[v]$ .
- New path to  $v$ :  $\langle s, \dots, u, v \rangle$ , length  $d[u] + w(u, v)$ .

# Updating Distance Estimates

- Current distance upper bound for  $v$ :  $d[v]$ .
- Vertex  $u$  just added to  $S$ . Edge  $(u, v)$  with weight  $w(u, v)$ .
- How do we update  $d[v]$ ?




- Current shortest path to  $v$ :  $\langle s, \dots, w, v \rangle$ , length  $d[v]$ .
- New path to  $v$ :  $\langle s, \dots, u, v \rangle$ , length  $d[u] + w(u, v)$ .
- If new path is shorter ( $d[u] + w(u, v) < d[v]$ ), update  $d[v]$   

$$d[v] = d[u] + w(u, v)$$

# Updating Distance Estimates

- Current distance upper bound for  $v$ :  $d[v]$ .
- Vertex  $u$  just added to  $S$ . Edge  $(u, v)$  with weight  $w(u, v)$ .
- How do we update  $d[v]$ ?



- Current shortest path to  $v$ :  $\langle s, \dots, w, v \rangle$ , length  $d[v]$ .
- New path to  $v$ :  $\langle s, \dots, u, v \rangle$ , length  $d[u] + w(u, v)$ .
- If new path is shorter ( $d[u] + w(u, v) < d[v]$ ), update  $d[v]$   

$$d[v] = d[u] + w(u, v)$$

Now we have a better (tighter) upper bound for  $d[v]$ . This is called **relaxing** the edge  $(u, v)$ .

# The Algorithm for Relaxing an Edge

---

Relax( $u, v$ )

**Input:** Update estimation of  $u$  according to distance of  $v$

**Output:** None

**if**  $d[u] + w(u, v) < d[v]$  **then**

|

**end**

# The Algorithm for Relaxing an Edge

---

Relax( $u, v$ )

**Input:** Update estimation of  $u$  according to distance of  $v$

**Output:** None

**if**  $d[u] + w(u, v) < d[v]$  **then**

$d[v] \leftarrow$

**end**

# The Algorithm for Relaxing an Edge

---

Relax( $u, v$ )

**Input:** Update estimation of  $u$  according to distance of  $v$

**Output:** None

**if**  $d[u] + w(u, v) < d[v]$  **then**

$d[v] \leftarrow d[u] + w(u, v);$

$pred[v] \leftarrow$

**end**



# The Algorithm for Relaxing an Edge

---

Relax( $u, v$ )

**Input:** Update estimation of  $u$  according to distance of  $v$

**Output:** None

**if**  $d[u] + w(u, v) < d[v]$  **then**

$d[v] \leftarrow d[u] + w(u, v);$

$pred[v] \leftarrow u;$

**end**

# The Algorithm for Relaxing an Edge: An Example

Relax( $u, v$ )

**Input:** Update estimation of  $u$  according to distance of  $v$







**Output:** None

**if**  $d[u] + w(u, v) < d[v]$  **then**

$d[v] \leftarrow d[u] + w(u, v);$

$pred[v] \leftarrow u;$

**end**



# The Algorithm for Relaxing an Edge

---

Relax( $u, v$ )

**Input:** Update estimation of  $u$  according to distance of  $v$

**Output:** None

**if**  $d[u] + w(u, v) < d[v]$  **then**

$d[v] \leftarrow d[u] + w(u, v);$

$pred[v] \leftarrow u;$

**end**

- **Remark 1:** The predecessor pointer  $pred[ ]$  is for determining the shortest paths.
- **Remark 2:** After edge  $(u, v)$  is relaxed, we have
$$d[v] \leq d[u] + w(u, v)$$

# Outline

---

- Review to Part IV
- Single-Source Shortest Paths Problem
- **Dijkstra's Algorithm**
  - The idea
  - **The algorithm**
  - Analysis of Dijkstra's algorithm
- The Bellman-Ford Algorithm(Optional)
  - The algorithm
  - Analysis of Bellman-Ford algorithm

# The Selection in Dijkstra's Algorithm

---

## Question

How do we perform this selection efficiently?

# The Selection in Dijkstra's Algorithm

---

## Question

How do we perform this selection efficiently?

**Answer:** We store the vertices of  $V \setminus S$  in a

# The Selection in Dijkstra's Algorithm

---

## Question

How do we perform this selection efficiently?

**Answer:** We store the vertices of  $V \setminus S$  in a **Priority queue**, where the key value of each vertex  $v$  is

# The Selection in Dijkstra's Algorithm

---

## Question

How do we perform this selection efficiently?

**Answer:** We store the vertices of  $V \setminus S$  in a **Priority queue**, where the key value of each vertex  $v$  is  $d[v]$ .



# The Selection in Dijkstra's Algorithm

---

## Question

How do we perform this selection efficiently?

**Answer:** We store the vertices of  $V \setminus S$  in a **Priority queue**, where the key value of each vertex  $v$  is  $d[v]$ .

- Note: if we implement the priority queue using a heap, we can perform the operations **Insert()**, **Extract-Min()**, and **Decrease-Key()**, each in  $O(\quad)$  time.

# The Selection in Dijkstra's Algorithm

---

## Question

How do we perform this selection efficiently?

**Answer:** We store the vertices of  $V \setminus S$  in a **Priority queue**, where the key value of each vertex  $v$  is  $d[v]$ .

- Note: if we implement the priority queue using a heap, we can perform the operations **Insert()**, **Extract-Min()**, and **Decrease-Key()**, each in  $O(\log n)$  time.

# Description of Dijkstra's Algorithm

---

Dijkstra( $G, w, s$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , source vertex  $s$

**Output:** None

**for**  $u \in V$  **do**

  |  $d[u] \leftarrow$

# Description of Dijkstra's Algorithm

---

Dijkstra( $G, w, s$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , source vertex  $s$

**Output:** None

**for**  $u \in V$  **do**

  |  $d[u] \leftarrow \infty, color[u] \leftarrow$

# Description of Dijkstra's Algorithm

---

Dijkstra( $G, w, s$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , source vertex  $s$

**Output:** None

**for**  $u \in V$  **do**

  |  $d[u] \leftarrow \infty, color[u] \leftarrow \text{WHITE}; // \text{Initialize}$

**end**

$d[s] \leftarrow$

# Description of Dijkstra's Algorithm

---

Dijkstra( $G, w, s$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , source vertex  $s$

**Output:** None

**for**  $u \in V$  **do**

$d[u] \leftarrow \infty, color[u] \leftarrow \text{WHITE};$  // Initialize

**end**

$d[s] \leftarrow 0;$

$pred[s] \leftarrow$

# Description of Dijkstra's Algorithm

---

Dijkstra( $G, w, s$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , source vertex  $s$

**Output:** None

**for**  $u \in V$  **do**

$d[u] \leftarrow \infty, color[u] \leftarrow \text{WHITE};$  // Initialize

**end**

$d[s] \leftarrow 0;$

$pred[s] \leftarrow \text{NULL};$

$Q \leftarrow$

# Description of Dijkstra's Algorithm

Dijkstra( $G, w, s$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , source vertex  $s$

**Output:** None

**for**  $u \in V$  **do**

$d[u] \leftarrow \infty, color[u] \leftarrow \text{WHITE};$  // Initialize

**end**

$d[s] \leftarrow 0;$

$pred[s] \leftarrow \text{NULL};$

$Q \leftarrow$  queue with all vertices;

**while**  $Non-Empty(Q)$  **do**

    // Process all vertices



**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , source vertex  $s$

**for**  $u \in V$  **do**

end

$$pred[s] \leftarrow \text{NULL};$$
**while** *Non-Empty*( $Q$ ) **do**

```

u ← ] ; // Find new vertex

```

# Description of Dijkstra's Algorithm

Dijkstra( $G, w, s$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , source vertex  $s$

**Output:** None

**for**  $u \in V$  **do**

$d[u] \leftarrow \infty, color[u] \leftarrow \text{WHITE};$  // Initialize

**end**

$d[s] \leftarrow 0;$

$pred[s] \leftarrow \text{NULL};$

$Q \leftarrow$  queue with all vertices;

**while**  $Non-Empty(Q)$  **do**

    // Process all vertices

$u \leftarrow \text{Extract-Min}(Q);$  // Find new vertex

# Description of Dijkstra's Algorithm

Dijkstra( $G, w, s$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , source vertex  $s$

**Output:** None

**for**  $u \in V$  **do**

$d[u] \leftarrow \infty, color[u] \leftarrow \text{WHITE};$  // Initialize

**end**

$d[s] \leftarrow 0;$

$pred[s] \leftarrow \text{NULL};$

$Q \leftarrow$  queue with all vertices;

**while**  $Non-Empty(Q)$  **do**

    // Process all vertices

$u \leftarrow \text{Extract-Min}(Q);$  // Find new vertex

**for**  $v \in Adj[u]$  **do**

        |

    |

# Description of Dijkstra's Algorithm

Dijkstra( $G, w, s$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , source vertex  $s$

**Output:** None

**for**  $u \in V$  **do**

$d[u] \leftarrow \infty, color[u] \leftarrow \text{WHITE};$  // Initialize

**end**

$d[s] \leftarrow 0;$

$pred[s] \leftarrow \text{NULL};$

$Q \leftarrow$  queue with all vertices;

**while**  $Non-Empty(Q)$  **do**

    // Process all vertices

$u \leftarrow \text{Extract-Min}(Q);$  // Find new vertex

**for**  $v \in Adj[u]$  **do**

**if**  $d[u] + w(u, v) < d[v]$  **then**

            // If estimate improves

# Description of Dijkstra's Algorithm

Dijkstra( $G, w, s$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , source vertex  $s$

**Output:** None

**for**  $u \in V$  **do**

$d[u] \leftarrow \infty, color[u] \leftarrow \text{WHITE};$  // Initialize

**end**

$d[s] \leftarrow 0;$

$pred[s] \leftarrow \text{NULL};$

$Q \leftarrow$  queue with all vertices;

**while**  $Non-Empty(Q)$  **do**

    // Process all vertices

$u \leftarrow \text{Extract-Min}(Q);$  // Find new vertex

**for**  $v \in Adj[u]$  **do**

**if**  $d[u] + w(u, v) < d[v]$  **then**

            // If estimate improves

$d[v] \leftarrow$

# Description of Dijkstra's Algorithm

Dijkstra( $G, w, s$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , source vertex  $s$

**Output:** None

**for**  $u \in V$  **do**

$d[u] \leftarrow \infty, color[u] \leftarrow \text{WHITE};$  // Initialize

**end**

$d[s] \leftarrow 0;$

$pred[s] \leftarrow \text{NULL};$

$Q \leftarrow$  queue with all vertices;

**while**  $Non-Empty(Q)$  **do**

    // Process all vertices

$u \leftarrow \text{Extract-Min}(Q);$  // Find new vertex

**for**  $v \in Adj[u]$  **do**

**if**  $d[u] + w(u, v) < d[v]$  **then**

            // If estimate improves

$d[v] \leftarrow d[u] + w(u, v);$  // relax

# Description of Dijkstra's Algorithm

Dijkstra( $G, w, s$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , source vertex  $s$

**Output:** None

**for**  $u \in V$  **do**

$d[u] \leftarrow \infty, color[u] \leftarrow \text{WHITE};$  // Initialize

**end**

$d[s] \leftarrow 0;$

$pred[s] \leftarrow \text{NULL};$

$Q \leftarrow$  queue with all vertices;

**while**  $Non-Empty(Q)$  **do**

    // Process all vertices

$u \leftarrow \text{Extract-Min}(Q);$  // Find new vertex

**for**  $v \in Adj[u]$  **do**

**if**  $d[u] + w(u, v) < d[v]$  **then**

            // If estimate improves

$d[v] \leftarrow d[u] + w(u, v);$  // relax

            Decrease-Key( $Q, v, d[v]$ );

# Description of Dijkstra's Algorithm

Dijkstra( $G, w, s$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , source vertex  $s$

**Output:** None

**for**  $u \in V$  **do**

$d[u] \leftarrow \infty, color[u] \leftarrow \text{WHITE};$  // Initialize

**end**

$d[s] \leftarrow 0;$

$pred[s] \leftarrow \text{NULL};$

$Q \leftarrow$  queue with all vertices;

**while**  $Non-Empty(Q)$  **do**

    // Process all vertices

$u \leftarrow \text{Extract-Min}(Q);$  // Find new vertex

**for**  $v \in Adj[u]$  **do**

**if**  $d[u] + w(u, v) < d[v]$  **then**

            // If estimate improves

$d[v] \leftarrow d[u] + w(u, v);$  // relax

            Decrease-Key( $Q, v, d[v]$ );

$pred[v] \leftarrow$



# Description of Dijkstra's Algorithm

Dijkstra( $G, w, s$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , source vertex  $s$

**Output:** None

**for**  $u \in V$  **do**

$d[u] \leftarrow \infty, color[u] \leftarrow \text{WHITE};$  // Initialize

**end**

$d[s] \leftarrow 0;$

$pred[s] \leftarrow \text{NULL};$

$Q \leftarrow$  queue with all vertices;

**while**  $Non-Empty(Q)$  **do**

    // Process all vertices

$u \leftarrow \text{Extract-Min}(Q);$  // Find new vertex

**for**  $v \in Adj[u]$  **do**

**if**  $d[u] + w(u, v) < d[v]$  **then**

            // If estimate improves

$d[v] \leftarrow d[u] + w(u, v);$  // relax

            Decrease-Key( $Q, v, d[v]$ );

$pred[v] \leftarrow u;$

**end**

**end**

$color[u] \leftarrow$

# Description of Dijkstra's Algorithm

Dijkstra( $G, w, s$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , source vertex  $s$

**Output:** None

**for**  $u \in V$  **do**

$d[u] \leftarrow \infty, color[u] \leftarrow \text{WHITE};$  // Initialize

**end**

$d[s] \leftarrow 0;$

$pred[s] \leftarrow \text{NULL};$

$Q \leftarrow$  queue with all vertices;

**while**  $Non-Empty(Q)$  **do**

    // Process all vertices

$u \leftarrow \text{Extract-Min}(Q);$  // Find new vertex

**for**  $v \in Adj[u]$  **do**

**if**  $d[u] + w(u, v) < d[v]$  **then**

            // If estimate improves

$d[v] \leftarrow d[u] + w(u, v);$  // relax

            Decrease-Key( $Q, v, d[v]$ );

$pred[v] \leftarrow u;$

**end**

**end**

$color[u] \leftarrow \text{BLACK};$

**end**

# An Example of Dijkstra's Algorithm

color

W	W	W	W	W
---	---	---	---	---

pred


N	N	N	N	N
---	---	---	---	---

d

$\infty$	$\infty$	$\infty$	$\infty$	$\infty$
----------	----------	----------	----------	----------

Q(Priority Queue)

1	2	3	4	5
---	---	---	---	---



# An Example of Dijkstra's Algorithm

color

W	W	W	W	W
---	---	---	---	---

pred


N	N	N	N	N
---	---	---	---	---

d

$\infty$	$\infty$	$\infty$	$\infty$	$\infty$
----------	----------	----------	----------	----------

Q(Priority Queue)

1	2	3	4	5
---	---	---	---	---



# An Example of Dijkstra's Algorithm

color

W	W	W	W	W
---	---	---	---	---

pred


N	N	N	N	N
---	---	---	---	---

d

0	$\infty$	$\infty$	$\infty$	$\infty$
---	----------	----------	----------	----------

Q(Priority Queue)

1	2	3	4	5
---	---	---	---	---



# An Example of Dijkstra's Algorithm

color

W	W	W	W	W
---	---	---	---	---

pred


N	N	N	N	N
---	---	---	---	---

d

0	$\infty$	$\infty$	$\infty$	$\infty$
---	----------	----------	----------	----------

Q(Priority Queue)

1	2	3	4	5
---	---	---	---	---



# An Example of Dijkstra's Algorithm

color

W	W	W	W	W
---	---	---	---	---

pred


N	1	1	N	N
---	---	---	---	---

d

0	2	7	$\infty$	$\infty$
---	---	---	----------	----------

Q(Priority Queue)

1	2	3	4	5
---	---	---	---	---



# An Example of Dijkstra's Algorithm

color

<b>B</b>	W	W	W	W
----------	---	---	---	---

pred


N	1	1	N	N
---	---	---	---	---

d

0	2	7	$\infty$	$\infty$
---	---	---	----------	----------

Q(Priority Queue)

<b>1</b>	2	3	4	5
----------	---	---	---	---





# An Example of Dijkstra's Algorithm

color

B	W	W	W	W
---	---	---	---	---

pred


N	1	1	N	N
---	---	---	---	---

d

0	2	7	$\infty$	$\infty$
---	---	---	----------	----------

Q(Priority Queue)

1	2	3	4	5
---	---	---	---	---



# An Example of Dijkstra's Algorithm

color

B	W	W	W	W
---	---	---	---	---

pred


N	1	2	2	2
---	---	---	---	---

d

0	2	5	10	7
---	---	---	----	---

Q(Priority Queue)

1	2	3	4	5
---	---	---	---	---



# An Example of Dijkstra's Algorithm

color

B	B	W	W	W
---	---	---	---	---

pred


N	1	2	2	2
---	---	---	---	---

d

0	2	5	10	7
---	---	---	----	---

Q(Priority Queue)

1	2	3	4	5
---	---	---	---	---



# An Example of Dijkstra's Algorithm

color

<b>B</b>	<b>B</b>	<b>W</b>	<b>W</b>	<b>W</b>
----------	----------	----------	----------	----------

pred


<b>N</b>	<b>1</b>	<b>2</b>	<b>2</b>	<b>2</b>
----------	----------	----------	----------	----------

d

<b>0</b>	<b>2</b>	<b>5</b>	<b>10</b>	<b>7</b>
----------	----------	----------	-----------	----------

Q(Priority Queue)

<b>1</b>	<b>2</b>	<b>3</b>	<b>4</b>	<b>5</b>
----------	----------	----------	----------	----------



# An Example of Dijkstra's Algorithm

color

B	B	W	W	W
---	---	---	---	---

pred


N	1	2	3	2
---	---	---	---	---

d

0	2	5	6	7
---	---	---	---	---

Q(Priority Queue)

1	2	3	4	5
---	---	---	---	---



# An Example of Dijkstra's Algorithm

color

B	B	B	W	W
---	---	---	---	---

pred


N	1	2	3	2
---	---	---	---	---

d

0	2	5	6	7
---	---	---	---	---

Q(Priority Queue)

1	2	3	4	5
---	---	---	---	---



# An Example of Dijkstra's Algorithm

color

B	B	B	W	W
---	---	---	---	---

pred


N	1	2	3	2
---	---	---	---	---

d

0	2	5	6	7
---	---	---	---	---

Q(Priority Queue)

1	2	3	4	5
---	---	---	---	---



# An Example of Dijkstra's Algorithm

color

B	B	B	W	W
---	---	---	---	---

pred


N	1	2	3	2
---	---	---	---	---

d

0	2	5	6	7
---	---	---	---	---

Q(Priority Queue)

1	2	3	4	5
---	---	---	---	---



**d[5] is not  
needed to be  
updated because  
 $d[4]+4 > d[5]$**



# An Example of Dijkstra's Algorithm

color

B	B	B	B	W
---	---	---	---	---

pred


N	1	2	3	2
---	---	---	---	---

d

0	2	5	6	7
---	---	---	---	---

Q(Priority Queue)

1	2	3	4	5
---	---	---	---	---



# An Example of Dijkstra's Algorithm

color

<b>B</b>	<b>B</b>	<b>B</b>	<b>B</b>	<b>W</b>
----------	----------	----------	----------	----------

pred


<b>N</b>	<b>1</b>	<b>2</b>	<b>3</b>	<b>2</b>
----------	----------	----------	----------	----------

d

<b>0</b>	<b>2</b>	<b>5</b>	<b>6</b>	<b>7</b>
----------	----------	----------	----------	----------

Q(Priority Queue)

<b>1</b>	<b>2</b>	<b>3</b>	<b>4</b>	<b>5</b>
----------	----------	----------	----------	----------



# An Example of Dijkstra's Algorithm

color

B	B	B	B	B
---	---	---	---	---

pred


N	1	2	3	2
---	---	---	---	---

d

0	2	5	6	7
---	---	---	---	---

Q(Priority Queue)

1	2	3	4	5
---	---	---	---	---



# An Example of Dijkstra's Algorithm

color

<b>B</b>	<b>B</b>	<b>B</b>	<b>B</b>	<b>B</b>
----------	----------	----------	----------	----------

pred


<b>N</b>	<b>1</b>	<b>2</b>	<b>3</b>	<b>2</b>
----------	----------	----------	----------	----------

d

<b>0</b>	<b>2</b>	<b>5</b>	<b>6</b>	<b>7</b>
----------	----------	----------	----------	----------

Q(Priority Queue)

<b>1</b>	<b>2</b>	<b>3</b>	<b>4</b>	<b>5</b>
----------	----------	----------	----------	----------



# Shortest Path Tree for Dijkstra's Algorithm

---

**Shortest Path Tree:**  $T = (V ; A)$ , where

$$A = \{(pred[v], v) | v \in V \setminus \{s\}\}$$

# Shortest Path Tree for Dijkstra's Algorithm

---

**Shortest Path Tree:**  $T = (V ; A)$ , where

$$A = \{(pred[v], v) | v \in V \setminus \{s\}\}$$

The array  $pred[v]$  is used to build the tree.


# Shortest Path Tree for Dijkstra's Algorithm

**Shortest Path Tree:**  $T = (V ; A)$ , where

$$A = \{(pred[v], v) | v \in V \setminus \{s\}\}$$

The array  $pred[v]$  is used to build the tree.

## Example



$v$	$s$	$a$	$b$	$c$	$d$
$d[v]$	0	2	5	6	7
$pred[v]$	NIL	$s$	$a$	$b$	$a$

# Outline

---

- Review to Part IV
- Single-Source Shortest Paths Problem
- **Dijkstra's Algorithm**
  - The idea
  - The algorithm
  - **Analysis of Dijkstra's algorithm**
- The Bellman-Ford Algorithm
  - The algorithm
  - Analysis of Bellman-Ford algorithm



# Observation

---

## Lemma


*Any sub-path of a shortest path must also be a shortest path*

# Observation

## Lemma

*Any sub-path of a shortest path must also be a shortest path*

## Example




$\langle a, b, c, e \rangle$  is a shortest path;

# Observation

## Lemma

*Any sub-path of a shortest path must also be a shortest path*

## Example




$\langle a, b, c, e \rangle$  is a shortest path; sub-path  $\langle a, b, c \rangle$  is also a shortest path.

# Observation

## Lemma

*Any sub-path of a shortest path must also be a shortest path*

## Example



$\langle a, b, c, e \rangle$  is a shortest path; sub-path  $\langle a, b, c \rangle$  is also a shortest path.

## Question

Why?


# Correctness of Dijkstra's Algorithm

---

**Theorem:** When a vertex  $u$  is added to  $S$  (i.e., dequeued from the queue),  $d[u] = \delta(s, u)$ .

# Correctness of Dijkstra's Algorithm

**Theorem:** When a vertex  $u$  is added to  $S$  (i.e., dequeued from the queue),  $d[u] = \delta(s, u)$ .




**Proof:**

- Suppose **to the contrary** that at some point Dijkstra's algorithm **first** attempts to add a vertex  $u$  to  $S$  for which  $d[u] \neq \delta(s, u)$ .

# Correctness of Dijkstra's Algorithm

**Theorem:** When a vertex  $u$  is added to  $S$  (i.e., dequeued from the queue),  $d[u] = \delta(s, u)$ .




**Proof:**

- Suppose **to the contrary** that at some point Dijkstra's algorithm **first** attempts to add a vertex  $u$  to  $S$  for which  $d[u] \neq \delta(s, u)$ .
- Since  $d[u] = \infty$  initially, and remains an **upper bound** of the true shortest distance, we have  $d[u] > \delta(s, u)$ .

# Correctness of Dijkstra's Algorithm

**Theorem:** When a vertex  $u$  is added to  $S$  (i.e., dequeued from the queue),  $d[u] = \delta(s, u)$ .




**Proof:**

- Suppose **to the contrary** that at some point Dijkstra's algorithm **first** attempts to add a vertex  $u$  to  $S$  for which  $d[u] \neq \delta(s, u)$ .
- Since  $d[u] = \infty$  initially, and remains an **upper bound** of the true shortest distance, we have  $d[u] > \delta(s, u)$ .
- Consider the situation just prior to the insertion of  $u$ .



# Correctness of Dijkstra's Algorithm

**Theorem:** When a vertex  $u$  is added to  $S$  (i.e., dequeued from the queue),  $d[u] = \delta(s, u)$ .




**Proof:**

- Suppose **to the contrary** that at some point Dijkstra's algorithm **first** attempts to add a vertex  $u$  to  $S$  for which  $d[u] \neq \delta(s, u)$ .
- Since  $d[u] = \infty$  initially, and remains an **upper bound** of the true shortest distance, we have  $d[u] > \delta(s, u)$ .
- Consider the situation just prior to the insertion of  $u$ .
- Consider the **true shortest path** from  $s$  to  $u$ .

# Correctness of Dijkstra's Algorithm

**Theorem:** When a vertex  $u$  is added to  $S$  (i.e., dequeued from the queue),  $d[u] = \delta(s, u)$ .




**Proof:**

- Suppose **to the contrary** that at some point Dijkstra's algorithm **first** attempts to add a vertex  $u$  to  $S$  for which  $d[u] \neq \delta(s, u)$ .
- Since  $d[u] = \infty$  initially, and remains an **upper bound** of the true shortest distance, we have  $d[u] > \delta(s, u)$ .
- Consider the situation just prior to the insertion of  $u$ .
- Consider the **true shortest path** from  $s$  to  $u$ .
- Because  $s \in S$  and  $u \in V \setminus S$ , at some point this path must

# Correctness of Dijkstra's Algorithm

**Theorem:** When a vertex  $u$  is added to  $S$  (i.e., dequeued from the queue),  $d[u] = \delta(s, u)$ .




**Proof:**

- Suppose **to the contrary** that at some point Dijkstra's algorithm **first** attempts to add a vertex  $u$  to  $S$  for which  $d[u] \neq \delta(s, u)$ .
- Since  $d[u] = \infty$  initially, and remains an **upper bound** of the true shortest distance, we have  $d[u] > \delta(s, u)$ .
- Consider the situation just prior to the insertion of  $u$ .
- Consider the **true shortest path** from  $s$  to  $u$ .
- Because  $s \in S$  and  $u \in V \setminus S$ , at some point this path must first take a jump out of  $S$ .

# Correctness of Dijkstra's Algorithm

**Theorem:** When a vertex  $u$  is added to  $S$  (i.e., dequeued from the queue),  $d[u] = \delta(s, u)$ .



**Proof:**


- Suppose **to the contrary** that at some point Dijkstra's algorithm **first** attempts to add a vertex  $u$  to  $S$  for which  $d[u] \neq \delta(s, u)$ .
- Since  $d[u] = \infty$  initially, and remains an **upper bound** of the true shortest distance, we have  $d[u] > \delta(s, u)$ .
- Consider the situation just prior to the insertion of  $u$ .
- Consider the **true shortest path** from  $s$  to  $u$ :  $\langle s, \dots, x, y, \dots, u \rangle$ .
- Because  $s \in S$  and  $u \in V \setminus S$ , at some point this path must first take a jump out of  $S$ . Let  $(x, y)$  be the edge taken by the path, where  $x \in S$  and  $y \in V \setminus S$  (it may be that  $x=s$  or/and  $y=u$ ).

# Correctness of Dijkstra's Algorithm

**Theorem:** When a vertex  $u$  is added to  $S$  (i.e., dequeued from the queue),  $d[u] = \delta(s, u)$ .


**Proof:**

We now prove that  $y \neq u$ .



# Correctness of Dijkstra's Algorithm

**Theorem:** When a vertex  $u$  is added to  $S$  (i.e., dequeued from the queue),  $d[u] = \delta(s, u)$ .



**Proof:**


We now prove that  $y \neq u$ .

- We have done relaxation when processing  $x$ , so

$$d[y] \leq d[x] + w(x, y) \quad (1)$$

# Correctness of Dijkstra's Algorithm

**Theorem:** When a vertex  $u$  is added to  $S$  (i.e., dequeued from the queue),  $d[u] = \delta(s, u)$ .



**Proof:**

We now prove that  $y \neq u$ .

- We have done relaxation when processing  $x$ , so


$$d[y] \leq d[x] + w(x, y) \quad (1)$$

- Since  $x$  is added to  $S$  earlier, by hypothesis,

$$d[x] = \delta(s, x) \quad (2)$$

# Correctness of Dijkstra's Algorithm

**Theorem:** When a vertex  $u$  is added to  $S$  (i.e., dequeued from the queue),  $d[u] = \delta(s, u)$ .



**Proof:**

We now prove that  $y \neq u$ .

- We have done relaxation when processing  $x$ , so

$$d[y] \leq d[x] + w(x, y) \quad (1)$$

- Since  $x$  is added to  $S$  earlier, by hypothesis,

$$d[x] = \delta(s, x) \quad (2)$$


- Since  $\langle s, \dots, x, y \rangle$  is sub-path of a shortest path,

$$\delta(s, y) = \delta(s, x) + w(x, y) = d[x] + w(x, y) \quad (3)$$



# Correctness of Dijkstra's Algorithm

**Theorem:** When a vertex  $u$  is added to  $S$  (i.e., dequeued from the queue),  $d[u] = \delta(s, u)$ .



**Proof:**

We now prove that  $y \neq u$ .

- We have done relaxation when processing  $x$ , so

$$d[y] \leq d[x] + w(x, y) \quad (1)$$

- Since  $x$  is added to  $S$  earlier, by hypothesis,

$$d[x] = \delta(s, x) \quad (2)$$


- Since  $\langle s, \dots, x, y \rangle$  is sub-path of a shortest path,

$$\delta(s, y) = \delta(s, x) + w(x, y) = d[x] + w(x, y) \quad (3)$$

- By (1) and (3),  $d[y] \leq \delta(s, y)$ . Hence  $d[y] = \delta(s, y)$ .

# Correctness of Dijkstra's Algorithm

**Theorem:** When a vertex  $u$  is added to  $S$  (i.e., dequeued from the queue),  $d[u] = \delta(s, u)$ .



**Proof:**

We now prove that  $y \neq u$ .

- We have done relaxation when processing  $x$ , so

$$d[y] \leq d[x] + w(x, y) \quad (1)$$

- Since  $x$  is added to  $S$  earlier, by hypothesis,

$$d[x] = \delta(s, x) \quad (2)$$


- Since  $\langle s, \dots, x, y \rangle$  is sub-path of a shortest path,

$$\delta(s, y) = \delta(s, x) + w(x, y) = d[x] + w(x, y) \quad (3)$$

- By (1) and (3),  $d[y] \leq \delta(s, y)$ . Hence  $d[y] = \delta(s, y)$ . So  $y \neq u$  (because we suppose  $d[u] > \delta(s, u)$ ).

# Correctness of Dijkstra's Algorithm

**Theorem:** When a vertex  $u$  is added to  $S$  (i.e., dequeued from the queue),  $d[u] = \delta(s, u)$ .




**Proof:**

Since  $y$  appears midway on the path from  $s$  to  $u$ , and all subsequent edges have non-negative weights, we have  $\delta(s, y) \leq \delta(s, u)$ , and thus

$$d[y] =$$

# Correctness of Dijkstra's Algorithm

**Theorem:** When a vertex  $u$  is added to  $S$  (i.e., dequeued from the queue),  $d[u] = \delta(s, u)$ .




**Proof:**

Since  $y$  appears midway on the path from  $s$  to  $u$ , and all subsequent edges have non-negative weights, we have  $\delta(s, y) \leq \delta(s, u)$ , and thus

$$d[y] = \delta(s, y)$$

# Correctness of Dijkstra's Algorithm

**Theorem:** When a vertex  $u$  is added to  $S$  (i.e., dequeued from the queue),  $d[u] = \delta(s, u)$ .




**Proof:**

Since  $y$  appears midway on the path from  $s$  to  $u$ , and all subsequent edges have non-negative weights, we have  $\delta(s, y) \leq \delta(s, u)$ , and thus

$$d[y] = \delta(s, y) \leq \delta(s, u)$$

# Correctness of Dijkstra's Algorithm

**Theorem:** When a vertex  $u$  is added to  $S$  (i.e., dequeued from the queue),  $d[u] = \delta(s, u)$ .




**Proof:**

Since  $y$  appears midway on the path from  $s$  to  $u$ , and all subsequent edges have non-negative weights, we have  $\delta(s, y) \leq \delta(s, u)$ , and thus

$$d[y] = \delta(s, y) \leq \delta(s, u) \quad d[u]$$

# Correctness of Dijkstra's Algorithm

**Theorem:** When a vertex  $u$  is added to  $S$  (i.e., dequeued from the queue),  $d[u] = \delta(s, u)$ .




**Proof:**

Since  $y$  appears midway on the path from  $s$  to  $u$ , and all subsequent edges have non-negative weights, we have  $\delta(s, y) \leq \delta(s, u)$ , and thus

$$d[y] = \delta(s, y) \leq \delta(s, u) < d[u]$$

# Correctness of Dijkstra's Algorithm

**Theorem:** When a vertex  $u$  is added to  $S$  (i.e., dequeued from the queue),  $d[u] = \delta(s, u)$ .



**Proof:**

Since  $y$  appears midway on the path from  $s$  to  $u$ , and all subsequent edges have non-negative weights, we have  $\delta(s, y) \leq \delta(s, u)$ , and thus

$$d[y] = \delta(s, y) \leq \delta(s, u) < d[u]$$


Thus  $y$  should have been added to  $S$  before  $u$ ,





# Correctness of Dijkstra's Algorithm

**Theorem:** When a vertex  $u$  is added to  $S$  (i.e., dequeued from the queue),  $d[u] = \delta(s, u)$ .



**Proof:**

Since  $y$  appears midway on the path from  $s$  to  $u$ , and all subsequent edges have non-negative weights, we have  $\delta(s, y) \leq \delta(s, u)$ , and thus

$$d[y] = \delta(s, y) \leq \delta(s, u) < d[u]$$

Thus  $y$  should have been added to  $S$  **before**  $u$ , in contradiction to our assumption that  $u$  is the next vertex to be added to  $S$ .

# Analysis of Dijkstra's Algorithm

---

- The initialization uses only  $O(n)$  time.

# Analysis of Dijkstra's Algorithm

---

- The initialization uses only  $O(|V|)$  time.

# Analysis of Dijkstra's Algorithm

---

- The initialization uses only  $O(|V|)$  time.
- Each vertex is processed exactly once, so `Non-Empty()` and `Extract-Min()` are called exactly once,

# Analysis of Dijkstra's Algorithm

---

- The initialization uses only  $O(|V|)$  time.
- Each vertex is processed exactly once, so `Non-Empty()` and `Extract-Min()` are called exactly once, i.e.,  $|V|$  times in total.

# Analysis of Dijkstra's Algorithm

---

- The initialization uses only  $O(|V|)$  time.
- Each vertex is processed exactly once, so `Non-Empty()` and `Extract-Min()` are called exactly once, i.e.,  $O(|V|)$  times in total.

# Analysis of Dijkstra's Algorithm

---

- The initialization uses only  $O(|V|)$  time.
- Each vertex is processed exactly once, so `Non-Empty()` and `Extract-Min()` are called exactly once, i.e.,  $O(|V|)$  times in total.
- The inner loop `for (each  $v \in \text{Adj}[u]$ )` is called once for each edge in the graph.



# Analysis of Dijkstra's Algorithm

---

- The initialization uses only  $O(|V|)$  time.
- Each vertex is processed exactly once, so `Non-Empty()` and `Extract-Min()` are called exactly once, i.e.,  $O(|V|)$  times in total.
- The inner loop `for (each  $v \in \text{Adj}[u]$ )` is called once for each edge in the graph. Each call of the inner loop does  $O(1)$  work

# Analysis of Dijkstra's Algorithm

---

- The initialization uses only  $O(|V|)$  time.
- Each vertex is processed exactly once, so `Non-Empty()` and `Extract-Min()` are called exactly once, i.e.,  $O(|V|)$  times in total.
- The inner loop `for (each  $v \in \text{Adj}[u]$ )` is called once for each edge in the graph. Each call of the inner loop does  $O(1)$  work plus, possibly, `one` Decrease-Key operation.

# Analysis of Dijkstra's Algorithm

---

- The initialization uses only  $O(|V|)$  time.
- Each vertex is processed exactly once, so `Non-Empty()` and `Extract-Min()` are called exactly once, i.e.,  $O(|V|)$  times in total.
- The inner loop `for (each  $v \in \text{Adj}[u]$ )` is called once for each edge in the graph. Each call of the inner loop does  $O(1)$  work plus, possibly, `one` Decrease-Key operation.
- Recalling that all of the priority queue operations require  $O(\log |Q|) = O(\log |V|)$  time, we have that the algorithm uses

# Analysis of Dijkstra's Algorithm

---

- The initialization uses only  $O(|V|)$  time.
- Each vertex is processed exactly once, so `Non-Empty()` and `Extract-Min()` are called exactly once, i.e.,  $O(|V|)$  times in total.
- The inner loop `for (each  $v \in \text{Adj}[u]$ )` is called once for each edge in the graph. Each call of the inner loop does  $O(1)$  work plus, possibly, `one` Decrease-Key operation.
- Recalling that all of the priority queue operations require  $O(\log |Q|) = O(\log |V|)$  time, we have that the algorithm uses
$$O(|V|) + |E| \cdot O(1 + \log |V|) = O(|E| \log |V|)$$
time.

# Description of Dijkstra's Algorithm

Dijkstra( $G, w, s$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , source vertex  $s$

**Output:** None

**for**  $u \in V$  **do**  
      $d[u] \leftarrow \infty, color[u] \leftarrow \text{WHITE}$ ; // Initialize

$O(|V|)$

**end**

$d[s] \leftarrow 0$ ;

$pred[s] \leftarrow \text{NULL}$ ;

$Q \leftarrow$  queue with all vertices;

**while**  $Non-Empty(Q)$  **do**

    // Process all vertices

$u \leftarrow \text{Extract-Min}(Q)$ ; // Find new vertex

**for**  $v \in Adj[u]$  **do**

**if**  $d[u] + w(u, v) < d[v]$  **then**

            // If estimate improves

$d[v] \leftarrow d[u] + w(u, v)$ ; // relax

            Decrease-Key( $Q, v, d[v]$ );

$pred[v] \leftarrow u$ ;

**end**

**end**

$color[u] \leftarrow \text{BLACK}$ ;

**end**

$O(\log |V|) \cdot |E|$

# Prim's Algorithm vs. Dijkstra's Algorithm

---

- Dijkstra's algorithm looks similar to Prim's algorithm.
- To understand the differences clearly, try them both on some example.

# Outline

---

- Review to Part IV
- Single-Source Shortest Paths Problem
- Dijkstra's Algorithm
  - The idea
  - The algorithm
  - Analysis of Dijkstra's algorithm
- **The Bellman-Ford Algorithm**
  - **The algorithm**
  - Analysis of Bellman-Ford algorithm

# Negative-weight edges


---

- If the graph contains a negative-weight cycle reachable from the source vertex  $s$ , shortest-path weights are not well defined.




# Negative-weight edges

- If the graph contains a negative-weight cycle reachable from the source vertex  $s$ , shortest-path weights are not well defined.




# Negative-weight edges

- If the graph contains a negative-weight cycle reachable from the source vertex  $s$ , shortest-path weights are not well defined.
- By following the proposed “shortest” path and then traversing the negative-weight cycle, we can always find a path with  $-\infty$  weight.



# Negative-weight edges

- If the graph contains a negative-weight cycle reachable from the source vertex  $s$ , shortest-path weights are not well defined.
- By following the proposed “shortest” path and then traversing the negative-weight cycle, we can always find a path with **lower** weight.



# Review of The Algorithm for Relaxing an Edge

$\text{Relax}(u, v)$

**Input:** Update estimation of  $u$  according to distance of  $v$







**Output:** None

**if**  $d[u] + w(u, v) < d[v]$  **then**

$d[v] \leftarrow d[u] + w(u, v);$

$\text{pred}[v] \leftarrow u;$

**end**



# Description of Bellman-Ford Algorithm

---

- The algorithm relaxes edges, progressively decreasing an estimate  $v.d$  on the weight of a shortest path from the source  $s$  to each vertex  $v \in V$  until it achieves the actual shortest-path weight  $\delta(s, v)$ .

Bellman-Ford( $G, w, s$ )

**Input:** A directed graph  $G$ , weights  $w$ , and the source vertex  $s$

**Output:** Return FALSE if  $G$  contains negative cycle, return TRUE if shortest paths from  $s$  to any other vertices obtained.

# Description of Bellman-Ford Algorithm

---

- The algorithm relaxes edges, progressively decreasing an estimate  $v.d$  on the weight of a shortest path from the source  $s$  to each vertex  $v \in V$  until it achieves the actual shortest-path weight  $\delta(s, v)$ .

Bellman-Ford( $G, w, s$ )

**Input:** A directed graph  $G$ , weights  $w$ , and the source vertex  $s$

**Output:** Return FALSE if  $G$  contains negative cycle, return TRUE if shortest paths from  $s$  to any other vertices obtained.

**for**  $u \in V$  **do**

  |  $d[u] \leftarrow \infty, pred[u] \leftarrow \text{NIL};$  // Initialize

**end**

# Description of Bellman-Ford Algorithm

- The algorithm relaxes edges, progressively decreasing an estimate  $v.d$  on the weight of a shortest path from the source  $s$  to each vertex  $v \in V$  until it achieves **the actual shortest-path weight**  $\delta(s, v)$ .

Bellman-Ford( $G, w, s$ )

**Input:** A directed graph  $G$ , weights  $w$ , and the source vertex  $s$

**Output:** Return FALSE if  $G$  contains negative cycle, return TRUE if shortest paths from  $s$  to any other vertices obtained.

```

for  $u \in V$  do
  |  $d[u] \leftarrow \infty, pred[u] \leftarrow \text{NIL};$  // Initialize
end
for  $i \leftarrow 1$  to  $|V| - 1$  do
  | for  $e \in E$  do
  | |
  | end
end

```

# Description of Bellman-Ford Algorithm

- The algorithm relaxes edges, progressively decreasing an estimate  $v.d$  on the weight of a shortest path from the source  $s$  to each vertex  $v \in V$  until it achieves the actual shortest-path weight  $\delta(s, v)$ .

Bellman-Ford( $G, w, s$ )

**Input:** A directed graph  $G$ , weights  $w$ , and the source vertex  $s$

**Output:** Return FALSE if  $G$  contains negative cycle, return TRUE if shortest paths from  $s$  to any other vertices obtained.

```

for  $u \in V$  do
  |  $d[u] \leftarrow \infty, pred[u] \leftarrow \text{NIL};$  // Initialize
end
for  $i \leftarrow 1$  to  $|V| - 1$  do
  | for  $e \in E$  do
  | | RELAX( $u, v, w$ );
  | end
end

```



# The Bellman-Ford Algorithm

- The algorithm relaxes edges, progressively decreasing an estimate  $v.d$  on the weight of a shortest path from the source  $s$  to each vertex  $v \in V$  until it achieves the actual shortest-path weight  $\delta(s, v)$ .

Bellman-Ford( $G, w, s$ )

**Input:** A directed graph  $G$ , weights  $w$ , and the source vertex  $s$

**Output:** Return FALSE if  $G$  contains negative cycle, return TRUE if shortest paths from  $s$  to any other vertices obtained.

```

for  $u \in V$  do
  |  $d[u] \leftarrow \infty, pred[u] \leftarrow \text{NIL};$  // Initialize
end
for  $i \leftarrow 1$  to  $|V| - 1$  do
  | for  $e \in E$  do
  | | RELAX( $u, v, w$ );
  | end
end
for  $e \in E$  do
  | if  $d[v] > d[u] + w(u, v)$  then
  | | return FALSE;
  | end
end
return

```

# Description of Bellman-Ford Algorithm

- The algorithm relaxes edges, progressively decreasing an estimate  $v.d$  on the weight of a shortest path from the source  $s$  to each vertex  $v \in V$  until it achieves the actual shortest-path weight  $\delta(s, v)$ .

Bellman-Ford( $G, w, s$ )

**Input:** A directed graph  $G$ , weights  $w$ , and the source vertex  $s$

**Output:** Return FALSE if  $G$  contains negative cycle, return TRUE if shortest paths from  $s$  to any other vertices obtained.

```

for  $u \in V$  do
  |  $d[u] \leftarrow \infty, pred[u] \leftarrow \text{NIL};$  // Initialize
end
for  $i \leftarrow 1$  to  $|V| - 1$  do
  | for  $e \in E$  do
  | | RELAX( $u, v, w$ );
  | end
end
for  $e \in E$  do
  | if  $d[v] > d[u] + w(u, v)$  then
  | | return FALSE;
  | end
end
return TRUE;

```

# An Example of Bellman-Ford Algorithm


## Initialization

d

$\infty$	$\infty$	$\infty$	$\infty$	$\infty$
----------	----------	----------	----------	----------

pred

N	N	N	N	N
---	---	---	---	---



# An Example of Bellman-Ford Algorithm


## Initialization

d

$\infty$	$\infty$	$\infty$	$\infty$	$\infty$
----------	----------	----------	----------	----------

pred

N	N	N	N	N
---	---	---	---	---



# An Example of Bellman-Ford Algorithm


## Initialization

d

0	$\infty$	$\infty$	$\infty$	$\infty$
---	----------	----------	----------	----------

pred

N	N	N	N	N
---	---	---	---	---



# An Example of Bellman-Ford Algorithm


## 1<sup>st</sup> round

d

0	$\infty$	$\infty$	$\infty$	$\infty$
---	----------	----------	----------	----------

pred

N	N	N	N	N
---	---	---	---	---



These edges do not cause Relaxation.

# An Example of Bellman-Ford Algorithm


## 1<sup>st</sup> round

d

0	2	7	$\infty$	$\infty$
---	---	---	----------	----------

pred

N	1	1	N	N
---	---	---	---	---



# An Example of Bellman-Ford Algorithm


## 2<sup>nd</sup> round

d

0	2	7	$\infty$	$\infty$
---	---	---	----------	----------

pred

N	1	1	N	N
---	---	---	---	---





# An Example of Bellman-Ford Algorithm


**2<sup>nd</sup>** round

d

0	2	7	$\infty$	$\infty$
---	---	---	----------	----------

pred

N	1	1	N	N
---	---	---	---	---



# An Example of Bellman-Ford Algorithm


## 2<sup>nd</sup> round

d

0	2	7	$\infty$	7
---	---	---	----------	---

pred

N	1	1	N	2
---	---	---	---	---



# An Example of Bellman-Ford Algorithm


## 2<sup>nd</sup> round

d

0	2	7	8	7
---	---	---	---	---

pred

N	1	1	3	2
---	---	---	---	---



# An Example of Bellman-Ford Algorithm


## 2<sup>nd</sup> round

d

0	2	5	8	7
---	---	---	---	---

pred

N	1	2	3	2
---	---	---	---	---



# An Example of Bellman-Ford Algorithm


## 2<sup>nd</sup> round

d

0	2	5	8	7
---	---	---	---	---

pred

N	1	2	3	2
---	---	---	---	---



# An Example of Bellman-Ford Algorithm


**3<sup>rd</sup>** round

d

0	2	5	8	7
---	---	---	---	---

pred

N	1	2	3	2
---	---	---	---	---



# An Example of Bellman-Ford Algorithm


**3<sup>rd</sup>** round

d

0	2	5	8	7
---	---	---	---	---

pred

N	1	2	3	2
---	---	---	---	---



# An Example of Bellman-Ford Algorithm


## 3<sup>rd</sup> round

d

0	2	5	6	7
---	---	---	---	---

pred

N	1	2	3	2
---	---	---	---	---





# An Example of Bellman-Ford Algorithm


## 3<sup>rd</sup> round

d

0	2	5	6	7
---	---	---	---	---

pred

N	1	2	3	2
---	---	---	---	---



# An Example of Bellman-Ford Algorithm


**4<sup>th</sup>** round

d

0	2	5	6	7
---	---	---	---	---

pred

N	1	2	3	2
---	---	---	---	---



# An Example of Bellman-Ford Algorithm


4<sup>th</sup> round

d

0	2	5	6	7
---	---	---	---	---

pred

N	1	2	3	2
---	---	---	---	---



# An Example of Bellman-Ford Algorithm


4<sup>th</sup> round

d

0	2	5	6	7
---	---	---	---	---

pred

N	1	2	3	2
---	---	---	---	---




# An Example of Bellman-Ford Algorithm

d

0	2	5	6	7
---	---	---	---	---

pred

N	1	2	3	2
---	---	---	---	---



# Outline

---

- Review to Part IV
- Single-Source Shortest Paths Problem
- Dijkstra's Algorithm
  - The idea
  - The algorithm
  - Analysis of Dijkstra's algorithm
- **The Bellman-Ford Algorithm**
  - The algorithm
  - **Analysis of Bellman-Ford algorithm**

# Analysis of Bellman-Ford Algorithm

- The Bellman-Ford algorithm runs in time  $O(|V| \cdot |E|)$  since the initialization takes  $O(|V|)$  time, each of the  $|V| - 1$  passes over the edges takes  $O(|E|)$  time, and the **for** loop takes  $O(|E|)$  time.

Bellman-Ford( $G, w, s$ )

**Input:** A directed graph  $G$ , weights  $w$ , and the source vertex  $s$

**Output:** Return FALSE if  $G$  contains negative cycle, return TRUE if shortest paths from  $s$  to any other vertices obtained.

```

for  $u \in V$  do
  |  $d[u] \leftarrow \infty, pred[u] \leftarrow \text{NIL};$  // Initialize
end
for  $i \leftarrow 1$  to  $|V| - 1$  do
  | for  $e \in E$  do
  | | RELAX( $u, v, w$ );
  | end
end
for  $e \in E$  do
  | if  $d[v] > d[u] + w(u, v)$  then
  | | return FALSE;
  | end
end
return TRUE;

```

# Analysis of Bellman-Ford Algorithm

- The Bellman-Ford algorithm runs in time  $O(|V| \cdot |E|)$  since the initialization takes  $O(|V|)$  time, each of the  $|V| - 1$  passes over the edges takes  $O(|E|)$  time, and the **for** loop takes  $O(|E|)$  time.

Bellman-Ford( $G, w, s$ )

**Input:** A directed graph  $G$ , weights  $w$ , and the source vertex  $s$

**Output:** Return FALSE if  $G$  contains negative cycle, return TRUE if shortest paths from  $s$  to any other vertices obtained.

```

for  $u \in V$  do
  |  $d[u] \leftarrow \infty, pred[u] \leftarrow \text{NIL};$  // Initialize  $O(|V|)$ 
end
for  $i \leftarrow 1$  to  $|V| - 1$  do  $O(|V| \cdot |E|)$ 
  | for  $e \in E$  do
  | |  $\text{RELAX}(u, v, w);$ 
  | end
end
for  $e \in E$  do  $O(|E|)$ 
  | if  $d[v] > d[u] + w(u, v)$  then
  | | return FALSE;
  | end
end
return TRUE;

```



dank u  
ju faleminderit  
Tack  
Asante 谢谢 Tak mulțumesc  
kiitos  
**Salamat!** Gracias  
Terima kasih Aliquam  
Merci  
Dankie Obrigado  
ありがとう köszönöm grazie  
Aliquam Go raibh maith agat  
děkuii Thank you