

# Design and Analysis of Algorithms

## Part IV: Graph Algorithms

### Lecture 11: Minimum Spanning Trees



**Yongxin Tong (童咏昕)**

School of CSE, Beihang University

[yxtong@buaa.edu.cn](mailto:yxtong@buaa.edu.cn)

# Outline

---

- Review to Part IV
- Minimum Spanning Trees
  - Spanning trees
  - Minimum spanning trees
- Prim's algorithm
  - The idea
  - The algorithm
  - Analysis for Prim's algorithm
- Kruskal's algorithm
  - The idea
  - The algorithm
  - The Disjoint Set Union-Find data structure
  - Analysis for Kruskal's algorithm

# Outline

---

- Review to Part IV
- Minimum Spanning Trees
  - Spanning trees
  - Minimum spanning trees
- Prim's algorithm
  - The idea
  - The algorithm
  - Analysis for Prim's algorithm
- Kruskal's algorithm
  - The idea
  - The algorithm
  - The Disjoint Set Union-Find data structure
  - Analysis for Kruskal's algorithm

# Introduction to Part IV

---

- In Part IV, we will illustrate several graph algorithm problems using several examples:
  - Basic Concepts of Graphs (图的基本概念)
  - Breadth-First Search [BFS] (广度优先搜索)
  - Depth-First Search [DFS] (深度优先搜索)
  - Topological Sort (拓扑排序)
  - Strongly Connected Components (强联通分量)
  - Minimum Spanning Trees (最小生成树)
  - Shortest Path (最短路径)
  - All-Pairs Shortest Paths (所有结点对的最短路径)
  - Maximum/Network Flows (最大流/网络流)

# Introduction to Part IV

---

- In Part IV, we will illustrate several graph algorithm problems using several examples:
  - Basic Concepts of Graphs (图的基本概念)
  - Breadth-First Search [BFS] (广度优先搜索)
  - Depth-First Search [DFS] (深度优先搜索)
  - Topological Sort (拓扑排序)
  - Strongly Connected Components (强联通分量)
  - **Minimum Spanning Trees (最小生成树)**
  - Shortest Path (最短路径)
  - All-Pairs Shortest Paths (所有结点对的最短路径)
  - Maximum/Network Flows (最大流/网络流)

# Outline

---

- Review to Part IV
- **Minimum Spanning Trees**
  - **Spanning trees**
  - Minimum spanning trees
- **Prim's algorithm**
  - The idea
  - The algorithm
  - Analysis for Prim's algorithm
- **Kruskal's algorithm**
  - The idea
  - The algorithm
  - The Disjoint Set Union-Find data structure
  - Analysis for Kruskal's algorithm

# Spanning Trees

---

## Definition


A **subgraph**  $T$  of a undirected graph  $G = (V, E)$  is a **spanning tree** of  $G$  if it is a tree and contains **every vertex** of  $G$

# Spanning Trees


## Definition

A **subgraph**  $T$  of a undirected graph  $G = (V, E)$  is a **spanning tree** of  $G$  if it is a tree and contains **every vertex** of  $G$


## Example




Graph



spanning tree 1



spanning tree 2



spanning tree 3



# Spanning Trees

---

## Theorem

*Every connected graph has a spanning tree.*

# Spanning Trees

---

## Theorem

*Every connected graph has a spanning tree.*

## Question

Why is this true?

# Spanning Trees

## Theorem


*Every connected graph has a spanning tree.*

## Question

Why is this true?

## Question

Given a connected graph  $G$ , how can you find a spanning tree of  $G$ ?



# Weighted Graphs

---

## Definition


A **weighted graph** is a graph, in which each edge has a **weight** (some real number)

# Weighted Graphs


## Definition

A **weighted graph** is a graph, in which each edge has a **weight** (some real number)


## Example




weighted graph



Tree 1.  $w=74$



Tree 2,  $w=71$




Tree 3,  $w=72$

# Weighted Graphs


## Definition

A **weighted graph** is a graph, in which each edge has a **weight** (some real number)


## Example




weighted graph



Tree 1.  $w=74$



Tree 2,  $w=71$



Tree 3,  $w=72$

## Definition

**Weight of a graph:** The sum of the weights of all edges

# Outline

---

- Review to Part IV
- **Minimum Spanning Trees**
  - Spanning trees
  - **Minimum Spanning Trees**
- Prim's algorithm
  - The idea
  - The algorithm
  - Analysis for Prim's algorithm
- Kruskal's algorithm
  - The idea
  - The algorithm
  - The Disjoint Set Union-Find data structure
  - Analysis for Kruskal's algorithm

# Minimum Spanning Trees

---

## Definition

A **Minimum spanning tree** of an undirected connected weighted graph is a spanning tree of **minimum weight** (among all spanning trees).




# Minimum Spanning Trees


## Definition

A **Minimum spanning tree** of an undirected connected weighted graph is a spanning tree of **minimum weight** (among all spanning trees).


## Example




weighted graph



Tree 1.  $w=74$



Tree 2,  $w=71$




Tree 3,  $w=72$


# Remark

The minimum spanning tree may not be **unique**


## Example



weighted graph



MST1




MST2


# Remark

The minimum spanning tree may not be **unique**


## Example



weighted graph



MST1



MST2

However, if the weights of all the edges are distinct, it is indeed unique (we won't prove this now)

# Minimum Spanning Tree Problem

---

## Definition (MST Problem)

Given a connected weighted undirected graph  $G$ , design an algorithm that outputs a minimum spanning tree (MST) of  $G$ .

# General strategy for solving the MST Problem

---

A tree is an **acyclic** graph

- start with an **empty** graph.

# General strategy for solving the MST Problem

---

A tree is an **acyclic** graph

- start with an **empty** graph.
- try to **add** edges one at a time, always making sure that what is built remains acyclic.

# General strategy for solving the MST Problem

---

A tree is an **acyclic** graph

- start with an **empty** graph.
- try to **add** edges one at a time, always making sure that what is built remains acyclic.
- if after adding each edge we are sure that the resulting graph is a **subset** of some minimum spanning trees, we are done.

# Generic Algorithm for MST problem

---

## Definition

Let  $A$  be a set of edges such that  $A \subseteq T$ , where  $T$  is a MST.



# Generic Algorithm for MST problem

---

## Definition

Let  $A$  be a set of edges such that  $A \subseteq T$ , where  $T$  is a MST. An edge  $(u, v)$  is a **safe edge** for  $A$ , if  $A \cup \{(u, v)\}$  is also a subset of some MST

# Generic Algorithm for MST problem

## Definition

Let  $A$  be a set of edges such that  $A \subseteq T$ , where  $T$  is a MST. An edge  $(u, v)$  is a **safe edge** for  $A$ , if  $A \cup \{(u, v)\}$  is also a subset of some MST

- If at each step, we can find a safe edge  $(u, v)$ , we can **grow** a MST

# Generic Algorithm for MST problem

## Definition

Let  $A$  be a set of edges such that  $A \subseteq T$ , where  $T$  is a MST. An edge  $(u, v)$  is a **safe edge** for  $A$ , if  $A \cup \{(u, v)\}$  is also a subset of some MST

- If at each step, we can find a safe edge  $(u, v)$ , we can **grow** a MST

Generic-MST( $G$ )

**Input:** A graph  $G$

**Output:**  $A$  is the MST of  $G$

$A \leftarrow \text{EMPTY};$

# Generic Algorithm for MST problem

## Definition

Let  $A$  be a set of edges such that  $A \subseteq T$ , where  $T$  is a MST. An edge  $(u, v)$  is a **safe edge** for  $A$ , if  $A \cup \{(u, v)\}$  is also a subset of some MST

- If at each step, we can find a safe edge  $(u, v)$ , we can **grow** a MST

## Generic-MST( $G$ )

**Input:** A graph  $G$

**Output:**  $A$  is the MST of  $G$

$A \leftarrow \text{EMPTY};$

**while**  $A$  does not form a spanning tree **do**

# Generic Algorithm for MST problem

## Definition

Let  $A$  be a set of edges such that  $A \subseteq T$ , where  $T$  is a MST. An edge  $(u, v)$  is a **safe edge** for  $A$ , if  $A \cup \{(u, v)\}$  is also a subset of some MST

- If at each step, we can find a safe edge  $(u, v)$ , we can **grow** a MST

## Generic-MST( $G$ )

**Input:** A graph  $G$

**Output:**  $A$  is the MST of  $G$

$A \leftarrow \text{EMPTY};$

**while**  $A$  does not form a spanning tree **do**

  | find an edge  $(u, v)$  that is **safe** for  $A$ ;

# Generic Algorithm for MST problem

## Definition

Let  $A$  be a set of edges such that  $A \subseteq T$ , where  $T$  is a MST. An edge  $(u, v)$  is a **safe edge** for  $A$ , if  $A \cup \{(u, v)\}$  is also a subset of some MST

- If at each step, we can find a safe edge  $(u, v)$ , we can **grow** a MST

## Generic-MST( $G$ )

**Input:** A graph  $G$

**Output:**  $A$  is the MST of  $G$

$A \leftarrow \text{EMPTY};$

**while**  $A$  does not form a spanning tree **do**

    | find an edge  $(u, v)$  that is **safe** for  $A$ ;

    | add  $(u, v)$  to  $A$ ;

# Generic Algorithm for MST problem

## Definition

Let  $A$  be a set of edges such that  $A \subseteq T$ , where  $T$  is a MST. An edge  $(u, v)$  is a **safe edge** for  $A$ , if  $A \cup \{(u, v)\}$  is also a subset of some MST

- If at each step, we can find a safe edge  $(u, v)$ , we can **grow** a MST

## Generic-MST( $G$ )

**Input:** A graph  $G$

**Output:**  $A$  is the MST of  $G$

$A \leftarrow \text{EMPTY};$

**while**  $A$  does not form a spanning tree **do**

    | find an edge  $(u, v)$  that is **safe** for  $A$ ;  
    | add  $(u, v)$  to  $A$ ;

**end**

**return**  $A$ ;

# Some Definitions

---

## Definition

Let  $G = (V, E)$  be a connected and undirected graph. A **cut**  $(S, V - S)$  of  $G$  is a partition of  $V$ .




# Some Definitions

## Definition

Let  $G = (V, E)$  be a connected and undirected graph. A **cut**  $(S, V - S)$  of  $G$  is a partition of  $V$ .

## Example




# Some Definitions

## Definition

Let  $G = (V, E)$  be a connected and undirected graph. A **cut**  $(S, V - S)$  of  $G$  is a partition of  $V$ .

## Example



## Definition


An edge  $(u, v) \in E$  **crosses** the cut  $(S, V - S)$  if one of its endpoints is in  $S$ , and the other is in  $V - S$ .

# Some Definitions

## Definition

Let  $G = (V, E)$  be a connected and undirected graph. A **cut**  $(S, V - S)$  of  $G$  is a partition of  $V$ .

## Example



## Definition

An edge  $(u, v) \in E$  **crosses** the cut  $(S, V - S)$  if one of its endpoints is in  $S$ , and the other is in  $V - S$ .


A cut **respects** a set  $A$  of edges if no edge in  $A$  crosses the cut.

# Some Definitions

## Definition

Let  $G = (V, E)$  be a connected and undirected graph. A **cut**  $(S, V - S)$  of  $G$  is a partition of  $V$ .

## Example



## Definition

An edge  $(u, v) \in E$  **crosses** the cut  $(S, V - S)$  if one of its endpoints is in  $S$ , and the other is in  $V - S$ .

A cut **respects** a set  $A$  of edges if no edge in  $A$  crosses the cut.

An edge is a **light edge** crossing a cut if its weight is the **minimum** of any edge crossing the cut.

# How to Find a Safe Edge?

## Lemma

- *Let  $G = (V, E)$  be a connected, undirected graph with a real-valued weight function  $w$  defined on  $E$*

# How to Find a Safe Edge?

## Lemma

- *Let  $G = (V, E)$  be a connected, undirected graph with a real-valued weight function  $w$  defined on  $E$*
- *$A$  be a subset of  $E$  that is included in some minimum spanning tree for  $G$ .*



# How to Find a Safe Edge?

## Lemma

- Let  $G = (V, E)$  be a connected, undirected graph with a real-valued weight function  $w$  defined on  $E$
- $A$  be a subset of  $E$  that is included in some minimum spanning tree for  $G$ .

Let

- $(S, V - S)$  be *any* cut of  $G$  that respects  $A$

# How to Find a Safe Edge?

## Lemma

- Let  $G = (V, E)$  be a connected, undirected graph with a real-valued weight function  $w$  defined on  $E$
- $A$  be a subset of  $E$  that is included in some minimum spanning tree for  $G$ .

Let

- $(S, V - S)$  be *any* cut of  $G$  that respects  $A$
- $(u, v)$  be a light edge crossing the cut  $(S, V - S)$



# How to Find a Safe Edge?


## Lemma

- Let  $G = (V, E)$  be a connected, undirected graph with a real-valued weight function  $w$  defined on  $E$
- $A$  be a subset of  $E$  that is included in some minimum spanning tree for  $G$ .

Let

- $(S, V - S)$  be *any* cut of  $G$  that respects  $A$
- $(u, v)$  be a light edge crossing the cut  $(S, V - S)$

Then, edge  $(u, v)$  is *safe* for  $A$ .



# How to Find a Safe Edge?

## Lemma


- Let  $G = (V, E)$  be a connected, undirected graph with a real-valued weight function  $w$  defined on  $E$
- $A$  be a subset of  $E$  that is included in some minimum spanning tree for  $G$ .

Let

- $(S, V - S)$  be *any* cut of  $G$  that respects  $A$
- $(u, v)$  be a light edge crossing the cut  $(S, V - S)$

Then, edge  $(u, v)$  is *safe* for  $A$ .

It means that we can find a safe edge by



# How to Find a Safe Edge?

## Lemma

- Let  $G = (V, E)$  be a connected, undirected graph with a real-valued weight function  $w$  defined on  $E$
- $A$  be a subset of  $E$  that is included in some minimum spanning tree for  $G$ .


Let

- $(S, V - S)$  be *any* cut of  $G$  that respects  $A$
- $(u, v)$  be a light edge crossing the cut  $(S, V - S)$

Then, edge  $(u, v)$  is *safe* for  $A$ .

It means that we can find a safe edge by

- 1 first finding a cut that respects  $A$ ,





# How to Find a Safe Edge?


## Lemma

- Let  $G = (V, E)$  be a connected, undirected graph with a real-valued weight function  $w$  defined on  $E$
- $A$  be a subset of  $E$  that is included in some minimum spanning tree for  $G$ .

Let

- $(S, V - S)$  be *any* cut of  $G$  that respects  $A$
- $(u, v)$  be a light edge crossing the cut  $(S, V - S)$

Then, edge  $(u, v)$  is *safe* for  $A$ .



It means that we can find a safe edge by

- 1 first finding a cut that respects  $A$ ,
- 2 then finding the light edge crossing that cut.

That light edge is a safe edge.

# Proof

---

- Let  $A \subseteq T$ , where  $T$  is a MST.

# Proof

---

- Let  $A \subseteq T$ , where  $T$  is a MST.
- Case 1:  $(u, v) \in T$

# Proof

---

- Let  $A \subseteq T$ , where  $T$  is a MST.
- Case 1:  $(u, v) \in T$ 
  - $A \cup \{(u, v)\} \subseteq T$ .
  - Hence  $(u, v)$  is safe for  $A$ .

## Proof (cont'd)

---

- Case 2:  $(u, v) \notin T$



## Proof (cont'd)

---

- Case 2:  $(u, v) \notin T$ 
  - Idea: construct **another** MST  $T'$  s.t.  $A \cup \{(u, v)\} \subseteq T'$ .

## Proof (cont'd)

---

- Case 2:  $(u, v) \notin T$ 
  - Idea: construct **another** MST  $T'$  s.t.  $A \cup \{(u, v)\} \subseteq T'$ .
  - Consider a path  $P$  in  $T$  from  $u$  to  $v$ .

# Proof (cont'd)

---

- Case 2:  $(u, v) \notin T$ 
  - Idea: construct **another** MST  $T'$  s.t.  $A \cup \{(u, v)\} \subseteq T'$ .
  - Consider a path  $P$  in  $T$  from  $u$  to  $v$ .
  - Since  $u$  and  $v$  are on opposite sides of the cut  $(S, V-S)$ ,
    - There is at least one edge in  $P$  that **crosses** the cut.

# Proof (cont'd)

---

- Case 2:  $(u, v) \notin T$ 
  - Idea: construct **another** MST  $T'$  s.t.  $A \cup \{(u, v)\} \subseteq T'$ .
  - Consider a path  $P$  in  $T$  from  $u$  to  $v$ .
  - Since  $u$  and  $v$  are on opposite sides of the cut  $(S, V-S)$ ,
    - There is at least one edge in  $P$  that **crosses** the cut.
    - Let  $(x, y)$  be such an edge.


# Proof (cont'd)

---

- Case 2:  $(u, v) \notin T$ 
  - Idea: construct **another** MST  $T'$  s.t.  $A \cup \{(u, v)\} \subseteq T'$ .
  - Consider a path  $P$  in  $T$  from  $u$  to  $v$ .
  - Since  $u$  and  $v$  are on opposite sides of the cut  $(S, V-S)$ ,
    - There is at least one edge in  $P$  that **crosses** the cut.
    - Let  $(x, y)$  be such an edge.
  - Since the cut respects  $A$ ,  $(x, y) \notin A$ .


# Proof (cont'd)

- Case 2:  $(u, v) \notin T$ 
  - Idea: construct **another** MST  $T'$  s.t.  $A \cup \{(u, v)\} \subseteq T'$ .
  - Consider a path  $P$  in  $T$  from  $u$  to  $v$ .
  - Since  $u$  and  $v$  are on opposite sides of the cut  $(S, V-S)$ ,
    - There is at least one edge in  $P$  that **crosses** the cut.
    - Let  $(x, y)$  be such an edge.
  - Since the cut respects  $A$ ,  $(x, y) \notin A$ .
  - Since  $(u, v)$  is a light edge crossing the cut, we have  $w(x, y) \geq w(u, v)$ .



# Proof (cont'd)


- Add  $(u, v)$  to  $T$ , it creates a cycle. By removing an edge from the cycle, it becomes a tree again. In particular, we remove  $(x, y)$  ( $\notin A$ ) to make a new tree  $T'$ .



# Proof (cont'd)

- Add  $(u, v)$  to  $T$ , it creates a cycle. By removing an edge from the cycle, it becomes a tree again. In particular, we remove  $(x, y) \notin A$  to make a new tree  $T'$ .
- The weight of  $T'$  is

$$w(T') = w(T) - w(x, y) + w(u, v)$$






# Proof (cont'd)

- Add  $(u, v)$  to  $T$ , it creates a cycle. By removing an edge from the cycle, it becomes a tree again. In particular, we remove  $(x, y)$  ( $\notin A$ ) to make a new tree  $T'$ .
- The weight of  $T'$  is

$$\begin{aligned} w(T') &= w(T) - w(x, y) + w(u, v) \\ &\leq w(T) \end{aligned}$$




# Proof (cont'd)

- Add  $(u, v)$  to  $T$ , it creates a cycle. By removing an edge from the cycle, it becomes a tree again. In particular, we remove  $(x, y)$  ( $\notin A$ ) to make a new tree  $T'$ .

- The weight of  $T'$  is

$$\begin{aligned} w(T') &= w(T) - w(x, y) + w(u, v) \\ &\leq w(T) \end{aligned}$$

- Since  $T$  is a MST, we must have  $w(T) = w(T')$ , hence  $T'$  is also a MST.



# Proof (cont'd)

- Add  $(u, v)$  to  $T$ , it creates a cycle. By removing an edge from the cycle, it becomes a tree again. In particular, we remove  $(x, y) (\notin A)$  to make a new tree  $T'$ .


- The weight of  $T'$  is

$$\begin{aligned} w(T') &= w(T) - w(x, y) + w(u, v) \\ &\leq w(T) \end{aligned}$$

- Since  $T$  is a MST, we must have  $w(T) = w(T')$ , hence  $T'$  is also a MST.

- Since  $A \cup \{(u, v)\} \subseteq T'$ ,  $(u, v)$  is safe for  $A$ .

- The Lemma is proved.



# Outline

---

- Review to Part IV
- Minimum Spanning Trees
  - Spanning trees
  - Minimum spanning trees
- Prim's algorithm
  - The idea
  - The algorithm
  - Analysis for Prim's algorithm
- Kruskal's algorithm
  - The idea
  - The algorithm
  - The Disjoint Set Union-Find data structure
  - Analysis for Kruskal's algorithm

# Prim's Algorithm

---

- The generic algorithm gives us an idea how to 'grow' a MST.

# Prim's Algorithm

---

- The generic algorithm gives us an idea how to 'grow' a MST.
  - If you read the theorem and the proof carefully, you will notice that the choice of a cut (and hence the corresponding light edge) in each iteration is arbitrary.

# Prim's Algorithm

---

- The generic algorithm gives us an idea how to 'grow' a MST.
  - If you read the theorem and the proof carefully, you will notice that the choice of a cut (and hence the corresponding light edge) in each iteration is arbitrary.
  - We can select **any cut** (that respects the selected edges) and find the light edge crossing that cut to proceed.

# Prim's Algorithm

---

- The generic algorithm gives us an idea how to 'grow' a MST.
  - If you read the theorem and the proof carefully, you will notice that the choice of a cut (and hence the corresponding light edge) in each iteration is arbitrary.
  - We can select **any cut** (that respects the selected edges) and find the light edge crossing that cut to proceed.
- **Prim's algorithm** makes a nature choice of the cut in each Iteration



# Prim's Algorithm

---

- The generic algorithm gives us an idea how to 'grow' a MST.
  - If you read the theorem and the proof carefully, you will notice that the choice of a cut (and hence the corresponding light edge) in each iteration is arbitrary.
  - We can select **any cut** (that respects the selected edges) and find the light edge crossing that cut to proceed.
- **Prim's algorithm** makes a nature choice of the cut in each Iteration
  - grows a single tree and adds a light edge in each iteration.

# Prim's Algorithm

---

- The generic algorithm gives us an idea how to 'grow' a MST.
  - If you read the theorem and the proof carefully, you will notice that the choice of a cut (and hence the corresponding light edge) in each iteration is arbitrary.
  - We can select **any cut** (that respects the selected edges) and find the light edge crossing that cut to proceed.
- **Prim's algorithm** makes a nature choice of the cut in each Iteration
  - grows a single tree and adds a light edge in each iteration.
  - Grow a tree

# Prim's Algorithm

---

- The generic algorithm gives us an idea how to 'grow' a MST.
  - If you read the theorem and the proof carefully, you will notice that the choice of a cut (and hence the corresponding light edge) in each iteration is arbitrary.
  - We can select **any cut** (that respects the selected edges) and find the light edge crossing that cut to proceed.
- **Prim's algorithm** makes a nature choice of the cut in each Iteration
  - grows a single tree and adds a light edge in each iteration.
  - Grow a tree
    - Start by picking **any** vertex  $r$  to be the root of the tree.

# Prim's Algorithm

---

- The generic algorithm gives us an idea how to 'grow' a MST.
  - If you read the theorem and the proof carefully, you will notice that the choice of a cut (and hence the corresponding light edge) in each iteration is arbitrary.
  - We can select **any cut** (that respects the selected edges) and find the light edge crossing that cut to proceed.
- **Prim's algorithm** makes a nature choice of the cut in each Iteration
  - grows a single tree and adds a light edge in each iteration.
  - Grow a tree
    - Start by picking **any** vertex  $r$  to be the root of the tree.
    - While the tree does not contain all vertices in the graph:


# Prim's Algorithm

---

- The generic algorithm gives us an idea how to 'grow' a MST.
  - If you read the theorem and the proof carefully, you will notice that the choice of a cut (and hence the corresponding light edge) in each iteration is arbitrary.
  - We can select **any cut** (that respects the selected edges) and find the light edge crossing that cut to proceed.
- **Prim's algorithm** makes a nature choice of the cut in each Iteration
  - grows a single tree and adds a light edge in each iteration.
  - Grow a tree
    - Start by picking **any** vertex  $r$  to be the root of the tree.
    - While the tree does not contain all vertices in the graph: find **shortest** edge leaving the tree and add it to the tree.

# More Details

## Example




Step 0:

- Choose any element  $r$ ; set  $S = \{r\}$  and  $A = \emptyset$ .
- (Take  $r$  as the root of our spanning tree.)

# More Details

## Example



Step 0:


- Choose any element  $r$ ; set  $S = \{r\}$  and  $A = \emptyset$ .
- (Take  $r$  as the root of our spanning tree.)

Step 1:

- Find a lightest edge such that one endpoint is in  $S$  and the other is in  $V \setminus S$ .

# More Details

## Example



Step 0:

- Choose any element  $r$ ; set  $S = \{r\}$  and  $A = \emptyset$ .
- (Take  $r$  as the root of our spanning tree.)


Step 1:

- Find a lightest edge such that one endpoint is in  $S$  and the other is in  $V \setminus S$ .
- Add this edge to  $A$  and its (other) endpoint to  $S$ .



# More Details

## Example



Step 0:

- Choose any element  $r$ ; set  $S = \{r\}$  and  $A = \emptyset$ .
- (Take  $r$  as the root of our spanning tree.)


Step 1:

- Find a lightest edge such that one endpoint is in  $S$  and the other is in  $V \setminus S$ .
- Add this edge to  $A$  and its (other) endpoint to  $S$ .


Step 2:

- If  $V \setminus S = \emptyset$ , then stop and output (minimum) spanning tree  $(S, A)$ ; Otherwise, go to Step 1.

# Prim's Example



Connected graph




Step 0

$S = \{1\}$

$V \setminus S = \{2,3,4,5,6,7\}$

lightest edge =  $\{1,2\}$

# Prim's Example




Step 1.1 before

$S = \{1\}$

$V \setminus S = \{2,3,4,5,6,7\}$

$A = \{\}$

lightest edge =  $\{1,2\}$



Step 1.1 after


$S = \{1,2\}$

$V \setminus S = \{3,4,5,6,7\}$

$A = \{ \{1,2\} \}$

lightest edge =  $\{1,3\}, \{2,4\}$

# Prim's Example




Step 1.2 before

$S = \{1,2\}$

$V \setminus S = \{3,4,5,6,7\}$

$A = \{ \{1,2\} \}$

lightest edge =  $\{1,3\}, \{2,4\}$



Step 1.2 after


$S = \{1,2,3\}$

$V \setminus S = \{4,5,6,7\}$

$A = \{ \{1,2\}, \{1,3\} \}$

lightest edge =  $\{3,6\}$

# Prim's Example




Step 1.3 before

$S = \{1,2,3\}$

$V \setminus S = \{4,5,6,7\}$

$A = \{ \{1,2\}, \{1,3\} \}$

lightest edge =  $\{3,6\}$



Step 1.3 after


$S = \{1,2,3,6\}$

$V \setminus S = \{4,5,7\}$

$A = \{ \{1,2\}, \{1,3\}, \{3,6\} \}$

lightest edge =  $\{3,4\}, \{6,4\}, \{6,7\}$

# Prim's Example




Step 1.4 before

$S = \{1, 2, 3, 6\}$

$V \setminus S = \{4, 5, 7\}$

$A = \{ \{1, 2\}, \{1, 3\}, \{3, 6\} \}$

lightest edge =  $\{3, 4\}, \{6, 4\}, \{6, 7\}$



Step 1.4 after


$S = \{1, 2, 3, 4, 6\}$

$V \setminus S = \{5, 7\}$

$A = \{ \{1, 2\}, \{1, 3\}, \{3, 6\}, \{3, 4\} \}$

lightest edge =  $\{6, 7\}$

# Prim's Example




Step 1.5 before

$S = \{1, 2, 3, 4, 6\}$

$V \setminus S = \{5, 7\}$

$A = \{ \{1, 2\}, \{1, 3\}, \{3, 6\}, \{3, 4\} \}$

lightest edge =  $\{6, 7\}$



Step 1.5 after


$S = \{1, 2, 3, 4, 6, 7\}$

$V \setminus S = \{5\}$

$A = \{ \{1, 2\}, \{1, 3\}, \{3, 6\}, \{3, 4\}, \{6, 7\} \}$

lightest edge =  $\{6, 5\}$

# Prim's Example




Step 1.6 before

$S = \{1, 2, 3, 4, 6, 7\}$

$V \setminus S = \{5\}$

$A = \{ \{1, 2\}, \{1, 3\}, \{3, 6\}, \{3, 4\}, \{6, 7\} \}$

lightest edge =  $\{6, 5\}$



Step 1.6 after

$S = \{1, 2, 3, 4, 5, 6, 7\}$

$V \setminus S = \{\}$

$A = \{ \{1, 2\}, \{1, 3\}, \{3, 6\}, \{3, 4\}, \{6, 7\}, \{6, 5\} \}$

MST completed



# Outline

---

- Review to Part IV
- Minimum Spanning Trees
  - Spanning trees
  - Minimum spanning trees
- Prim's algorithm
  - The idea
  - The algorithm
  - Analysis for Prim's algorithm
- Kruskal's algorithm
  - The idea
  - The algorithm
  - The Disjoint Set Union-Find data structure
  - Analysis for Kruskal's algorithm

# Recall Idea of Prim's Algorithm

---

**Step 0:** Choose any element  $r$  and set  $S = \{r\}$  and  $A = \emptyset$ . (Take  $r$  as the root of our spanning tree.)

**Step 1:** Find a lightest edge such that one endpoint is in  $S$  and the other is in  $V \setminus S$ . Add this edge to  $A$  and its (other) endpoint to  $S$ .

**Step 2:** If  $V \setminus S = \emptyset$ , then stop and output the minimum spanning tree  $(S, A)$ ; Otherwise go to Step 1.

# Recall Idea of Prim's Algorithm

---

**Step 0:** Choose any element  $r$  and set  $S = \{r\}$  and  $A = \emptyset$ . (Take  $r$  as the root of our spanning tree.)

**Step 1:** Find a lightest edge such that one endpoint is in  $S$  and the other is in  $V \setminus S$ . Add this edge to  $A$  and its (other) endpoint to  $S$ .

**Step 2:** If  $V \setminus S = \emptyset$ , then stop and output the minimum spanning tree  $(S, A)$ ; Otherwise go to Step 1.

## Questions:

- How does the algorithm update  $S$  efficiently?
- How does the algorithm find the lightest edge and update  $A$  efficiently?

# Prim's Algorithm

---

## Question

How does the algorithm update  $S$  efficiently?

# Prim's Algorithm

---

## Question

How does the algorithm update  $S$  efficiently?

**Answer:** Color the vertices.

- Initially all are white.

# Prim's Algorithm

---

## Question

How does the algorithm update  $S$  efficiently?

**Answer:** Color the vertices.

- Initially all are white.
- Change the color to black when the vertex is moved to  $S$ .

# Prim's Algorithm

---

## Question

How does the algorithm update  $S$  efficiently?

**Answer:** Color the vertices.

- Initially all are white.
- Change the color to black when the vertex is moved to  $S$ .
- Use `color[v]` to store color.

# Prim's Algorithm

## Question

How does the algorithm update  $S$  efficiently?

**Answer:** Color the vertices.

- Initially all are white.
- Change the color to black when the vertex is moved to  $S$ .
- Use `color[v]` to store color.

## Question

How does the algorithm find the **lightest** edge and update  $A$  efficiently?



# Prim's Algorithm

## Question

How does the algorithm update  $S$  efficiently?

**Answer:** Color the vertices.

- Initially all are white.
- Change the color to black when the vertex is moved to  $S$ .
- Use `color[v]` to store color.

## Question

How does the algorithm find the **lightest** edge and update  $A$  efficiently?

**Answer:**

- 1 Use a **priority queue** to find the lightest edge.

# Prim's Algorithm

## Question

How does the algorithm update  $S$  efficiently?

**Answer:** Color the vertices.

- Initially all are white.
- Change the color to black when the vertex is moved to  $S$ .
- Use `color[v]` to store color.

## Question

How does the algorithm find the **lightest** edge and update  $A$  efficiently?

**Answer:**

- 1 Use a **priority queue** to find the lightest edge.
- 2 Use `pred[v]` to update  $A$ .

# Reviewing Priority Queues

---

Priority Queue is a data structure

# Reviewing Priority Queues

Priority Queue is a data structure



# Reviewing Priority Queues

Priority Queue is a data structure



- can be implemented as a **heap**

# Reviewing Priority Queues

Priority Queue is a data structure



- can be implemented as a **heap**

Supports the following operations:

# Reviewing Priority Queues

Priority Queue is a data structure



- can be implemented as a **heap**

Supports the following operations:

**Insert**(**u**, **key**): Insert **u** with the key value **key** in Q.

# Reviewing Priority Queues

Priority Queue is a data structure



- can be implemented as a **heap**

Supports the following operations:

**Insert(*u*, *key*)**: Insert *u* with the key value *key* in *Q*.

***u* = Extract-Min()**: Extract the item with minimum key value.



# Reviewing Priority Queues

Priority Queue is a data structure



- can be implemented as a **heap**

Supports the following operations:

**Insert(*u*, *key*)**: Insert *u* with the key value *key* in *Q*.

***u* = Extract-Min()**: Extract the item with minimum key value.

**Decrease-Key(*u*, *new-key*)**: Decrease *u*'s key value to *new-key*.

# Reviewing Priority Queues

Priority Queue is a data structure



- can be implemented as a **heap**

Supports the following operations:

**Insert**(**u**, **key**): Insert **u** with the key value **key** in Q.

**u = Extract-Min**(): Extract the item with minimum key value.


**Decrease-Key**(**u**, **new-key**): Decrease **u**'s key value to **new-key**.

**Remark**: Priority Queues can be implemented so that each operation takes time  $O(\log |Q|)$ . See Lecture 5 & Chapter 6.5 CLRS.

# Reviewing Extract-Min


---

- Copy the last element to the root (i.e., overwrite the minimum element stored there)
- Restore the min-heap property by percolate down (or bubble down): if the element is larger than either of its children, then interchange it with the smaller of its children.



# Reviewing Extract-Min


- Copy the last element to the root (i.e., overwrite the minimum element stored there)
- Restore the min-heap property by percolate down (or bubble down): if the element is larger than either of its children, then interchange it with the smaller of its children.



Copy the last element to the root


# Reviewing Extract-Min

- Copy the last element to the root (i.e., overwrite the minimum element stored there)
- Restore the min-heap property by percolate down (or bubble down): if the element is larger than either of its children, then interchange it with the smaller of its children.




# Reviewing Extract-Min

- Copy the last element to the root (i.e., overwrite the minimum element stored there)
- Restore the min-heap property by percolate down (or bubble down): if the element is larger than either of its children, then interchange it with the smaller of its children.



# Reviewing Extract-Min


- Copy the last element to the root (i.e., overwrite the minimum element stored there)
- Restore the min-heap property by percolate down (or bubble down): if the element is larger than either of its children, then interchange it with the smaller of its children.



- Correctness: after each swap, the min-heap property is satisfied for all nodes except the node containing the element (with respect to its children)

# Reviewing Extract-Min

- Copy the last element to the root (i.e., overwrite the minimum element stored there)
- Restore the min-heap property by percolate down (or bubble down): if the element is larger than either of its children, then interchange it with the smaller of its children.



- Correctness: after each swap, the min-heap property is satisfied for all nodes except the node containing the element (with respect to its children)
- Time complexity =  $O(\text{height}) = O(\log n)$



## Using a Priority Queue to Find the Lightest Edge

---

Each item of the queue is a pair  $(u, \text{key}[u])$ ,

## Using a Priority Queue to Find the Lightest Edge

---


Each item of the queue is a pair  $(u, \text{key}[u])$ , where

- $u$  is a vertex in  $V \setminus S$ ,

# Using a Priority Queue to Find the Lightest Edge

Each item of the queue is a pair  $(u, \text{key}[u])$ , where

- $u$  is a vertex in  $V \setminus S$ ,
- $\text{key}[u]$  is the weight of the **lightest** edge from  $u$  to any vertex in  $S$ . (The endpoint of this edge in  $S$  is stored in  $\text{pred}[u]$ , which is used to build the MST tree.)




$\text{key}[f] = 8, \text{pred}[f] = e$

$\text{key}[i] = \text{infinity}, \text{pred}[i] = \text{nil}$

$\text{key}[g] = 16, \text{pred}[g] = c$

$\text{key}[h] = 24, \text{pred}[h] = b$

→  $f$  has the minimum key



new edge

$\text{key}[i] = 23, \text{pred}[i] = f$

After adding the new edge and vertex  $f$ , update the  $\text{key}[v]$  and  $\text{pred}[v]$  for each vertex  $v$  adjacent to  $f$

# Description of Prim's Algorithm

---

Prim( $G, w, r$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , the algorithm will start at root vertex  $r$

**Output:** None

Let  $color[1...|V|]$ ,  $key[1...|V|]$ ,  $pred[1...|V|]$  be new arrays;

**for**  $u \in V$  **do**

$color[u] \leftarrow$

# Description of Prim's Algorithm

---

Prim( $G, w, r$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , the algorithm will start at root vertex  $r$

**Output:** None

Let  $color[1...|V|], key[1...|V|], pred[1...|V|]$  be new arrays;

**for**  $u \in V$  **do**

  |  $color[u] \leftarrow \text{WHITE}, key[u] \leftarrow$

# Description of Prim's Algorithm

---

Prim( $G, w, r$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , the algorithm will start at root vertex  $r$

**Output:** None

Let  $color[1...|V|], key[1...|V|], pred[1...|V|]$  be new arrays;

**for**  $u \in V$  **do**

  |  $color[u] \leftarrow \text{WHITE}, key[u] \leftarrow +\infty;$  // Initialize

# Description of Prim's Algorithm

$\text{Prim}(G, w, r)$

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , the algorithm will start at root vertex  $r$

**Output:** None

Let  $color[1...|V|]$ ,  $key[1...|V|]$ ,  $pred[1...|V|]$  be new arrays;

**for**  $u \in V$  **do**

  |  $color[u] \leftarrow \text{WHITE}, key[u] \leftarrow +\infty$ ; // Initialize

**end**

$key[r] \leftarrow 0, pred[r] \leftarrow \text{NULL}$ ; // Start at root vertex

# Description of Prim's Algorithm

$\text{Prim}(G, w, r)$

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , the algorithm will start at root vertex  $r$

**Output:** None

Let  $color[1...|V|]$ ,  $key[1...|V|]$ ,  $pred[1...|V|]$  be new arrays;

**for**  $u \in V$  **do**

  |  $color[u] \leftarrow \text{WHITE}, key[u] \leftarrow +\infty$ ; // Initialize

**end**

$key[r] \leftarrow 0, pred[r] \leftarrow \text{NULL}$ ; // Start at root vertex

$Q \leftarrow \text{new PriQueue}(V)$ ; // put vertices in  $Q$



# Description of Prim's Algorithm

Prim( $G, w, r$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , the algorithm will start at root vertex  $r$

**Output:** None

Let  $color[1...|V|]$ ,  $key[1...|V|]$ ,  $pred[1...|V|]$  be new arrays;

**for**  $u \in V$  **do**

$color[u] \leftarrow \text{WHITE}, key[u] \leftarrow +\infty$ ; // Initialize

**end**

$key[r] \leftarrow 0, pred[r] \leftarrow \text{NULL}$ ; // Start at root vertex

$Q \leftarrow \text{new PriQueue}(V)$ ; // put vertices in  $Q$

**while**  $Q$  is nonempty **do**

$u \leftarrow Q.\text{Extract-Min}()$ ; // lightest edge

# Description of Prim's Algorithm

Prim( $G, w, r$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , the algorithm will start at root vertex  $r$

**Output:** None

Let  $color[1...|V|]$ ,  $key[1...|V|]$ ,  $pred[1...|V|]$  be new arrays;

**for**  $u \in V$  **do**

$color[u] \leftarrow \text{WHITE}, key[u] \leftarrow +\infty$ ; // Initialize

**end**

$key[r] \leftarrow 0, pred[r] \leftarrow \text{NULL}$ ; // Start at root vertex

$Q \leftarrow \text{new PriQueue}(V)$ ; // put vertices in  $Q$

**while**  $Q$  is nonempty **do**

$u \leftarrow Q.\text{Extract-Min}()$ ; // lightest edge

**for**  $v \in adj[u]$  **do**

        |

        |

# Description of Prim's Algorithm

$\text{Prim}(G, w, r)$

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , the algorithm will start at root vertex  $r$

**Output:** None

Let  $color[1...|V|]$ ,  $key[1...|V|]$ ,  $pred[1...|V|]$  be new arrays;

**for**  $u \in V$  **do**

$color[u] \leftarrow \text{WHITE}, key[u] \leftarrow +\infty$ ; // Initialize

**end**

$key[r] \leftarrow 0, pred[r] \leftarrow \text{NULL}$ ; // Start at root vertex

$Q \leftarrow \text{new PriQueue}(V)$ ; // put vertices in  $Q$

**while**  $Q$  is nonempty **do**

$u \leftarrow Q.\text{Extract-Min}()$ ; // lightest edge

**for**  $v \in adj[u]$  **do**

**if**  $(color[v] \leftarrow \text{WHITE}) \&\& (w[u, v] < key[v])$  **then**

$key[v] \leftarrow w[u, v]$ ; // new lightest edge

# Description of Prim's Algorithm

$\text{Prim}(G, w, r)$

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , the algorithm will start at root vertex  $r$

**Output:** None

Let  $color[1...|V|]$ ,  $key[1...|V|]$ ,  $pred[1...|V|]$  be new arrays;

**for**  $u \in V$  **do**

$color[u] \leftarrow \text{WHITE}, key[u] \leftarrow +\infty$ ; // Initialize

**end**

$key[r] \leftarrow 0, pred[r] \leftarrow \text{NULL}$ ; // Start at root vertex

$Q \leftarrow \text{new PriQueue}(V)$ ; // put vertices in  $Q$

**while**  $Q$  is nonempty **do**

$u \leftarrow Q.\text{Extract-Min}()$ ; // lightest edge

**for**  $v \in \text{adj}[u]$  **do**

**if**  $(color[v] \leftarrow \text{WHITE}) \&\& (w[u, v] < key[v])$  **then**

$key[v] \leftarrow w[u, v]$ ; // new lightest edge

$Q.\text{Decrease-Key}(v, key[v])$ ;

# Description of Prim's Algorithm

$\text{Prim}(G, w, r)$

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , the algorithm will start at root vertex  $r$

**Output:** None

Let  $color[1...|V|]$ ,  $key[1...|V|]$ ,  $pred[1...|V|]$  be new arrays;

**for**  $u \in V$  **do**

$color[u] \leftarrow \text{WHITE}, key[u] \leftarrow +\infty$ ; // Initialize

**end**

$key[r] \leftarrow 0, pred[r] \leftarrow \text{NULL}$ ; // Start at root vertex

$Q \leftarrow \text{new PriQueue}(V)$ ; // put vertices in  $Q$

**while**  $Q$  is nonempty **do**

$u \leftarrow Q.\text{Extract-Min}()$ ; // lightest edge

**for**  $v \in adj[u]$  **do**

**if**  $(color[v] \leftarrow \text{WHITE}) \&\& (w[u, v] < key[v])$  **then**

$key[v] \leftarrow w[u, v]$ ; // new lightest edge

$Q.\text{Decrease-Key}(v, key[v])$ ;

$pred[v] \leftarrow u$ ;

# Description of Prim's Algorithm

Prim( $G, w, r$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , the algorithm will start at root vertex  $r$

**Output:** None

Let  $color[1...|V|]$ ,  $key[1...|V|]$ ,  $pred[1...|V|]$  be new arrays;

**for**  $u \in V$  **do**

$color[u] \leftarrow \text{WHITE}, key[u] \leftarrow +\infty$ ; // Initialize

**end**

$key[r] \leftarrow 0, pred[r] \leftarrow \text{NULL}$ ; // Start at root vertex

$Q \leftarrow \text{new PriQueue}(V)$ ; // put vertices in  $Q$

**while**  $Q$  is nonempty **do**

$u \leftarrow Q.\text{Extract-Min}()$ ; // lightest edge

**for**  $v \in adj[u]$  **do**

**if**  $(color[v] \leftarrow \text{WHITE}) \&\& (w[u, v] < key[v])$  **then**

$key[v] \leftarrow w[u, v]$ ; // new lightest edge

$Q.\text{Decrease-Key}(v, key[v])$ ;

$pred[v] \leftarrow u$ ;

**end**

**end**

$color[u] \leftarrow \text{BLACK}$ ;

**end**

# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| W | W | W | W | W | W | W |
|---|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | N | N | N | N | N | N |
|---|---|---|---|---|---|---|

key

|          |          |          |          |          |          |          |
|----------|----------|----------|----------|----------|----------|----------|
| $\infty$ | $\infty$ | $\infty$ | $\infty$ | $\infty$ | $\infty$ | $\infty$ |
|----------|----------|----------|----------|----------|----------|----------|

Q

|             |             |             |             |             |             |             |
|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| 1, $\infty$ | 2, $\infty$ | 3, $\infty$ | 4, $\infty$ | 5, $\infty$ | 6, $\infty$ | 7, $\infty$ |
|-------------|-------------|-------------|-------------|-------------|-------------|-------------|



# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| W | W | W | W | W | W | W |
|---|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | N | N | N | N | N | N |
|---|---|---|---|---|---|---|

key

|          |          |          |          |          |          |          |
|----------|----------|----------|----------|----------|----------|----------|
| $\infty$ | $\infty$ | $\infty$ | $\infty$ | $\infty$ | $\infty$ | $\infty$ |
|----------|----------|----------|----------|----------|----------|----------|

Q

|             |             |             |             |             |             |             |
|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| 1, $\infty$ | 2, $\infty$ | 3, $\infty$ | 4, $\infty$ | 5, $\infty$ | 6, $\infty$ | 7, $\infty$ |
|-------------|-------------|-------------|-------------|-------------|-------------|-------------|





# Prim's Example

color

|          |   |   |   |   |   |   |
|----------|---|---|---|---|---|---|
| <b>B</b> | W | W | W | W | W | W |
|----------|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | N | N | N | N | N | N |
|---|---|---|---|---|---|---|

key

|          |          |          |          |          |          |          |
|----------|----------|----------|----------|----------|----------|----------|
| <b>0</b> | $\infty$ | $\infty$ | $\infty$ | $\infty$ | $\infty$ | $\infty$ |
|----------|----------|----------|----------|----------|----------|----------|

Q

|            |             |             |             |             |             |             |
|------------|-------------|-------------|-------------|-------------|-------------|-------------|
| <b>1,0</b> | 2, $\infty$ | 3, $\infty$ | 4, $\infty$ | 5, $\infty$ | 6, $\infty$ | 7, $\infty$ |
|------------|-------------|-------------|-------------|-------------|-------------|-------------|



# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| B | W | W | W | W | W | W |
|---|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | N | N | N | N | N | N |
|---|---|---|---|---|---|---|

key

|   |          |          |          |          |          |          |
|---|----------|----------|----------|----------|----------|----------|
| 0 | $\infty$ | $\infty$ | $\infty$ | $\infty$ | $\infty$ | $\infty$ |
|---|----------|----------|----------|----------|----------|----------|

Q

|             |             |             |             |             |             |
|-------------|-------------|-------------|-------------|-------------|-------------|
| 7, $\infty$ | 2, $\infty$ | 3, $\infty$ | 4, $\infty$ | 5, $\infty$ | 6, $\infty$ |
|-------------|-------------|-------------|-------------|-------------|-------------|



# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| B | W | W | W | W | W | W |
|---|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | N | N | N | N |
|---|---|---|---|---|---|---|

key

|   |   |   |          |          |          |          |
|---|---|---|----------|----------|----------|----------|
| 0 | 4 | 8 | $\infty$ | $\infty$ | $\infty$ | $\infty$ |
|---|---|---|----------|----------|----------|----------|

Q

|             |      |      |             |             |             |
|-------------|------|------|-------------|-------------|-------------|
| 7, $\infty$ | 2, 4 | 3, 8 | 4, $\infty$ | 5, $\infty$ | 6, $\infty$ |
|-------------|------|------|-------------|-------------|-------------|



# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| B | W | W | W | W | W | W |
|---|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | N | N | N | N |
|---|---|---|---|---|---|---|

key

|   |   |   |          |          |          |          |
|---|---|---|----------|----------|----------|----------|
| 0 | 4 | 8 | $\infty$ | $\infty$ | $\infty$ | $\infty$ |
|---|---|---|----------|----------|----------|----------|

Q

|     |             |     |             |             |             |
|-----|-------------|-----|-------------|-------------|-------------|
| 2,4 | 7, $\infty$ | 3,8 | 4, $\infty$ | 5, $\infty$ | 6, $\infty$ |
|-----|-------------|-----|-------------|-------------|-------------|



# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| B | B | W | W | W | W | W |
|---|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | N | N | N | N |
|---|---|---|---|---|---|---|

key

|   |   |   |          |          |          |          |
|---|---|---|----------|----------|----------|----------|
| 0 | 4 | 8 | $\infty$ | $\infty$ | $\infty$ | $\infty$ |
|---|---|---|----------|----------|----------|----------|

Q

|     |             |             |             |             |
|-----|-------------|-------------|-------------|-------------|
| 3,8 | 7, $\infty$ | 6, $\infty$ | 4, $\infty$ | 5, $\infty$ |
|-----|-------------|-------------|-------------|-------------|



# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| B | B | W | W | W | W | W |
|---|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | N | N | N | N |
|---|---|---|---|---|---|---|

key

|   |   |   |          |          |          |          |
|---|---|---|----------|----------|----------|----------|
| 0 | 4 | 8 | $\infty$ | $\infty$ | $\infty$ | $\infty$ |
|---|---|---|----------|----------|----------|----------|

Q

|     |             |             |             |             |
|-----|-------------|-------------|-------------|-------------|
| 3,8 | 7, $\infty$ | 6, $\infty$ | 4, $\infty$ | 5, $\infty$ |
|-----|-------------|-------------|-------------|-------------|



# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| B | B | W | W | W | W | W |
|---|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | 2 | 2 | N | N |
|---|---|---|---|---|---|---|

key

|   |   |   |   |    |          |          |
|---|---|---|---|----|----------|----------|
| 0 | 4 | 8 | 8 | 10 | $\infty$ | $\infty$ |
|---|---|---|---|----|----------|----------|

Q

|     |             |             |     |      |
|-----|-------------|-------------|-----|------|
| 3,8 | 7, $\infty$ | 6, $\infty$ | 4,8 | 5,10 |
|-----|-------------|-------------|-----|------|



# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| B | B | W | W | W | W | W |
|---|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | 2 | 2 | N | N |
|---|---|---|---|---|---|---|

key

|   |   |   |   |    |          |          |
|---|---|---|---|----|----------|----------|
| 0 | 4 | 8 | 8 | 10 | $\infty$ | $\infty$ |
|---|---|---|---|----|----------|----------|

Q

|     |     |             |             |      |
|-----|-----|-------------|-------------|------|
| 3,8 | 4,8 | 6, $\infty$ | 7, $\infty$ | 5,10 |
|-----|-----|-------------|-------------|------|





# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| B | B | B | W | W | W | W |
|---|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | 2 | 2 | N | N |
|---|---|---|---|---|---|---|

key

|   |   |   |   |    |          |          |
|---|---|---|---|----|----------|----------|
| 0 | 4 | 8 | 8 | 10 | $\infty$ | $\infty$ |
|---|---|---|---|----|----------|----------|

Q

|     |      |             |             |
|-----|------|-------------|-------------|
| 4,8 | 5,10 | 6, $\infty$ | 7, $\infty$ |
|-----|------|-------------|-------------|



# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| B | B | B | W | W | W | W |
|---|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | 2 | 2 | N | N |
|---|---|---|---|---|---|---|

key

|   |   |   |   |    |          |          |
|---|---|---|---|----|----------|----------|
| 0 | 4 | 8 | 8 | 10 | $\infty$ | $\infty$ |
|---|---|---|---|----|----------|----------|

Q

|     |      |             |             |
|-----|------|-------------|-------------|
| 4,8 | 5,10 | 6, $\infty$ | 7, $\infty$ |
|-----|------|-------------|-------------|



# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| B | B | B | W | W | W | W |
|---|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | 3 | 2 | 3 | N |
|---|---|---|---|---|---|---|

key

|   |   |   |   |    |   |          |
|---|---|---|---|----|---|----------|
| 0 | 4 | 8 | 2 | 10 | 1 | $\infty$ |
|---|---|---|---|----|---|----------|

Q

|      |       |      |             |
|------|-------|------|-------------|
| 4, 2 | 5, 10 | 6, 1 | 7, $\infty$ |
|------|-------|------|-------------|



# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| B | B | B | W | W | W | W |
|---|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | 3 | 2 | 3 | N |
|---|---|---|---|---|---|---|

key

|   |   |   |   |    |   |          |
|---|---|---|---|----|---|----------|
| 0 | 4 | 8 | 2 | 10 | 1 | $\infty$ |
|---|---|---|---|----|---|----------|

Q

|     |      |     |             |
|-----|------|-----|-------------|
| 6,1 | 5,10 | 4,2 | 7, $\infty$ |
|-----|------|-----|-------------|



# Prim's Example

color

|   |   |   |   |   |          |   |
|---|---|---|---|---|----------|---|
| B | B | B | W | W | <b>B</b> | W |
|---|---|---|---|---|----------|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | 3 | 2 | 3 | N |
|---|---|---|---|---|---|---|

key

|   |   |   |   |    |   |          |
|---|---|---|---|----|---|----------|
| 0 | 4 | 8 | 2 | 10 | 1 | $\infty$ |
|---|---|---|---|----|---|----------|

Q

|     |      |             |
|-----|------|-------------|
| 4,2 | 5,10 | 7, $\infty$ |
|-----|------|-------------|



# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| B | B | B | W | W | B | W |
|---|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | 3 | 2 | 3 | N |
|---|---|---|---|---|---|---|

key

|   |   |   |   |    |   |          |
|---|---|---|---|----|---|----------|
| 0 | 4 | 8 | 2 | 10 | 1 | $\infty$ |
|---|---|---|---|----|---|----------|

Q

|     |      |             |
|-----|------|-------------|
| 4,2 | 5,10 | 7, $\infty$ |
|-----|------|-------------|



# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| B | B | B | W | W | B | W |
|---|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | 3 | 6 | 3 | 6 |
|---|---|---|---|---|---|---|

key

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| 0 | 4 | 8 | 2 | 5 | 1 | 2 |
|---|---|---|---|---|---|---|

Q

|     |     |     |
|-----|-----|-----|
| 4,2 | 5,5 | 7,2 |
|-----|-----|-----|



# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| B | B | B | W | W | B | W |
|---|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | 3 | 6 | 3 | 6 |
|---|---|---|---|---|---|---|

key

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| 0 | 4 | 8 | 2 | 5 | 1 | 2 |
|---|---|---|---|---|---|---|

Q

|     |     |     |
|-----|-----|-----|
| 4,2 | 5,5 | 7,2 |
|-----|-----|-----|





# Prim's Example

color

|   |   |   |          |   |   |   |
|---|---|---|----------|---|---|---|
| B | B | B | <b>B</b> | W | B | W |
|---|---|---|----------|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | 3 | 6 | 3 | 6 |
|---|---|---|---|---|---|---|

key

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| 0 | 4 | 8 | 2 | 5 | 1 | 2 |
|---|---|---|---|---|---|---|

Q

|     |     |
|-----|-----|
| 7,2 | 5,5 |
|-----|-----|



# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| B | B | B | B | W | B | W |
|---|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | 3 | 6 | 3 | 6 |
|---|---|---|---|---|---|---|

key

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| 0 | 4 | 8 | 2 | 5 | 1 | 2 |
|---|---|---|---|---|---|---|

Q

|     |     |
|-----|-----|
| 7,2 | 5,5 |
|-----|-----|



# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| B | B | B | B | W | B | W |
|---|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | 3 | 6 | 3 | 6 |
|---|---|---|---|---|---|---|

key

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| 0 | 4 | 8 | 2 | 5 | 1 | 2 |
|---|---|---|---|---|---|---|

Q

|     |     |
|-----|-----|
| 7,2 | 5,5 |
|-----|-----|



# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| B | B | B | B | W | B | B |
|---|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | 3 | 6 | 3 | 6 |
|---|---|---|---|---|---|---|

key

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| 0 | 4 | 8 | 2 | 5 | 1 | 2 |
|---|---|---|---|---|---|---|

Q

|     |
|-----|
| 5,5 |
|-----|



# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| B | B | B | B | W | B | B |
|---|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | 3 | 6 | 3 | 6 |
|---|---|---|---|---|---|---|

key

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| 0 | 4 | 8 | 2 | 5 | 1 | 2 |
|---|---|---|---|---|---|---|

Q

|     |
|-----|
| 5,5 |
|-----|



# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| B | B | B | B | W | B | B |
|---|---|---|---|---|---|---|

pred


|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | 3 | 6 | 3 | 6 |
|---|---|---|---|---|---|---|

key

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| 0 | 4 | 8 | 2 | 5 | 1 | 2 |
|---|---|---|---|---|---|---|

Q

|     |
|-----|
| 5,5 |
|-----|



# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| B | B | B | B | B | B | B |
|---|---|---|---|---|---|---|


pred

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | 3 | 6 | 3 | 6 |
|---|---|---|---|---|---|---|

key

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| 0 | 4 | 8 | 2 | 5 | 1 | 2 |
|---|---|---|---|---|---|---|

Q



# Prim's Example

color

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| B | B | B | B | B | B | B |
|---|---|---|---|---|---|---|


pred

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| N | 1 | 1 | 3 | 6 | 3 | 6 |
|---|---|---|---|---|---|---|

key

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| 0 | 4 | 8 | 2 | 5 | 1 | 2 |
|---|---|---|---|---|---|---|

Weight of MST = 22





# Outline

---

- Review to Part IV
- Minimum Spanning Trees
  - Spanning trees
  - Minimum spanning trees
- Prim's algorithm
  - The idea
  - The algorithm
  - Analysis for Prim's algorithm
- Kruskal's algorithm
  - The idea
  - The algorithm
  - The Disjoint Set Union-Find data structure
  - Analysis for Kruskal's algorithm

# Analysis of Prim's Algorithm...

---

Prim( $G, w, r$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , the algorithm will start at root vertex  $r$

**Output:** None

Let  $color[1...|V|]$ ,  $key[1...|V|]$ ,  $pred[1...|V|]$  be new arrays;

# Analysis of Prim's Algorithm...

---

Prim( $G, w, r$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , the algorithm will start at root vertex  $r$

**Output:** None

Let  $color[1...|V|], key[1...|V|], pred[1...|V|]$  be new arrays;

**for**  $u \in V$  **do**

$color[u] \leftarrow \text{WHITE}, key[u] \leftarrow +\infty; // O(V)$

# Analysis of Prim's Algorithm...

---

Prim( $G, w, r$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , the algorithm will start at root vertex  $r$

**Output:** None

Let  $color[1...|V|]$ ,  $key[1...|V|]$ ,  $pred[1...|V|]$  be new arrays;

**for**  $u \in V$  **do**

  |  $color[u] \leftarrow \text{WHITE}, key[u] \leftarrow +\infty; // O(V)$

**end**

$key[r] \leftarrow 0, pred[r] \leftarrow \text{NULL};$

# Analysis of Prim's Algorithm...

Prim( $G, w, r$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , the algorithm will start at root vertex  $r$

**Output:** None

Let  $color[1...|V|]$ ,  $key[1...|V|]$ ,  $pred[1...|V|]$  be new arrays;

**for**  $u \in V$  **do**

  |  $color[u] \leftarrow \text{WHITE}, key[u] \leftarrow +\infty; // O(V)$

**end**

$key[r] \leftarrow 0, pred[r] \leftarrow \text{NULL};$

$Q \leftarrow \text{new PriQueue}(V); // O(V)$

# Analysis of Prim's Algorithm...

Prim( $G, w, r$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , the algorithm will start at root vertex  $r$

**Output:** None

Let  $color[1...|V|]$ ,  $key[1...|V|]$ ,  $pred[1...|V|]$  be new arrays;

**for**  $u \in V$  **do**

$color[u] \leftarrow \text{WHITE}, key[u] \leftarrow +\infty; // O(V)$

**end**

$key[r] \leftarrow 0, pred[r] \leftarrow \text{NULL};$

$Q \leftarrow \text{new PriQueue}(V); // O(V)$

**while**  $Q$  is nonempty **do**

$u \leftarrow Q.\text{Extract-Min}(); // O(\log V)$

# Analysis of Prim's Algorithm...

Prim( $G, w, r$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , the algorithm will start at root vertex  $r$

**Output:** None

Let  $color[1...|V|]$ ,  $key[1...|V|]$ ,  $pred[1...|V|]$  be new arrays;

**for**  $u \in V$  **do**

$color[u] \leftarrow \text{WHITE}, key[u] \leftarrow +\infty; // O(V)$

**end**

$key[r] \leftarrow 0, pred[r] \leftarrow \text{NULL};$

$Q \leftarrow \text{new PriQueue}(V); // O(V)$

**while**  $Q$  is nonempty **do**

$u \leftarrow Q.\text{Extract-Min}(); // O(\log V)$

**for**  $v \in adj[u]$  **do**

**if**  $(color[v] \leftarrow \text{WHITE}) \&\& (w[u, v] < key[v])$  **then**

$key[v] \leftarrow w[u, v];$

# Analysis of Prim's Algorithm...

Prim( $G, w, r$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , the algorithm will start at root vertex  $r$

**Output:** None

Let  $color[1...|V|]$ ,  $key[1...|V|]$ ,  $pred[1...|V|]$  be new arrays;

**for**  $u \in V$  **do**

$color[u] \leftarrow \text{WHITE}, key[u] \leftarrow +\infty; // O(V)$

**end**

$key[r] \leftarrow 0, pred[r] \leftarrow \text{NULL};$

$Q \leftarrow \text{new PriQueue}(V); // O(V)$

**while**  $Q$  is nonempty **do**

$u \leftarrow Q.\text{Extract-Min}(); // O(\log V)$

**for**  $v \in adj[u]$  **do**

**if**  $(color[v] \leftarrow \text{WHITE}) \&\& (w[u, v] < key[v])$  **then**

$key[v] \leftarrow w[u, v];$

$Q.\text{Decrease-Key}(v, key[v]); // O(\log V)$



# Analysis of Prim's Algorithm...

Prim( $G, w, r$ )

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$ , the algorithm will start at root vertex  $r$

**Output:** None

Let  $color[1...|V|]$ ,  $key[1...|V|]$ ,  $pred[1...|V|]$  be new arrays;

**for**  $u \in V$  **do**

$color[u] \leftarrow \text{WHITE}, key[u] \leftarrow +\infty; // O(V)$

**end**

$key[r] \leftarrow 0, pred[r] \leftarrow \text{NULL};$

$Q \leftarrow \text{new PriQueue}(V); // O(V)$

**while**  $Q$  is nonempty **do**

$u \leftarrow Q.\text{Extract-Min}(); // O(\log V)$

**for**  $v \in adj[u]$  **do**

**if**  $(color[v] \leftarrow \text{WHITE}) \&\& (w[u, v] < key[v])$  **then**

$key[v] \leftarrow w[u, v];$

$Q.\text{Decrease-Key}(v, key[v]); // O(\log V)$

$pred[v] \leftarrow u;$

**end**

**end**

$color[u] \leftarrow \text{BLACK};$

**end**

# Analysis of Prim's Algorithm

---

The data structure **PriQueue** (heap) supports the following two operations: (See CLRS)

- $O(\log V)$  for **Extract-Min** on a PriQueue of size at most  $V$ .

# Analysis of Prim's Algorithm

---

The data structure **PriQueue** (heap) supports the following two operations: (See CLRS)

- $O(\log V)$  for **Extract-Min** on a PriQueue of size at most  $V$ .

Total cost:  $O(V \log V)$

# Analysis of Prim's Algorithm

---

The data structure **PriQueue** (heap) supports the following two operations: (See CLRS)

- $O(\log V)$  for **Extract-Min** on a PriQueue of size at most  $V$ .

Total cost:  $O(V \log V)$

- $O(\log V)$  time for **Decrease-Key** on a PriQueue of size at most  $E$ .

# Analysis of Prim's Algorithm

---

The data structure **PriQueue** (heap) supports the following two operations: (See CLRS)

- $O(\log V)$  for **Extract-Min** on a PriQueue of size at most  $V$ .  
Total cost:  $O(V \log V)$
- $O(\log V)$  time for **Decrease-Key** on a PriQueue of size at most  $E$ .  
Total cost:  $O(E \log V)$ .

# Analysis of Prim's Algorithm

---

The data structure **PriQueue** (heap) supports the following two operations: (See CLRS)

- $O(\log V)$  for **Extract-Min** on a PriQueue of size at most  $V$ .  
Total cost:  $O(V \log V)$
- $O(\log V)$  time for **Decrease-Key** on a PriQueue of size at most  $E$ .  
Total cost:  $O(E \log V)$ .

Total cost is then  $O((V + E) \log V) = O(E \log V)$

# Outline

---

- Review to Part IV
- Minimum Spanning Trees
  - Spanning trees
  - Minimum spanning trees
- Prim's algorithm
  - The idea
  - The algorithm
  - Analysis for Prim's algorithm
- **Kruskal's algorithm**
  - **The idea**
  - The algorithm
  - The Disjoint Set Union-Find data structure
  - Analysis for Kruskal's algorithm

# Recalling the Generic Algorithm

- Start with an **empty** graph.
- Try to **add** edges **one** at a time, always making sure that what is built remains **acyclic**.
- If we are sure at each step that the resulting graph is a **subset** of some minimum spanning tree, we are done.

## Lemma

- *Let  $G = (V, E)$  be a connected, undirected graph with a real-valued weight function  $w$  defined on  $E$*
- *Let  $A$  be a subset of  $E$  that is included in some minimum spanning tree for  $G$ .*

*Let*

- *$(S, V - S)$  be **any** cut of  $G$  that respects  $A$*
- *$(u, v)$  be a light edge crossing the cut  $(S, V - S)$*

*Then, edge  $(u, v)$  is **safe** for  $A$ .*



# Idea of Kruskal's Algorithm

---

- **Kruskal's Algorithm** is based directly on the generic algorithm.

# Idea of Kruskal's Algorithm

---

- **Kruskal's Algorithm** is based directly on the generic algorithm.
- Unlike Prim's algorithm, which grows one tree, Kruskal's algorithm grows a **collection** of trees (a **forest**).

# Idea of Kruskal's Algorithm

---

- **Kruskal's Algorithm** is based directly on the generic algorithm.
- Unlike Prim's algorithm, which grows one tree, Kruskal's algorithm grows a **collection** of trees (a **forest**).
- Initially, this forest consists of the **vertices** only (no edges).

# Idea of Kruskal's Algorithm

---

- **Kruskal's Algorithm** is based directly on the generic algorithm.
- Unlike Prim's algorithm, which grows one tree, Kruskal's algorithm grows a **collection** of trees (a **forest**).
- Initially, this forest consists of the **vertices** only (no edges).
- In each step the cheapest edge that does not create a **cycle** is added.


# Idea of Kruskal's Algorithm

---

- **Kruskal's Algorithm** is based directly on the generic algorithm.
- Unlike Prim's algorithm, which grows one tree, Kruskal's algorithm grows a **collection** of trees (a **forest**).
- Initially, this forest consists of the **vertices** only (no edges).
- In each step the cheapest edge that does not create a **cycle** is added.
- Continue until the forest 'merges into' a single tree.


# Kruskal's Example

---




# Kruskal's Example

---



# Kruskal's Example


---






# Kruskal's Example

---




# Kruskal's Example

---




# Kruskal's Example

---




# Kruskal's Example




# Kruskal's Example

---




# Kruskal's Example

---




# Kruskal's Example

---



# Kruskal's Example


---






# Kruskal's Example

---




# Kruskal's Example

---




# Kruskal's Example

---




# Kruskal's Example

---




# Kruskal's Example

---




# Kruskal's Example

---




# Kruskal's Example

---



# Kruskal's Example


---





# Kruskal's Example

---



# Outline

---

- Review to Part IV
- Minimum Spanning Trees
  - Spanning trees
  - Minimum spanning trees
- Prim's algorithm
  - The idea
  - The algorithm
  - Analysis for Prim's algorithm
- **Kruskal's algorithm**
  - The idea
  - **The algorithm**
  - The Disjoint Set Union-Find data structure
  - Analysis for Kruskal's algorithm

# The Framework of Kruskal's Algorithm

---

- Set  $A = \emptyset$  and  $F = E$ , the set of all edges.

# The Framework of Kruskal's Algorithm

---

- Set  $A = \emptyset$  and  $F = E$ , the set of all edges.
- Choose an edge  $e$  in  $F$  of **minimum** weight, and check whether adding  $e$  to  $A$  creates a **cycle**.

# The Framework of Kruskal's Algorithm

---

- Set  $A = \emptyset$  and  $F = E$ , the set of all edges.
- Choose an edge  $e$  in  $F$  of **minimum** weight, and check whether adding  $e$  to  $A$  creates a **cycle**.
  - If "yes", remove  $e$  from  $F$ .

# The Framework of Kruskal's Algorithm

---

- Set  $A = \emptyset$  and  $F = E$ , the set of all edges.
- Choose an edge  $e$  in  $F$  of **minimum** weight, and check whether adding  $e$  to  $A$  creates a **cycle**.
  - If "yes", remove  $e$  from  $F$ .
  - If "no", move  $e$  from  $F$  to  $A$ .

# The Framework of Kruskal's Algorithm

---

- Set  $A = \emptyset$  and  $F = E$ , the set of all edges.
- Choose an edge  $e$  in  $F$  of **minimum** weight, and check whether adding  $e$  to  $A$  creates a **cycle**.
  - If "yes", remove  $e$  from  $F$ .
  - If "no", move  $e$  from  $F$  to  $A$ .
- If  $F = \emptyset$ , stop and output the minimal spanning tree  $(V, A)$ .

# The Framework of Kruskal's Algorithm

---

- Set  $A = \emptyset$  and  $F = E$ , the set of all edges.
- Choose an edge  $e$  in  $F$  of **minimum** weight, and check whether adding  $e$  to  $A$  creates a **cycle**.
  - If "yes", remove  $e$  from  $F$ .
  - If "no", move  $e$  from  $F$  to  $A$ .
- If  $F = \emptyset$ , stop and output the minimal spanning tree  $(V, A)$ . Otherwise go to Step 2.



# The Framework of Kruskal's Algorithm

- Set  $A = \emptyset$  and  $F = E$ , the set of all edges.
- Choose an edge  $e$  in  $F$  of **minimum** weight, and check whether adding  $e$  to  $A$  creates a **cycle**.
  - If "yes", remove  $e$  from  $F$ .
  - If "no", move  $e$  from  $F$  to  $A$ .
- If  $F = \emptyset$ , stop and output the minimal spanning tree  $(V, A)$ . Otherwise go to Step 2.

## Questions

- How does algorithm **choose** edge  $e \in F$  with minimum weight?
- How does algorithm **check** whether adding  $e$  to  $A$  creates a cycle?

# How to Choose the Edge of Least Weight?

---

## Question

How does algorithm **choose** edge  $e \in F$  with minimum weight?

# How to Choose the Edge of Least Weight?

---

## Question

How does algorithm **choose** edge  $e \in F$  with minimum weight?

## Answer:

- Start by **sorting** edges in  $E$  in order of increasing weight.

# How to Choose the Edge of Least Weight?

---

## Question

How does algorithm **choose** edge  $e \in F$  with minimum weight?

## Answer:

- Start by **sorting** edges in  $E$  in order of increasing weight.
- Walk through the edges in this order.

# How to Choose the Edge of Least Weight?

---

## Question

How does algorithm **choose** edge  $e \in F$  with minimum weight?

## Answer:

- Start by **sorting** edges in  $E$  in order of increasing weight.
- Walk through the edges in this order.
- (Once edge  $e$  causes a cycle it will always cause a cycle, so it can be thrown away.)

# How to Check for Cycles?

---

**Observations:**

# How to Check for Cycles?

---

## Observations:

- At each step of the framework algorithm,  $(V, A)$  is acyclic so it is a forest.

# How to Check for Cycles?

---

## Observations:

- At each step of the framework algorithm,  $(V, A)$  is acyclic so it is a forest.
- If  $u$  and  $v$  are in the same tree, then adding edge  $\{u, v\}$  to  $A$  creates a cycle.



# How to Check for Cycles?

---

## Observations:

- At each step of the framework algorithm,  $(V,A)$  is acyclic so it is a forest.
- If  $u$  and  $v$  are in the same tree, then adding edge  $\{u,v\}$  to  $A$  creates a cycle.
- If  $u$  and  $v$  are not in the same tree, then adding edge  $\{u,v\}$  to  $A$  does not create a cycle.

# How to Check for Cycles?

---

## Observations:

- At each step of the framework algorithm,  $(V, A)$  is acyclic so it is a forest.
- If  $u$  and  $v$  are in the same tree, then adding edge  $\{u, v\}$  to  $A$  creates a cycle.
- If  $u$  and  $v$  are not in the same tree, then adding edge  $\{u, v\}$  to  $A$  does not create a cycle.

## Question

How to test whether  $u$  and  $v$  are in the same tree?

# How to Check for Cycles?

---

## Observations:

- At each step of the framework algorithm,  $(V, A)$  is acyclic so it is a forest.
- If  $u$  and  $v$  are in the same tree, then adding edge  $\{u, v\}$  to  $A$  creates a cycle.
- If  $u$  and  $v$  are not in the same tree, then adding edge  $\{u, v\}$  to  $A$  does not create a cycle.

## Question

How to test whether  $u$  and  $v$  are in the same tree?

**High-Level Answer:** Use a **disjoint-set data structure**

# How to Check for Cycles?

---

## Observations:

- At each step of the framework algorithm,  $(V, A)$  is acyclic so it is a forest.
- If  $u$  and  $v$  are in the same tree, then adding edge  $\{u, v\}$  to  $A$  creates a cycle.
- If  $u$  and  $v$  are not in the same tree, then adding edge  $\{u, v\}$  to  $A$  does not create a cycle.

## Question

How to test whether  $u$  and  $v$  are in the same tree?

**High-Level Answer:** Use a disjoint-set data structure

- Vertices in a tree are considered to be in same set.

# How to Check for Cycles?

## Observations:

- At each step of the framework algorithm,  $(V, A)$  is acyclic so it is a forest.
- If  $u$  and  $v$  are in the same tree, then adding edge  $\{u, v\}$  to  $A$  creates a cycle.
- If  $u$  and  $v$  are not in the same tree, then adding edge  $\{u, v\}$  to  $A$  does not create a cycle.

## Question

How to test whether  $u$  and  $v$  are in the same tree?

**High-Level Answer:** Use a disjoint-set data structure

- Vertices in a tree are considered to be in same set.
- Test if  $\text{Find-Set}(u) = \text{Find-Set}(v)$ ?

# How to Check for Cycles?

## Observations:

- At each step of the framework algorithm,  $(V, A)$  is acyclic so it is a forest.
- If  $u$  and  $v$  are in the same tree, then adding edge  $\{u, v\}$  to  $A$  creates a cycle.
- If  $u$  and  $v$  are not in the same tree, then adding edge  $\{u, v\}$  to  $A$  does not create a cycle.

## Question

How to test whether  $u$  and  $v$  are in the same tree?

**High-Level Answer:** Use a disjoint-set data structure

- Vertices in a tree are considered to be in same set.
- Test if  $\text{Find-Set}(u) = \text{Find-Set}(v)$ ?

**Low-Level Answer:**

- The Union-Find data structure implements this

# Outline

---

- Review to Part IV
- Minimum Spanning Trees
  - Spanning trees
  - Minimum spanning trees
- Prim's algorithm
  - The idea
  - The algorithm
  - Analysis for Prim's algorithm
- **Kruskal's algorithm**
  - The idea
  - The algorithm
  - **The Disjoint Set Union-Find data structure**
  - Analysis for Kruskal's algorithm

# The Union-Find Data Structure

---

**Union-Find** supports three operations on collections of **disjoint sets** over some universe  $U$ . Let  $n = |U|$ . For any  $u, v \in U$ :



# The Union-Find Data Structure

---

**Union-Find** supports three operations on collections of **disjoint sets** over some universe  $U$ . Let  $n = |U|$ . For any  $u, v \in U$ :

- **Create-Set( $u$ )**: Create a set containing the single element  $u$ .
  - **$O(1)$**  time

# The Union-Find Data Structure

---

**Union-Find** supports three operations on collections of **disjoint sets** over some universe  $U$ . Let  $n = |U|$ . For any  $u, v \in U$ :

- **Create-Set( $u$ )**: Create a set containing the single element  $u$ .
  - $O(1)$  time
- **Find-Set( $u$ )**: Find the set containing the element  $u$ . (Say each set has a unique ID)
  - $O(\log n)$  time

# The Union-Find Data Structure

---

**Union-Find** supports three operations on collections of **disjoint sets** over some universe  $U$ . Let  $n = |U|$ . For any  $u, v \in U$ :

- **Create-Set( $u$ )**: Create a set containing the single element  $u$ .
  - $O(1)$  time
- **Find-Set( $u$ )**: Find the set containing the element  $u$ . (Say each set has a unique ID)
  - $O(\log n)$  time
- **Union( $u, v$ )**: Merge the sets containing  $u$  and  $v$  respectively into a common set.
  - $O(\log n)$  time

# The Union-Find Data Structure

---


**Union-Find** supports three operations on collections of **disjoint sets** over some universe  $U$ . Let  $n = |U|$ . For any  $u, v \in U$ :

- **Create-Set( $u$ )**: Create a set containing the single element  $u$ .
  - $O(1)$  time
- **Find-Set( $u$ )**: Find the set containing the element  $u$ . (Say each set has a unique ID)
  - $O(\log n)$  time
- **Union( $u, v$ )**: Merge the sets containing  $u$  and  $v$  respectively into a common set.
  - $O(\log n)$  time

For now we treat Union-Find as a black box. We will present its implementation.

# Up-Tree Implementation


---



- Every item is in a **tree**. (Do **not** confuse these with the subtrees formed by Kruskal's algorithm.)

# Up-Tree Implementation


---



- Every item is in a **tree**. (Do **not** confuse these with the subtrees formed by Kruskal's algorithm.)
- The **root** of the tree is the **representative** item of all items in that tree

# Up-Tree Implementation


---



- Every item is in a **tree**. (Do **not** confuse these with the subtrees formed by Kruskal's algorithm.)
- The **root** of the tree is the **representative** item of all items in that tree
  - i.e., the root of the tree represents the whole items.

# Up-Tree Implementation

---




- Every item is in a **tree**. (Do **not** confuse these with the subtrees formed by Kruskal's algorithm.)
- The **root** of the tree is the **representative** item of all items in that tree
  - i.e., the root of the tree represents the whole items.
  - use the root's ID as the unique ID of the set.



# Up-Tree Implementation


---



- Every item is in a **tree**. (Do **not** confuse these with the subtrees formed by Kruskal's algorithm.)
- The **root** of the tree is the **representative** item of all items in that tree
  - i.e., the root of the tree represents the whole items.
  - use the root's ID as the unique ID of the set.
- In this up-tree implementation, every node (except the root) has a pointer pointing to its **parent**.

# Up-Tree Implementation

---



- Every item is in a **tree**. (Do **not** confuse these with the subtrees formed by Kruskal's algorithm.)
- The **root** of the tree is the **representative** item of all items in that tree
  - i.e., the root of the tree represents the whole items.
  - use the root's ID as the unique ID of the set.
- In this up-tree implementation, every node (except the root) has a pointer pointing to its **parent**.
  - The root element has a pointer pointing to itself.

# Create-Set(x) and Find-Set(x)

---

Create-Set(x): easy

```
x.parent ← x;
```

# Create-Set(x) and Find-Set(x)

---

Create-Set(x): easy

$x.\text{parent} \leftarrow x;$

Find-Set(x): also easy

- simply trace the parent point until we hit the root, then return the root element.

# Create-Set(x) and Find-Set(x)

---

Create-Set(x): easy

```
x.parent  $\leftarrow$  x;
```

Find-Set(x): also easy

- simply trace the parent point until we hit the root, then return the root element.

```
while x  $\neq$  x.parent do  
  | x  $\leftarrow$  x.parent;  
end
```

# Union(x, y)

---


Naive solution:

- put the parent pointer of the representation of x pointing to the representation of y.

# Union(x, y)

Naive solution:


- put the parent pointer of the representation of x pointing to the representation of y.



# Union(x, y)

Naive solution:

- put the parent pointer of the representation of x pointing to the representation of y.




## Question

Is it a good idea?




# Union(x, y)

---




# Union(x, y)

---



May become a **linked-list** at the end! Hence it is not efficient.

# Union(x, y)




May become a **linked-list** at the end! Hence it is not efficient.

## Question

Can we do better?

# Union(x, y)




May become a **linked-list** at the end! Hence it is not efficient.

## Question

Can we do better?

Simple trick (**Union by height**):

# Union(x, y)



May become a **linked-list** at the end! Hence it is not efficient.

## Question

Can we do better?

Simple trick (**Union by height**):

- when we union two trees together, we always make the root of the **taller** tree the parent of shorter tree.

# Up-Tree Implementation : Union by Height

---

- The root of every tree also holds the **height** of the tree.

# Up-Tree Implementation : Union by Height

---

- The root of every tree also holds the **height** of the tree.
- In case two trees have the same height, we choose the root of the first tree point to the root of the second.

# Up-Tree Implementation : Union by Height

---

- The root of every tree also holds the **height** of the tree.
- In case two trees have the same height, we choose the root of the first tree point to the root of the second. And the tree height is increased by 1.



# Up-Tree Implementation : Union by Height

---

- The root of every tree also holds the **height** of the tree.
- In case two trees have the same height, we choose the root of the first tree point to the root of the second. And the tree height is increased by 1.

$\text{Union}(x, y)$

**Input:** Two elements  $x, y \in U$

**Output:** None

# Up-Tree Implementation : Union by Height

---

- The root of every tree also holds the **height** of the tree.
- In case two trees have the same height, we choose the root of the first tree point to the root of the second. And the tree height is increased by 1.

$\text{Union}(x, y)$

**Input:** Two elements  $x, y \in U$

**Output:** None

$a \leftarrow \text{Find-Set}(x);$

$b \leftarrow \text{Find-Set}(y);$

# Up-Tree Implementation : Union by Height

- The root of every tree also holds the **height** of the tree.
- In case two trees have the same height, we choose the root of the first tree point to the root of the second. And the tree height is increased by 1.

Union( $x, y$ )

**Input:** Two elements  $x, y \in U$

**Output:** None

$a \leftarrow \text{Find-Set}(x);$

$b \leftarrow \text{Find-Set}(y);$

**if**  $a.\text{height} \leq b.\text{height}$  **then**

**if**  $a.\text{height}$  is equal to  $b.\text{height}$  **then**

# Up-Tree Implementation : Union by Height

- The root of every tree also holds the **height** of the tree.
- In case two trees have the same height, we choose the root of the first tree point to the root of the second. And the tree height is increased by 1.

Union( $x, y$ )

**Input:** Two elements  $x, y \in U$

**Output:** None

$a \leftarrow \text{Find-Set}(x);$

$b \leftarrow \text{Find-Set}(y);$

**if**  $a.\text{height} \leq b.\text{height}$  **then**

**if**  $a.\text{height}$  is equal to  $b.\text{height}$  **then**

$b.\text{height}++;$

**end**

# Up-Tree Implementation : Union by Height

- The root of every tree also holds the **height** of the tree.
- In case two trees have the same height, we choose the root of the first tree point to the root of the second. And the tree height is increased by 1.

Union( $x, y$ )

**Input:** Two elements  $x, y \in U$

**Output:** None

$a \leftarrow \text{Find-Set}(x);$

$b \leftarrow \text{Find-Set}(y);$

**if**  $a.\text{height} \leq b.\text{height}$  **then**

**if**  $a.\text{height}$  is equal to  $b.\text{height}$  **then**

$b.\text{height}++;$

**end**

$a.\text{parent} \leftarrow b;$

**end**

**else**

# Up-Tree Implementation : Union by Height

- The root of every tree also holds the **height** of the tree.
- In case two trees have the same height, we choose the root of the first tree point to the root of the second. And the tree height is increased by 1.

Union( $x, y$ )

**Input:** Two elements  $x, y \in U$

**Output:** None

$a \leftarrow \text{Find-Set}(x);$

$b \leftarrow \text{Find-Set}(y);$

**if**  $a.\text{height} \leq b.\text{height}$  **then**

**if**  $a.\text{height}$  is equal to  $b.\text{height}$  **then**

$b.\text{height}++;$

**end**

$a.\text{parent} \leftarrow b;$

**end**

**else**

$b.\text{parent} \leftarrow a;$

**end**

# Lemma

---

## Lemma

*For the root  $x$  of any tree, let  $\text{size}(x)$  denote the number of nodes and  $h(x)$  be the height of the tree. Then  $\text{size}(x) \geq 2^{h(x)}$ .*

# Lemma

## Lemma

For the root  $x$  of any tree, let  $\text{size}(x)$  denote the number of nodes and  $h(x)$  be the height of the tree. Then  $\text{size}(x) \geq 2^{h(x)}$ .

## Proof.

(By induction)

- 1 At beginning,  $h(x) = 0$ , and  $\text{size}(x) = 1$ . We have  $1 \geq 2^0 = 1$ .



# Lemma

## Lemma

*For the root  $x$  of any tree, let  $\text{size}(x)$  denote the number of nodes and  $h(x)$  be the height of the tree. Then  $\text{size}(x) \geq 2^{h(x)}$ .*

## Proof.

(By induction)

- ① At beginning,  $h(x) = 0$ , and  $\text{size}(x) = 1$ . We have  $1 \geq 2^0 = 1$ .
- ② Suppose the assumption is true for any  $x$  and  $y$  before  $\text{Union}(x, y)$ .

# Lemma

## Lemma

For the root  $x$  of any tree, let  $\text{size}(x)$  denote the number of nodes and  $h(x)$  be the height of the tree. Then  $\text{size}(x) \geq 2^{h(x)}$ .

## Proof.

(By induction)

- 1 At beginning,  $h(x) = 0$ , and  $\text{size}(x) = 1$ . We have  $1 \geq 2^0 = 1$ .
- 2 Suppose the assumption is true for any  $x$  and  $y$  before  $\text{Union}(x, y)$ . Let the size and height of the resulting tree be  $\text{size}(x')$ , and  $h(x')$ .

# Lemma

## Lemma

For the root  $x$  of any tree, let  $\text{size}(x)$  denote the number of nodes and  $h(x)$  be the height of the tree. Then  $\text{size}(x) \geq 2^{h(x)}$ .

## Proof.

(By induction)

- ① At beginning,  $h(x) = 0$ , and  $\text{size}(x) = 1$ . We have  $1 \geq 2^0 = 1$ .
- ② Suppose the assumption is true for any  $x$  and  $y$  before  $\text{Union}(x, y)$ . Let the size and height of the resulting tree be  $\text{size}(x')$ , and  $h(x')$ .
  - $h(x) < h(y)$ , we have

$$\text{size}(x') =$$

# Lemma

## Lemma

For the root  $x$  of any tree, let  $\text{size}(x)$  denote the number of nodes and  $h(x)$  be the height of the tree. Then  $\text{size}(x) \geq 2^{h(x)}$ .

## Proof.

(By induction)

- ① At beginning,  $h(x) = 0$ , and  $\text{size}(x) = 1$ . We have  $1 \geq 2^0 = 1$ .
- ② Suppose the assumption is true for any  $x$  and  $y$  before  $\text{Union}(x, y)$ . Let the size and height of the resulting tree be  $\text{size}(x')$ , and  $h(x')$ .
  - $h(x) < h(y)$ , we have

$$\text{size}(x') = \text{size}(x) + \text{size}(y) \geq$$

# Lemma

## Lemma

For the root  $x$  of any tree, let  $\text{size}(x)$  denote the number of nodes and  $h(x)$  be the height of the tree. Then  $\text{size}(x) \geq 2^{h(x)}$ .

## Proof.

(By induction)

- ① At beginning,  $h(x) = 0$ , and  $\text{size}(x) = 1$ . We have  $1 \geq 2^0 = 1$ .
- ② Suppose the assumption is true for any  $x$  and  $y$  before  $\text{Union}(x, y)$ . Let the size and height of the resulting tree be  $\text{size}(x')$ , and  $h(x')$ .
  - $h(x) < h(y)$ , we have

$$\text{size}(x') = \text{size}(x) + \text{size}(y) \geq 2^{h(x)} + 2^{h(y)} \geq$$

# Lemma

## Lemma

For the root  $x$  of any tree, let  $\text{size}(x)$  denote the number of nodes and  $h(x)$  be the height of the tree. Then  $\text{size}(x) \geq 2^{h(x)}$ .

## Proof.

(By induction)

- ① At beginning,  $h(x) = 0$ , and  $\text{size}(x) = 1$ . We have  $1 \geq 2^0 = 1$ .
- ② Suppose the assumption is true for any  $x$  and  $y$  before  $\text{Union}(x, y)$ . Let the size and height of the resulting tree be  $\text{size}(x')$ , and  $h(x')$ .
  - $h(x) < h(y)$ , we have

$$\text{size}(x') = \text{size}(x) + \text{size}(y) \geq 2^{h(x)} + 2^{h(y)} \geq 2^{h(y)} =$$

# Lemma

## Lemma

For the root  $x$  of any tree, let  $\text{size}(x)$  denote the number of nodes and  $h(x)$  be the height of the tree. Then  $\text{size}(x) \geq 2^{h(x)}$ .

## Proof.

(By induction)

- ① At beginning,  $h(x) = 0$ , and  $\text{size}(x) = 1$ . We have  $1 \geq 2^0 = 1$ .
- ② Suppose the assumption is true for any  $x$  and  $y$  before  $\text{Union}(x, y)$ . Let the size and height of the resulting tree be  $\text{size}(x')$ , and  $h(x')$ .
  - $h(x) < h(y)$ , we have

$$\text{size}(x') = \text{size}(x) + \text{size}(y) \geq 2^{h(x)} + 2^{h(y)} \geq 2^{h(y)} = 2^{h(x')}.$$

# Lemma

## Lemma

For the root  $x$  of any tree, let  $\text{size}(x)$  denote the number of nodes and  $h(x)$  be the height of the tree. Then  $\text{size}(x) \geq 2^{h(x)}$ .

## Proof.

(By induction)

- ① At beginning,  $h(x) = 0$ , and  $\text{size}(x) = 1$ . We have  $1 \geq 2^0 = 1$ .
- ② Suppose the assumption is true for any  $x$  and  $y$  before  $\text{Union}(x, y)$ . Let the size and height of the resulting tree be  $\text{size}(x')$ , and  $h(x')$ .

- $h(x) < h(y)$ , we have

$$\text{size}(x') = \text{size}(x) + \text{size}(y) \geq 2^{h(x)} + 2^{h(y)} \geq 2^{h(y)} = 2^{h(x')}.$$

- $h(x) = h(y)$ , we have

$$\text{size}(x') =$$



# Lemma

## Lemma

For the root  $x$  of any tree, let  $\text{size}(x)$  denote the number of nodes and  $h(x)$  be the height of the tree. Then  $\text{size}(x) \geq 2^{h(x)}$ .

## Proof.

(By induction)

- ① At beginning,  $h(x) = 0$ , and  $\text{size}(x) = 1$ . We have  $1 \geq 2^0 = 1$ .
- ② Suppose the assumption is true for any  $x$  and  $y$  before  $\text{Union}(x, y)$ . Let the size and height of the resulting tree be  $\text{size}(x')$ , and  $h(x')$ .

- $h(x) < h(y)$ , we have

$$\text{size}(x') = \text{size}(x) + \text{size}(y) \geq 2^{h(x)} + 2^{h(y)} \geq 2^{h(y)} = 2^{h(x')}.$$

- $h(x) = h(y)$ , we have

$$\text{size}(x') = \text{size}(x) + \text{size}(y) \geq$$

# Lemma

## Lemma

For the root  $x$  of any tree, let  $\text{size}(x)$  denote the number of nodes and  $h(x)$  be the height of the tree. Then  $\text{size}(x) \geq 2^{h(x)}$ .

## Proof.

(By induction)

- ① At beginning,  $h(x) = 0$ , and  $\text{size}(x) = 1$ . We have  $1 \geq 2^0 = 1$ .
- ② Suppose the assumption is true for any  $x$  and  $y$  before  $\text{Union}(x, y)$ . Let the size and height of the resulting tree be  $\text{size}(x')$ , and  $h(x')$ .

- $h(x) < h(y)$ , we have

$$\text{size}(x') = \text{size}(x) + \text{size}(y) \geq 2^{h(x)} + 2^{h(y)} \geq 2^{h(y)} = 2^{h(x')}.$$

- $h(x) = h(y)$ , we have

$$\text{size}(x') = \text{size}(x) + \text{size}(y) \geq 2^{h(x)} + 2^{h(y)} =$$

# Lemma

## Lemma

For the root  $x$  of any tree, let  $\text{size}(x)$  denote the number of nodes and  $h(x)$  be the height of the tree. Then  $\text{size}(x) \geq 2^{h(x)}$ .

## Proof.

(By induction)

- ① At beginning,  $h(x) = 0$ , and  $\text{size}(x) = 1$ . We have  $1 \geq 2^0 = 1$ .
- ② Suppose the assumption is true for any  $x$  and  $y$  before  $\text{Union}(x, y)$ . Let the size and height of the resulting tree be  $\text{size}(x')$ , and  $h(x')$ .

- $h(x) < h(y)$ , we have

$$\text{size}(x') = \text{size}(x) + \text{size}(y) \geq 2^{h(x)} + 2^{h(y)} \geq 2^{h(y)} = 2^{h(x')}.$$

- $h(x) = h(y)$ , we have

$$\text{size}(x') = \text{size}(x) + \text{size}(y) \geq 2^{h(x)} + 2^{h(y)} = 2^{h(y)+1} =$$

# Lemma

## Lemma

For the root  $x$  of any tree, let  $\text{size}(x)$  denote the number of nodes and  $h(x)$  be the height of the tree. Then  $\text{size}(x) \geq 2^{h(x)}$ .

## Proof.

(By induction)

- ① At beginning,  $h(x) = 0$ , and  $\text{size}(x) = 1$ . We have  $1 \geq 2^0 = 1$ .
- ② Suppose the assumption is true for any  $x$  and  $y$  before  $\text{Union}(x, y)$ . Let the size and height of the resulting tree be  $\text{size}(x')$ , and  $h(x')$ .

- $h(x) < h(y)$ , we have

$$\text{size}(x') = \text{size}(x) + \text{size}(y) \geq 2^{h(x)} + 2^{h(y)} \geq 2^{h(y)} = 2^{h(x')}.$$

- $h(x) = h(y)$ , we have

$$\text{size}(x') = \text{size}(x) + \text{size}(y) \geq 2^{h(x)} + 2^{h(y)} = 2^{h(y)+1} = 2^{h(x')}.$$

# Lemma

## Lemma

For the root  $x$  of any tree, let  $\text{size}(x)$  denote the number of nodes and  $h(x)$  be the height of the tree. Then  $\text{size}(x) \geq 2^{h(x)}$ .

## Proof.

(By induction)

- ① At beginning,  $h(x) = 0$ , and  $\text{size}(x) = 1$ . We have  $1 \geq 2^0 = 1$ .
- ② Suppose the assumption is true for any  $x$  and  $y$  before  $\text{Union}(x, y)$ . Let the size and height of the resulting tree be  $\text{size}(x')$ , and  $h(x')$ .

- $h(x) < h(y)$ , we have

$$\text{size}(x') = \text{size}(x) + \text{size}(y) \geq 2^{h(x)} + 2^{h(y)} \geq 2^{h(y)} = 2^{h(x')}.$$

- $h(x) = h(y)$ , we have

$$\text{size}(x') = \text{size}(x) + \text{size}(y) \geq 2^{h(x)} + 2^{h(y)} = 2^{h(y)+1} = 2^{h(x')}.$$

- $h(x) > h(y)$ , it is similar to the first case



# Lemma

---

## Lemma

*For  $n$  items, the running time of*

- *Create-Set is  $O(1)$ ,*

# Lemma

---

## Lemma

*For  $n$  items, the running time of*

- *Create-Set is  $O(1)$ ,*
- *Find-Set is  $O(\log n)$ , and*

# Lemma

---

## Lemma

*For  $n$  items, the running time of*

- *Create-Set is  $O(1)$ ,*
- *Find-Set is  $O(\log n)$ , and*
- *Union is  $O(\log n)$*

*respectively.*



# Lemma

## Lemma

*For  $n$  items, the running time of*

- *Create-Set is  $O(1)$ ,*
- *Find-Set is  $O(\log n)$ , and*
- *Union is  $O(\log n)$*

*respectively.*

## Proof.

- Obviously,  $\text{Create-Set}(x)$  is  $O(1)$ , and the running time of  $\text{Union}(x, y)$  depends on  $\text{Find-Set}(x)$ .

# Lemma

## Lemma

*For  $n$  items, the running time of*

- *Create-Set is  $O(1)$ ,*
- *Find-Set is  $O(\log n)$ , and*
- *Union is  $O(\log n)$*

*respectively.*

## Proof.

- Obviously, Create-Set( $x$ ) is  $O(1)$ , and the running time of Union( $x, y$ ) depends on Find-Set( $x$ ).
- Since the running time of Find-Set( $x$ ) depends on the height of the tree. From previous lemma, for any tree, we have

$$n \geq 2^h \Rightarrow h$$

# Lemma

## Lemma

*For  $n$  items, the running time of*

- *Create-Set is  $O(1)$ ,*
- *Find-Set is  $O(\log n)$ , and*
- *Union is  $O(\log n)$*

*respectively.*

## Proof.

- Obviously, Create-Set( $x$ ) is  $O(1)$ , and the running time of Union( $x, y$ ) depends on Find-Set( $x$ ).
- Since the running time of Find-Set( $x$ ) depends on the height of the tree. From previous lemma, for any tree, we have

$$\begin{aligned} n \geq 2^h &\Rightarrow h \leq \log n \\ &\Rightarrow h = O(\log n) \end{aligned}$$

# Lemma

## Lemma

*For  $n$  items, the running time of*

- *Create-Set is  $O(1)$ ,*
- *Find-Set is  $O(\log n)$ , and*
- *Union is  $O(\log n)$*

*respectively.*

## Proof.

- Obviously, Create-Set( $x$ ) is  $O(1)$ , and the running time of Union( $x, y$ ) depends on Find-Set( $x$ ).
- Since the running time of Find-Set( $x$ ) depends on the height of the tree. From previous lemma, for any tree, we have

$$\begin{aligned} n \geq 2^h &\Rightarrow h \leq \log n \\ &\Rightarrow h = O(\log n) \end{aligned}$$

Hence we have Find-Set( $x$ ) =  $O(\log n)$ .



# Outline

---

- Review to Part IV
- Minimum Spanning Trees
  - Spanning trees
  - Minimum spanning trees
- Prim's algorithm
  - The idea
  - The algorithm
  - Analysis for Prim's algorithm
- **Kruskal's algorithm**
  - The idea
  - The algorithm
  - The Disjoint Set Union-Find data structure
  - **Analysis for Kruskal's algorithm**

# Why Kruskal's Algorithm is Correct?

---

Let  $A$  be the edge set selected by Kruskal's Algorithm, and let  $(u, v)$  be the edge to be added next. It suffices to show that

# Why Kruskal's Algorithm is Correct?

---

Let  $A$  be the edge set selected by Kruskal's Algorithm, and let  $(u, v)$  be the edge to be added next. It suffices to show that

- there is a cut that **respects**  $A$ , and

# Why Kruskal's Algorithm is Correct?

---

Let  $A$  be the edge set selected by Kruskal's Algorithm, and let  $(u, v)$  be the edge to be added next. It suffices to show that

- there is a cut that **respects**  $A$ , and
- $(u, v)$  is the **light** edge crossing this cut




# Why Kruskal's Algorithm is Correct?

Let  $A$  be the edge set selected by Kruskal's Algorithm, and let  $(u, v)$  be the edge to be added next. It suffices to show that

- there is a cut that **respects**  $A$ , and
- $(u, v)$  is the **light** edge crossing this cut

- Let  $A' = (V', E')$  denote the **tree** of the **forest**  $A$  that contains  $u$ .




# Why Kruskal's Algorithm is Correct?

Let  $A$  be the edge set selected by Kruskal's Algorithm, and let  $(u, v)$  be the edge to be added next. It suffices to show that

- there is a cut that **respects**  $A$ , and
- $(u, v)$  is the **light** edge crossing this cut


- Let  $A' = (V', E')$  denote the **tree** of the **forest**  $A$  that contains  $u$ . Consider the cut  $(V', V - V')$ .



# Why Kruskal's Algorithm is Correct?

Let  $A$  be the edge set selected by Kruskal's Algorithm, and let  $(u, v)$  be the edge to be added next. It suffices to show that

- there is a cut that **respects**  $A$ , and
- $(u, v)$  is the **light** edge crossing this cut




- Let  $A' = (V', E')$  denote the **tree** of the **forest**  $A$  that contains  $u$ . Consider the cut  $(V', V - V')$ .
- There is no edge in  $A$  that crosses this cut, so the cut **respects**  $A$ .

# Why Kruskal's Algorithm is Correct?

Let  $A$  be the edge set selected by Kruskal's Algorithm, and let  $(u, v)$  be the edge to be added next. It suffices to show that

- there is a cut that **respects**  $A$ , and
- $(u, v)$  is the **light** edge crossing this cut




- Let  $A' = (V', E')$  denote the **tree** of the **forest**  $A$  that contains  $u$ . Consider the cut  $(V', V - V')$ .
- There is no edge in  $A$  that crosses this cut, so the cut **respects**  $A$ .
- Since adding  $(u, v)$  to  $A'$  does not induce a cycle,  $(u, v)$  **crosses** the cut.

# Why Kruskal's Algorithm is Correct?

Let  $A$  be the edge set selected by Kruskal's Algorithm, and let  $(u, v)$  be the edge to be added next. It suffices to show that

- there is a cut that **respects**  $A$ , and
- $(u, v)$  is the **light** edge crossing this cut



- Let  $A' = (V', E')$  denote the **tree** of the **forest**  $A$  that contains  $u$ . Consider the cut  $(V', V - V')$ .
- There is no edge in  $A$  that crosses this cut, so the cut **respects**  $A$ .
- Since adding  $(u, v)$  to  $A'$  does not induce a cycle,  $(u, v)$  **crosses** the cut.
- Moreover, since  $(u, v)$  is currently the smallest edge,  $(u, v)$  is the **light edge** crossing the cut.

# Time Complexity of Kruskal's Algorithm

---

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$

**Output:** MST of  $G$

# Time Complexity of Kruskal's Algorithm

---

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$

**Output:** MST of  $G$

Sort  $E$  in increasing order by weight  $w$ ;

# Time Complexity of Kruskal's Algorithm

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$

**Output:** MST of  $G$

Sort  $E$  in increasing order by weight  $w$ ; //  $O(|E| \log |E|)$

// After sorting  $E = \langle \{u_1, v_1\}, \{u_2, v_2\}, \dots, \{u_{|E|}, v_{|E|}\} \rangle$



# Time Complexity of Kruskal's Algorithm

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$

**Output:** MST of  $G$

Sort  $E$  in increasing order by weight  $w$ ; //  $O(|E| \log |E|)$

// After sorting  $E = \langle \{u_1, v_1\}, \{u_2, v_2\}, \dots, \{u_{|E|}, v_{|E|}\} \rangle$

$A \leftarrow \{\}$ ;

# Time Complexity of Kruskal's Algorithm

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$

**Output:** MST of  $G$

Sort  $E$  in increasing order by weight  $w$ ; //  $O(|E| \log |E|)$

// After sorting  $E = \langle \{u_1, v_1\}, \{u_2, v_2\}, \dots, \{u_{|E|}, v_{|E|}\} \rangle$

$A \leftarrow \{\}$ ;

**for**  $u \in V$  **do**

# Time Complexity of Kruskal's Algorithm

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$

**Output:** MST of  $G$

Sort  $E$  in increasing order by weight  $w$ ; //  $O(|E| \log |E|)$

// After sorting  $E = \langle \{u_1, v_1\}, \{u_2, v_2\}, \dots, \{u_{|E|}, v_{|E|}\} \rangle$

$A \leftarrow \{\}$ ;

**for**  $u \in V$  **do**

  | Create-Set( $u$ );

**end**

# Time Complexity of Kruskal's Algorithm

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$

**Output:** MST of  $G$

Sort  $E$  in increasing order by weight  $w$ ; //  $O(|E| \log |E|)$

// After sorting  $E = \langle \{u_1, v_1\}, \{u_2, v_2\}, \dots, \{u_{|E|}, v_{|E|}\} \rangle$

$A \leftarrow \{\}$ ;

**for**  $u \in V$  **do**

  | Create-Set( $u$ ); //  $O(|V|)$

**end**

# Time Complexity of Kruskal's Algorithm

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$

**Output:** MST of  $G$

Sort  $E$  in increasing order by weight  $w$ ; //  $O(|E| \log |E|)$

// After sorting  $E = \langle \{u_1, v_1\}, \{u_2, v_2\}, \dots, \{u_{|E|}, v_{|E|}\} \rangle$

$A \leftarrow \{\}$ ;

**for**  $u \in V$  **do**

  | Create-Set( $u$ ); //  $O(|V|)$

**end**

**for**  $e_i \in E$  **do**

# Time Complexity of Kruskal's Algorithm

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$

**Output:** MST of  $G$

Sort  $E$  in increasing order by weight  $w$ ; //  $O(|E| \log |E|)$

// After sorting  $E = \langle \{u_1, v_1\}, \{u_2, v_2\}, \dots, \{u_{|E|}, v_{|E|}\} \rangle$

$A \leftarrow \{\}$ ;

**for**  $u \in V$  **do**

  | Create-Set( $u$ ); //  $O(|V|)$

**end**

**for**  $e_i \in E$  **do**

  | //  $O(|E| \log |V|)$

  | **if**  $\text{Find-Set}(u_i) \neq \text{Find-Set}(v_i)$  **then**

# Time Complexity of Kruskal's Algorithm

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$

**Output:** MST of  $G$

Sort  $E$  in increasing order by weight  $w$ ; //  $O(|E| \log |E|)$

// After sorting  $E = \langle \{u_1, v_1\}, \{u_2, v_2\}, \dots, \{u_{|E|}, v_{|E|}\} \rangle$

$A \leftarrow \{\}$ ;

**for**  $u \in V$  **do**

  | Create-Set( $u$ ); //  $O(|V|)$

**end**

**for**  $e_i \in E$  **do**

  | //  $O(|E| \log |V|)$

  | **if**  $\text{Find-Set}(u_i) \neq \text{Find-Set}(v_i)$  **then**

    | add  $\{u_i, v_i\}$  to  $A$ ;

# Time Complexity of Kruskal's Algorithm

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$

**Output:** MST of  $G$

Sort  $E$  in increasing order by weight  $w$ ; //  $O(|E| \log |E|)$

// After sorting  $E = \langle \{u_1, v_1\}, \{u_2, v_2\}, \dots, \{u_{|E|}, v_{|E|}\} \rangle$

$A \leftarrow \{\}$ ;

**for**  $u \in V$  **do**

  | Create-Set( $u$ ); //  $O(|V|)$

**end**

**for**  $e_i \in E$  **do**

  //  $O(|E| \log |V|)$

**if**  $\text{Find-Set}(u_i) \neq \text{Find-Set}(v_i)$  **then**

    | add  $\{u_i, v_i\}$  to  $A$ ;

    | Union( $u_i, v_i$ );

**end**

**end**



# Time Complexity of Kruskal's Algorithm

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$

**Output:** MST of  $G$

Sort  $E$  in increasing order by weight  $w$ ; //  $O(|E| \log |E|)$

// After sorting  $E = \langle \{u_1, v_1\}, \{u_2, v_2\}, \dots, \{u_{|E|}, v_{|E|}\} \rangle$

$A \leftarrow \{\}$ ;

**for**  $u \in V$  **do**

    | Create-Set( $u$ ); //  $O(|V|)$

**end**

**for**  $e_i \in E$  **do**

    | //  $O(|E| \log |V|)$

    | **if**  $\text{Find-Set}(u_i) \neq \text{Find-Set}(v_i)$  **then**

        | add  $\{u_i, v_i\}$  to  $A$ ;

        | Union( $u_i, v_i$ );

    | **end**

**end**

**return**

# Time Complexity of Kruskal's Algorithm

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$

**Output:** MST of  $G$

Sort  $E$  in increasing order by weight  $w$ ; //  $O(|E| \log |E|)$

// After sorting  $E = \langle \{u_1, v_1\}, \{u_2, v_2\}, \dots, \{u_{|E|}, v_{|E|}\} \rangle$

$A \leftarrow \{\}$ ;

**for**  $u \in V$  **do**

    | Create-Set( $u$ ); //  $O(|V|)$

**end**

**for**  $e_i \in E$  **do**

    | //  $O(|E| \log |V|)$

    | **if**  $\text{Find-Set}(u_i) \neq \text{Find-Set}(v_i)$  **then**

        | add  $\{u_i, v_i\}$  to  $A$ ;

        | Union( $u_i, v_i$ );

    | **end**

**end**

**return**  $A$ ;

# Time Complexity of Kruskal's Algorithm

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$

**Output:** MST of  $G$

Sort  $E$  in increasing order by weight  $w$ ; //  $O(|E| \log |E|)$

// After sorting  $E = \langle \{u_1, v_1\}, \{u_2, v_2\}, \dots, \{u_{|E|}, v_{|E|}\} \rangle$

$A \leftarrow \{\}$ ;

**for**  $u \in V$  **do**

    | Create-Set( $u$ ); //  $O(|V|)$

**end**

**for**  $e_i \in E$  **do**

    | //  $O(|E| \log |V|)$

    | **if**  $\text{Find-Set}(u_i) \neq \text{Find-Set}(v_i)$  **then**

        | add  $\{u_i, v_i\}$  to  $A$ ;

        | Union( $u_i, v_i$ );

    | **end**

**end**

**return**  $A$ ;

**Remark:** With a proper implementation of Union-Find, Kruskal's algorithm has running time  $O(|E| \log |E|) = O(|E| \log |V|)$ .

# Time Complexity of Kruskal's Algorithm

**Input:** A graph  $G$ , a matrix  $w$  representing the weights between vertices in  $G$

**Output:** MST of  $G$

Sort  $E$  in increasing order by weight  $w$ ; //  $O(|E| \log |E|)$

// After sorting  $E = \langle \{u_1, v_1\}, \{u_2, v_2\}, \dots, \{u_{|E|}, v_{|E|}\} \rangle$

$A \leftarrow \{\}$ ;

**for**  $u \in V$  **do**

    | Create-Set( $u$ ); //  $O(|V|)$

**end**

**for**  $e_i \in E$  **do**

    | //  $O(|E| \log |V|)$

    | **if**  $\text{Find-Set}(u_i) \neq \text{Find-Set}(v_i)$  **then**

        | add  $\{u_i, v_i\}$  to  $A$ ;

        | Union( $u_i, v_i$ );

    | **end**

**end**

**return**  $A$ ;

$$\log |E| \leq \log |V|^2 = 2 \log |V| = O(\log |V|)$$

**Remark:** With a proper implementation of Union-Find, Kruskal's algorithm has running time  $O(|E| \log |E|) = O(|E| \log |V|)$ .

# Summary

---

- Prim's algorithm always grows one tree.
- Kruskal's algorithm grows a collection of trees, namely a forest.
- Both Prim's algorithm and Kruskal's algorithm take  $O(|E|\log|V|)$  time, but they adopt different data structures.

