

NobbZ-Emacs Configuration

Norbert Melzer

August 14, 2016

Contents

1	Foreword	3
2	Helpers	4
3	Packages	5
3.1	which-key	5
3.1.1	Install and load	6
3.1.2	Configuration	6
3.1.3	Key-chords	6
3.2	company-mode	7
3.2.1	Install and load	7
3.2.2	TODO Configuration	7
3.2.3	TODO Key-chords	7
3.3	project-explorer	7
3.3.1	Install and load	7
3.3.2	Configuration	7
3.3.3	TODO Key-chords	7
3.4	Puppet-Mode	8
3.4.1	Install and load	8
3.4.2	Configuration	8
3.4.3	Key-Chords	8
3.5	haskell-mode	9
3.5.1	Install and load	9
3.6	lfe-mode	9
3.6.1	Install and load	9
3.7	alchemist	9
3.7.1	Install and load	9
3.7.2	TODO Configuration	9

3.7.3	TODO Keybindings	9
4	TODO Security	10
5	Appearance, UI Elements, and the Emacs server	10
5.1	The server	10
5.2	Appearance	10
5.2.1	Theme & Faces	10
5.2.2	UI Elements	11
5.2.3	Welcome Screen	12
5.2.4	TODO Window Geometry	12
5.2.5	TODO Scrolling	12
6	Encoding	12
7	Pathes	12
7.1	Autosave and Backup	12
7.2	TODO Dropbox	12
8	Window Movement	13
9	Debugging	13
10	Trailing Whitespace	13
10.1	But do not display in some modes	13
11	TODO Dired	14
11.1	General Settings	14
12	Org-Mode	14
12.1	Installation	14
12.2	General settings	14
12.3	Allow execution of src-blocks	15
12.3.1	L ^A T _E X	15
12.3.2	Emacs-Lisp	15
12.3.3	Ditaa	15
12.3.4	Applying the stuff	15
12.3.5	Execution security	15
12.4	Syntax-Highlighting in sourceblocks	16
12.5	HTML Export	16
12.6	PDF-Export	16

12.7 Agenda	16
-----------------------	----

1 Foreword

A properly rendered version of this document is available at the following places:

PDF <https://nobbz.github.io/emacs.d/settings.pdf>

HTML <https://nobbz.github.io/emacs.d/settings.html>

This file is massively inspired/shamelessly stolen from the one shown at <https://ogbe.net/emacsconfig.html>

Before this file is actually loaded the following `init.el` is executed.

```
;; NobbZ init.el
;; Real stuff happens in =settings.org=

(require 'package)
(setq package-archives
      '(("gnu" . "http://elpa.gnu.org/packages/")
        ("melpa" . "http://melpa.org/packages/")
        ("org" . "http://orgmode.org/elpa/")))
(when (boundp 'package-pinned-packages)
  (setq package-pinned-packages
        '((org . "org"))))
(package-initialize)
(unless (package-installed-p 'use-package)
  (package-refresh-contents)
  (package-install 'use-package))

(eval-when-compile
  (require 'use-package))

;; Set the load path
(add-to-list 'load-path "~/.emacs.d/lisp/")
(add-to-list 'load-path "~/.emacs.d/vendor/org/lisp" t)
(add-to-list 'load-path "~/.emacs.d/vendor/org/contrib/lisp" t)

;; Moved all the custom.el stuff into its own file called
```

```
;; ~/.emacs.d/customize.el=
(setq custom-file "~/.emacs.d/customize.el")
(load custom-file)

(setq hostname
  (replace-regexp-in-string "\\`[ \\t\\n]*" ""
    (replace-regexp-in-string "[ \\t\\n]*\\`" ""
      (shell-command-to-string "hostname"))))

(require 'org)

(setq org-ditaa-jar-path "~/.emacs.d/vendor/org/contrib/scripts/ditaa.jar")

(defface org-block-begin-line
  '((t (:foreground "#99968b" :background "#303030"))
    "Face used for line delimiting the begin of source blocks.")

(defface org-block-end-line
  '((t (:foreground "#99968b" :background "#303030"))
    "Face used for line delimiting the end of source blocks.")

(org-babel-load-file "~/.emacs.d/settings.org")
```

The structure of the loading sequence as it is today can be seen in figure 1, while the planned way to load can be found in figure 2.

2 Helpers

Small little helpers which make it easier to live-reload the config:

```
(defun reload-settings ()
  (interactive)
  (org-babel-load-file "~/.emacs.d/settings.org"))
(defun settings ()
  (interactive)
  (find-file "~/.emacs.d/settings.org"))
```



Figure 1: Current file loading structure

3 Packages

```
(setq package-list '(use-package framemove htmlize))

;; (unless package-archive-contents
;;   (package-refresh-contents))

(dolist (package package-list)
  (unless (package-installed-p package)
    (package-install package)))

(use-package framemove)
```

3.1 which-key

`which-key` provides a minor mode, that displays the key bindings following your currently entered incomplete command in a pop up.

<https://github.com/justbur/emacs-which-key>




Figure 2: Planned file loading structure

3.1.1 Install and load

```
(unless (package-installed-p 'which-key)
  (package-install 'which-key))
(require 'which-key)
(which-key-mode)
```

3.1.2 Configuration

1 second is a very long delay, I do think that about a tenth of a second is enough.

```
(setq which-key-idle-delay 0.1)
```

3.1.3 Key-chords

`which-key` does not have any key-chords on its own, but I will enter some global stuff here.

```
(which-key-add-key-based-replacements
  "C-x C-f" "Open file"
  "C-x C-s" "Save file")
```

3.2 company-mode

company-mode is a text completion framework for Emacs.

<http://company-mode.github.io/>

3.2.1 Install and load

```
(unless (package-installed-p 'company)
  (package-install 'company))
(require 'company)
(add-hook 'after-init-hook 'global-company-mode)
```

3.2.2 TODO Configuration

3.2.3 TODO Key-chords

3.3 project-explorer

project-explorer is a tree explorer.

<https://github.com/sabof/project-explorer>

3.3.1 Install and load

We are only allowed to load `project-explorer` when in interactive mode.

```
(unless (package-installed-p 'project-explorer)
  (package-install 'project-explorer))
(unless noninteractive
  (require 'project-explorer))
```

3.3.2 Configuration

There is nothing special to configure right now.

3.3.3 TODO Key-chords

Toggle the explorer.

```
(global-set-key (kbd "C-c p e") 'project-explorer-toggle)
```

Also we do need to update the descriptions in `=which-key=s` dialog.

```
(which-key-add-key-based-replacements
  "C-c p"    "Project-Explorer"
  "C-c p e"  "Toggle PE")
```

3.4 Puppet-Mode

`puppet-mode` does provide syntax-highlighting, alignment and navigation for puppet-code.

<https://github.com/lunaryorn/puppet-mode>

3.4.1 Install and load

```
(unless (package-installed-p 'puppet-mode)
  (package-install 'puppet-mode))
```

Also we want to open `Puppetfile=s` in `=ruby-mode`.

```
(add-to-list
  'auto-mode-alist '("\\`Puppetfile\\`" . ruby-mode))
```

3.4.2 Configuration

We need to alter the `puppet-lint-command` a bit to have it actually work in our projects.

```
(setq puppet-lint-command "puppet-lint -no-autoloader_layout-check -with-context -log-")
```

3.4.3 Key-Chords

```
(which-key-add-major-mode-key-based-replacements 'puppet-mode
  "C-c C-a" "Align parameters"
  "C-c C-'" "Toggle quoting"
  "C-c C-;" "Blank string"
  "C-c C-j" "Jump to"
  "C-c C-c" "dry-run"
  "C-c C-v" "Validate syntax"
  "C-c C-l" "Check semantic")
```


3.5 haskell-mode

`haskell-mode` does provide syntax-highlighting, alignment and navigation for haskell source code.

<http://haskell.github.io/haskell-mode/>

3.5.1 Install and load

```
(unless (package-installed-p 'haskell-mode)
  (package-install 'haskell-mode))
```

3.6 lfe-mode

`lfe-mode` is used to highlight and complete lfe-files. It is currently not available at any repository, so it is delivered with this settings-file.

3.6.1 Install and load

```
(defvar lfe-mode-dir "~/.emacs.d/vendor/lfe")
(add-to-list 'load-path lfe-mode-dir)
(require 'lfe-start)
```

3.7 alchemist

Elixir Tooling Integration Into Emacs.

<https://github.com/tonini/alchemist.el>

ATTENTION: We do need to make sure, that nothing in this section is done, when we do not have `emacs` 24.4 or later!

3.7.1 Install and load

```
(unless (package-installed-p 'alchemist)
  (package-install 'alchemist))
```

3.7.2 TODO Configuration

3.7.3 TODO Keybindings

Currently all keybindings used by `alchemist` do violate emacs keybinding conventions.

A bug has been reported: <https://github.com/tonini/alchemist.el/issues/246>

And in the meantime it was closed (by me) in favor of the older `https://github.com/tonini/alchemist.el/issues/229`.

Until it got fixed, I won't configure any further key-bindings.

4 TODO Security

5 Appearance, UI Elements, and the Emacs server

First start a server and then set some important appearance settings. Note that some of the settings are in `init.el`.

5.1 The server

Start the server if not already running.

```
(load "server")
(unless (server-running-p) (server-start))
```

When connected to a server using `emacsclient`, we want to kill the client using `C-x k`, the way it seems natural.

```
(add-hook 'server-switch-hook
  (lambda ()
    (when (current-local-map)
      (use-local-map (copy-keymap (current-local-map))))
    (local-set-key (kbd "C-x k") 'server-edit)))
```

5.2 Appearance

5.2.1 Theme & Faces

```
(load-theme 'wheatgrass) ;; A nice dark theme
(set-face-attribute 'default nil :height 100) ;; 10pt font height
;; (set-face-attribute 'default nil :family "Consolas")
(set-face-attribute 'fringe nil :background "#2d2d2d")
(set-face-attribute 'font-lock-comment-face nil :slant 'italic :weight 'semibold)
;; (set-fontset-font "fontset-default" 'unicode "DejaVu Sans Mono for Powerline")

(global-hl-line-mode t)
```

We want to use `FiraCode` if possible by any means.

[illegible]

5.2.2 UI Elements

Get rid of that ugly disturbing stuff no one needs

```
(menu-bar-mode -1)
(when (display-graphic-p)
  (tool-bar-mode -1)
  (scroll-bar-mode -1))
```

5.2.3 Welcome Screen

We also want to get rid of the splash screen and start into home directory.

```
(setq inhibit-startup-message t)
(setq inhibit-splash-screen t)
(setq initial-scratch-message nil)
```

5.2.4 TODO Window Geometry

5.2.5 TODO Scrolling

I need to find out how to let emacs behave as with spacemacs smooth-scrolling setting.

6 Encoding

Most of the time I want to have UTF-8 as my file encoding.

```
(set-language-environment "UTF-8")
```

7 Pathes

7.1 Autosave and Backup

Autosaves directly beneath the edited files do clutter up the sourcetree. Instead let's throw them inside ~/tmp/.

```
(defvar backup-dir (expand-file-name "~/tmp/emacs_backup/"))
(defvar autosave-dir (expand-file-name "~/tmp/emacs_autosave/"))

(setq backup-directory-alist (list (cons ".*" backup-dir)))
(setq auto-save-list-file-prefix autosave-dir)
(setq auto-save-file-name-transforms `((".*" ,autosave-dir t)))
(setq tramp-backup-directory-alist backup-directory-alist)
(setq tramp-auto-save-directory autosave-dir)
```

7.2 TODO Dropbox

We need to know the basepath of dropbox.

The current function to read the path from `dropbox`' config is very ugly and needs some care to make it more beautiful.

```

(require 'json)

(defun find-dropbox-folder ()
  (interactive)
  (let ((json-path (if (eq system-type 'gnu/linux)
                       (expand-file-name "~/.dropbox/info.json")
                       (concat (getenv "APPDATA") "\\..\\Local\\Dropbox\\info.json"))))
    (cdr (assoc 'path (car (json-read-file json-path))))))
  (defvar dropbox-base-path (find-dropbox-folder))

```

8 Window Movement

Use Shift-<Arrow> to navigate through windows.

```

(unless (package-installed-p 'framemove)
  (package-install 'framemove))
(require 'framemove)
(windmove-default-keybindings)
(setq framemove-hook-into-windmove t)

```

9 Debugging

Setup some keys to make it easier to use GUD.

```

(global-set-key (kbd "<f7>") 'gud-cont)
(global-set-key (kbd "<f6>") 'gud-step)
(global-set-key (kbd "<f5>") 'gud-next)
(global-set-key (kbd "<f8>") 'gud-finish)

```

10 Trailing Whitespace

We want to see trailing whitespace, since it is the devil.

```

(require 'whitespace)
(setq-default show-trailing-whitespace t)

```

10.1 But do not display in some modes

```

(defun no-trailing-whitespace ()
  (setq show-trailing-whitespace nil))

```

Add a line for each mode:

```
(add-hook 'buffer-mode-hook 'no-trailing-whitespace)

(add-hook 'minibuffer-setup-hook 'no-trailing-whitespace)
(add-hook 'term-mode-hook      'no-trailing-whitespace)
```

11 TODO Dired

11.1 General Settings

The first two lines stop dired from asking me if I really want to recursively delete/copy directories. I never answer "no" to that question.

The other lines enable "Do What I Mean" mode for dired, using the other buffers location as target when copying in split-screen mode.

```
(setq dired-recursive-copies 'always)
(setq dired-recursive-deletes 'always)
(setq dired-dwim-target t)
(setq dired-listing-switches "-alh")
```

12 Org-Mode

org-mode might be THE killer app for emacs.

12.1 Installation

```
(use-package org
  :ensure t
  :defer t
  :pin org)
```

12.2 General settings

Some general settings for org.

```
(require 'org)
(setq-default
  org-return-follows-link t
  org-image-actual-width '(400)
  org-highlight-latex-and-related '(latex script entities))
(add-hook 'org-mode-hook 'turn-on-auto-fill)
```

12.3 Allow execution of src-blocks

First we need an empty list

```
(setq nobbz-babel-languages-alist '())
```

12.3.1 L^AT_EX

```
(require 'ob-latex)
(add-to-list 'nobbz-babel-languages-alist '(latex . t))
```

12.3.2 Emacs-Lisp

```
(add-to-list 'nobbz-babel-languages-alist '(emacs-lisp . t))
```

12.3.3 Dita

```
(add-to-list 'nobbz-babel-languages-alist '(dita . t))
```

12.3.4 Applying the stuff

```
(org-babel-do-load-languages
 'org-babel-load-languages
 nobbz-babel-languages-alist)
```



Hello World!

12.3.5 Execution security

```
(defun nobbz-org-confirm-babel-evaluate (lang body)
  (not (string= lang "dita"))) ; don't ask for dita
(setq org-confirm-babel-evaluate 'nobbz-org-confirm-babel-evaluate)
```

12.4 Syntax-Highlighting in sourceblocks

This is a very important feature in an org-document. Also adds native <tab> behaviour in those blocks.

```
(setq
  org-src-fontify-natively t
  org-src-tab-acts-natively t)
```

12.5 HTML Export

There shall be a custom stylesheet for HTML export.

```
(require 'ox-html)
(setq org-html-htlize-output-type 'inline-css)
```

12.6 PDF-Export

Use minted as a highlighter.

```
(require 'ox-latex)
(add-to-list 'org-latex-packages-alist '("" "minted"))
(setq org-latex-listings 'minted)
```

Also we want to use `latexmk` as the build-manager and `lualatex` as the engine.

```
(setq org-latex-pdf-process
  '("latexmk -lualatex -f -shell-escape %f"))
```

12.7 Agenda

We want to have this file itself on our agenda.

```
(setq org-default-notes-file (concat dropbox-base-path "/Dokumente/org/TODO.org"))
(add-to-list 'org-agenda-files (concat dropbox-base-path "/Dokumente/org/TODO.org"))
(add-to-list 'org-agenda-files "~/emacs.d/settings.org")
```

Also, we do need to have some additional convinience functions which help to find the various agenda related files.


```
(defun open-todo ()  
  (interactive)  
  (find-file (concat dropbox-base-path "/Dokumente/org/TODO.org")))  
(defun open-timing ()  
  (interactive)  
  (find-file (concat dropbox-base-path "/Dokumente/org/time-sheet.org")))
```