

Instructor created

6.23 C++ Memory Management: new and delete

C++ allows us to allocate the memory of a variable or an array in run time. This is known as dynamic memory allocation.

In other programming languages such as Java and Python, the compiler automatically manages the memories allocated to variables. But this is not the case in C++.

In C++, we need to deallocate the dynamically allocated memory manually after we have no use for the variable.

We can allocate and then deallocate memory dynamically using the `new` and `delete` operators respectively.

C++ new Operator

The `new` operator allocates memory to a variable. For example,

```
// declare an int pointer
int* pointVar;

// dynamically allocate memory
// using the new keyword
pointVar = new int;

// assign value to allocated memory
*pointVar = 45;
```

Here, we have dynamically allocated memory for an `int` variable using the `new` operator.

Notice that we have used the pointer `pointVar` to allocate the memory dynamically. This is because the `new` operator returns the address of the memory location.

In the case of an array, the `new` operator returns the address of the first element of the array.

From the example above, we can see that the syntax for using the `new` operator is

```
pointerVariable = new dataType;
```

delete Operator

Once we no longer need to use a variable that we have declared dynamically, we can deallocate the memory occupied by the variable.

For this, the `delete` operator is used. It returns the memory to the operating system. This is known as **memory deallocation**.

The syntax for this operator is

```
delete pointerVariable;
```

Consider the code:

```
// declare an int pointer
int* pointVar;

// dynamically allocate memory
// for an int variable
pointVar = new int;

// assign value to the variable memory
*pointVar = 45;

// print the value stored in memory
cout << *pointVar; // Output: 45

// deallocate the memory
delete pointVar;
```

Here, we have dynamically allocated memory for an `int` variable using the pointer `pointVar`.

After printing the contents of `pointVar`, we deallocated the memory using `delete`.

Note: If the program uses a large amount of unwanted memory using `new`, the system may crash because there will be no memory available for the operating system. In this case, the `delete` operator can help the system from crash.

Code Editor 6.23.1: C++ Dynamic Memory Allocation

Click run to see the output.

Load default template...

```
1 #include <iostream>
2 using namespace std;
3
4 int main() {
5     // declare an int pointer
6     int* pointInt;
7
8     // declare a float pointer
9     float* pointFloat;
10
11     // dynamically allocate memory
12     pointInt = new int;
13     pointFloat = new float;
14
15     // assigning value to the memory
16     *pointInt = 45;
17     *pointFloat = 45.45f;
18 }
```

Run

In this program, we dynamically allocated memory to two variables of `int` and `float` types. After assigning values to them and printing them, we finally deallocate the memories using the code

```
delete pointInt, pointFloat;
```

Note: Dynamic memory allocation can make memory management more efficient.

Especially for arrays, where a lot of the times we don't know the size of the array until the run time.

Code Editor 6.23.2: C++ new and delete Operator for Arrays

Click run to see the output.

Load default template...

```
1 // C++ Program to store GPA of n number of students and display it
2 // where n is the number of students entered by the user
3
4 #include <iostream>
5 #include <cstring>
6 using namespace std;
7
8 int main() {
9     int num;
10    cout << "Enter total number of students: ";
11    cin >> num;
12    cout << num << endl;
13    float* ptr;
14
15    // memory allocation of num number of floats
16    ptr = new float[num];
17
18    cout << "Enter GPA of students." << endl;
```

43.63.13.92.9

Run

In this program, we have asked the user to enter the number of students and store it in the `num` variable.

Then, we have allocated the memory dynamically for the `float` array using `new`.

We enter data into the array (and later print them) using pointer notation.

After we no longer need the array, we deallocate the array memory using the code `delete [] ptr;`

Notice the use of `[]` after `delete`. We use the square brackets `[]` in order to denote that the memory deallocation is that of an array.

[Feedback?](#)