

Dividimos y No Conquistamos (D&!C)

Contents

1	Template	2
1.1	C++ Template	2
1.2	Bash CMD	2
1.3	C++ Int128	2
1.4	C++ RNG	3
1.5	Python Template	3
2	Search	3
2.1	Ternary	3
3	Data structures	3
3.1	Fenwick	3
3.2	Fenwick - 2D	3
3.3	DSU	4
3.4	Sparse Table	4
3.5	Segment tree	4
3.6	Segment Tree Iterativo	5
3.7	Segment Tree Persistente	5
3.8	Policy Based	5
3.9	Chull Trick	6
4	Graph	6
4.1	Bellman Ford	6
4.2	SCC	6
4.3	Bipartite Matching Hopcroft-Karp - With Konig	6
4.4	Hungarian	7
4.5	Flow - Dinics	8
4.6	Flow - MinCostMaxFlow	9
4.7	2-Sat	10
4.8	Euler Tour	11
5	Trees	11
5.1	Heavy Light Decomposition	11
5.2	Centroid	11
5.3	LCA - Const Time	12
6	Dynamic Programming	12

6.1	LIS	12
7	Strings	12
7.1	Hashing	12
7.2	KMP	13
7.3	Z-Function	13
7.4	Manacher	13
7.5	Aho-Corasick	13
7.6	Suffix-Array	14
7.7	Suffix-Automaton	14
8	Math	15
8.1	Euclidean Extended	15
8.2	Euler Totient	15
8.3	Josephus	15
8.4	Mobius	16
8.5	NTT	16
8.6	FFT	17
8.7	Rho	17
8.8	Get Divisors	18
8.9	Simpson	18
8.10	Simplex	19
9	Geometry	19
9.1	Point Definition	19
9.2	Convex Hull	20
9.3	Operations	20
9.4	Polygon Area	20
9.5	Ray Casting	21
10	Other	21
10.1	Mo's algorithm	21
11	Ecuations	21
11.1	Combinatorics	21
11.2	Discreta	22
11.3	Trigonometry	23
11.4	Catalan Numbers	24
11.5	Geometry	24
11.6	Useful math	25
11.7	Mobius	27
11.8	Burnside	28

1 Template

1.1 C++ Template

```

1 #pragma GCC target ("avx2")
2 #pragma GCC optimize ("O3")
3 #pragma GCC optimize ("unroll-loops")
4 #include <bits/stdc++.h>
5 using namespace std;
6 #define L(i, j, n) for (int i = (j); i < (int)n; i++)
7 #define SZ(x) int((x).size())
8 #define ALL(x) begin(x),end(x)
9 #define vec vector
10 #define pb push_back
11 #define eb emplace_back
12 using ll = long long;
13 using ld = long double;
14 void solve(){}
15 int main(){
16     ios::sync_with_stdio(0);cin.tie(0);
17     int TT = 1;
18     //cin >> TT;
19     while (TT--) {solve();}
20 }
21 // IF NEEDED FOR FILE READ
22 // freopen("in.txt", "r", stdin);
23 // freopen("out.txt", "w", stdout);

```

1.2 Bash CMD

```

1 co(){g++ $1/$1.cpp -o $1/$1 --std=c++20 -Wall -Wshadow -Wextra}
2 run(){for f in `ls ./`$1/*.txt`;do echo $f ;./$1/$1 < $f; done}
3 #Build, template.cpp must exist!
4 for x in {A..Z}; do mkdir $x; cp template.cpp $x/$x.cpp; touch $x/in.txt;done

```

1.3 C++ Int128

```

1 __int128 read() {
2     __int128 x=0,f=1;
3     char ch=getchar();
4     while (ch<'0' || ch>'9') {
5         if(ch == '-')f=-1;
6         ch=getchar();
7     }

```

```

8     while (ch >= '0' && ch <= '9') {
9         x=x*10+ch-'0';
10        ch=getchar();
11    }
12    return x * f;
13 }
14 void print(__int128 x) {
15     if (x < 0) {
16         putchar('-');
17         x = -x;
18     }
19     if (x > 9) print(x / 10);
20     putchar(x % 10 + '0');
21 }

```

1.4 C++ RNG

```

1 using my_clock = chrono::steady_clock;
2 struct Random {
3     mt19937_64 engine;
4     Random(): engine(my_clock::now().time_since_epoch().count()) {}
5     template<class Int>Int integer(Int n) {return integer<Int>(0, n);} //
6     ' [0,n) '
7     template<class Int>Int integer(Int l, Int r)
8     {return uniform_int_distribution{1, r-1}(engine);} // ' [1,r) '
9     double real() {return uniform_real_distribution{}(engine);} // ' [0,1) '
10 } rng;

```

1.5 Python Template

```

1 import os, sys, io
2 finput = io.BytesIO(os.read(0, os.fstat(0).st_size)).readline
3 fprint = sys.stdout.write

```

2 Search

2.1 Ternary

```

1 // Minimo de 'f' en '(l,r)'.
2 template<class Fun>ll ternary(Fun f, ll l, ll r) {
3     for (ll d = r-l; d > 2; d = r-l) {
4         ll a = l + d/3, b = r - d/3;
5         if (f(a) > f(b)) l = a; else r = b;
6     }

```

```

7   return l + 1;
8 }
9 // para error < EPS, usar iters=log((r-l)/EPS)/log(1.618)
10 template<class Fun>double golden(Fun f, double l, double r, int iters){
11     double const ratio = (3-sqrt(5))/2;
12     double x1=l+(r-l)*ratio, x2=r-(r-l)*ratio, f1=f(x1), f2=f(x2);
13     while (iters--) {
14         if (f1 > f2) l=x1, x1=x2, f1=f2, x2=r-(r-l)*ratio, f2=f(x2);
15         else      r=x2, x2=x1, f2=f1, x1=l+(r-l)*ratio, f1=f(x1);
16     }
17     return (l+r)/2;
18 }

```

3 Data structures

3.1 Fenwick

```

1 #define LSO(S) (S & -S) //LeastsignificantOne
2 struct FT { // 1-Index
3     vec<int> ft; int n;
4     FT(vec<int> &v): ft(SZ(v)+1), n(SZ(v)+1) { // 0(n)
5         L(i, 1, n){
6             ft[i] += v[i-1];
7             if (i + LSO(i) <= n) ft[i + LSO(i)]+=ft[i];
8         }
9     }
10    void update(int pos, int x){ for (int it=pos;it<=n;it+=LSO(it))ft[it]
11        +=x; }
12    int sum(int pos){
13        int res = 0;
14        for (int it=pos;it>0;it-=LSO(it))res+=ft[it];
15        return res;
16    }
17    int getSum(int l, int r){return sum(r) - sum(l - 1);}
18 };

```

3.2 Fenwick - 2D

```

1 #define LSO(S) (S & -S)
2 struct BIT { // 1-Index
3     vec<vec<int>> B;
4     int n; // BUILD: N * N * log(N) * log(N)
5     BIT(int n_ = 1): B(n_+1,vec<int>(n_+1)), sz(n_) {}

```

```

6     void add(int i, int j, int delta){ // log(N) * log(N)
7         for (int x = i; x <= n; x += LSO(x))
8             for (int y = j; y <= n; y += LSO(y))
9                 B[x][y] += delta;
10    }
11    int sum(int i, int j){ // log(N) * log(N)
12        int tot = 0;
13        for (int x = i; x > 0; x -= LSO(x))
14            for(int y = j; y > 0; y -= LSO(y))
15                tot += B[x][y];
16        return tot;
17    }
18    int getSum(int x1, int y1, int x2, int y2) {return sum(x2, y2) - sum
19        (x2, y1) - sum(x1, y2) + sum(x1-1,y1-1);}
20 };

```

3.3 DSU

```

1 struct DSU {
2     vec<int> par, sz; int n;
3     DSU(int n = 1): par(n), sz(n, 1), n(n) { iota(ALL(par), 0); }
4     int find(int a){return a == par[a] ? a : par[a] = find(par[a]);}
5     void join(int a, int b){
6         a=find(a);b=find(b);
7         if (a == b) return;
8         if (sz[b] > sz[a]) swap(a,b);
9         par[b] = a; sz[a] += sz[b];
10    }
11 };

```

3.4 Sparse Table

```

1 struct SPT {
2     vec<vec<int>> st;
3     SPT(vec<int> &a) {
4         int n = SZ(a), K = 0; while((1<<K)<=n) K ++;
5         st = vec<vec<int>>(K, vec<int>(n));
6         L(i,0,n) st[0][i] = a[i];
7         L(i,1,K) for (int j = 0; j + (1 << i) <= n; j ++ )
8             st[i][j] = min(st[i-1][j], st[i - 1][j + (1 << (i - 1))]);
9         // change op
10    }
11    int get(int l, int r) {
12        int bit = log2(r - l + 1);

```

```

12     return min(st[bit][l], st[bit][r - (1<<bit) + 1]); // change op
13 }
14 };

```

3.5 Segment tree

```

1 #define LC(v) (v<<1)
2 #define RC(v) ((v<<1)|1)
3 #define MD(L, R) (L+((R-L)>>1))
4 struct node { ll mx; ll cant; };
5 struct ST {
6     vec<node> st; vec<ll> lz; int n;
7     ST(int n = 1): st(4 * n + 10, {oo, oo}), lz(4 * n + 10, 0), n(n) {
8         build(1, 0, n - 1);}
9     node merge(node a, node b){
10         if (a.mx == oo) return b; if (b.mx == oo) return a;
11         if (a.mx == b.mx) return {a.mx, a.cant + b.cant};
12         return {max(a.mx, b.mx), a.mx > b.mx ? a.cant : b.cant};
13     }
14     void build(int v, int L, int R){
15         if (L == R){ st[v] = {0, 1}; return; }
16         int m = MD(L, R);
17         build(LC(v), L, m); build(RC(v), m + 1, R);
18         st[v] = merge(st[LC(v)], st[RC(v)]);
19     }
20     void push(int v, int L, int R){
21         if (lz[v]){
22             if (L != R){
23                 st[LC(v)].mx += lz[v]; // Apply to left
24                 st[RC(v)].mx += lz[v]; // And right
25                 lz[LC(v)] += lz[v];
26                 lz[RC(v)] += lz[v];
27             }
28             lz[v] = 0;
29         }
30     }
31     void update(int v, int L, int R, int ql, int qr, ll w){
32         if (ql > R || qr < L) return;
33         push(v, L, R);
34         if (ql == L && qr == R){
35             st[v].mx += w; // Update actual node
36             lz[v] += w; // Add lazy
37             push(v, L, R); // Initial spread

```

```

37     return;
38 }
39 int m = MD(L, R);
40 update(LC(v), L, m, ql, min(qr, m), w);
41 update(RC(v), m + 1, R, max(m + 1, ql), qr, w);
42 st[v] = merge(st[LC(v)], st[RC(v)]);
43 }
44 node query(int v, int L, int R, int ql, int qr){
45     if (ql > R || qr < L) return {oo, oo};
46     push(v, L, R);
47     if (ql == L && qr == R) return st[v];
48     int m = MD(L, R);
49     return merge(query(LC(v), L, m, ql, min(m, qr)), query(RC(v), m
50         + 1, R, max(m + 1, ql), qr));
51 }
52 node query(int l, int r){return query(1, 0, n - 1, l, r);}
53 void update(int l, int r, ll w){update(1, 0, n - 1, l, r, w);}
54 };

```

3.6 Segment Tree Iterativo

```

1 struct STI {
2     vec<ll> st; int n, K;
3     STI(vec<ll> &a): n(SZ(a)), K(1) {
4         while(K<=n) K<<=1;
5         st.assign(2*K, 0); // 0 default
6         L(i,0,n) st[K+i] = a[i];
7         for (int i = K - 1; i > 0; i --) st[i] = st[i*2] + st[i*2+1];}
8     void upd(int i, ll w) {
9         i += K; st[i] += w;
10        while(i>=1)st[i]=st[i*2]+st[i*2+1];}
11    ll query(int l, int r) { // [l, r)
12        ll res = 0;
13        for (l += K, r += K; l < r; l>>=1, r>>=1){
14            if (l & 1) res += st[l++];
15            if (r & 1) res += st[--r];
16        }
17        return res;
18    }
19 };

```

3.7 Segment Tree Persistente

```

1 struct Vertex{Vertex * l, *r;int sum;};

```

```

2 const int MVertex = 6000000; // ~= N * logN * 2
3 Vertex pool[MVertex]; // the idea is to keep versions on vec<Vertex*>
   roots; roots.pb(build(ST_L, ST_R));
4 int p_num = 0; //
5 Vertex * init_leaf(int x) {
6     pool[p_num].sum = x;
7     pool[p_num].l = pool[p_num].r = NULL;
8     return &pool[p_num++];
9 }
10 Vertex * init_node(Vertex * l, Vertex * r) {
11     int sum = 0;
12     if (l) sum += l->sum;
13     if (r) sum += r->sum;
14     pool[p_num].sum = sum; pool[p_num].l = l; pool[p_num].r = r;
15     return &pool[p_num++];
16 Vertex * build(int L, int R){
17     if (L == R){return init_leaf(0);}
18     int m = MD(L, R); return init_node(build(L, m), build(m + 1, R));}
19 Vertex * update(Vertex * v, int L, int R, int pos, int w){
20     if (L == R)return init_leaf(v->sum + w);
21     int m = MD(L, R);
22     if (pos <= m) return init_node(update(v->l, L, m, pos, w), v->r);
23     return init_node(v->l, update(v->r, m + 1, R, pos, w));}
24 int query(Vertex * vl, Vertex * vr, int L, int R, int ql, int qr) {
25     if (!vl || !vr) return 0;
26     if (ql > R || qr < L) return 0;
27     if (ql == L && qr == R) {return vr->sum - vl->sum;}
28     int m = MD(L, R);
29     return query(vl->l, vr->l, L, m, ql, min(m, qr)) +
30         query(vl->r, vr->r, m + 1, R, max(m + 1, ql), qr);}

```

3.8 Policy Based

```

1 #include <ext/pb_ds/assoc_container.hpp>
2 using namespace __gnu_pbds;
3 template<typename Key, typename Val=null_type>
4 using indexed_set = tree<Key, Val, less<Key>, rb_tree_tag,
   tree_order_statistics_node_update>;
5 // indexed_set<char> s;
6 // char val = *s.find_by_order(0); // acceso por indice
7 // int idx = s.order_of_key('a'); // busca indice del valor
8 template<class Key, class Val=null_type>using htable=gp_hash_table<Key,
   Val>;

```

```

10 // como unordered_map (o unordered_set si Val es vacio), pero sin metodo
   count

```

3.9 Chull Trick

```

1 typedef ll tc;
2 const tc is_query=-(1LL<<62); // special value for query
3 struct Line {
4     tc m,b;
5     mutable multiset<Line>::iterator it,end;
6     const Line* succ(multiset<Line>::iterator it) const {
7         return (++it==end? NULL : &*it);}
8     bool operator<(const Line& rhs) const {
9         if(rhs.b!=is_query)return m<rhs.m;
10        const Line *s=succ(it);
11        if(!s)return 0;
12        return b-s->b<(s->m-m)*rhs.m;
13    }
14 };
15 struct HullDynamic : public multiset<Line> { // for maximum
16     bool bad(iterator y){
17         iterator z=next(y);
18         if(y==begin()){
19             if(z==end())return false;
20             return y->m==z->m&& y->b<=z->b;
21         }
22         iterator x=prev(y);
23         if(z==end())return y->m==x->m&& y->b<=x->b;
24         return 1.0*(x->b-y->b)*(z->m-y->m)>=1.0*(y->b-z->b)*(y->m-x->m);
25     } //Take care of overflow!
26     iterator next(iterator y){return ++y;}
27     iterator prev(iterator y){return --y;}
28     void add(tc m, tc b){
29         iterator y=insert((Line){m,b});
30         y->it=y; y->end=end();
31         if(bad(y)){erase(y);return;}
32         while(next(y)!=end()&&bad(next(y)))erase(next(y));
33         while(y!=begin()&&bad(prev(y)))erase(prev(y));
34     }
35     tc eval(tc x){
36         Line l=*lower_bound((Line){x,is_query});
37         return l.m*x+l.b;
38     }

```

```
39 };
```

4 Graph

4.1 Bellman Ford

```
1 struct Edge {int a, b, cost;};
2 vector<Edge> edges;
3 int solve(int s) // Source
4 {
5     vector<int> d(n, INF);
6     d[s] = 0;
7     for (int i = 0; i < n - 1; ++i)
8         for (Edge e : edges)
9             if (d[e.a] < INF)
10                d[e.b] = min(d[e.b], d[e.a] + e.cost);
11 }
```

4.2 SCC

```
1 vec<int> dfs_num(N, -1), dfs_low(N, -1), in_stack(N);
2 int dfs_count = 0;
3 int numSCC = 0;
4 stack<int> st;
5 void dfs(int u){
6     dfs_low[u]=dfs_num[u]=dfs_count++;
7     st.push(u);
8     in_stack[u] = 1;
9     for(int v: G[u]) {
10         if (dfs_num[v] == -1) dfs(v);
11         if (in_stack[v]) dfs_low[u] = min(dfs_low[u], dfs_low[v]);
12     }
13     if (dfs_num[u] == dfs_low[u]){
14         numSCC++;
15         while(1){
16             int v = st.top(); st.pop();
17             in_stack[v] = 0;
18             if (u == v) break;
19         }
20     }
21 }
```

4.3 Bipartite Matching Hopcroft-Karp - With Konig

```
1 mt19937 rng((int) chrono::steady_clock::now().time_since_epoch().count()
2 );
3 struct hopcroft_karp {
4     int n, m; // n is Left Partition Size, m is Right Partition Size
5     vec<vec<int>> g;
6     vec<int> dist, nxt, ma, mb;
7     hopcroft_karp(int n_, int m_) : n(n_), m(m_), g(n),
8         dist(n), nxt(n), ma(n, -1), mb(m, -1) {}
9     void add(int a, int b) { g[a].pb(b); }
10    bool dfs(int i) {
11        for (int &id = nxt[i]; id < g[i].size(); id++) {
12            int j = g[i][id];
13            if (mb[j] == -1 or (dist[mb[j]] == dist[i]+1 and dfs(mb[j]))) {
14                ma[i] = j, mb[j] = i;
15                return true;
16            }
17        }
18        return false;
19    }
20    bool bfs() {
21        for (int i = 0; i < n; i++) dist[i] = n;
22        queue<int> q;
23        for (int i = 0; i < n; i++) if (ma[i] == -1) {
24            dist[i] = 0;
25            q.push(i);
26        }
27        bool rep = 0;
28        while (q.size()) {
29            int i = q.front(); q.pop();
30            for (int j : g[i]) {
31                if (mb[j] == -1) rep = 1;
32                else if (dist[mb[j]] > dist[i] + 1) {
33                    dist[mb[j]] = dist[i] + 1;
34                    q.push(mb[j]);
35                }
36            }
37        }
38        return rep;
39    }
40    int matching() {
41        int ret = 0;
42        for (auto& i : g) shuffle(ALL(i), rng);
43        while (bfs()) {
```

```

43     for (int i = 0; i < n; i++) nxt[i] = 0;
44     for (int i = 0; i < n; i++)
45         if (ma[i] == -1 and dfs(i)) ret++;
46     }
47     return ret;
48 }
49 vec<int> cover[2]; // if cover[i][j] = 1 -> node i, j is part of cover
50 int konig() {
51     cover[0].assign(n,1); // n left size
52     cover[1].assign(m,0); // m right size
53     auto go = [&](auto&& me, int u) -> void {
54         cover[0][u] = false;
55         for (auto v : g[u]) if (!cover[1][v]) {
56             cover[1][v] = true;
57             me(me,mb[v]);
58         }
59     };
60     L(u,0,n) if (ma[u] < 0) go(go,u);
61     return size;
62 }
63 };

```

4.4 Hungarian

```

1 using vi = vec<int>;
2 using vd = vec<ld>;
3 const ld INF = 1e100; // Para max asignacion, INF = 0, y negar costos
4 bool zero(ld x) {return fabs(x) < 1e-9;} // Para int/ll: return x==0;
5 vec<pii> ans; // Guarda las aristas usadas en el matching: [0..n)x[0..m)
6 struct Hungarian{
7     int n; vec<vd> cs; vi vL, vR;
8     Hungarian(int N, int M) : n(max(N,M)), cs(n,vd(n)), vL(n), vR(n){
9         L(x, 0, N) L(y, 0, M) cs[x][y] = INF;
10    }
11    void set(int x, int y, ld c) { cs[x][y] = c; }
12    ld assign(){
13        int mat = 0; vd ds(n), u(n), v(n); vi dad(n), sn(n);
14        L(i, 0, n) u[i] = *min_element(ALL(cs[i]));
15        L(j, 0, n){
16            v[j] = cs[0][j]-u[0];
17            L(i, 1, n) v[j] = min(v[j], cs[i][j] - u[i]);
18        }
19        vL = vR = vi(n, -1);

```

```

20    L(i,0, n) L(j, 0, n) if(vR[j] == -1 and zero(cs[i][j] - u[i] - v[j]))
21        ){
22        vL[i] = j; vR[j] = i; mat++; break;
23    }
24    for(; mat < n; mat++){
25        int s = 0, j = 0, i;
26        while(vL[s] != -1) s++;
27        fill(ALL(dad), -1); fill(ALL(sn), 0);
28        L(k, 0, n) ds[k] = cs[s][k]-u[s]-v[k];
29        while(true){
30            j = -1;
31            L(k, 0, n) if(!sn[k] and (j == -1 or ds[k] < ds[j])) j = k;
32            sn[j] = 1; i = vR[j];
33            if(i == -1) break;
34            L(k, 0, n) if(!sn[k]){
35                auto new_ds = ds[j] + cs[i][k] - u[i]-v[k];
36                if(ds[k] > new_ds) ds[k]=new_ds, dad[k]=j;
37            }
38            L(k, 0, n) if(k!=j and sn[k]){
39                auto w = ds[k]-ds[j]; v[k] += w, u[vR[k]] -= w;
40            }
41            u[s] += ds[j];
42            while(dad[j] >= 0){ int d = dad[j]; vR[j] = vR[d]; vL[vR[j]] = j;
43                j = d; }
44            vR[j] = s; vL[s] = j;
45        }
46        ld value = 0; L(i, 0, n) value += cs[i][vL[i]], ans.pb({i, vL[i]});
47        return value;
48    }
49 };

```

4.5 Flow - Dinics

```

1 const int oo = (int)1e9;
2 struct Dinic {
3     bool scaling = false; // com scaling -> O(nm log(MAXCAP)),
4     int lim; // com constante alta
5     struct edge {
6         int to, cap, rev, flow;
7         bool res;
8         edge(int to_, int cap_, int rev_, bool res_)
9             : to(to_), cap(cap_), rev(rev_), flow(0), res(res_) {}

```

```

10 };
11 vec<vec<edge>> g;
12 vec<int> lev, beg;
13 ll F;
14 Dinic(int n) : g(n), F(0) {}
15 void add(int a, int b, int c) {
16     g[a].emplace_back(b, c, g[b].size(), false);
17     g[b].emplace_back(a, 0, g[a].size()-1, true);
18 }
19 bool bfs(int s, int t) {
20     lev = vector<int>(g.size(), -1); lev[s] = 0;
21     beg = vector<int>(g.size(), 0);
22     queue<int> q; q.push(s);
23     while (q.size()) {
24         int u = q.front(); q.pop();
25         for (auto& i : g[u]) {
26             if (lev[i.to] != -1 or (i.flow == i.cap)) continue;
27             if (scaling and i.cap - i.flow < lim) continue;
28             lev[i.to] = lev[u] + 1;
29             q.push(i.to);
30         }
31     }
32     return lev[t] != -1;
33 }
34 int dfs(int v, int s, int f = oo) {
35     if (!f or v == s) return f;
36     for (int& i = beg[v]; i < g[v].size(); i++) {
37         auto& e = g[v][i];
38         if (lev[e.to] != lev[v] + 1) continue;
39         int foi = dfs(e.to, s, min(f, e.cap - e.flow));
40         if (!foi) continue;
41         e.flow += foi, g[e.to][e.rev].flow -= foi;
42         return foi;
43     }
44     return 0;
45 }
46 ll max_flow(int s, int t) {
47     for (lim = scaling ? (1<<30) : 1; lim; lim /= 2)
48         while (bfs(s, t)) while (int ff = dfs(s, t)) F += ff;
49     return F;
50 }
51 };
52 vec<pair<int, int>> get_cut(Dinic& g, int s, int t) {

```

```

53     g.max_flow(s, t);
54     vec<pair<int, int>> cut;
55     vec<int> vis(g.g.size(), 0), st = {s};
56     vis[s] = 1;
57     while (st.size()) {
58         int u = st.back(); st.pop_back();
59         for (auto e : g.g[u]) if (!vis[e.to] and e.flow < e.cap)
60             vis[e.to] = 1, st.push_back(e.to);
61     }
62     for (int i = 0; i < g.g.size(); i++) for (auto e : g.g[i])
63         if (vis[i] and !vis[e.to] and !e.res) cut.emplace_back(i, e.to);
64     return cut;
65 }

```

4.6 Flow - MinCostMaxFlow

```

1 // 0(nm + f * m log n)
2 // const ll oo = (1ll)1e18;
3 template<typename T> struct mcmf {
4     struct edge {
5         int to, rev, flow, cap; // para, id da reversa, fluxo, capacidade
6         bool res; // se eh reversa
7         T cost; // custo da unidade de fluxo
8         edge() : to(0), rev(0), flow(0), cap(0), cost(0), res(false) {}
9         edge(int to_, int rev_, int flow_, int cap_, T cost_, bool res_)
10             : to(to_), rev(rev_), flow(flow_), cap(cap_), res(res_), cost(
11                 cost_) {}
12 };
13 vec<vec<edge>> g;
14 vec<int> par_idx, par;
15 T inf;
16 vec<T> dist;
17 mcmf(int n) : g(n), par_idx(n), par(n), inf(numeric_limits<T>::max()
18     /3) {}
19 void add(int u, int v, int w, T cost) { // de u pra v com cap w e
20     custo cost
21     edge a = edge(v, g[v].size(), 0, w, cost, false);
22     edge b = edge(u, g[u].size(), 0, 0, -cost, true);
23     g[u].push_back(a);
24     g[v].push_back(b);
25 }
26 vec<T> spfa(int s) { // nao precisa se nao tiver custo negativo
27     deque<int> q;

```



```

25     vec<bool> is_inside(g.size(), 0);
26     dist = vec<T>(g.size(), inf);
27     dist[s] = 0;
28     q.push_back(s);
29     is_inside[s] = true;
30     while (!q.empty()) {
31         int v = q.front();
32         q.pop_front();
33         is_inside[v] = false;
34         for (int i = 0; i < g[v].size(); i++) {
35             auto [to, rev, flow, cap, res, cost] = g[v][i];
36             if (flow < cap and dist[v] + cost < dist[to]) {
37                 dist[to] = dist[v] + cost;
38
39                 if (is_inside[to]) continue;
40                 if (!q.empty() and dist[to] > dist[q.front()]) q.push_back(to)
41                     ;
42                 else q.push_front(to);
43                 is_inside[to] = true;
44             }
45         }
46     }
47     return dist;
48 }
49 bool dijkstra(int s, int t, vec<T>& pot) {
50     priority_queue<pair<T, int>, vec<pair<T, int>>, greater<>> q;
51     dist = vec<T>(g.size(), inf);
52     dist[s] = 0;
53     q.emplace(0, s);
54     while (q.size()) {
55         auto [d, v] = q.top();
56         q.pop();
57         if (dist[v] < d) continue;
58         for (int i = 0; i < g[v].size(); i++) {
59             auto [to, rev, flow, cap, res, cost] = g[v][i];
60             cost += pot[v] - pot[to];
61             if (flow < cap and dist[v] + cost < dist[to]) {
62                 dist[to] = dist[v] + cost;
63                 q.emplace(dist[to], to);
64                 par_idx[to] = i, par[to] = v;
65             }
66         }
67     }
68 }

```

```

67     return dist[t] < inf;
68 }
69 pair<int, T> min_cost_flow(int s, int t, int flow = (int)1e9) {
70     vec<T> pot(g.size(), 0);
71     pot = spfa(s); // mudar algoritmo de caminho minimo aqui
72     int f = 0;
73     T ret = 0;
74     while (f < flow and dijkstra(s, t, pot)) {
75         for (int i = 0; i < g.size(); i++)
76             if (dist[i] < inf) pot[i] += dist[i];
77         int mn_flow = flow - f, u = t;
78         while (u != s){
79             mn_flow = min(mn_flow,
80                 g[par[u]][par_idx[u]].cap - g[par[u]][par_idx[u]].flow);
81             u = par[u];
82         }
83         ret += pot[t] * mn_flow;
84         u = t;
85         while (u != s) {
86             g[par[u]][par_idx[u]].flow += mn_flow;
87             g[u][g[par[u]][par_idx[u]].rev].flow -= mn_flow;
88             u = par[u];
89         }
90         f += mn_flow;
91     }
92     return make_pair(f, ret);
93 }
94 // Opcional: retorna as arestas originais por onde passa flow = cap
95 vec<pair<int,int>> recover() {
96     vec<pair<int,int>> used;
97     for (int i = 0; i < g.size(); i++) for (edge e : g[i])
98         if (e.flow == e.cap && !e.res) used.push_back({i, e.to});
99     return used;
100 }
101 };

```

4.7 2-Sat

```

1 struct TwoSat {
2     int n, v_n;
3     vec<bool> vis, assign;
4     vec<int> order, comp;
5     vec<vec<int>> g, g_t;

```

```

6   TwoSat(int n_): n(n_), v_n(2 * n_), vis(v_n) , assign(n_), comp(v_n
    , - 1), g(v_n), g_t(v_n) {
7       order.reserve(v_n);
8   }
9   void add_disj(int a, bool na, int b, bool nb) { // negated_a,
    negated_b
10       a = 2 * a ^ na;
11       b = 2 * b ^ nb;
12       int neg_a = a ^ 1;
13       int neg_b = b ^ 1;
14       g[neg_a].pb(b);
15       g[neg_b].pb(a);
16       g_t[a].pb(neg_b);
17       g_t[b].pb(neg_a);
18   }
19   void dfs1(int u){
20       vis[u] = 1;
21       for (int v: g[u]) if (!vis[v]) dfs1(v);
22       order.pb(u);
23   }
24   void dfs2(int u, int cc) {
25       comp[u] = cc;
26       for (int v: g_t[u]) if (comp[v] == -1) dfs2(v, cc);
27   }
28   bool solve() {
29       order.clear();
30       vis.assign(v_n, 0);
31       L(i,0, v_n) if (!vis[i]) dfs1(i);
32       comp.assign(v_n, - 1);
33       int cc = 0;
34       L(i, 0, v_n) {
35           int v = order[v_n - 1 - i];
36           if (comp[v] == -1) dfs2(v, cc ++);
37       }
38       assign.assign(n, false);
39       for (int i = 0; i < v_n; i += 2) {
40           if (comp[i] == comp[i+1]) return false;
41           assign[i / 2] = comp[i] > comp[i + 1];
42       }
43       return true;
44   }
45 };

```

4.8 Euler Tour

```

1 // Directed version (uncomment commented code for undirected)
2 struct edge {
3     int y;
4     // list<edge>::iterator rev;
5     edge(int y):y(y){}
6 };
7 list<edge> g[N];
8 void add_edge(int a, int b){
9     g[a].push_front(edge(b)); //auto ia=g[a].begin();
10    // g[b].push_front(edge(a)); auto ib=g[b].begin();
11    // ia->rev=ib; ib->rev=ia;
12 }
13 vec<int> p;
14 void go(int x){
15     while(g[x].size()){
16         int y=g[x].front().y;
17         //g[y].erase(g[x].front().rev);
18         g[x].pop_front();
19         go(y);
20     }
21     p.push_back(x);
22 }
23 vec<int> get_path(int x){ // get a path that begins in x
24 // check that a path exists from x before calling to get_path!
25     p.clear(); go(x); reverse(p.begin(), p.end());
26     return p;
27 }

```

5 Trees

5.1 Heavy Light Decomposition

```

1 int ans[N], par[N], depth[N], head[N], pos[N];
2 vec<int> heavy(N, - 1);
3 int t = 0;
4 vec<int> g[N];
5 int dfs(int u) {
6     int size = 1;
7     int max_size = 0;
8     for (int v: g[u]) if (v != par[u]) {
9         par[v] = u;

```

```

10     depth[v] = depth[u] + 1;
11     int cur_size = dfs(v);
12     size += cur_size;
13     if (cur_size > max_size) {
14         max_size = cur_size;
15         heavy[u] = v;
16     }
17 }
18 return size;
19 }
20 void decompose(int u, int h){
21     head[u] = h;
22     pos[u] = t++;
23     if (heavy[u] != -1){ decompose(heavy[u], h); }
24     for (int v: G[u]) if (v != par[u] && v != heavy[u]) {
25         decompose(v, v);
26     }
27 }
28 int query(int a, int b) {
29     int resp = -1;
30     for (; head[a] != head[b]; b = par[head[b]]){ // Subi todo el heavy
31         path y a su padre // Next
32         if (depth[head[a]] > depth[head[b]]) swap(a, b);
33         resp = max(resp, st.query(pos[head[b]], pos[b])); // pos[head[b]] < pos[b]
34     }
35     if (depth[a] > depth[b]) swap(a, b); // Una vez misma path(head)
36     entonces es una query [a,b]
37     resp = max(resp, st.query(pos[a], pos[b]));
38     return resp;
39 }
40 dfs(root);
41 decompose(root, root);

```

5.2 Centroid

```

1 int sz[N];
2 bool removed[N];
3 int getSize(int u, int p){
4     sz[u] = 1;
5     for(int v: G[u]) if (v != p && !removed[v]){
6         sz[u] += getSize(v, u);
7     }

```

```

8     return sz[u];
9 }
10 int centroid(int u, int p, int tz){
11     for (int v: g[u])
12         if (v != p && !removed[v] && sz[v] * 2 > tz) return centroid(v, u, tz);
13     return u;
14 }
15 int build(int u){
16     int c = centroid(u, -1, getSize(u, -1));
17     removed[c] = 1;
18     for (int v: G[c]) if (!removed[v]) { build(v); }
19     return c;
20 }

```

5.3 LCA - Const Time

```

1 struct LCA {
2     vec<int> depth, in, euler;
3     vec<vec<int>> g, st;
4     int K, n;
5     inline int Min(int i, int j) {return depth[i] <= depth[j] ? i : j;}
6     void dfs(int u, int p) {
7         in[u] = SZ(euler);
8         euler.pb(u);
9         for (int v: g[u]) if (v != p){
10             depth[v] = depth[u] + 1;
11             dfs(v, u);
12             euler.pb(u);
13         }
14     }
15     LCA(int n_): depth(n_), g(vec<vec<int>>(n_)), K(0), n(n_), in(n_) {
16         euler.reserve(2 * n); }
17     void add_edge(int u, int v) {g[u].pb(v);}
18     void build(int root){
19         dfs(root, -1);
20         int ln = SZ(euler);
21         while((1<<K)<=ln)K++;
22         st = vec<vec<int>>(K, vec<int>(ln));
23         L(i,0,ln) st[0][i] = euler[i];
24         for (int i = 1; (1 << i) <= ln; i++) {
25             for (int j = 0; j + (1<<i) <= ln; j++) {
26                 st[i][j] = Min(st[i-1][j], st[i-1][j + (1<<(i-1))]);

```

```

26     }
27 }
28 }
29 int get(int u, int v) {
30     int su = in[u];
31     int sv = in[v];
32     if (sv < su) swap(sv, su);
33     int bit = log2(sv - su + 1);
34     return Min(st[bit][su], st[bit][sv - (1<<bit) + 1]);
35 }
36 };

```

6 Dynamic Programming

6.1 LIS

```

1 int LIS(vec<int>& a){
2     vec<int> P;
3     P.pb(a[0]);
4     L(i,1,SZ(a)) {
5         if (a[i] > P.back()) P.pb(a[i]);
6         else {
7             auto ix = upper_bound()
8         }
9     }
10 }
11 return SZ(P);
12 }

```

7 Strings

7.1 Hashing

```

1 static constexpr ll ms[] = {1'000'000'007, 1'000'000'403};
2 static constexpr ll b = 500'000'000;
3 struct StrHash { // Hash polinomial con exponentes decrecientes.
4     vec<ll> hs[2], bs[2];
5     StrHash(string const& s) {
6         int n = SZ(s);
7         L(k, 0, 2) {
8             hs[k].resize(n+1), bs[k].resize(n+1, 1);
9             L(i, 0, n) {
10                 hs[k][i+1] = (hs[k][i] * b + s[i]) % ms[k];

```

```

11         bs[k][i+1] = bs[k][i] * b % ms[k];
12     }
13 }
14 }
15 ll get(int idx, int len) const { // Hashes en 's[idx, idx+len)'.
16     ll h[2];
17     L(k, 0, 2) {
18         h[k] = hs[k][idx+len] - hs[k][idx] * bs[k][len] % ms[k];
19         if (h[k] < 0) h[k] += ms[k];
20     }
21     return (h[0] << 32) | h[1];
22 }
23 };

```

7.2 KMP

```

1 struct KMP {
2     string s; int n; vec<int> p; vec<vec<int>> dfa;
3     KMP(string &s_): s(s_), n(SZ(s_)), p(SZ(s_) + 1), dfa(SZ(s_)+1, vec<
4         int>(26)) {
5         L(i,1,n) p[i + 1] = nxt(p[i], s[i]); // Calculate phi
6     }
7     int nxt(int i, char c) {for (;i=p[i]);if(i<n&&c==s[i])return i+1;
8         return s[0]==c;}
9     void build_dfa(){
10         dfa[0][s[0]-'a'] = 1; // WARN: check lower_case vs upper
11         L(i,1,n+1)L(c,0,26) // If complicated char set use map
12             if (i<n&&s[i]=='a'+c)dfa[i][c]=i+1;
13             else dfa[i][c]=dfa[p[i]][c]; // fallar en i e ir al c
14     }
15     int go(int v, char c){return dfa[v][c-'a'];}
16 };

```

7.3 Z-Function

```

1 vec<int> zfun(const string &w){
2     int n = SZ(w), l = 0, r = 0; vec<int> z(n);
3     z[0] = n;
4     L(i, 1, n) {
5         if (i <= r) {z[i] = min(r - i + 1, z[i - 1]);}
6         while (i + z[i] < n && w[z[i]] == w[i + z[i]]) {++z[i];}
7         if (i + z[i] - 1 > r) {l = i, r = i + z[i] - 1;}
8     }
9     return z;

```

```
10 | }
```

7.4 Manacher

```
1 struct Manacher {
2     vec<int> p;
3     Manacher(string const& s) {
4         int n = SZ(s), m = 2*n+1, l = -1, r = 1;
5         vec<char> t(m); L(i, 0, n) t[2*i+1] = s[i];
6         p.resize(m); L(i, 1, m) {
7             if (i < r) p[i] = min(r-i, p[l+r-i]);
8             while (p[i] <= i && i < m-p[i] && t[i-p[i]] == t[i+p[i]]) ++p[i];
9             if (i+p[i] > r) l = i-p[i], r = i+p[i];
10        }
11    } // Retorna palindromos de la forma {comienzo, largo}.
12    pii at(int i) const {int k = p[i]-1; return pair{i/2-k/2, k};}
13    pii odd(int i) const {return at(2*i+1);} // Mayor centrado en s[i].
14    pii even(int i) const {return at(2*i);} // Mayor centrado en s[i-1,i].
15 };
```

7.5 Aho-Corasick

```
1 struct node {
2     int ch[26], next[26]; // Full DFA Transitions
3     int link = 0, minx = oo; // Suffix Link
4     vec<int> ix; // Indices of patterns ending here
5     node() { memset(ch, -1, sizeof(ch)); }
6 };
7 vec<node> t; vec<int> bfs_order; // easy traverse from short to longer
8 words
9 void init_aho() {t.clear();t.pb(node());bfs_order.clear();}
10 void add_string(const string &s, const int ix) {
11     int v = 0;
12     for (char c_raw : s) {
13         int c = c_raw - 'a';
14         if (t[v].ch[c] == -1) {
15             t[v].ch[c] = SZ(t);
16             t.pb(node());
17         }
18         v = t[v].ch[c];
19     }
20     t[v].ix.pb(ix);
21 }
22 void build_aho() {
```

```
22     bfs_order.pb(0); // Root is first
23     L(c,0,26){
24         if (t[0].ch[c] != -1) {
25             t[0].next[c] = t[0].ch[c];
26             bfs_order.pb(t[0].ch[c]);
27         } else t[0].next[c] = 0;
28     }
29     L(q, 1, SZ(bfs_order)){ // warn: 1 not 0!
30         int u = bfs_order[q];
31         L(c,0,26){
32             if (t[u].ch[c] != -1) {
33                 int v = t[u].ch[c];
34                 t[u].next[c] = v;
35                 t[v].link = t[t[u].link].next[c];
36                 bfs_order.pb(v);
37             } else t[u].next[c] = t[t[u].link].next[c];
38         }
39     }
40 }
```

7.6 Suffix-Array

```
1 #define RB(x) ((x) < n ? r[x] : 0)
2 void csort(vec<int>& sa, vec<int>& r, int k) {
3     int n = SZ(sa);
4     vec<int> f(max(255, n)), t(n);
5     L(i,0, n) ++f[RB(i+k)];
6     int sum = 0;
7     L(i,0, max(255, n)) f[i] = (sum += f[i]) - f[i];
8     L(i,0, n) t[f[RB(sa[i]+k)]++] = sa[i];
9     sa = t;
10 }
11 vec<int> compute_sa(string& s){ // O(n*log2(n))
12     int n = SZ(s) + 1, rank;
13     vec<int> sa(n), r(n), t(n);
14     iota(ALL(sa), 0);
15     L(i,0, n) r[i] = s[i];
16     for (int k = 1; k < n; k *= 2) {
17         csort(sa, r, k), csort(sa, r, 0);
18         t[sa[0]] = rank = 0;
19         L(i, 1, n) {
20             if (r[sa[i]] != r[sa[i-1]] || RB(sa[i]+k) != RB(sa[i-1]+k)) ++rank;
21             t[sa[i]] = rank;
```

```

22     }
23     r = t;
24     if (r[sa[n-1]] == n-1) break;
25 }
26 return sa; // sa[i] = i-th suffix of s in lexicographical order
27 }
28 vec<int> compute_lcp(string& s, vec<int>& sa){
29     int n = SZ(s) + 1, K = 0;
30     vec<int> lcp(n), plcp(n), phi(n);
31     phi[sa[0]] = -1;
32     L(i, 1, n) phi[sa[i]] = sa[i-1];
33     L(i,0,n) {
34         if (phi[i] < 0) { plcp[i] = 0; continue; }
35         while(s[i+K] == s[phi[i]+K]) ++K;
36         plcp[i] = K;
37         K = max(K - 1, 0);
38     }
39     L(i,0, n) lcp[i] = plcp[sa[i]];
40     return lcp; // lcp[i] = longest common prefix between sa[i-1] and sa[i]
41 }

```

7.7 Suffix-Automaton

```

1 struct state {int len,link;map<char,int> next;}; //clear next!!
2 state st[2 * N]; // Important 2 * n
3 int sz,last;
4 void sa_init(){
5     last=st[0].len=0;sz=1;
6     st[0].link=-1;
7 }
8 void sa_extend(char c){
9     int k=sz++,p;
10    st[k].len=st[last].len+1;
11    for(p=last;p!=-1&&!st[p].next.count(c);p=st[p].link)st[p].next[c]=k;
12    if(p==-1)st[k].link=0;
13    else {
14        int q=st[p].next[c];
15        if(st[p].len+1==st[q].len)st[k].link=q;
16        else {
17            int w=sz++;
18            st[w].len=st[p].len+1;
19            st[w].next=st[q].next;st[w].link=st[q].link;

```

```

20         for(;p!=-1&&st[p].next[c]==q;p=st[p].link)st[p].next[c]=w;
21         st[q].link=st[k].link=w;
22     }
23 }
24 last=k;
25 }

```

8 Math

8.1 Euclidean Extended

```

1 ll extendedGCD(ll a, ll b, ll &x, ll &y) {
2     if (b == 0) {
3         x = 1;
4         y = 0;
5         return a;
6     }
7     ll x1, y1;
8     ll gcd = extendedGCD(b, a % b, x1, y1);
9     x = y1;
10    y = x1 - (a / b) * y1;
11    return gcd;
12 }
13
14 bool findSolutionWithConstraints(ll a, ll b, ll c, ll x_min, ll y_min,
15     ll &x, ll &y) {
16     ll g = extendedGCD(a, b, x, y);
17
18     if (c % g != 0) return false;
19
20     x *= c / g;
21     y *= c / g;
22
23     // Ajustamos las variables a/g y b/g para mover las soluciones
24     a /= g;
25     b /= g;
26
27     if (x < x_min) {
28         ll k = (x_min - x + b - 1) / b; // Redondeo hacia arriba
29         x += k * b;
30         y -= k * a;
31     } else if (x > x_min) {
32         ll k = (x - x_min) / b;

```

```

32     x -= k * b;
33     y += k * a;
34 }
35
36 if (y < y_min) {
37     ll k = (y_min - y + a - 1) / a; // Redondeo hacia arriba
38     x += k * b;
39     y -= k * a;
40 } else if (y > y_min) {
41     ll k = (y - y_min) / a;
42     x -= k * b;
43     y += k * a;
44 }
45
46 return x >= x_min && y >= y_min;
47 }

```

8.2 Euler Totient

```

1 vector<ll> compute_totients(ll n) {
2     vector<ll> phi(n + 1);
3     for (ll i = 0; i <= n; i++) phi[i] = i;
4     for (ll i = 2; i <= n; i++) {
5         if (phi[i] != i) continue;
6         for (ll j = i; j <= n; j += i)
7             phi[j] = phi[j] * (i - 1) / i;
8     }
9     return phi;
10 }

```

8.3 Josephus

```

1 ll josephus_iterative(ll n, ll k) {
2     ll result = 0;
3     for (ll i = 2; i <= n; ++i)
4         result = (result + k) % i;
5     return result;
6 }
7 ll josephus_recursive(ll n, ll k) {
8     if (n == 1) return 0;
9     return (josephus_recursive(n - 1, k) + k) % n;
10 }
11 ll josephus_power_of_2(ll n) {
12     ll power = 1;

```

```

13 while (power <= n) power <<= 1;
14 power >>= 1;
15 return 2 * (n - power);
16 }

```

8.4 Mobius

```

1 vector<ll> compute_mobius(ll n) {
2     vector<ll> mu(n + 1, 1);
3     vector<bool> is_prime(n + 1, true);
4     for (ll i = 2; i <= n; i++) {
5         if (is_prime[i]) { // i es un primo
6             for (ll j = i; j <= n; j += i) {
7                 mu[j] *= -1; // Multiplicamos por -1 para cada primo
8                 is_prime[j] = false;
9             }
10            for (ll j = i * i; j <= n; j += i * i) {
11                mu[j] = 0; // Si tiene un cuadrado de un primo, se pone
12                           // en 0
13            }
14        }
15    }
16    return mu;
17 }
18 ll mobius(ll x) {
19     ll count = 0;
20     for (ll i = 2; i * i <= x; i++) {
21         if (x % (i * i) == 0)
22             return 0;
23         if (x % i == 0) {
24             count++;
25             x /= i;
26         }
27     }
28     if (x > 1) count++;
29     return (count % 2 == 0) ? 1 : -1;
30 }

```

8.5 NTT

```

1 #include <bits/stdc++.h>
2 using namespace std;
3 using cd = complex<double>;
4 typedef long long ll;

```

```

5  const ll mod = 998244353;
6  const ll root = 31;
7  const ll root_1 = inverse(root, mod);
8  const ll root_pw = 1 << 23;
9
10 ll inverse(ll a, ll m) {
11     ll res = 1, exp = m - 2;
12     while (exp) {
13         if (exp % 2 == 1) res = (1LL * res * a) % m;
14         a = (1LL * a * a) % m;
15         exp /= 2;
16     }
17     return res;
18 }
19
20 void ntt(vector<ll> & a, bool invert) {
21     int n = a.size();
22
23     for (int i = 1, j = 0; i < n; i++) {
24         int bit = n >> 1;
25         for (; j & bit; bit >>= 1)
26             j ^= bit;
27         j ^= bit;
28
29         if (i < j)
30             swap(a[i], a[j]);
31     }
32
33     for (int len = 2; len <= n; len <= 1) {
34         int wlen = invert ? root_1 : root;
35         for (int i = len; i < root_pw; i <= 1)
36             wlen = (int)(1LL * wlen * wlen % mod);
37
38         for (int i = 0; i < n; i += len) {
39             int w = 1;
40             for (int j = 0; j < len / 2; j++) {
41                 int u = a[i+j], v = (int)(1LL * a[i+j+len/2] * w % mod);
42                 a[i+j] = u + v < mod ? u + v : u + v - mod;
43                 a[i+j+len/2] = u - v >= 0 ? u - v : u - v + mod;
44                 w = (int)(1LL * w * wlen % mod);
45             }
46         }
47     }

```

```

48
49     if (invert) {
50         int n_1 = inverse(n, mod);
51         for (auto & x : a)
52             x = (int)(1LL * x * n_1 % mod);
53     }
54 }
55
56 vector<ll> multiply(vector<ll> const &a, vector<ll> const &b) {
57     vector<ll> fa(a.begin(), a.end()), fb(b.begin(), b.end());
58     ll n = 1;
59     while (n < a.size() + b.size())
60         n <= 1;
61     fa.resize(n);
62     fb.resize(n);
63
64     ntt(fa, false);
65     ntt(fb, false);
66     for (ll i = 0; i < n; i++)
67         fa[i] = (fa[i] * fb[i]) % mod;
68     ntt(fa, true);
69
70     vector<ll> result(n);
71     for (ll i = 0; i < n; i++)
72         result[i] = fa[i];
73     return result;
74 }

```

8.6 FFT

```

1  typedef long long ll;
2  typedef complex<double> C;
3  typedef vector<double> vd;
4  typedef vector<ll> vll;
5  const double PI = acos(-1);
6
7  void fft(vector<C>& a) {
8      int n = a.size(), L = 31 - __builtin_clz(n);
9      static vector<C> R(2, 1);
10     static vector<C> rt(2, 1);
11     for (static int k = 2; k < n; k *= 2) {
12         R.resize(n); rt.resize(n);
13         auto x = polar(1.0, PI / k);

```



```

14     for (int i = k; i < 2 * k; i++)
15         rt[i] = R[i] = i & 1 ? R[i / 2] * x : R[i / 2];
16     }
17     vector<int> rev(n);
18     for (int i = 0; i < n; i++) rev[i] = (rev[i / 2] | (i & 1) << L) /
19         2;
20     for (int i = 0; i < n; i++) if (i < rev[i]) swap(a[i], a[rev[i]]);
21     for (int k = 1; k < n; k *= 2)
22         for (int i = 0; i < n; i += 2 * k) for (int j = 0; j < k; j++) {
23             auto x = (double*)&rt[j + k], y = (double*)&a[i + j + k];
24             C z(x[0] * y[0] - x[1] * y[1], x[0] * y[1] + x[1] * y[0]);
25             a[i + j + k] = a[i + j] - z;
26             a[i + j] += z;
27         }
28 }
29 vll multiply(const vll& a, const vll& b) {
30     if (a.empty() || b.empty()) return {};
31     vd fa(a.begin(), a.end()), fb(b.begin(), b.end());
32     int L = 32 - __builtin_clz(fa.size() + fb.size() - 1), n = 1 << L;
33     vector<C> in(n), out(n);
34
35     for (int i = 0; i < a.size(); i++) in[i] = C(fa[i], 0);
36     for (int i = 0; i < b.size(); i++) in[i].imag(fb[i]);
37
38     fft(in);
39     for (C& x : in) x *= x;
40     for (int i = 0; i < n; i++) out[i] = in[-i & (n - 1)] - conj(in[i]);
41     // Corregido aqui
42     fft(out);
43
44     vll res(a.size() + b.size() - 1);
45     for (int i = 0; i < res.size(); i++) {
46         res[i] = llround(imag(out[i]) / (4 * n));
47     }
48     return res;
49 }

```

8.7 Rho

```

1 ll mul(ll a, ll b, ll mod) {
2     return (__int128)a * b % mod;
3 }

```

```

4 ll power(ll a, ll b, ll mod) {
5     ll res = 1;
6     while (b) {
7         if (b & 1) res = mul(res, a, mod);
8         a = mul(a, a, mod);
9         b >>= 1;
10    }
11    return res;
12 }
13
14 bool isPrime(ll n) {
15     if (n < 2) return false;
16     for (ll p : {2, 3, 5, 7, 11, 13, 17, 19, 23}) {
17         if (n % p == 0) return n == p;
18     }
19     ll d = n - 1, s = 0;
20     while ((d & 1) == 0) d >>= 1, ++s;
21     for (ll a : {2, 325, 9375, 28178, 450775, 9780504, 1795265022}) {
22         if (a % n == 0) continue;
23         ll x = power(a, d, n);
24         if (x == 1 || x == n - 1) continue;
25         bool ok = false;
26         for (int i = 0; i < s; ++i) {
27             x = mul(x, x, n);
28             if (x == n - 1) { ok = true; break; }
29         }
30         if (!ok) return false;
31     }
32     return true;
33 }
34
35 ll rho(ll n) {
36     if (n % 2 == 0) return 2;
37     while (true) {
38         ll c = rand() % (n - 1) + 1;
39         ll x = 2, y = 2, d = 1;
40         while (d == 1) {
41             x = (mul(x, x, n) + c) % n;
42             y = (mul(y, y, n) + c) % n;
43             y = (mul(y, y, n) + c) % n;
44             d = std::gcd((x > y ? x - y : y - x), n);
45         }
46     }

```

```

47     if (d != n) return d;
48 }
49 }
50
51 void fact(ll n, std::map<ll, int>& f) {
52     if (n == 1) return;
53     if (isPrime(n)) { f[n]++; return; }
54     ll d = rho(n);
55     if (d == n) {
56         f[n]++;
57         return;
58     }
59     fact(d, f);
60     fact(n / d, f);
61 }

```

8.8 Get Divisors

```

1 vector<ll> getDivisors(const map<ll, int>& f) {
2     vector<ll> divisors = { 1 };
3     for (auto [p, e] : f) {
4         vector<ll> next;
5         ll pe = 1;
6         for (int i = 0; i <= e; i++) {
7             for (ll d : divisors) next.pb(d * pe);
8             pe *= p;
9         }
10        divisors.swap(next);
11    }
12    sort(ALL(divisors));
13    return divisors;
14 }

```

8.9 Simpson

```

1 ld simpsonRule(function<ld(ld)> f, ld a, ld b, int n) {
2     // Asegurarse de que n sea par
3     if (n % 2 != 0) {
4         n++;
5     }
6     ld h = (b - a) / n;
7     ld s = f(a) + f(b);
8
9     // Suma de terminos interiores con los factores apropiados

```

```

10     for (int i = 1; i < n; i++) {
11         ld x = a + i * h;
12         s += (i % 2 == 1 ? 4.0L : 2.0L) * f(x);
13     }
14     // Multiplica por h/3
15     return (h / 3.0L) * s;
16 }
17 // Ejemplo: integrar la funcion x^2 entre 0 y 3
18 auto f = [&](ld x){ return x * x; };
19 ld a = 0.0L, b = 3.0L;
20 int n = 1000; // numero de subintervalos
21 ld resultado = simpsonRule(f, a, b, n);

```

8.10 Simplex

```

1 pair<ld, vec<ld>> simplex(vec<vec<ld>> A, vec<ld> b, vec<ld> c) {
2     const ld EPS = (ld)1e-9;
3     int n = SZ(b), m = SZ(c);
4
5     vec<int> X(m), Y(n);
6     L(j, 0, m) X[j] = j;
7     L(i, 0, n) Y[i] = m + i;
8
9     ld z = 0;
10
11     auto pivot = [&](int x, int y) {
12         swap(X[y], Y[x]);
13
14         ld inv = (ld)1 / A[x][y];
15         b[x] *= inv;
16         L(j, 0, m) if (j != y) A[x][j] *= inv;
17         A[x][y] = inv;
18
19         L(i, 0, n) if (i != x && fabs1(A[i][y]) > EPS) {
20             ld coef = A[i][y];
21             b[i] -= coef * b[x];
22             L(j, 0, m) if (j != y) A[i][j] -= coef * A[x][j];
23             A[i][y] = -coef * A[x][y];
24         }
25
26         z += c[y] * b[x];
27         L(j, 0, m) if (j != y) c[j] -= c[y] * A[x][j];
28         c[y] = -c[y] * A[x][y];

```

```

29     };
30
31     while (true) {
32         int x = -1, y = -1;
33         ld mn = -EPS;
34         L(i, 0, n) if (b[i] < mn) { mn = b[i]; x = i; }
35         if (x < 0) break;
36         L(j, 0, m) if (A[x][j] < -EPS) { y = j; break; }
37         if (y < 0) {
38             return { numeric_limits<ld>::quiet_NaN(), {} };
39         }
40         pivot(x, y);
41     }
42
43     while (true) {
44         int y = -1, x = -1;
45         ld mx = EPS;
46         L(j, 0, m) if (c[j] > mx) { mx = c[j]; y = j; }
47         if (y < 0) break;
48
49         ld best = numeric_limits<ld>::infinity();
50         L(i, 0, n) if (A[i][y] > EPS) {
51             ld val = b[i] / A[i][y];
52             if (val < best) { best = val; x = i; }
53         }
54         if (x < 0) {
55             return { numeric_limits<ld>::infinity(), {} };
56         }
57         pivot(x, y);
58     }
59
60     vec<ld> sol(m, 0);
61     L(i, 0, n) if (Y[i] < m) sol[Y[i]] = b[i];
62     return { z, sol };
63 }

```

9 Geometry

9.1 Point Definition

```

1 const double EPS = 1e-7;
2 struct pt { // for 3D add z coordinate, define EPS
3     double x,y;

```

```

4     pt(double x, double y):x(x),y(y){}
5     pt(){}
6     double norm2(){return *this**this;}
7     double norm(){return sqrt(norm2());}
8     bool operator==(pt p){return abs(x-p.x)<=EPS&&abs(y-p.y)<=EPS;}
9     pt operator+(pt p){return pt(x+p.x,y+p.y);}
10    pt operator-(pt p){return pt(x-p.x,y-p.y);}
11    pt operator*(double t){return pt(x*t,y*t);}
12    pt operator/(double t){return pt(x/t,y/t);}
13    double operator*(pt p){return x*p.x+y*p.y;} // dot prod
14    // pt operator^(pt p){ // only for 3D
15    //     return pt(y*p.z-z*p.y,z*p.x-x*p.z,x*p.y-y*p.x);}
16    double angle(pt p){ // redefine acos for values out of range
17        return acos(*this*p/(norm()*p.norm()));}
18    pt unit(){return *this/norm();}
19    double operator%(pt p){return x*p.y-y*p.x;} // cross prod
20    // 2D from now on
21    bool operator<(pt p)const{ // for convex hull
22        return x<p.x-EPS|| (abs(x-p.x)<=EPS&&y<p.y-EPS);}
23    bool left(pt p, pt q){ // is it to the left of directed line pq?
24        return (q-p)%(*this-p)>EPS;}
25    pt rot(pt r){return pt(*this%r,*this*r);}
26    pt rot(double a){return rot(pt(sin(a),cos(a)));}
27 };
28 pt ccw90(1,0);
29 pt cw90(-1,0);

```

9.2 Convex Hull

```

1 typedef pair<ll, ll> Point;
2 ll cross_product(Point O, Point A, Point B) {
3     return (A.first - O.first) * (B.second - O.second) - (A.second - O.
4         second) * (B.first - O.first);
5 }
6 vector<Point> convex_hull(vector<Point>& points) {
7     sort(points.begin(), points.end());
8     points.erase(unique(points.begin(), points.end()), points.end());
9     vector<Point> hull;
10    // Parte inferior
11    for (const auto& p : points) {
12        while (hull.size() >= 2 && cross_product(hull[hull.size() - 2],
13            hull[hull.size() - 1], p) < 0)
14            hull.pop_back();

```

```

13     if (hull.empty() || hull.back() != p) {
14         hull.push_back(p);
15     }
16 }
17 // Parte superior
18 int t = hull.size() + 1;
19 for (int i = points.size() - 1; i >= 0; --i) {
20     while (hull.size() >= t && cross_product(hull[hull.size() - 2],
21         hull[hull.size() - 1], points[i]) < 0)
22         hull.pop_back();
23     if (hull.empty() || hull.back() != points[i]) {
24         hull.push_back(points[i]);
25     }
26 }
27 hull.pop_back();
28 return hull;
29 }

```

9.3 Operations

```

1 ll cross_product(pair<ll, ll> P1, pair<ll, ll> P2, pair<ll, ll> P3) {
2     ll x1 = P2.first - P1.first;
3     ll y1 = P2.second - P1.second;
4     ll x2 = P3.first - P1.first;
5     ll y2 = P3.second - P1.second;
6     return x1 * y2 - y1 * x2;
7 }
8 double distancia(pair<ll, ll> P1, pair<ll, ll> P2) {
9     return sqrt((P2.first - P1.first) * (P2.first - P1.first) +
10         (P2.second - P1.second) * (P2.second - P1.second));
11 }
12 ll dot_product(pair<ll, ll> P1, pair<ll, ll> P2, pair<ll, ll> P3) {
13     ll x1 = P2.first - P1.first;
14     ll y1 = P2.second - P1.second;
15     ll x2 = P3.first - P1.first;
16     ll y2 = P3.second - P1.second;
17     return x1 * x2 + y1 * y2;
18 }

```

9.4 Polygon Area

```

1 typedef pair<ll, ll> Point;
2 double polygon_area(const vector<Point>& polygon) {
3     ll area = 0;

```

```

4     int n = polygon.size();
5     for (int i = 0; i < n; ++i) {
6         ll j = (i + 1) % n;
7         area += (polygon[i].first * polygon[j].second - polygon[i].
8             second * polygon[j].first);
9     }
10    return abs(area) / 2.0;
11 }

```

9.5 Ray Casting

```

1 int inPolygon(const vector<pt>& p, pt a) { // 0: Outside, 1: Inside, 2:
2     Boundary
3     int ans = 0; int n = SZ(p);
4     L(i,0,n) {
5         pt p1 = p[i], p2 = p[(i + 1) % n];
6         if ((p2 - p1) % (a - p1) == 0 &&
7             min(p1.x, p2.x) <= a.x && a.x <= max(p1.x, p2.x) &&
8             min(p1.y, p2.y) <= a.y && a.y <= max(p1.y, p2.y)) return 2;
9         if ((p1.y > a.y) != (p2.y > a.y)) {
10             ll cp = (p2 - p1) % (a - p1);
11             if (p1.y < p2.y ? cp > 0 : cp < 0) ans = 1 - ans;
12         }
13     }
14    return ans;
15 }

```

10 Other

10.1 Mo's algorithm

```

1 const int BLOCK_SIZE = 450; using U64 = uint64_t;
2 struct query {int l, r, id; U64 order;};
3 U64 hiltbertorder(U64 x, U64 y) {
4     const U64 logn = __lg(max(x, y) * 2 + 1) | 1;
5     const U64 maxn = (1ull << logn) - 1;
6     U64 res = 0;
7     for (U64 s = 1ull << (logn - 1); s; s >>= 1) {
8         bool rx = x & s, ry = y & s;
9         res = (res << 2) | (rx ? ry ? 2 : 1 : ry ? 3 : 0);
10        if (!rx) {
11            if (ry) x ^= maxn, y ^= maxn;
12            swap(x, y);

```

```

13     }
14 }
15 return res;
16 } // sort by this order
17 auto add = [&](int ix) { /* Add A[ix] to state*/};
18 auto rem = [&](int ix) { /* Remove A[ix] from state*/};
19 int c_l = 0, c_r = -1; // Cursors [0,-1] so r add 0 on first q
20 for(const auto &q: qs){
21     while(c_l > qr.l) add(--c_l);
22     while(c_r < qr.r) add(++c_r);
23     while(c_l < qr.l) rem(c_l++);
24     while (c_r > qr.r) rem(c_r--);
25     ans[qr.id] = /*State.Answer()*/;
26 }

```

11 Ecuations

11.1 Combinatorics

$$\binom{n}{k} = \binom{n}{n-k}$$

$$\binom{n}{k} = \frac{n}{k} \binom{n-1}{k-1}, \quad (1 \leq k \leq n)$$

$$\sum_{k=0}^n \binom{n}{k} = 2^n$$

$$\sum_{m=0}^n \binom{m}{k} = \binom{n+1}{k+1}, \quad (n \geq k \geq 0)$$

$$\sum_{k=0}^m \binom{n+k}{k} = \binom{n+m+1}{m}$$

$$\binom{n}{0}^2 + \binom{n}{1}^2 + \cdots + \binom{n}{n}^2 = \binom{2n}{n}$$

$$\sum_{k=1}^n k \binom{n}{k} = n2^{n-1}$$

$$F_n = \sum_{k=0}^{\lfloor \frac{n-1}{2} \rfloor} \binom{n-k-1}{k}$$

$$F_{n+1} = \sum_{k=0}^{\lfloor \frac{n}{2} \rfloor} \binom{n-k}{k}$$

11.2 Discreta

Vandermonde convolution:

$$\sum_{k=0}^n \binom{r}{k} \binom{s}{n-k} = \binom{r+s}{n}$$

Multinomial theorem:

$$(x_1 + \cdots + x_m)^n = \sum_{\substack{a_1 + \cdots + a_m = n \\ a_i \geq 0}} \frac{n!}{a_1! \cdots a_m!} x_1^{a_1} \cdots x_m^{a_m}$$

Binomial inversion (sequence form):

$$g(n) = \sum_{k=0}^n \binom{n}{k} f(k) \iff f(n) = \sum_{k=0}^n (-1)^{n-k} \binom{n}{k} g(k)$$

Stars and bars (nonnegative):

$$x_1 + \cdots + x_k = n, \quad x_i \geq 0 \Rightarrow \# = \binom{n+k-1}{k-1}$$

Positive parts:

$$x_1 + \cdots + x_k = n, \ x_i \geq 1 \Rightarrow \# = \binom{n-1}{k-1}$$

Compositions of n:

$$\#\{\text{ordered positive sum of } n \text{ into } k \text{ parts}\} = \binom{n-1}{k-1}, \quad \#\{\text{all compositions}\} = 2^{n-1}$$

Upper bounds via inclusion-exclusion:

$$x_1 + \cdots + x_k = n, \ 0 \leq x_i \leq u_i \Rightarrow \# = \sum_{S \subseteq \{1, \dots, k\}} (-1)^{|S|} \binom{n - \sum_{i \in S} (u_i + 1) + k - 1}{k-1}$$

$$(\text{toma } \binom{t}{k-1} = 0 \text{ si } t < k-1)$$

Multiset combinations:

$$\#\{k\text{-multicombinations from } n \text{ types}\} = \binom{n+k-1}{k}$$

Multiset permutations:

$$\#\{\text{perm of multiset with counts } m_1, \dots, m_r\} = \frac{(m_1 + \cdots + m_r)!}{m_1! \cdots m_r!}$$

Circular permutations:

$$\#\{\text{distinct cyclic orders of } n \text{ items}\} = (n-1)!$$

Surjections count (onto functions):

$$\#\{f : [m] \rightarrow [n] \text{ onto}\} = \sum_{j=0}^n (-1)^j \binom{n}{j} (n-j)^m = n! S(m, n)$$

Derangements:

$$!n = n! \sum_{i=0}^n \frac{(-1)^i}{i!} \quad \text{and} \quad !n \approx \frac{n!}{e}$$

Stirling numbers (second kind):

$$S(n, k) = k S(n-1, k) + S(n-1, k-1), \quad S(0, 0) = 1$$

Stirling numbers (first kind, unsigned):

$$c(n, k) = c(n-1, k-1) + (n-1) c(n-1, k), \quad c(0, 0) = 1$$

Expansions with falling powers:

$$x^n = \sum_{k=0}^n s(n, k) x^{\underline{k}}, \quad x^n = \sum_{k=0}^n S(n, k) x^{\underline{k}}$$

$$(\text{here } x^{\underline{k}} = x(x-1) \cdots (x-k+1), \ s(n, k) = (-1)^{n-k} c(n, k))$$

Bell numbers:

$$B_n = \sum_{k=0}^n S(n, k), \quad \sum_{n \geq 0} B_n \frac{x^n}{n!} = \exp(e^x - 1)$$

Cayley trees:

$$\#\{\text{labeled trees on } n \text{ vertices}\} = n^{n-2}$$

Perfect matchings in complete graph:

$$\#\{\text{perfect matchings in } K_{2n}\} = (2n-1)!! = \frac{(2n)!}{2^n n!}$$

Grid shortest paths:

$$\#\{\text{monotone paths from } (0, 0) \text{ to } (a, b)\} = \binom{a+b}{a}$$

Ballot (Bertrand special case):

$$p > q \Rightarrow \#\{\text{prefix-wise leading sequences}\} = \frac{p-q}{p+q} \binom{p+q}{q}$$

Alternating binomial sums:

$$\sum_{k=0}^n (-1)^k \binom{n}{k} = 0 \quad (n \geq 1), \quad \sum_{k=0}^n (-1)^k \binom{n}{k} k^m = 0 \quad (0 \leq m < n)$$

Lucas theorem (mod prime p):

$$n = \sum n_i p^i, \quad k = \sum k_i p^i \Rightarrow \binom{n}{k} \equiv \prod_i \binom{n_i}{k_i} \pmod{p}$$

11.3 Trigonometry

$$\begin{aligned} \sin(-x) &= -\sin x, & \cos(-x) &= \cos x, & \tan(-x) &= -\tan x \\ \sin^2 x + \cos^2 x &= 1, & 1 + \tan^2 x &= \sec^2 x, & 1 + \cot^2 x &= \csc^2 x \end{aligned}$$

$$\sin(\alpha \pm \beta) = \sin \alpha \cos \beta \pm \cos \alpha \sin \beta$$

$$\cos(\alpha \pm \beta) = \cos \alpha \cos \beta \mp \sin \alpha \sin \beta$$

$$\tan(\alpha \pm \beta) = \frac{\tan \alpha \pm \tan \beta}{1 \mp \tan \alpha \tan \beta}$$

$$\sin(2x) = 2 \sin x \cos x$$

$$\cos(2x) = \cos^2 x - \sin^2 x = 1 - 2 \sin^2 x = 2 \cos^2 x - 1$$

$$\tan(2x) = \frac{2 \tan x}{1 - \tan^2 x}$$

$$\sin(3x) = 3 \sin x - 4 \sin^3 x, \quad \cos(3x) = 4 \cos^3 x - 3 \cos x$$

$$\sin^2 \frac{x}{2} = \frac{1 - \cos x}{2}, \quad \cos^2 \frac{x}{2} = \frac{1 + \cos x}{2}, \quad \tan \frac{x}{2} = \frac{\sin x}{1 + \cos x} = \frac{1 - \cos x}{\sin x}$$

$$\sin \alpha \sin \beta = \frac{1}{2} [\cos(\alpha - \beta) - \cos(\alpha + \beta)]$$

$$\cos \alpha \cos \beta = \frac{1}{2} [\cos(\alpha - \beta) + \cos(\alpha + \beta)]$$

$$\sin \alpha \cos \beta = \frac{1}{2} [\sin(\alpha + \beta) + \sin(\alpha - \beta)]$$

$$\sin \alpha \pm \sin \beta = 2 \sin \frac{\alpha \pm \beta}{2} \cos \frac{\alpha \mp \beta}{2}$$

$$\cos \alpha + \cos \beta = 2 \cos \frac{\alpha + \beta}{2} \cos \frac{\alpha - \beta}{2}$$

$$\cos \alpha - \cos \beta = -2 \sin \frac{\alpha + \beta}{2} \sin \frac{\alpha - \beta}{2}$$

$$\sum_{k=0}^{n-1} \cos(a + kd) = \frac{\sin(\frac{nd}{2})}{\sin(\frac{d}{2})} \cos\left(a + \frac{(n-1)d}{2}\right)$$

$$\sum_{k=0}^{n-1} \sin(a + kd) = \frac{\sin(\frac{nd}{2})}{\sin(\frac{d}{2})} \sin\left(a + \frac{(n-1)d}{2}\right)$$

$$\text{Law of sines: } \frac{a}{\sin A} = \frac{b}{\sin B} = \frac{c}{\sin C} = 2R$$

$$\text{Law of cosines: } c^2 = a^2 + b^2 - 2ab \cos C \quad (\text{and cyclic})$$

$$\text{Area: } \Delta = \frac{1}{2} ab \sin C = \frac{1}{2} bc \sin A = \frac{1}{2} ca \sin B$$

$$(x', y') = (x \cos \theta - y \sin \theta, x \sin \theta + y \cos \theta)$$

$$e^{ix} = \cos x + i \sin x, \quad \cos x = \frac{e^{ix} + e^{-ix}}{2}, \quad \sin x = \frac{e^{ix} - e^{-ix}}{2i}$$

$$\pi \text{ rad} = 180^\circ, \quad 1^\circ = \frac{\pi}{180} \text{ rad}$$

11.4 Catalan Numbers

Recursive definition:

$$C_0 = C_1 = 1$$

$$C_n = \sum_{k=0}^{n-1} C_k C_{n-1-k}, \quad n \geq 2$$

Closed form:

$$C_n = \frac{1}{n+1} \binom{2n}{n}$$

Combinatorial equivalent:

$$C_n = \binom{2n}{n} - \binom{2n}{n-1} = \frac{1}{n+1} \binom{2n}{n}, \quad n \geq 0$$

Combinatorial meaning:

Number of ways to: (i) arrange n balanced parenthesis pairs; (ii) full binary trees with $n+1$ leaves; (iii) Dyck paths of length $2n$ that never cross the diagonal.

Generalized form (k):

$$C_n^{(k)} = \frac{k+1}{n+k+1} \binom{2n+k}{n}$$

Extended recurrence:

$$C_n^{(k)} = \sum_{a_1+\dots+a_k=n} C_{a_1} C_{a_2} \dots C_{a_k}, \quad C_0 = 1$$

Efficient recurrence (for computation):

$$C_n = \frac{2(2n-1)}{n+1} C_{n-1}, \quad n \geq 1$$

Generating function:

$$C(x) = \sum_{n=0}^{\infty} C_n x^n = \frac{1 - \sqrt{1-4x}}{2x}$$

Asymptotic behavior:

$$C_n \sim \frac{4^n}{n^{3/2} \sqrt{\pi}}$$

Examples:

$$C_0 = 1, \quad C_1 = 1, \quad C_2 = 2, \quad C_3 = 5, \quad C_4 = 14, \quad C_5 = 42$$

11.5 Geometry

Rectangle:

$$A = b h$$

Area with base b and height h .

Triangle:

$$A = \frac{1}{2} b h$$

$$A = \sqrt{s(s-a)(s-b)(s-c)}, \quad s = \frac{a+b+c}{2} \quad (\text{Heron})$$

Base-height or Heron using side lengths a, b, c .

Parallelogram & rhombus:

$$A_{\text{parallelogram}} = b h, \quad A_{\text{rhombus}} = \frac{D d}{2}$$

D, d are diagonals of a rhombus.

Trapezoid:

$$A = \frac{(B+b)}{2} h$$

B and b are the parallel sides (bases).

Regular n -gon:

$$A = \frac{1}{2} P a = \frac{n l a}{2}$$

P perimeter, l side, a apothem.

Circle:

$$A = \pi r^2, \quad C = 2\pi r$$

Circular sector (angle in radians):

$$A = \frac{1}{2} r^2 \theta, \quad \text{arc length } L = r \theta$$

Circular segment (height h):

$$A = r^2 \arccos\left(\frac{r-h}{r}\right) - (r-h) \sqrt{2rh - h^2}$$

Region cut by a chord; $0 < h < 2r$.

Annulus (circular crown):

$$A = \pi(R^2 - r^2)$$

Difference of two concentric disks ($R > r$).

Ellipse:

$$A = \pi a b$$

a, b are semi-axes.

Polygon by coordinates (shoelace):

$$A = \frac{1}{2} \left| \sum_{i=1}^n (x_i y_{i+1} - x_{i+1} y_i) \right|, \quad (x_{n+1}, y_{n+1}) = (x_1, y_1)$$

Works for any simple polygon in the plane.

Triangle by coordinates:

$$A = \frac{1}{2} |x_1(y_2 - y_3) + x_2(y_3 - y_1) + x_3(y_1 - y_2)|$$

Triangle from sides and circumradius/inradius:

$$A = \frac{abc}{4R}, \quad A = r s$$

R circumradius, r inradius, s semiperimeter.

Lune (difference of two circular sectors):

$$A_{\text{lune}} = \frac{1}{2} r_1^2 \theta_1 - \frac{1}{2} r_2^2 \theta_2$$

Two sectors overlapping with angles θ_1, θ_2 matching the same chord.

Lens (two equal circles radius r , center distance d):

$$A = 2r^2 \arccos\left(\frac{d}{2r}\right) - \frac{d}{2} \sqrt{4r^2 - d^2}, \quad 0 < d < 2r$$

Intersection of two equal disks.

Spherical cap (radius R , height h):

$$A_{\text{cap}} = 2\pi R h$$

Surface area of the cap on a sphere. (Volume: $V = \frac{\pi h^2}{3}(3R - h)$)

11.6 Useful math

Arithmetic series:

$$\sum_{k=1}^n k = \frac{n(n+1)}{2}$$

Squares & cubes:

$$\sum_{k=1}^n k^2 = \frac{n(n+1)(2n+1)}{6}, \quad \sum_{k=1}^n k^3 = \left(\frac{n(n+1)}{2}\right)^2$$

Geometric series ($r \neq 1$):

$$\sum_{i=0}^{n-1} r^i = \frac{r^n - 1}{r - 1}$$

For mod prime p : multiply by $(r-1)^{-1} \equiv (r-1)^{p-2} \pmod{p}$.

Power sum of base a :

$$1 + a + \dots + a^n = \frac{a^{n+1} - 1}{a - 1} \quad (a \neq 1), \quad = n + 1 \quad (a = 1)$$

Harmonic numbers:

$$H_n = \sum_{k=1}^n \frac{1}{k} \approx \ln n + \gamma + \frac{1}{2n}$$

$\gamma \approx 0.57721$ (Euler–Mascheroni). Useful for estimates.

Basic mod rules:

$$(a \pm b) \pmod{m} = ((a \pmod{m}) \pm (b \pmod{m})) \pmod{m}$$

$$(a \cdot b) \pmod{m} = ((a \pmod{m}) \cdot (b \pmod{m})) \pmod{m}$$

Fermat little theorem (prime p):

$$a^{p-1} \equiv 1 \pmod{p} \quad \text{if } p \nmid a, \quad a^{-1} \equiv a^{p-2} \pmod{p}$$

Euler theorem:

$$a^{\varphi(m)} \equiv 1 \pmod{m} \quad \text{if } \gcd(a, m) = 1$$

Chinese remainder (pairwise coprime):

$$x \equiv a_i \pmod{m_i} \Rightarrow x \equiv \sum_i a_i M_i y_i \pmod{M}$$

$$M = \prod m_i, M_i = M/m_i, y_i \equiv M_i^{-1} \pmod{m_i}.$$

gcd/lcm relation:

$$\text{lcm}(a, b) = \frac{|ab|}{\text{gcd}(a, b)}$$

Binomial theorem:

$$(x + y)^n = \sum_{k=0}^n \binom{n}{k} x^{n-k} y^k$$

Stars and bars (non-neg.):

$$x_1 + \cdots + x_k = n, x_i \geq 0 \Rightarrow \# = \binom{n+k-1}{k-1}$$

Permutations & combinations:

$$P(n, k) = \frac{n!}{(n-k)!}, \quad \binom{n}{k} = \frac{n!}{k!(n-k)!}$$

Derangements (approx):

$$!n = \left\lfloor \frac{n!}{e} + \frac{1}{2} \right\rfloor, \quad !n = n! \sum_{i=0}^n \frac{(-1)^i}{i!}$$

Stirling approximation:

$$n! \approx \sqrt{2\pi n} \left(\frac{n}{e}\right)^n$$

Inclusion-Exclusion (finite):

$$\left| \bigcup_{i=1}^m A_i \right| = \sum_i |A_i| - \sum_{i < j} |A_i \cap A_j| + \cdots + (-1)^{m+1} |A_1 \cap \cdots \cap A_m|$$

Dot and cross (2D):

$$u \cdot v = u_x v_x + u_y v_y = |u||v| \cos \theta, \quad u \times v = u_x v_y - u_y v_x$$

$$|u \times v| = 2 \times \text{triangle area}(u, v). \text{ Orientation by sign of } u \times v.$$

Distance point to line AB:

$$\text{dist}(P, AB) = \frac{|(B-A) \times (P-A)|}{|B-A|}$$

Projection length on AB:

$$\text{proj}_{AB}(P) = \frac{(P-A) \cdot (B-A)}{|B-A|}$$

AM-GM (non-neg.):

$$\frac{x_1 + \cdots + x_n}{n} \geq (x_1 \cdots x_n)^{1/n}$$

Cauchy-Schwarz:

$$\left(\sum_i a_i b_i \right)^2 \leq \left(\sum_i a_i^2 \right) \left(\sum_i b_i^2 \right)$$

Log rules:

$$\log_a b = \frac{\ln b}{\ln a}, \quad \log(ab) = \log a + \log b$$

Fast exponent splits:

$$a^{x+y} = a^x a^y, \quad a^{2^k} = \underbrace{(a^2)^2 \cdots)^2}_{k \text{ times}}$$

Divisor count/sum (multiplicative):

$$n = \prod p_i^{e_i} \Rightarrow \tau(n) = \prod (e_i + 1), \quad \sigma(n) = \prod \frac{p_i^{e_i+1} - 1}{p_i - 1}$$

$$\tau(n) = \text{number of divisors}, \sigma(n) = \text{sum of divisors}.$$

Linearity of expectation:

$$\mathbb{E} \left[\sum_i X_i \right] = \sum_i \mathbb{E}[X_i] \quad (\text{no independence needed})$$

Binomial distribution:

$$X \sim \text{Bin}(n, p) \Rightarrow \mathbb{E}[X] = np, \text{Var}(X) = np(1-p)$$

11.7 Mobius

Mobius function mu:

$$\mu(1) = 1$$

$$\mu(n) = 0 \text{ if } \exists p^2 \mid n, \quad \mu(n) = (-1)^k \text{ if } n \text{ is square-free with } k \text{ distinct primes.}$$

Basic convolutions:

$$\sum_{d \mid n} \mu(d) = \begin{cases} 1, & n = 1, \\ 0, & n > 1, \end{cases} \quad (\mu * \mathbf{1})(n) = \varepsilon(n).$$

Mobius inversion (divisor-sum):

If

$$g(n) = \sum_{d \mid n} f(d),$$

then

$$f(n) = \sum_{d \mid n} \mu(d) g\left(\frac{n}{d}\right) = \sum_{d \mid n} \mu\left(\frac{n}{d}\right) g(d).$$

Inversion over multiples:

If

$$G(n) = \sum_{k \geq 1} f(kn),$$

then

$$f(n) = \sum_{k \geq 1} \mu(k) G(kn).$$

Euler totient via mu:

$$\varphi(n) = \sum_{d \mid n} \mu(d) \frac{n}{d}.$$

Counting coprimes up to x:

$$\#\{1 \leq m \leq x : \gcd(m, n) = 1\} = \sum_{d \mid n} \mu(d) \left\lfloor \frac{x}{d} \right\rfloor.$$

Square-free count up to x:

$$Q(x) = \#\{n \leq x : n \text{ square-free}\} = \sum_{k \leq \sqrt{x}} \mu(k) \left\lfloor \frac{x}{k^2} \right\rfloor.$$

GCD=1 k-tuples:

$$\#\{1 \leq x_1, \dots, x_k \leq n : \gcd(x_1, \dots, x_k) = 1\} = \sum_{d=1}^n \mu(d) \left\lfloor \frac{n}{d} \right\rfloor^k.$$

Dirichlet series:

$$\sum_{n=1}^{\infty} \frac{\mu(n)}{n^s} = \frac{1}{\zeta(s)}, \quad \Re(s) > 1.$$

Mertens function:

$$M(x) = \sum_{n \leq x} \mu(n).$$

11.8 Burnside

Necklaces under cyclic C_n (gcd form):

$$N_{\text{rot}} = \frac{1}{n} \sum_{k=0}^{n-1} m^{\gcd(n,k)}.$$

Equivalent divisor form (for C_n):

$$N_{\text{rot}} = \frac{1}{n} \sum_{d \mid n} \varphi(d) m^{n/d}.$$

Necklaces/bracelets under dihedral D_n (gcd form):

$$N = \begin{cases} \frac{1}{2n} \left(\sum_{k=0}^{n-1} m^{\gcd(n,k)} + n m^{(n+1)/2} \right), & n \text{ odd,} \\ \frac{1}{2n} \left(\sum_{k=0}^{n-1} m^{\gcd(n,k)} + \frac{n}{2} m^{n/2} + \frac{n}{2} m^{n/2+1} \right), & n \text{ even.} \end{cases}$$

Here gcd is the greatest common divisor. A rotation by k positions has $\gcd(n, k)$ cycles.