

EU SAE Application Package v5.0.2

Download and first launch instructions

Release page: https://github.com/Noboyoshida227/EU_SAE_application_package/releases/tag/v5.0.2

Before You Start

- Install R 4.2.0 or later from <https://cran.r-project.org/>.
- The dashboard runs locally on your computer. Downloading and using the package does not upload survey data to GitHub.
- RStudio is optional. Windows users can launch with Start_Dashboard.bat; macOS/Linux users can use Start_Dashboard.sh.
- If you plan to use Stata .dta files, run install_packages.R once so the haven package is installed.

1. Download the v5.0.2 Package

Step	What to do	Notes
1	Open the v5.0.2 release page and expand Assets if needed.	The public release can be downloaded without signing in to GitHub.
2	Download Source code (zip), or the package zip asset if one is listed.	Use the v5.0.2 release rather than an older release.
3	Extract the zip file to a stable folder on your computer.	Do not run the dashboard from inside the compressed zip file.
4	Open the extracted package folder. Its name may include the release tag, such as EU_SAE_application_package-5.0.2.	The correct folder is the one containing app.R and Start_Dashboard.bat. You may rename the folder to EU_SAE_application_package if that is easier.

2. Prepare Data Files

In v5.0.2, users can choose input files from any folder on their computer using the dashboard Browse buttons. The files no longer have to be placed in EU_SAE_application_package/data/.

- Household survey and auxiliary covariate files: .rds, .RData/.rda, .csv, .tsv, .txt, .dta, .xlsx, or .xls.
- Geometry files: .rds, .RData/.rda, ESRI shapefile .zip, .gpkg, .geojson, .json, .kml, or .gml.
- For ESRI shapefiles, upload one .zip containing valid, non-empty shapefile components, especially .shp, .shx, and .dbf. The .dbf usually stores the domain ID used to join estimates to map polygons; a standalone .shp file is not sufficient. Include .prj when available.
- Optional benchmark target and domain population files are selected only when those options are needed.

3. Launch the Dashboard

System	How to launch
Windows	Double-click Start_Dashboard.bat in the extracted package folder.
macOS/Linux	Open a terminal in the extracted package folder and run bash Start_Dashboard.sh.
Any system with R	From the extracted package folder, run shiny::runApp('app.R') in R if you prefer to start manually.

The first launch may take several minutes while required R packages are checked or installed. Keep the terminal or launcher window open. The browser usually opens <http://127.0.0.1:7777> or the next available port.

4. First Run in the Dashboard

- Use the Data inputs Browse buttons to choose the survey, auxiliary, and geometry files.
- For ESRI shapefiles, choose a .zip that contains valid, non-empty .shp, .shx, and .dbf files. Do not browse only the .shp file.
- Use the searchable variable-mapping dropdowns, or type variable names directly. Invalid typed names are highlighted in red.
- If benchmarking is required, click Apply benchmarking. You can upload an external Benchmark Target Database, clear a selected benchmark file, and choose a benchmark-level column for grouped benchmarking.
- If benchmarking is not selected, benchmark columns are not exported in user-facing Excel files.
- Click Check Data Readiness before running the analysis. Diagnostics focus on the selected analysis years and flag invalid or duplicated auxiliary domain/year keys and geometry read or mapping problems as blocking errors.
- After a successful run, current outputs are written to outputs/ and archived under app_runs/[run timestamp]_[run label]/outputs.

v5.0.2 can save and reload dashboard setup choices. After the first successful setup, use Save Current Setup and then Load Last Setup in later sessions so only changed items need to be updated.

Quick Troubleshooting

- If data are not found, browse to the correct files again; files can be outside the package folder.
- If Stata .dta files do not load, run install_packages.R to install haven.
- If geometry readiness reports an error or maps do not render, confirm the geometry domain ID matches the mapped shapefile/geometries domain column. For ESRI shapefiles, also confirm the .zip contains valid, non-empty .shp, .shx, and .dbf files.
- If Check Data Readiness reports missing or duplicated auxiliary domain/year columns, review the auxiliary domain field and year mapping, then re-run the readiness check.
- If using OneDrive, make sure the package folder and data files are available offline before launching.
- If R package installation fails, rerun install_packages.R or confirm R 4.2.0 or later is installed.