

EU SAE Application Package v3.0

Download and first launch instructions

Release page: https://github.com/Noboyoshida227/EU_SAE_application_package/releases/tag/V3

Before You Start

- Install R 4.2.0 or later from <https://cran.r-project.org/>.
- The dashboard runs locally on your computer. Downloading and using the package does not upload your survey data to GitHub.
- RStudio is optional. The package includes launch scripts for Windows, macOS, and Linux.

1. Download the v3 Package

Step	What to do	Notes
1	Open the v3 release page and expand Assets if it is collapsed.	The public release can be downloaded without signing in to GitHub.
2	Download Source code (zip) , or the package zip asset if one is listed.	Use the v3 release rather than an older preliminary release.
3	Extract the zip file to a stable folder on your computer.	Do not run the dashboard from inside the compressed zip file.
4	Open the extracted EU_SAE_application_package folder.	Keep the folder structure unchanged after extraction.

2. Put Your Data in the Package data/ Folder

For v3, users should place their input datasets in the package subfolder named **data/**:

- **household survey data** as an .rds file
- **auxiliary covariates** as an .rds file
- **shapefiles/geometries** as an .rds file, usually an sf object

The files can have any names. It is also fine if the data/ folder contains more than these three files, including sample files from the package. Users do not need to delete the sample datasets. In the dashboard, use the Browse buttons to select the three files needed for the run.

Optional files, such as a Benchmark Target Database or domain population sizes, can also be selected from the dashboard when those options are needed.

3. Launch the Dashboard

System	How to launch
Windows	Double-click Start_Dashboard.bat in the package folder.
macOS/Linux	Open a terminal in the package folder and run bash Start_Dashboard.sh .
Any system with R	From the package folder, run shiny::runApp('app.R') in R if you prefer to start manually.

The first launch may take several minutes because required R packages are checked or installed. Keep the terminal or launcher window open. The launcher opens a local browser address, usually <http://127.0.0.1:7777> or the next available port.

4. First Run in the Dashboard

- Use the Data inputs Browse buttons to choose the survey, auxiliary, and shapefile/geometries .rds files from data/.
- Complete the variable mapping and other analysis settings.
- If benchmarking is required, click Apply benchmarking and then provide the Benchmark Target Database or benchmark level.
- Click Check Data Readiness before running the analysis.
- After a successful run, outputs are written to outputs/ and archived under app_runs/[run timestamp]/outputs.

v3 can save and reload dashboard setup choices. After the first successful setup, use Save Current Setup and then Load Last Setup in later sessions so only changed items need to be updated.

Quick Troubleshooting

- If the dashboard cannot find data, confirm that the .rds files are inside EU_SAE_application_package/data/ and that the package was fully extracted.
- If a file is larger than 5 MB, use v3 and select it from the data/ folder. v3 raises the upload limit for larger .rds inputs.
- If using OneDrive, make sure the package folder and data files are available offline before launching the dashboard.
- If R package installation fails, rerun install_packages.R or check that R 4.2.0 or later is installed.