```
/*WAP to implement DDA algorithm in Cpp*/
//Digital Differential Analyzer Algorithm
#include <iostream>//line(x1,y1,x2,y2)
#include <cmath>
#include <graphics.h>
using namespace std;
float x_1,x_2,y_1,y_2,m;
void line_plot_m_s() // |m| \le 1, x(n+1)=x(n)+1, y(n+1)=y(n)+m, small slope
{
  x_1++;
  y_1=y_1+m;
  putpixel(x_1,(int)(y_1),GREEN);
void line_plot_m_l()// |m| > 1, y(n+1)=y(n)+1, x(n+1) = x(n)+1/m, large slope
{
  y_1++;
  x 1=x 1+1/m;
  putpixel((int)(x_1),y_1,GREEN);
}
int main()
{
  int i;
  while(1)
  {
    cout<<"\n\n\t\t\t\t1366*768";
    cout<<"\n\n\t\t Enter line coordinates (x1,y1), (x2,y2) with in range (0,0)
to (1365,767)";
    cout<<"\n\n Enter (x1,y1)";
    cout<<"\n Enter x1: ";</pre>
    cin>>x 1;
    cout<<" Enter y1: ";
    cin>>y 1;
    cout<<"\n\n Enter (x2,y2)";
    cout<<"\n Enter x2: ";</pre>
    cin>>x 2;
    cout<<" Enter y2: ";
    cin>>y_2;
```

```
initwindow(1366,768);
for(i=0; i<=1365; i++) // creates white background
  line(0,i,1365,i);
//setcolor(GREEN);
//line(x_1+50,y_1+50,x_2+50,y_2+50);
m=(y_2-y_1)/(x_2-x_1);
putpixel(x_1,y_1,GREEN);
if (fabs(m)<=1)
  if (x_2<x_1)//swap
    x_1=x_1+x_2;
    x_2=x_1-x_2;
    x_1=x_1-x_2;
    y_1=y_1+y_2;
    y_2=y_1-y_2;
   y_1=y_1-y_2;
  while(x_1< x_2)//small slope |m|<=1
    line_plot_m_s();
 }
}
else
  if (y_2<y_1)//swap
    x_1=x_1+x_2;
    x_2=x_1-x_2;
    x_1=x_1-x_2;
    y_1=y_1+y_2;
    y_2=y_1-y_2;
   y_1=y_1-y_2;
  while(y_1<y_2)//large slope |m|>1
```

```
{
        line_plot_m_l();
      }
    }
    getch();
    closegraph();
  }
  return 0;
}
Test lines (x1,y1,x2,y2,slope)
(50,60,1200,600,0.46)
(1200,600,50,60,0.46)
(50,600,1200,70,-0.46)
(1200,70,50,600,-0.46)
(50,60,600,700,1.16)
(600,700,50,60,1.16)
(70,600,400,60,-1.63)
(400,60,70,600,-1.63)
(50,50,70,70,1)
(70,70,50,50,1)
(70,30,50,50,-1)
(50,50,70,30,-1)
(80,70,900,70,0)
(900,70,80,70,0)
(80,70,80,700,1/0)
(80,700,80,70,-1/0)
*/
```