Adding Database Persistence with Spring Data JPA

CampusTaskboardApplication.java

src > main > java > edu > brooklyn > cisc3130 > taskboard > CampusTaskboardApplication.java > ...

```java
package edu.brooklyn.cisc3130.taskboard;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication
public class CampusTaskboardApplication {

    Run | Debug
    public static void main(String[] args) {
        SpringApplication.run(primarySource: CampusTaskboardApplication.class, args);
    }

}
```

PROBLEMS 2 OUTPUT DEBUG CONSOLE TERMINAL TEST RESULTS PORTS

```
noelmaderajr@Mac Adding Database Persistence with Spring Data JPA % ./mvnw spring-boot:run

  .   ____          _            __ _ _
 /\\ / ___'_ __ _ _(_)_ __  __ _ \ \ \ \
( ( )\___ | '_ | '_| | '_ \/ _` | \ \ \ \
 \\/  ___)| |_)| | | | | || (_| |  ) ) ) )
  '  |____| .__|_| |_|_| |_\__, | / / / /
 =========|_|==============|___/=/_/_/_/

 :: Spring Boot ::                (v4.0.5)

2026-04-07T03:47:26.138-04:00  INFO 5978 --- [  restartedMain] e.b.c.t.CampusTaskboardApplication       : Starting CampusTaskboardApplication using Java 25.0.1 with PID 5978 (/Users/noelmaderajr/Desktop/Adding Databa
se Persistence with Spring Data JPA/target/classes started by noelmaderajr in /Users/noelmaderajr/Desktop/Adding Database Persistence with Spring Data JPA)
2026-04-07T03:47:26.139-04:00  INFO 5978 --- [  restartedMain] e.b.c.t.CampusTaskboardApplication       : No active profile set, falling back to 1 default profile: "default"
2026-04-07T03:47:26.156-04:00  INFO 5978 --- [  restartedMain] .e.DevToolsPropertyDefaultsPostProcessor : Devtools property defaults active! Set 'spring.devtools.add-properties' to 'false' to disable
2026-04-07T03:47:26.156-04:00  INFO 5978 --- [  restartedMain] .e.DevToolsPropertyDefaultsPostProcessor : For additional web related logging consider setting the 'logging.level.web' property to 'DEBUG'
2026-04-07T03:47:26.319-04:00  INFO 5978 --- [  restartedMain] .s.d.r.c.RepositoryConfigurationDelegate : Bootstrapping Spring Data JPA repositories in DEFAULT mode.
2026-04-07T03:47:26.333-04:00  INFO 5978 --- [  restartedMain] .s.d.r.c.RepositoryConfigurationDelegate : Finished Spring Data repository scanning in 12 ms. Found 1 JPA repository interface.
2026-04-07T03:47:26.452-04:00  INFO 5978 --- [  restartedMain] o.s.boot.tomcat.TomcatWebServer          : Tomcat initialized with port 8080 (http)
2026-04-07T03:47:26.460-04:00  INFO 5978 --- [  restartedMain] o.apache.catalina.core.StandardService   : Starting service [Tomcat]
2026-04-07T03:47:26.460-04:00  INFO 5978 --- [  restartedMain] o.apache.catalina.core.StandardEngine    : Starting Servlet engine: [Apache Tomcat/11.0.20]
2026-04-07T03:47:26.471-04:00  INFO 5978 --- [  restartedMain] b.w.c.s.WebApplicationContextInitializer : Root WebApplicationContext: initialization completed in 314 ms
2026-04-07T03:47:26.517-04:00  INFO 5978 --- [  restartedMain] org.hibernate.orm.jpa                    : HHH008540: Processing PersistenceUnitInfo [name: default]
2026-04-07T03:47:26.529-04:00  INFO 5978 --- [  restartedMain] org.hibernate.orm.core                   : HHH000001: Hibernate ORM core version 7.2.7.Final
2026-04-07T03:47:26.645-04:00  INFO 5978 --- [  restartedMain] o.s.o.j.p.SpringPersistenceUnitInfo      : No LoadTimeWeaver setup: ignoring JPA class transformer
2026-04-07T03:47:26.653-04:00  INFO 5978 --- [  restartedMain] com.zaxxer.hikari.HikariDataSource       : HikariPool-1 - Starting...
2026-04-07T03:47:26.700-04:00  INFO 5978 --- [  restartedMain] com.zaxxer.hikari.pool.HikariPool        : HikariPool-1 - Added connection conn0: url=jdbc:h2:mem:taskboarddb user=SA
2026-04-07T03:47:26.700-04:00  INFO 5978 --- [  restartedMain] com.zaxxer.hikari.HikariDataSource       : HikariPool-1 - Start completed.
2026-04-07T03:47:26.706-04:00  WARN 5978 --- [  restartedMain] org.hibernate.orm.deprecation            : HHH90000025: H2Dialect does not need to be specified explicitly using 'hibernate.dialect' (remove the property
 setting and it will be selected by default)
2026-04-07T03:47:26.713-04:00  INFO 5978 --- [  restartedMain] org.hibernate.orm.connections.pooling    : HHH10001005: Database info:
        Database JDBC URL [jdbc:h2:mem:taskboarddb]
        Database driver: H2 JDBC Driver
        Database dialect: H2Dialect
        Database version: 2.4.240
        Default catalog/schema: TASKBOARDDB/PUBLIC
        Autocommit mode: undefined/unknown
        Isolation level: READ_COMMITTED [default READ_COMMITTED]
        JDBC fetch size: 100
        Pool: DataSourceConnectionProvider
        Minimum pool size: undefined/unknown
        Maximum pool size: undefined/unknown
2026-04-07T03:47:26.944-04:00  INFO 5978 --- [  restartedMain] org.hibernate.orm.core                   : HHH000489: No JTA platform available (set 'hibernate.transaction.jta.platform' to enable JTA platform integrat
ion)
Hibernate:
    create table tasks (
```

zsh

Run: Camp...

main* 0 2 Java: Ready Ln 14, Col 1 Tab Size: 4 UTF-8 LF { } Java

Adding Database Persistence with Spring Data JPA

CampusTaskboardApplication.java

src > main > java > edu > brooklyn > cisc3130 > taskboard > CampusTaskboardApplication.java > ...

```java
package edu.brooklyn.cisc3130.taskboard;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication
public class CampusTaskboardApplication {

    Run | Debug
    public static void main(String[] args) {
        SpringApplication.run(primarySource: CampusTaskboardApplication.class, args);
    }

}
```

PROBLEMS 2 OUTPUT DEBUG CONSOLE TERMINAL TEST RESULTS PORTS

```
noelmaderajr@Mac Adding Database Persistence with Spring Data JPA % ./mvnw spring-boot:run
        Maximum pool size: undefined/unknown
2026-04-07T03:47:26.944-04:00  INFO 5978 --- [  restartedMain] org.hibernate.orm.core                  : HHH000489: No JTA platform available (set 'hibernate.transaction.jta.platform' to enable JTA platform integrat
ion)
Hibernate:
    create table tasks (
        id integer generated by default as identity,
        completed boolean not null,
        created_at timestamp(6) not null,
        description varchar(500),
        priority enum ('HIGH','LOW','MEDIUM') not null,
        title varchar(100) not null,
        updated_at timestamp(6),
        primary key (id)
    )
2026-04-07T03:47:26.963-04:00  INFO 5978 --- [  restartedMain] j.LocalContainerEntityManagerFactoryBean : Initialized JPA EntityManagerFactory for persistence unit 'default'
2026-04-07T03:47:26.989-04:00  INFO 5978 --- [  restartedMain] o.s.d.j.r.query.QueryEnhancerFactories   : Hibernate is in classpath; If applicable, HQL parser will be used.
2026-04-07T03:47:27.187-04:00  WARN 5978 --- [  restartedMain] JpaBaseConfiguration$JpaWebConfiguration : spring.jpa.open-in-view is enabled by default. Therefore, database queries may be performed during view render
ing. Explicitly configure spring.jpa.open-in-view to disable this warning
2026-04-07T03:47:27.264-04:00  INFO 5978 --- [  restartedMain] o.s.b.h.a.H2ConsoleAutoConfiguration     : H2 console available at '/h2-console'. Database available at 'jdbc:h2:mem:taskboarddb'
2026-04-07T03:47:27.280-04:00  INFO 5978 --- [  restartedMain] o.s.boot.tomcat.TomcatWebServer          : Tomcat started on port 8080 (http) with context path '/'
2026-04-07T03:47:27.282-04:00  INFO 5978 --- [  restartedMain] e.b.c.t.CampusTaskboardApplication       : Started CampusTaskboardApplication in 1.241 seconds (process running for 1.363)
Hibernate:
    select
        count(*)
    from
        tasks t1_0
Hibernate:
    insert
    into
        tasks
        (completed, created_at, description, priority, title, updated_at, id)
    values
        (?, ?, ?, ?, ?, ?, default)
Hibernate:
    insert
    into
        tasks
        (completed, created_at, description, priority, title, updated_at, id)
    values
        (?, ?, ?, ?, ?, ?, default)
Hibernate:
    insert
    into
        tasks
        (completed, created_at, description, priority, title, updated_at, id)
```

zsh

Run: Camp...

main* 0 2 Java: Ready Ln 14, Col 1 Tab Size: 4 UTF-8 LF { } Java

Adding Database Persistence with Spring Data JPA

CampusTaskboardApplication.java

src > main > java > edu > brooklyn > cisc3130 > taskboard > CampusTaskboardApplication.java > ...

```java
package edu.brooklyn.cisc3130.taskboard;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication
public class CampusTaskboardApplication {

    Run | Debug
    public static void main(String[] args) {
        SpringApplication.run(primarySource: CampusTaskboardApplication.class, args);
    }

}
```

PROBLEMS 2 OUTPUT DEBUG CONSOLE TERMINAL TEST RESULTS PORTS

```
noelmaderajr@Mac Adding Database Persistence with Spring Data JPA % ./mvnw spring-boot:run
Hibernate:
    insert
    into
        tasks
        (completed, created_at, description, priority, title, updated_at, id)
    values
        (?, ?, ?, ?, ?, ?, default)
2026-04-07T03:48:45.590-04:00  INFO 5978 --- [nio-8080-exec-2] o.a.c.c.C.[Tomcat].[localhost].[/]       : Initializing Spring DispatcherServlet 'dispatcherServlet'
2026-04-07T03:48:45.590-04:00  INFO 5978 --- [nio-8080-exec-2] o.s.web.servlet.DispatcherServlet        : Initializing Servlet 'dispatcherServlet'
2026-04-07T03:48:45.591-04:00  INFO 5978 --- [nio-8080-exec-2] o.s.web.servlet.DispatcherServlet        : Completed initialization in 1 ms
Hibernate:
    insert
    into
        tasks
        (completed, created_at, description, priority, title, updated_at, id)
    values
        (?, ?, ?, ?, ?, ?, default)
Hibernate:
    select
        t1_0.id,
        t1_0.completed,
        t1_0.created_at,
        t1_0.description,
        t1_0.priority,
        t1_0.title,
        t1_0.updated_at
    from
        tasks t1_0
Hibernate:
    insert
    into
        tasks
        (completed, created_at, description, priority, title, updated_at, id)
    values
        (?, ?, ?, ?, ?, ?, default)
Hibernate:
    insert
    into
        tasks
        (completed, created_at, description, priority, title, updated_at, id)
    values
        (?, ?, ?, ?, ?, ?, default)
Hibernate:
    insert
    into
```

zsh

Run: Camp...

main* 0 2 Java: Ready Ln 14, Col 1 Tab Size: 4 UTF-8 LF { } Java

Adding Database Persistence with Spring Data JPA

CampusTaskboardApplication.java

src > main > java > edu > brooklyn > cisc3130 > taskboard > CampusTaskboardApplication.java > ...

```java
package edu.brooklyn.cisc3130.taskboard;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication
public class CampusTaskboardApplication {

    Run | Debug
    public static void main(String[] args) {
        SpringApplication.run(primarySource: CampusTaskboardApplication.class, args);
    }

}
```

PROBLEMS 2 OUTPUT DEBUG CONSOLE TERMINAL TEST RESULTS PORTS

```
noelmaderajr@Mac Adding Database Persistence with Spring Data JPA % ./mvnw spring-boot:run
    from
        tasks t1_0
Hibernate:
    insert
    into
        tasks
        (completed, created_at, description, priority, title, updated_at, id)
    values
        (?, ?, ?, ?, ?, ?, default)
Hibernate:
    insert
    into
        tasks
        (completed, created_at, description, priority, title, updated_at, id)
    values
        (?, ?, ?, ?, ?, ?, default)
Hibernate:
    insert
    into
        tasks
        (completed, created_at, description, priority, title, updated_at, id)
    values
        (?, ?, ?, ?, ?, ?, default)
Hibernate:
    insert
    into
        tasks
        (completed, created_at, description, priority, title, updated_at, id)
    values
        (?, ?, ?, ?, ?, ?, default)
Hibernate:
    insert
    into
        tasks
        (completed, created_at, description, priority, title, updated_at, id)
    values
        (?, ?, ?, ?, ?, ?, default)
Hibernate:
    insert
    into
        tasks
        (completed, created_at, description, priority, title, updated_at, id)
    values
        (?, ?, ?, ?, ?, ?, default)
Hibernate:
    insert
    into
        tasks
        (completed, created_at, description, priority, title, updated_at, id)
    values
        (?, ?, ?, ?, ?, ?, default)
```

zsh

Run: Camp...

main* 0 2 Java: Ready Ln 14, Col 1 Tab Size: 4 UTF-8 LF { } Java