

1. S1 Appendix. Mathematical framework and executable bridge

1.1. Minimal State-Space Formulation

For readers who prefer a compact technical summary, the present hypothesis can be expressed as a two-timescale state-space model:

$$A_{b(t)} = A_b^{f(x_{b(t)}, s(t), C(t))} A_b^{s(M_{b(t)})} \quad (1)$$

$$\dot{x}_b = A_{b(t)} F_{b(x, I, s)} \quad (2)$$

$$\dot{s}_i = G_{i(s, x, M)} \quad (3)$$

$$\dot{M}_b = \eta E_{b(t)} \sigma(\delta(t) - \theta_\delta) \left(1 - \frac{M_{b(t)}}{M_{\max}} \right) - \lambda_M M_{b(t)} + \sqrt{2T_{\text{eff}}} \xi_{b(t)} \quad (4)$$

$$R_{\mu(t)} = \sum_b a_{\mu b} A_{b(t)} x_{b(t)} \quad (5)$$

The interpretation is:

- x_b : fast dendritic integration state,
- s_i : local spine/synapse accessibility,
- A_b : effective branch accessibility,
- M_b : slow branch-level structural state,
- E_b : eligibility trace,
- $a_{\mu b}$: branch allocation for trace μ ,
- R_μ : support for retrieval of memory trace μ .

In this formulation, the hypothesis does not require that cytoskeletal variables store memory content directly. Instead, they modulate the accessibility structure over which memory traces are encoded and later retrieved. The quantity R_μ should be read as pre-threshold recall support; a later nonlinear readout or recurrent completion stage may convert support into full pattern completion.

1.2. Phenomenological interpretation of the write terms

Two terms in the slow update deserve explicit biological framing because they are phenomenological rather than molecule-specific. The delayed threshold θ_δ should be read as a coarse write-enable condition: only when modulatory, biochemical, or replay-linked consolidation signals exceed a local threshold does recent eligibility get converted into a durable branch update. This could correspond, in compressed form, to saturation-like requirements on calcium/CaMKII signaling, synaptic-capture conditions, or other delayed plasticity-permissive gates rather than to a single directly measured concentration [1], [2], [3], [4], [5].

The capacity term $M_{\max}$ plays a different role. It is not meant to imply a hard count of microtubules, spines, or proteins. Instead, it provides a bounded phenomenological surrogate for the fact that branch-local structural support is finite: transport resources, physical occupancy, local translation capacity, and active-matter-like nonequilibrium constraints all limit how much accessibility can be durably stabilized in one compartment before turnover and competition dominate [6], [7], [8], [9], [10], [11]. In other words, $M_{\max}$ is a reviewer-facing way to keep the model from smuggling in unlimited structural write capacity.

1.3. Factorized Accessibility View

The central formal move in the paper is the factorization

$$A_{b(t)} = A_b^{f(t)} A_b^{s(t)} \quad (6)$$

where A_b^f summarizes faster dendritic, contextual, or circuit-level opening, and A_b^s summarizes slower structural accessibility. This is the cleanest mathematical way to state the paper's USP: memory participation depends on a slow structural gating bias beneath faster dendritic and circuit gating.

1.4. Resource-Capture Extension

If one wishes to model local translation or branch-specific stabilization resources explicitly, introduce

$$\tau_P \dot{P}_b = -P_b + \rho_\nu \nu(t) + \rho_{\text{sleep}} \Omega(t) r_{b(t)} \quad (7)$$

where P_b denotes a branch-local capture or consolidation resource, $\nu(t)$ denotes a global neuro-modulatory or salience-related drive, $\Omega(t)$ denotes consolidation-window intensity (for example spindle- or replay-rich sleep opportunity), and $r_{b(t)}$ denotes branch-local replay or reactivation recruitment.

and replace the slow update with

$$\dot{M}_b = \eta E_{b(t)} P_{b(t)} \sigma(\delta(t) - \theta_\delta) \left(1 - \frac{M_{b(t)}}{M_{\max}} \right) - \lambda_M M_{b(t)} + \sqrt{2T_{\text{eff}}} \xi_{b(t)} \quad (8)$$

Here P_b is not itself the access state. Rather, it is a local capture or consolidation resource that helps determine whether tagged branches become durably rewritten.

1.5. Correspondence between general and executable forms

The main text uses the executable simulator form, where replay-linked consolidation support is represented explicitly as $P_{b(t)} W(t)$:

$$\dot{M}_b = \eta E_{b(t)} P_{b(t)} W(t) (M_{\max} - M_b) - \lambda_M M_b + \varepsilon_{b(t)} \quad (9)$$

This collapses the more general $\sigma(\delta(t) - \theta_\delta)$ write-permission gate into a binary consolidation window $W(t)$, and makes the resource-capture variable P_b an explicit, traceable column in the simulator export. The general state-space form (Eq. S1.1) and the resource-capture extension (Eq. S1.8) both reduce to this executable form when $\sigma(\delta - \theta_\delta) \approx W(t)$ and $\Omega(t) r_{b(t)}$ approximates the replay drive used in the main-text experiments. Reviewers comparing the main text equations with S1 should treat Eq. S1.8 as the bridge between the biological state-space notation and the implemented simulator.

1.6. Branch Allocation And Memory Linking

An explicit branch-allocation view treats a trace as depending on a subset of branches:

$$a_{\mu b} \in [0, 1] \quad (10)$$

with recall

$$R_{\mu(t)} = \sum_b a_{\mu b} A_{b(t)} x_{b(t)} \quad (11)$$

and a simple linking metric

$$L_{\mu\nu} = \sum_b a_{\mu b} a_{\nu b} M_{b(t)} \quad (12)$$

Under this view, memories formed close in time should become more linked when they reuse overlapping branches that remain in high structural accessibility states.

1.7. Accessibility Matrix View

It is sometimes useful to summarize slow structural constraints by an effective accessibility matrix $A(M)$:

$$A_{ij}(M) \quad (13)$$

where diagonal terms capture branch-local accessibility and off-diagonal terms summarize effective couplings induced by shared dendritic resources, correlated allocation history, or common transport constraints. This should be interpreted as an effective summary object, not as a claim that distinct branches are connected by literal microtubule wires.

1.8. Optional Attractor-Energy View

For readers who prefer an associative-memory formulation, define

$$W_{\text{eff}(t)} = D_{A(t)} W D_{A(t)} \quad (14)$$

where $D_{A(t)}$ is the diagonal matrix whose entries are the branch accessibility values.

and the energy-like quantity

$$E_{\text{attr}(x,t)} = -\frac{1}{2} x^T W_{\text{eff}(t)} x + \sum_b U_{b(x_b)} \quad (15)$$

This makes explicit that synaptic couplings provide a baseline landscape, while slow structural accessibility deforms which basins are easiest to enter or stabilize. We treat this as optional because it abstracts away from much of the biology emphasized in the main text [12], [13], [14].

1.9. Executable Bridge And Claim Classes

The executable section of the present unified manuscript helps sharpen the epistemic status of several claims made in the biological theory. In particular, it distinguishes three classes of consequence that are easy to blur in prose alone.

First, some consequences are largely architectural. In the executable model, context-sensitive disambiguation can already arise from the fast contextual layer, and linking is more fragile than single-trace recall under focal overlap damage partly because the linking metric weights shared branches multiplicatively. These are still meaningful results, but they should be read as consequences of the formal architecture rather than as uniquely diagnostic evidence for slow structural rewriting.

Second, some consequences become mechanistically diagnostic only after executable perturbation. Comparator baselines showed that overlap-branch strengthening, linking growth after consolidation, and selective rescue of association disappear when replay-specific slow structural writing is removed. These signatures therefore track the slow structural layer more specifically than context sensitivity or overlap geometry alone.

Third, the broader overlap-motif analysis showed that the theory is not confined to a single hand-built two-trace example. Linking scaled with structured overlap across weak, chain, strong, and hub motifs, while weak overlap marked a boundary condition below which a shared branch does not automatically become a structural hub. This is useful for the present theory

because it suggests that the prediction is gradated: shared structural allocation should matter in proportion to how strongly replay and allocation repeatedly recruit the same dendritic subunits.

The executable bridge also clarifies one formal point. In the biological formalization, recall support is written schematically as $R_{\mu(t)} = \sum_b a_{\mu b} A_{b(t)} x_{b(t)}$ to make the role of accessibility explicit. In the simulator, the same accessibility factor is absorbed earlier into branch activity, so recall support is computed from access-gated x_b rather than by multiplying accessibility twice at readout. The conceptual role is the same: slow structural accessibility still biases which branches can participate in recall. The difference is implementation order, not theoretical meaning.

Theory variable	Executable surrogate	Same role or simplification
A_b^f, A_b^s, A_b	<code>fast_access</code> , <code>slow_access</code> , <code>effective_access</code>	same factorized access roles
M_b	<code>branch.structural.accessibility</code>	same slow structural accessibility variable
E_b	<code>branch.eligibility.value</code>	same eligibility / local-tag role
P_b or local capture state	<code>branch.translation_readiness.value</code>	same consolidation-support role in compressed form
$R_\mu = \sum_b a_{\mu b} A_b x_b$	<code>R_mu = sum_b a_(mu b) x_b</code> with access-gated <code>x_b</code>	same conceptual role; accessibility applied earlier rather than twice at readout

Table S1.1: Theory-to-executable mapping for recall-support and access variables.

Bibliography

- [1] S. Yagishita and et al., “A critical time window for dopamine actions on dendritic spines,” *Science*, vol. 345, no. 6202, pp. 1616–1620, 2014, doi: [10.1126/science.1255514](https://doi.org/10.1126/science.1255514).
- [2] R. L. Redondo and R. G. M. Morris, “Making memories last: the synaptic tagging and capture hypothesis,” *Nature Reviews Neuroscience*, vol. 12, no. 1, pp. 17–30, 2011, doi: [10.1038/nrn2963](https://doi.org/10.1038/nrn2963).
- [3] W. Gerstner, M. Lehmann, V. Liakoni, D. Corneil, and J. Brea, “Eligibility traces and plasticity on behavioral time scales: experimental support of neoHebbian three-factor learning rules,” *Frontiers in Neural Circuits*, vol. 12, p. 53, 2018, doi: [10.3389/fncir.2018.00053](https://doi.org/10.3389/fncir.2018.00053).
- [4] T. Rogerson *et al.*, “Synaptic tagging during memory allocation,” *Nature Reviews Neuroscience*, vol. 15, no. 3, pp. 157–169, 2014, doi: [10.1038/nrn3667](https://doi.org/10.1038/nrn3667).
- [5] M. Z. B. Ibrahim, Z. Wang, and S. Sajikumar, “Synapses tagged, memories kept: synaptic tagging and capture hypothesis in brain health and disease,” *Philosophical Transactions of the Royal Society B: Biological Sciences*, 2024, doi: [10.1098/rstb.2023.0237](https://doi.org/10.1098/rstb.2023.0237).
- [6] É. Fodor, C. Nardini, M. E. Cates, J. Tailleur, P. Visco, and F. van Wijland, “How far from equilibrium is active matter?,” *Physical review letters*, vol. 117, no. 3, p. 38103, 2016.
- [7] D. Needleman and Z. Dogic, “Active matter at the interface between materials science and cell biology,” *Nature Reviews Materials*, vol. 2, no. 9, pp. 1–14, 2017.
- [8] A. Govindarajan, I. Israely, S.-Y. Huang, and S. Tonegawa, “The dendritic branch is the preferred integrative unit for protein synthesis-dependent LTP,” *Neuron*, vol. 69, no. 1, pp. 132–146, 2011, doi: [10.1016/j.neuron.2010.12.008](https://doi.org/10.1016/j.neuron.2010.12.008).

- [9] V. Rangaraju, M. Lauterbach, and E. M. Schuman, “Spatially Stable Mitochondrial Compartments Fuel Local Translation during Plasticity,” *Cell*, vol. 176, pp. 73–84, 2019, doi: [10.1016/j.cell.2018.12.013](https://doi.org/10.1016/j.cell.2018.12.013).
- [10] S. Das, P. J. Lituma, P. E. Castillo, and R. H. Singer, “Maintenance of a short-lived protein required for long-term memory involves cycles of transcription and local translation,” *Neuron*, vol. 111, no. 13, p. 2051–2064.e6, 2023, doi: [10.1016/j.neuron.2023.04.005](https://doi.org/10.1016/j.neuron.2023.04.005).
- [11] E. Hacisuleyman *et al.*, “Neuronal activity rapidly reprograms dendritic translation via eIF4G2:uORF binding,” *Nature Neuroscience*, vol. 27, no. 5, pp. 822–835, 2024, doi: [10.1038/s41593-024-01615-5](https://doi.org/10.1038/s41593-024-01615-5).
- [12] W. F. Podlaski, E. J. Agnes, and T. P. Vogels, “High Capacity and Dynamic Accessibility in Associative Memory Networks with Context-Dependent Neuronal and Synaptic Gating,” *Physical Review X*, vol. 15, no. 1, p. 11057, 2025, doi: [10.1103/PhysRevX.15.011057](https://doi.org/10.1103/PhysRevX.15.011057).
- [13] C. Koch, *Biophysics of Computation: Information Processing in Single Neurons*. Oxford University Press, 1999.
- [14] J. J. Knierim and J. P. Neunuebel, “Tracking the flow of hippocampal computation: Pattern separation, pattern completion, and attractor dynamics,” *Neurobiology of Learning and Memory*, vol. 129, pp. 38–49, 2016, doi: [10.1016/j.nlm.2015.10.008](https://doi.org/10.1016/j.nlm.2015.10.008).