




# **Determinism versus Nondeterminism**

- $TIME(t(n)) \subseteq NTIME(t(n))$
- is the inclusion proper?
- intuitively yes for time constructible  $t(n)$
- proof of  $TIME(n) \subsetneq NTIME(n)$ : Paul, Pippenger, Szemerédi and Trotter 1983
- based on: Reischuk and Paul 1978.





- $TIME(t(n)) \subseteq NTIME(t(n))$
- is the inclusion proper?
- intuitively yes for time constructible  $t(n)$
- proof of  $TIME(n) \subsetneq NTIME(n)$ : Paul, Pippenger, Szemeredi and Trotter 1983
- based on: Reischuk and Paul 1978.





# 1 Uniformly time bounded nondeterministic machines

reminder: nondeterministic Turing machines

- 

$$M = (Z, \Sigma, \delta, z_0, Z_A)$$

- set valued transition function

$$\delta : Z \times \Sigma \rightarrow 2^{Z \times \Sigma \times \{L, N, R\}}$$

- transition *relation*  $k \vdash k'$
- computations: *sequences*

$$(k_0, k_1, \dots, k_t) \quad \text{with} \quad k_i \vdash k_{i+1} \quad \text{for all } i$$

computation is *accepting* if

$$z_t \in Z_A$$

- $M$  *accepts*  $w$  if *there exists* an accepting computation of  $M$  started with  $w$ .
- accepted language

$$L_M = \{w : M \text{ accepts}\}$$

# 1 Uniformly time bounded nondeterministic machines

reminder: nondeterministic Turing machines

- 

$$M = (Z, \Sigma, \delta, z_0, Z_A)$$

- set valued transition function

$$\delta : Z \times \Sigma \rightarrow 2^{Z \times \Sigma \times \{L, N, R\}}$$

- transition *relation*  $k \vdash k'$

- computations: *sequences*

$$(k_0, k_1, \dots, k_t) \quad \text{with} \quad k_i \vdash k_{i+1} \quad \text{for all } i$$

computation is *accepting* if

$$z_t \in Z_A$$

- $M$  *accepts*  $w$  if *there exists* an accepting computation of  $M$  started with  $w$ .

- accepted language

$$L_M = \{w : M \text{ accepts}\}$$

**def: computation tree:**  $tree(M, w)$  of  $M$  started with  $w$

- root: start configuration  $z_0 w$

- let  $k$  be a node in the tree, then each successor configuration  $k'$  of  $k$ , i.e. satisfying  $k \vdash k'$  is a son of  $k$

- this are all nodes

# 1 Uniformly time bounded nondeterministic machines

## reminder: nondeterministic Turing machines

- 

$$M = (Z, \Sigma, \delta, z_0, Z_A)$$

- set valued transition function

$$\delta : Z \times \Sigma \rightarrow 2^{Z \times \Sigma \times \{L, N, R\}}$$

- transition *relation*  $k \vdash k'$

- computations: *sequences*

$$(k_0, k_1, \dots, k_t) \quad \text{with} \quad k_i \vdash k_{i+1} \quad \text{for all } i$$

computation is *accepting* if

$$z_t \in Z_A$$

- $M$  *accepts*  $w$  if *there exists* an accepting computation of  $M$  started with  $w$ .

- accepted language

$$L_M = \{w : M \text{ accepts}\}$$

**def: computation tree:**  $tree(M, w)$  of  $M$  started with  $w$

- root: start configuration  $z_0 w$

- let  $k$  be a node in the tree, then each successor configuration  $k'$  of  $k$ , i.e. satisfying  $k \vdash k'$  is a son of  $k$

- this are all nodes

## accepting nodes in the tree:

- a leaf is accepting if it's state is accepting
- an inner node  $k$  is accepting if *there exists* a son  $k'$  of  $k$  which is accepting.

**Lemma 1.**  $M$  *accepts*  $w$  iff the root of  $tree(M, w)$  is accepting



# 1 Uniformly time bounded nondeterministic machines

## reminder: nondeterministic Turing machines

- 

$$M = (Z, \Sigma, \delta, z_0, Z_A)$$

- set valued transition function

$$\delta : Z \times \Sigma \rightarrow 2^{Z \times \Sigma \times \{L, N, R\}}$$

- transition *relation*  $k \vdash k'$
- computations: *sequences*

$$(k_0, k_1, \dots, k_t) \quad \text{with} \quad k_i \vdash k_{i+1} \quad \text{for all } i$$

computation is *accepting* if

$$z_t \in Z_A$$

- $M$  *accepts*  $w$  if *there exists* an accepting computation of  $M$  started with  $w$ .
- accepted language

$$L_M = \{w : M \text{ accepts}\}$$

**def: computation tree:**  $tree(M, w)$  of  $M$  started with  $w$

- root: start configuration  $z_0 w$
- let  $k$  be a node in the tree, then each successor configuration  $k'$  of  $k$ , i.e. satisfying  $k \vdash k'$  is a son of  $k$
- this are all nodes

## accepting nodes in the tree:

- a leaf is accepting if its state is accepting
- an inner node  $k$  is accepting if *there exists* a son  $k'$  of  $k$  which is accepting.

**Lemma 1.**  $M$  *accepts*  $w$  iff the root of  $tree(M, w)$  is accepting

**def: uniformly time bounded machines** A nondeterministic Turing machine is *uniformly*  $t(n)$  time bounded, if *every* computation of the machine with an input of length  $n$  makes at most  $t(n)$  steps.

If  $M$  is uniformly  $t(n)$  time bounded if for every input  $w$  with length  $n$  its computation tree  $tree(M, w)$  has depth at most  $t(n)$ .



# 1 Uniformly time bounded nondeterministic machines

## reminder: nondeterministic Turing machines

- 

$$M = (Z, \Sigma, \delta, z_0, Z_A)$$

- set valued transition function

$$\delta : Z \times \Sigma \rightarrow 2^{Z \times \Sigma \times \{L, N, R\}}$$

- transition *relation*  $k \vdash k'$
- computations: *sequences*

$$(k_0, k_1, \dots, k_t) \quad \text{with} \quad k_i \vdash k_{i+1} \quad \text{for all } i$$

computation is *accepting* if

$$z_t \in Z_A$$

- $M$  *accepts*  $w$  if *there exists* an accepting computation of  $M$  started with  $w$ .
- accepted language

$$L_M = \{w : M \text{ accepts}\}$$

**def: computation tree:**  $tree(M, w)$  of  $M$  started with  $w$

- root: start configuration  $z_0 w$
- let  $k$  be a node in the tree, then each successor configuration  $k'$  of  $k$ , i.e. satisfying  $k \vdash k'$  is a son of  $k$
- this are all nodes

## accepting nodes in the tree:

- a leaf is accepting if its state is accepting
- an inner node  $k$  is accepting if *there exists* a son  $k'$  of  $k$  which is accepting.

**Lemma 1.**  $M$  accepts  $w$  iff the root of  $tree(M, w)$  is accepting

**def: uniformly time bounded machines** A nondeterministic Turing machine is *uniformly*  $t(n)$  time bounded, if *every* computation of the machine with an input of length  $n$  makes at most  $t(n)$  steps.

If  $M$  is uniformly  $t(n)$  time bounded if for every input  $w$  with length  $n$  its computation tree  $tree(M, w)$  has depth at most  $t(n)$ .

**Lemma 2.** For time constructible  $t(n)$  every  $t(n)$  time bounded nondeterministic Turing machine can be simulated by a uniformly  $t(n)$  time bounded Turing machine.

- with inputs of length  $n$  first compute  $t(n)$ . Then count steps on an extra tape.
- if the time bound is exceeded, stop and reject.



# 1 Uniformly time bounded nondeterministic machines

## reminder: nondeterministic Turing machines

- 

$$M = (Z, \Sigma, \delta, z_0, Z_A)$$

- set valued transition function

$$\delta : Z \times \Sigma \rightarrow 2^{Z \times \Sigma \times \{L, N, R\}}$$

- transition *relation*  $k \vdash k'$
- computations: *sequences*

$$(k_0, k_1, \dots, k_t) \quad \text{with} \quad k_i \vdash k_{i+1} \quad \text{for all } i$$

computation is *accepting* if

$$z_t \in Z_A$$

- $M$  *accepts*  $w$  if *there exists* an accepting computation of  $M$  started with  $w$ .
- accepted language

$$L_M = \{w : M \text{ accepts}\}$$

**def: computation tree:**  $tree(M, w)$  of  $M$  started with  $w$

- root: start configuration  $z_0 w$
- let  $k$  be a node in the tree, then each successor configuration  $k'$  of  $k$ , i.e. satisfying  $k \vdash k'$  is a son of  $k$
- this are all nodes

## accepting nodes in the tree:

- a leaf is accepting if its state is accepting
- an inner node  $k$  is accepting if *there exists* a son  $k'$  of  $k$  which is accepting.

**Lemma 1.**  $M$  accepts  $w$  iff the root of  $tree(M, w)$  is accepting

**def: uniformly time bounded machines** A nondeterministic Turing machine is *uniformly*  $t(n)$  time bounded, if *every* computation of the machine with an input of length  $n$  makes at most  $t(n)$  steps.

If  $M$  is uniformly  $t(n)$  time bounded if for every input  $w$  with length  $n$  its computation tree  $tree(M, w)$  has depth at most  $t(n)$ .

**Lemma 2.** For time constructible  $t(n)$  every  $t(n)$  time bounded nondeterministic Turing machine can be simulated by a uniformly  $t(n)$  time bounded Turing machine.

- with inputs of length  $n$  first compute  $t(n)$ . Then count steps on an extra tape.
- if the time bound is exceeded, stop and reject.

**Lemma 3.** For time constructible functions  $t(n)$  the class  $NTIME(t(n))$  is the set of languages accepted by uniformly  $O(t(n))$ -timebounded Turing machines.

## 2 Alternating Turing machines

def: alternating Turing machines

$$M = (E, U, \Sigma, \delta, z_0, Z_A)$$

- $E$  finite set of *existential states* (corresponding exactly to states of nondeterministic machines)
- $U$  finite set of *universal states* with  $U \cap E = \emptyset$ . The set of states is

$$Z = E \cup U$$

- $\Sigma, \delta, z_0, Z_A$  as for nondeterministic machines



## 2 Alternating Turing machines

**def: alternating Turing machines**

$$M = (E, U, \Sigma, \delta, z_0, Z_A)$$

- $E$  finite set of *existential states* (corresponding exactly to states of nondeterministic machines)
- $U$  finite set of *universal states* with  $U \cap E = \emptyset$ . The set of states is

$$Z = E \cup U$$

- $\Sigma, \delta, z_0, Z_A$  as for nondeterministic machines

**def: semantics of alternating machines**

- computation trees defined as for nondeterministic machines
- a leaf is accepting, when its state is accepting and rejecting otherwise.
- an inner node  $k$  with existential state is accepting if *there exists* a son  $k'$  of  $k$  which is accepting. Node  $k$  is rejecting otherwise
- an inner node  $k$  with universal state is accepting if *all* sons  $k'$  of  $k$  are accepting. Node  $k$  is rejecting otherwise

## 2 Alternating Turing machines

**def: alternating Turing machines**

$$M = (E, U, \Sigma, \delta, z_0, Z_A)$$

- $E$  finite set of *existential states* (corresponding exactly to states of nondeterministic machines)
- $U$  finite set of *universal states* with  $U \cap E = \emptyset$ . The set of states is

$$Z = E \cup U$$

- $\Sigma, \delta, z_0, Z_A$  as for nondeterministic machines

**def: semantics of alternating machines**

- computation trees defined as for nondeterministic machines
- a leaf is accepting, when its state is accepting and rejecting otherwise.
- an inner node  $k$  with existential state is accepting if *there exists* a son  $k'$  of  $k$  which is accepting. Node  $k$  is rejecting otherwise
- an inner node  $k$  with universal state is accepting if *all* sons  $k'$  of  $k$  are accepting. Node  $k$  is rejecting otherwise

**def: time bounded alternating machines:** this is defined as for uniformly time bounded nondeterministic machines.  $M$  is  $t(n)$  time bounded, if for all inputs  $w$  of length  $n$  the depth of the computation tree  $tree(M, w)$  is bounded by  $t(n)$ .



## 2 Alternating Turing machines

**def: alternating Turing machines**

$$M = (E, U, \Sigma, \delta, z_0, Z_A)$$

- $E$  finite set of *existential states* (corresponding exactly to states of nondeterministic machines)
- $U$  finite set of *universal states* with  $U \cap E = \emptyset$ . The set of states is

$$Z = E \cup U$$

- $\Sigma, \delta, z_0, Z_A$  as for nondeterministic machines

**def: semantics of alternating machines**

- computation trees defined as for nondeterministic machines

- a leaf is accepting, when its state is accepting and rejecting otherwise.
- an inner node  $k$  with existential state is accepting if *there exists* a son  $k'$  of  $k$  which is accepting. Node  $k$  is rejecting otherwise
- an inner node  $k$  with universal state is accepting if *all* sons  $k'$  of  $k$  are accepting. Node  $k$  is rejecting otherwise

**alternating complexity classes:**

$$ATIME(t(n)) = \{L : L \text{ accepted by an } O(t(n)) \text{ -- time bounded alternating TM}\}$$

Alternating polynomial time is defined as

$$AP = \bigcup_k ATIME(n^k)$$

**def: time bounded alternating machines:** this is defined as for uniformly time bounded nondeterministic machines.  $M$  is  $t(n)$  time bounded, if for all inputs  $w$  of length  $n$  the depth of the computation tree  $tree(M, w)$  is bounded by  $t(n)$ .



## 2 Alternating Turing machines

### def: alternating Turing machines

$$M = (E, U, \Sigma, \delta, z_0, Z_A)$$

- $E$  finite set of *existential states* (corresponding exactly to states of nondeterministic machines)
- $U$  finite set of *universal states* with  $U \cap E = \emptyset$ . The set of states is

$$Z = E \cup U$$

- $\Sigma, \delta, z_0, Z_A$  as for nondeterministic machines

### def: semantics of alternating machines

- computation trees defined as for nondeterministic machines
- a leaf is accepting, when its state is accepting and rejecting otherwise.
- an inner node  $k$  with existential state is accepting if *there exists* a son  $k'$  of  $k$  which is accepting. Node  $k$  is rejecting otherwise
- an inner node  $k$  with universal state is accepting if *all* sons  $k'$  of  $k$  are accepting. Node  $k$  is rejecting otherwise

**def: time bounded alternating machines:** this is defined as for uniformly time bounded nondeterministic machines.  $M$  is  $t(n)$  time bounded, if for all inputs  $w$  of length  $n$  the depth of the computation tree  $tree(M, w)$  is bounded by  $t(n)$ .

### alternating complexity classes:

$$ATIME(t(n)) = \{L : L \text{ accepted by an } O(t(n)) \text{ -- time bounded alternating TM}\}$$

Alternating polynomial time is defined as

$$AP = \bigcup_k ATIME(n^k)$$

**example 1 (Sipser):** A *tautology* is a Boolean expression  $A$  such that  $\varphi(A) = 1$  for all valuations  $\varphi$ .

**Lemma 4.**

$$\{A : A \text{ is a tautology}\} \in AP$$

- with input  $A$  universally (i.e. in universal states) guess assignment  $\varphi$
- for the guessed assignment evaluate  $\varphi(A)$
- accept if  $\varphi(A) = 1$ , otherwise reject.



## 2 Alternating Turing machines

**def: alternating Turing machines**

$$M = (E, U, \Sigma, \delta, z_0, Z_A)$$

- $E$  finite set of *existential states* (corresponding exactly to states of nondeterministic machines)
- $U$  finite set of *universal states* with  $U \cap E = \emptyset$ . The set of states is

$$Z = E \cup U$$

- $\Sigma, \delta, z_0, Z_A$  as for nondeterministic machines

**def: semantics of alternating machines**

- computation trees defined as for nondeterministic machines

- a leaf is accepting, when its state is accepting and rejecting otherwise.
- an inner node  $k$  with existential state is accepting if *there exists* a son  $k'$  of  $k$  which is accepting. Node  $k$  is rejecting otherwise
- an inner node  $k$  with universal state is accepting if *all* sons  $k'$  of  $k$  are accepting. Node  $k$  is rejecting otherwise

**def: time bounded alternating machines:** this is defined as for uniformly time bounded nondeterministic machines.  $M$  is  $t(n)$  time bounded, if for all inputs  $w$  of length  $n$  the depth of the computation tree  $tree(M, w)$  is bounded by  $t(n)$ .

alternating complexity classes:

$$ATIME(t(n)) = \{L : L \text{ accepted by an } O(t(n)) \text{ -- time bounded alternating TM}\}$$

Alternating polynomial time is defined as

$$AP = \bigcup_k ATIME(n^k)$$

**example 1 (Sipser):** A *tautology* is a Boolean expression  $A$  such that  $\varphi(A) = 1$  for all valuations  $\varphi$ .

**Lemma 4.**

$$\{A : A \text{ is a tautology}\} \in AP$$

- with input  $A$  universally (i.e. in universal states) guess assignment  $\varphi$
- for the guessed assignment evaluate  $\varphi(A)$
- accept if  $\varphi(A) = 1$ , otherwise reject.

**example 2 (Sipser):** Each Boolean Expression with  $n$  variables computes a Boolean function  $f_A : \mathbb{B}^n \rightarrow \mathbb{B}$ . A Boolean expression  $A$  is *minimal* if it is the shortest expression computing  $f_A$

**Lemma 5.**

$$\{A : A \text{ is minimal}\} \in AP$$

- with input  $A$  universally guess a shorter expression  $B$
- then existentially guess a valuation  $\varphi$  for  $A$  and  $B$
- evaluate both  $\varphi(A)$  and  $\varphi(B)$
- accept if  $\varphi(A) \neq \varphi(B)$ , otherwise reject.

### 3 Alternation bounded Turing Machines

**def: alternation bounded Turing machines** An alternating Turing machine  $M$  is  $x$ -alternation bounded if for all inputs  $w$  holds: on any path in the computation tree of  $M$  started with  $w$  existential and universal states change/alternate at most  $x$  times.

#### examples

- the machine accepting tautologies was 0-alternation bounded
- the machine accepting minimal expressions was 1-alternation bounded.



### 3 Alternation bounded Turing Machines

**def: alternation bounded Turing machines** An alternating Turing machine  $M$  is  $x$ -alternation bounded if for all inputs  $w$  holds: on any path in the computation tree of  $M$  started with  $w$  existential and universal states change/alternate at most  $x$  times.

#### examples

- the machine accepting tautologies was 0-alternation bounded
- the machine accepting minimal expressions was 1-alternation bounded.

#### complexity classes

$$ATIME_k^x(t(n)) = \{L : L \text{ accepted by an } i\text{-alternation bounded } k\text{-tape TM}\}$$

$$ATIME^x(t(n)) = \bigcup_k ATIME_k^x(t(n))$$

$$ATIME^{fin}(t(n)) = \bigcup ATIME^x(t(n))$$

The latter class contains the languages which can be accepted with finitely many alternations

#### tape reduction

**Lemma 6.** For time constructible  $t(n)$

$$ATIME^x(t(n)) \subseteq ATIME_2^{2x+1}(t(n))$$

### 3 Alternation bounded Turing Machines

**def: alternation bounded Turing machines** An alternating Turing machine  $M$  is  $x$ -alternation bounded if for all inputs  $w$  holds: on any path in the computation tree of  $M$  started with  $w$  existential and universal states change/alternate at most  $x$  times.

#### examples

- the machine accepting tautologies was 0-alternation bounded
- the machine accepting minimal expressions was 1-alternation bounded.

#### complexity classes

$$\begin{aligned} ATIME_k^x(t(n)) &= \{L : L \text{ accepted by an } i\text{-alternation bounded } k\text{-tape TM}\} \\ ATIME^x(t(n)) &= \bigcup_k ATIME_k^x(t(n)) \\ ATIME^{fin}(t(n)) &= \bigcup ATIME^x(t(n)) \end{aligned}$$

The latter class contains the languages which can be accepted with finitely many alternations

#### tape reduction

**Lemma 6.** For time constructible  $t(n)$

$$ATIME^x(t(n)) \subseteq ATIME_2^{2x+1}(t(n))$$

**def: step record of machine  $M$**  : for a  $k$ -tape machine  $M$  this is a pair

$$((z, a), (z', b, m)) \in (Z \times \Sigma^k) \times (Z \times \Sigma^k \times \{L, N, R\}^k)$$

satisfying

$$(z', b, m) \in \delta(z, a)$$

and records the step, when machine  $M$  reads in state  $z$  symbols  $a$  on the tapes and then i) goes to state  $z'$ , prints symbols  $b$  and makes head movements prescribed by  $m$ .

value of a stepping function from OS-Support in hardware lab

I took the concept from from complexity theory



### 3 Alternation bounded Turing Machines

#### complexity classes

$$ATIME_k^x(t(n)) = \{L : L \text{ accepted by an } i\text{-alternation bounded } k\text{-tape TM}\}$$

$$ATIME^x(t(n)) = \bigcup_k ATIME_k^x(t(n))$$

$$ATIME^{fin}(t(n)) = \bigcup ATIME^x(t(n))$$

The latter class contains the languages which can be accepted with finitely many alternations

#### tape reduction

**Lemma 6.** For time constructible  $t(n)$

$$ATIME^x(t(n)) \subseteq ATIME_2^{2x+1}(t(n))$$

**def: step record of machine  $M$**  : for a  $k$ -tape machine  $M$  this is a pair

$$((z, a), (z', b, m)) \in (Z \times \Sigma^k) \times (Z \times \Sigma^k \times \{L, N, R\}^k)$$

satisfying

$$(z', b, m) \in \delta(z, a)$$

and records the step, when machine  $M$  reads in state  $z$  symbols  $a$  on the tapes and then i) goes to state  $z'$ , prints symbols  $b$  and makes head movements prescribed by  $m$ .

simulating  $k$ -tape machines  $M$  with input  $w$ . Let  $|w| = n$

- for  $i = 0$  to  $c \cdot t(n)$  guess each entry  $s(i)$  of step sequence  $s[0 : c \cdot t(n)]$  in two steps:

1. existentially guess for components  $s(i).a$  of the step sequence, i.e the symbols read in step  $i$ . If  $M$  starts in a universal state this adds an extra level of alternation. Also initialize

$$s(0).z = z_0$$

to the start state of  $M$

2. set

$$s(i).z = s(i-1).z'$$

and guess

$$(s(i).z', s(i).b, s(i).m) \in \delta(s(i).z, s(i).a)$$

This guess is done existentially if  $s(i).z$  is existential and universally if  $s(i).z$  is universal. The number of alternations is at most doubled.



### 3 Alternation bounded Turing Machines

#### complexity classes

$$ATIME_k^x(t(n)) = \{L : L \text{ accepted by an } i\text{-alternation bounded } k\text{-tape TM}\}$$

$$ATIME^x(t(n)) = \bigcup_k ATIME_k^x(t(n))$$

$$ATIME^{fin}(t(n)) = \bigcup ATIME^x(t(n))$$

The latter class contains the languages which can be accepted with finitely many alternations

#### tape reduction

**Lemma 6.** For time constructible  $t(n)$

$$ATIME^x(t(n)) \subseteq ATIME_2^{2x+1}(t(n))$$

**def: step record of machine  $M$**  : for a  $k$ -tape machine  $M$  this is a pair

$$((z, a), (z', b, m)) \in (Z \times \Sigma^k) \times (Z \times \Sigma^k \times \{L, N, R\}^k)$$

satisfying

$$(z', b, m) \in \delta(z, a)$$

and records the step, when machine  $M$  reads in state  $z$  symbols  $a$  on the tapes and then i) goes to state  $z'$ , prints symbols  $b$  and makes head movements prescribed by  $m$ .

simulating  $k$ -tape machines  $M$  with input  $w$ . Let  $|w| = n$

- for  $i = 0$  to  $c \cdot t(n)$  guess each entry  $s(i)$  of step sequence  $s[0 : c \cdot t(n)]$  in two steps:

1. existentially guess for components  $s(i).a$  of the step sequence, i.e the symbols read in step  $i$ . If  $M$  starts in a universal state this adds an extra level of alternation. Also initialize

$$s(0).z = z_0$$

to the start state of  $M$

2. set

$$s(i).z = s(i-1).z'$$

and guess

$$(s(i).z', s(i).b, s(i).m) \in \delta(s(i).z, s(i).a)$$

This guess is done existentially if  $s(i).z$  is existential and universally if  $s(i).z$  is universal. The number of alternations is at most doubled.

- if the last guessed state is rejecting reject.
- if the last guessed state is accepting check the consistency of the symbols  $b$  written and the guess of symbols  $a$  for the  $k$  tapes of  $M$  sequentially (using 2 tapes for each check). To check tape  $j$ 
  1. Use the input (for  $j = 1$ ) and components  $s(i).b_j, s(i).m_j$  to simulate the actions of  $M$  on tape  $j$ . If in any step  $i$  machine  $M$  reads a symbol  $\neq a_i$ , i.e. differing from the guessed symbol, abort all consistency checks and reject.
  2. if no consistency check fails, accept.

you have seen this check in the exercises



### 3 Alternation bounded Turing Machines

#### complexity classes

$ATIME_k^x(t(n)) = \{L : L \text{ accepted by an } i\text{-alternation bounded } k\text{-tape TM}\}$

$$ATIME^x(t(n)) = \bigcup_k ATIME_k^x(t(n))$$

$$ATIME^{fin}(t(n)) = \bigcup ATIME^x(t(n))$$

The latter class contains the languages which can be accepted with finitely many alternations

#### tape reduction

**Lemma 6.** For time constructible  $t(n)$

$$ATIME^x(t(n)) \subseteq ATIME_2^{2x+1}(t(n))$$

**Lemma 8.** For time constructible  $t(n)$

$$L \in ATIME^x(t(n)) \rightarrow \bar{L} \in ATIME^x(t(n))$$

Given an acceptor  $M_u$  for  $L$  obtain an acceptor  $M_{\bar{u}}$  for  $\bar{L}$  by exchanging in  $M_u$

- accepting and rejecting states
- universal and existential states.

#### time hierarchy

**Lemma 9.** Let  $t(n)$  and  $T(n)$  be time constructible and  $t(n) = o(T(n))$ . Then

$$ATIME^x(t(n)) \subsetneq ATIME^{2x+2}(T(n))$$

### 3 Alternation bounded Turing Machines

#### complexity classes

$ATIME_k^x(t(n)) = \{L : L \text{ accepted by an } i\text{-alternation bounded } k\text{-tape TM}\}$

$$ATIME^x(t(n)) = \bigcup_k ATIME_k^x(t(n))$$

$$ATIME^{fin}(t(n)) = \bigcup ATIME^x(t(n))$$

The latter class contains the languages which can be accepted with finitely many alternations

#### tape reduction

**Lemma 6.** For time constructible  $t(n)$

$$ATIME^x(t(n)) \subseteq ATIME_2^{2x+1}(t(n))$$

#### closure under complement

**Lemma 8.** For time constructible  $t(n)$

$$L \in ATIME^x(t(n)) \rightarrow \bar{L} \in ATIME^x(t(n))$$

Given an acceptor  $M_u$  for  $L$  obtain an acceptor  $M_{\bar{u}}$  for  $\bar{L}$  by exchanging in  $M_u$

- accepting and rejecting states
- universal and existential states.

#### time hierarchy

**Lemma 9.** Let  $t(n)$  and  $T(n)$  be time constructible and  $t(n) = o(T(n))$ . Then

$$ATIME^x(t(n)) \subsetneq ATIME^{2x+2}(T(n))$$

- show

$$ATIME^x(t(n)) \subseteq ATIME_2^{2x+1}(t(n)) \subsetneq ATIME_3^{2x+2}(T(n))$$

- for the second (proper) inclusion proceed as in the time hierarchy theorem:
  1. use a universal 2 tape alternating machine  $M_u$
  2. with input  $u\#v$  simulate 2-tape machine  $M_{\bar{u}}$  for  $t(n)/|\bar{u}|$  steps.
  3. use an extra tape to count steps.



## 4 Assume $DTIME(n) = NTIME(n)$

**Collapsing the alternation bounded hierarchy  $ATIME^x(n)$**

**Lemma 10.** *Assume  $DTIME(n) = NTIME(n)$ . Then for all  $x$*

$$ATIME^x(n) = DTIME(n)$$

## 4 Assume $DTIME(n) = NTIME(n)$

**Collapsing the alternation bounded hierarchy**  $ATIME^x(n)$

**Lemma 10.** Assume  $DTIME(n) = NTIME(n)$ . Then for all  $x$

$$ATIME^x(n) = DTIME(n)$$

induction on  $x$ .

- $x = 0$ : Let

$$L \in ATIME^0(n)$$

accepted by machine  $M$ .

1. case: states of  $M$  existential:

$$L \in NTIME(n) = DTIME(n) \text{ by assumption}$$



## 4 Assume $DTIME(n) = NTIME(n)$

**Collapsing the alternation bounded hierarchy**  $ATIME^x(n)$

**Lemma 10.** Assume  $DTIME(n) = NTIME(n)$ . Then for all  $x$

$$ATIME^x(n) = DTIME(n)$$

induction on  $x$ .

- $x = 0$ : Let

$$L \in ATIME^0(n)$$

accepted by machine  $M$ .

1. case: states of  $M$  existential:

$$L \in NTIME(n) = DTIME(n) \quad \text{by assumption}$$

2. case: states of  $M$  universal. Then (proof of lemma 8)

$$\bar{L} \in NTIME(n) = DTIME(n)$$

$$\rightarrow L \in DTIME(n)$$

## 4 Assume $DTIME(n) = NTIME(n)$

**Collapsing the alternation bounded hierarchy**  $ATIME^x(n)$

**Lemma 10.** Assume  $DTIME(n) = NTIME(n)$ . Then for all  $x$

$$ATIME^x(n) = DTIME(n)$$

induction on  $x$ .

- $x = 0$ : Let

$$L \in ATIME^0(n)$$

accepted by machine  $M$ .

1. case: states of  $M$  existential:

$$L \in NTIME(n) = DTIME(n) \quad \text{by assumption}$$

2. case: states of  $M$  universal. Then (proof of lemma 8)

$$\bar{L} \in NTIME(n) = DTIME(n)$$

$$\rightarrow L \in DTIME(n)$$

- $x \rightarrow x + 1$ : Let  $M$  be  $(x + 1)$  alternation bounded and  $O(n)$  time bounded acceptor for  $L$ . Modify  $M$  started with input  $w$

1. run until first alternation and interrupt there:
2. partition tape 1 into  $2k$  tracks and store there state of  $M$ , head positions and inscriptions of all tapes
3. erase tapes except tape 1; move head to start of inscription
4. now run machine  $M'$ , which reconstructs the configuration where  $M$  interrupted and then behaves like  $M$  started from the saved state.



## 4 Assume $DTIME(n) = NTIME(n)$

**Collapsing the alternation bounded hierarchy**  $ATIME^x(n)$

**Lemma 10.** Assume  $DTIME(n) = NTIME(n)$ . Then for all  $x$

$$ATIME^x(n) = DTIME(n)$$

induction on  $x$ .

- $x = 0$ : Let

$$L \in ATIME^0(n)$$

accepted by machine  $M$ .

1. case: states of  $M$  existential:

$$L \in NTIME(n) = DTIME(n) \quad \text{by assumption}$$

2. case: states of  $M$  universal. Then (proof of lemma 8)

$$\bar{L} \in NTIME(n) = DTIME(n)$$

$$\rightarrow L \in DTIME(n)$$

- $x \rightarrow x + 1$ : Let  $M$  be  $(x + 1)$  alternation bounded and  $O(n)$  time bounded acceptor for  $L$ . Modify  $M$  started with input  $w$ 
  1. run until first alternation and interrupt there:
  2. partition tape 1 into  $2k$  tracks and store there state of  $M$ , head positions and inscriptions of all tapes
  3. erase tapes except tape 1; move head to start of inscription
  4. now run machine  $M'$ , which reconstructs the configuration where  $M$  interrupted and then behaves like  $M$  started from the saved state.
- machine  $M'$  is  $O(n)$  time bounded and  $x$ -alternation bounded. By induction hypothesis we can replace it by deterministic  $O(n)$ -time bounded machine  $M''$ .
- replace in the modified machine  $M'$  by  $M''$ . The resulting machine is 0-alternation bounded. Apply the base case of the lemma.



## 4 Assume $DTIME(n) = NTIME(n)$

**Collapsing the alternation bounded hierarchy  $ATIME^x(n)$**

**Lemma 10.** Assume  $DTIME(n) = NTIME(n)$ . Then for all  $x$

$$ATIME^x(n) = DTIME(n)$$

induction on  $x$ .

- $x = 0$ : Let

$$L \in ATIME^0(n)$$

accepted by machine  $M$ .

1. case: states of  $M$  existential:

$$L \in NTIME(n) = DTIME(n) \quad \text{by assumption}$$

2. case: states of  $M$  universal. Then (proof of lemma 8)

$$\bar{L} \in NTIME(n) = DTIME(n)$$

$$\rightarrow L \in DTIME(n)$$

- $x \rightarrow x + 1$ : Let  $M$  be  $(x + 1)$  alternation bounded and  $O(n)$  time bounded acceptor for  $L$ . Modify  $M$  started with input  $w$

1. run until first alternation and interrupt there:
2. partition tape 1 into  $2k$  tracks and store there state of  $M$ , head positions and inscriptions of all tapes
3. erase tapes except tape 1; move head to start of inscription
4. now run machine  $M'$ , which reconstructs the configuration where  $M$  interrupted and then behaves like  $M$  started from the saved state.

- machine  $M'$  is  $O(n)$  time bounded and  $x$ -alternation bounded. By induction hypothesis we can replace it by deterministic  $O(n)$ -time bounded machine  $M''$ .

- replace in the modified machine  $M'$  by  $M''$ . The resulting machine is 0-alternation bounded. Apply the base case of the lemma.

### padding

**Lemma 11.** Assume  $DTIME(n) = NTIME(n)$  and  $t(n)$  is time constructible. Then

$$ATIME^{fin}(t(n)) = DTIME(t(n))$$

*Proof.* Pad input  $w$  to  $w\#^{t(|w|)-|w|}$

□



## 5 Segregators of graphs

### 5.1 Definitions

removing a set of nodes  $S$  from a dag and its adjacent edges

- Let  $G = (V, E)$  be a DAG and  $S \subset V$
- define  $G - S = (V', E')$  by
  1.  $V' = V \setminus S$
  2.  $E' = E \cap (V' \times V')$

## 5 Segregators of graphs

### 5.1 Definitions

removing a set of nodes  $S$  from a dag and its adjacent edges

- Let  $G = (V, E)$  be a DAG and  $S \subset V$
- define  $G - S = (V', E')$  by
  1.  $V' = V \setminus S$
  2.  $E' = E \cap (V' \times V')$

**def: segregator** A subset  $S \subset V$  is an  $s(n)$ -segregator of dag  $G = (V, E)$  if with  $|V| = n$  holds

- $$|S| = O(s(n))$$
- every node in  $G - S$  has at most  $O(s(n))$  predecessors



## 5 Segregators of graphs

### 5.1 Definitions

**removing a set of nodes  $S$  from a dag** and its adjacent edges

- Let  $G = (V, E)$  be a DAG and  $S \subset V$
- define  $G - S = (V', E')$  by
  1.  $V' = V \setminus S$
  2.  $E' = E \cap (V' \times V')$

**def: segregator** A subset  $S \subset V$  is an  $s(n)$ -segregator of dag  $G = (V, E)$  if with  $|V| = n$  holds

- $$|S| = O(s(n))$$
- every node in  $G - S$  has at most  $O(s(n))$  predecessors

### 5.2 Block respecting Turing Machines

**goal: simplify structure of TM computation graphs.**

**def: block respecting** Let  $M$  be a deterministic  $t(n)$ -time bounded  $k$ -tape TM. On input with length  $n$  divide time into time intervals and tapes into blocks of length  $\lambda$ . Machine  $M$  is *block respecting* if heads cross block boundaries only as the last step of time intervals.

## 5 Segregators of graphs

### 5.1 Definitions

**removing a set of nodes  $S$  from a dag** and its adjacent edges

- Let  $G = (V, E)$  be a DAG and  $S \subset V$
- define  $G - S = (V', E')$  by
  1.  $V' = V \setminus S$
  2.  $E' = E \cap (V' \times V')$

**def: segregator** A subset  $S \subset V$  is an  $s(n)$ -segregator of dag  $G = (V, E)$  if with  $|V| = n$  holds

- $$|S| = O(s(n))$$
- every node in  $G - S$  has at most  $O(s(n))$  predecessors

### 5.2 Block respecting Turing Machines

**goal: simplify structure of TM computation graphs.**

**def: block respectig** Let  $M$  be a deterministic  $t(n)$ -time bounded  $k$ -tape TM. On input with length  $n$  divide time into time intervals and tapes into blocks of length  $\lambda$ . Machine  $M$  is *block respecting* if heads cross block boundaries only as the last step of time intervals.

**Lemma 12.** *Let  $t(n)$  and  $\lambda(n)$  be time constructible and let  $M$  be a  $t(n)$ -time bounded  $k$ -tape Turing machine. Then  $M$  can be simulated by a block respecting  $O(t(n))$ -time bounded  $(k + 1)$ -tape Turing machine.*



## 5 Segregators of graphs

### 5.1 Definitions

**removing a set of nodes  $S$  from a dag** and its adjacent edges

- Let  $G = (V, E)$  be a DAG and  $S \subset V$
- define  $G - S = (V', E')$  by
  1.  $V' = V \setminus S$
  2.  $E' = E \cap (V' \times V')$

**def: segregator** A subset  $S \subset V$  is an  $s(n)$ -segregator of dag  $G = (V, E)$  if with  $|V| = n$  holds

- $|S| = O(s(n))$
- every node in  $G - S$  has at most  $O(s(n))$  predecessors

### 5.2 Block respecting Turing Machines

**goal: simplify structure of TM computation graphs.**

**def: block respectig** Let  $M$  be a deterministic  $t(n)$ -time bounded  $k$ -tape TM. On input with length  $n$  divide time into time intervals and tapes into blocks of length  $\lambda$ . Machine  $M$  is *block respecting* if heads cross block boundaries only as the last step of time intervals.

**Lemma 12.** Let  $t(n)$  and  $\lambda(n)$  be time constructible and let  $M$  be a  $t(n)$ -time bounded  $k$ -tape Turing machine. Then  $M$  can be simulated by a block respecting  $O(t(n))$ -time bounded  $(k + 1)$ -tape Turing machine.

- extra tape (as usual) for counting up to  $\lambda$
- for each block  $b_2$  code on 3 tracks  $b_2$  together with its neighbors  $b_1$  and  $b_3$  as shown in figure 1




Figure 1: Folding 3 successive blocks on 3 tracks of 1 block. The outer blocks are written backwards on their tracks.



## 5 Segregators of graphs

### 5.1 Definitions

**removing a set of nodes  $S$  from a dag** and its adjacent edges

- Let  $G = (V, E)$  be a DAG and  $S \subset V$
- define  $G - S = (V', E')$  by
  1.  $V' = V \setminus S$
  2.  $E' = E \cap (V' \times V')$

**def: segregator** A subset  $S \subset V$  is an  $s(n)$ -segregator of dag  $G = (V, E)$  if with  $|V| = n$  holds

- $|S| = O(s(n))$
- every node in  $G - S$  has at most  $O(s(n))$  predecessors

### 5.2 Block respecting Turing Machines

**goal: simplify structure of TM computation graphs.**

**def: block respectig** Let  $M$  be a deterministic  $t(n)$ -time bounded  $k$ -tape TM. On input with length  $n$  divide time into time intervals and tapes into blocks of length  $\lambda$ . Machine  $M$  is *block respecting* if heads cross block boundaries only as the last step of time intervals.

**Lemma 12.** Let  $t(n)$  and  $\lambda(n)$  be time constructible and let  $M$  be a  $t(n)$ -time bounded  $k$ -tape Turing machine. Then  $M$  can be simulated by a block respecting  $O(t(n))$ -time bounded  $(k + 1)$ -tape Turing machine.

- extra tape (as usual) for counting up to  $\lambda$
- for each block  $b_2$  code on 3 tracks  $b_2$  together with its neighbors  $b_1$  and  $b_3$  as shown in figure 1




Figure 1: Folding 3 successive blocks on 3 tracks of 1 block. The outer blocks are written backwards on their tracks.

- for each time interval  $t$ 
  1. first simulate without crossing block boundaries
  2. then fix the coding of blocks in a block respecting way.



## 5.2 Block respecting Turing Machines

goal: simplify structure of TM computation graphs.

**def: block respectig** Let  $M$  be a deterministic  $t(n)$ -time bounded  $k$ -tape TM. On input with length  $n$  divide time into time intervals and tapes into blocks of length  $\lambda$ . Machine  $M$  is *block respecting* if heads cross block boundaries only as the last step of time intervals.

**Lemma 12.** Let  $t(n)$  and  $\lambda(n)$  be time constructible and let  $M$  be a  $t(n)$ -time bounded  $k$ -tape Turing machine. Then  $M$  can be simulated by a block respecting  $O(t(n))$ -time bounded  $(k + 1)$ -tape Turing machine.

## 5.3 The structure of computation graphs for block respecting machines

- for a single tape and edges between successive time intervals: illustrated in figure 2.
  1. spine with edges  $(t, t + 1)$  between successive intervals
  2. spine + left half and spine + right half are both planar
  3. in each half edges outside the spine have a bracket structure.
- for  $k$  tapes:  $2k$  such halves glued together at a common spine.




Figure 2: TM computation graph for 1 tape and the spine of a block respecting machine. Edges in each half do not cross

## 5.4 Segregator lemma and consequences

**def:**  $\log^*$

$$T(1) = 2$$

$$T(x) = 2^{T(x-1)}$$

$$T(x) = 2^{2^{\dots}} \quad x \text{ times}$$

$$\log^* n = \max\{x : T(x) \leq n\}$$

unbounded but *very* slowly growing function.



## 5.4 Segregator lemma and consequences

**def:**  $\log^*$

$$T(1) = 2$$

$$T(x) = 2^{T(x-1)}$$

$$T(x) = 2^{2^{\dots}} \quad x \text{ times}$$

$$\log^* n = \max\{x : T(x) \leq n\}$$

unbounded but *very* slowly growing function.

### Segregator lemma

**Lemma 13.** *Let  $G = (V, E)$  be a TM computation graph of a block respecting Turing machine and  $|V| = n$ . Then  $G$  has an  $O(n/\log^* n)$ -segregator*

Proof in section 6

## 5.4 Segregator lemma and consequences

**def:**  $\log^*$

$$T(1) = 2$$

$$T(x) = 2^{T(x-1)}$$

$$T(x) = 2^{2^{\dots}} \quad x \text{ times}$$

$$\log^* n = \max\{x : T(x) \leq n\}$$

unbounded but *very* slowly growing function.

### Segregator lemma

**Lemma 13.** *Let  $G = (V, E)$  be a TM computation graph of a block respecting Turing machine and  $|V| = n$ . Then  $G$  has an  $O(n/\log^* n)$ -segregator*

Proof in section 6

### fast simulation of deterministic machines with a bounded number of alternations

**Lemma 14.** *Let  $t(n)$  be time constructible. Then*

$$DTIME(t(n)) \subseteq ATIME^2(t(n)/\log^*(t(n)))$$



## 5.4 Segregator lemma and consequences

**def:**  $\log^*$

$$\begin{aligned}T(1) &= 2 \\T(x) &= 2^{T(x-1)} \\T(x) &= 2^{2^{\dots}} \quad x \text{ times} \\ \log^* n &= \max\{x : T(x) \leq n\}\end{aligned}$$

unbounded but *very* slowly growing function.

### Segregator lemma

**Lemma 13.** *Let  $G = (V, E)$  be a TM computation graph of a block respecting Turing machine and  $|V| = n$ . Then  $G$  has an  $O(n/\log^* n)$ -segregator*

Proof in section 6

### fast simulation of deterministic machines with a bounded number of alternations

**Lemma 14.** *Let  $t(n)$  be time constructible. Then*

$$DTIME(t(n)) \subseteq ATIME^2(t(n)/\log^*(t(n)))$$

Let  $M$  be a  $C \cdot t(n)$ -time bounded block respecting  $k$ -tape machine. With input of length  $n$  simulate as follows

- choose  $t = C \cdot t(n)$  and time interval length and block size

$$\lambda = t^{2/3}$$

- existentially guess head positions at end of time intervals
- compute the computation graph using block size  $\lambda$ . This graph has  $t^{1/3}$  nodes

## 5.4 Segregator lemma and consequences

**def:**  $\log^*$

$$\begin{aligned} T(1) &= 2 \\ T(x) &= 2^{T(x-1)} \\ T(x) &= 2^{2^{\dots}} \quad x \text{ times} \\ \log^* n &= \max\{x : T(x) \leq n\} \end{aligned}$$

unbounded but *very* slowly growing function.

### Segregator lemma

**Lemma 13.** *Let  $G = (V, E)$  be a TM computation graph of a block respecting Turing machine and  $|V| = n$ . Then  $G$  has an  $O(n/\log^* n)$ -segregator*

Proof in section 6

### fast simulation of deterministic machines with a bounded number of alternations

**Lemma 14.** *Let  $t(n)$  be time constructible. Then*

$$DTIME(t(n)) \subseteq ATIME^2(t(n)/\log^*(t(n)))$$

Let  $M$  be a  $C \cdot t(n)$ -time bounded block respecting  $k$ -tape machine. With input of length  $n$  simulate as follows

- choose  $t = C \cdot t(n)$  and time interval length and block size

$$\lambda = t^{2/3}$$

- existentially guess head positions at end of time intervals
- compute the computation graph using block size  $\lambda$ . This graph has  $t^{1/3}$  nodes
- existentially guess a segregator  $S$  of size

$$O(t^{1/3}/\log^*(t^{1/3})) = O(t^{1/3}/\log^* t)$$

- existentially guess results  $res(i)$  for all  $i \in S$ . This takes time

$$O(t^{2/3} \cdot |S|) = O(t/\log^* t)$$



## 5.4 Segregator lemma and consequences

def:  $\log^*$

$$\begin{aligned} T(1) &= 2 \\ T(x) &= 2^{T(x-1)} \\ T(x) &= 2^{2^{\dots}} \quad x \text{ times} \\ \log^* n &= \max\{x : T(x) \leq n\} \end{aligned}$$

unbounded but *very* slowly growing function.

### Segregator lemma

**Lemma 13.** *Let  $G = (V, E)$  be a TM computation graph of a block respecting Turing machine and  $|V| = n$ . Then  $G$  has an  $O(n/\log^* n)$ -segregator*

Proof in section 6

### fast simulation of deterministic machines with a bounded number of alternations

**Lemma 14.** *Let  $t(n)$  be time constructible. Then*

$$DTIME(t(n)) \subseteq ATIME^2(t(n)/\log^*(t(n)))$$

Let  $M$  be a  $C \cdot t(n)$ -time bounded block respecting  $k$ -tape machine. With input of length  $n$  simulate as follows

- choose  $t = C \cdot t(n)$  and time interval length and block size

$$\lambda = t^{2/3}$$

- existentially guess head positions at end of time intervals
- compute the computation graph using block size  $\lambda$ . This graph has  $t^{1/3}$  nodes

- existentially guess a segregator  $S$  of size

$$O(t^{1/3}/\log^*(t^{1/3})) = O(t^{1/3}/\log^* t)$$

- existentially guess results  $res(i)$  for all  $i \in S$ . This takes time

$$O(t^{2/3} \cdot |S|) = O(t/\log^* t)$$

- universally choose a node  $i \in S$ . Trace the set  $P$  of its predecessors in  $S$  or the input (if there are too many predecessors, reject because  $S$  is not a segregator) and compute  $res(i)$  from the  $res(j)$ ,  $j \in P$  and the input. If the result equals the guessed  $res(i)$  continue, otherwise reject. This takes time

$$O(t^{2/3} \cdot |P|) = O(t/\log^* t)$$

- accept iff the state at the end of the last time interval is accepting

## 5.4 Segregator lemma and consequences

**def:**  $\log^*$

$$\begin{aligned}T(1) &= 2 \\T(x) &= 2^{T(x-1)} \\T(x) &= 2^{2^{\dots}} \quad x \text{ times} \\ \log^* n &= \max\{x : T(x) \leq n\}\end{aligned}$$

unbounded but *very* slowly growing function.

### Segregator lemma

**Lemma 13.** *Let  $G = (V, E)$  be a TM computation graph of a block respecting Turing machine and  $|V| = n$ . Then  $G$  has an  $O(n/\log^* n)$ -segregator*

Proof in section 6

### fast simulation of deterministic machines with a bounded number of alternations

**Lemma 14.** *Let  $t(n)$  be time constructible. Then*

$$DTIME(t(n)) \subseteq ATIME^2(t(n)/\log^*(t(n)))$$

**proving  $DTIME(n) \neq NTIME(n)$ :** otherwise set  $T(n) = n \log^* n$

$$\begin{aligned}ATIME^{fin}(T(n)) &\subseteq DTIME(T(n)) \quad (\text{lemma 11}) \\ &\subseteq ATIME^2(n) \\ &\subsetneq ATIME_3^6(T(n)) \quad (\text{time hierarchy}) \\ &\subseteq ATIME^{fin}(T(n))\end{aligned}$$



**def:**  $\log^*$

## 6 Proof of the segregator lemma

$$T(1) = 2$$

$$T(x) = 2^{T(x-1)}$$

$$T(x) = 2^{2^{\dots}} \quad x \text{ times}$$

$$\log^* n = \max\{x : T(x) \leq n\}$$

**def:**  $\log^*$

## 6 Proof of the segregator lemma

$$T(1) = 2$$

$$T(x) = 2^{T(x-1)}$$

$$T(x) = 2^{2^{\dots}} \quad x \text{ times}$$

$$\log^* n = \max\{x : T(x) \leq n\}$$

### 6.1 Some very quickly growing sequences of numbers

Let

$$n \geq T(4) = 2^{16}$$

$$k = \lceil \frac{\log^* n}{3} \rceil$$

$$\geq 2$$

$$e_0 = 1$$

$$e_{\ell+1} = k^{2+2e_\ell}$$



**def:**  $\log^*$

## 6 Proof of the segregator lemma

$$T(1) = 2$$

$$T(x) = 2^{T(x-1)}$$

$$T(x) = 2^{2^{\dots}} \quad x \text{ times}$$

$$\log^* n = \max\{x : T(x) \leq n\}$$

### 6.1 Some very quickly growing sequences of numbers

Let

$$n \geq T(4) = 2^{16}$$

$$k = \lceil \frac{\log^* n}{3} \rceil$$

$$\geq 2$$

$$e_0 = 1$$

$$e_{\ell+1} = k^{2+2e_\ell}$$

**Lemma 15.**

$$e_\ell \leq T(k + 2\ell)$$

def:  $\log^*$

## 6 Proof of the segregator lemma

$$\begin{aligned}T(1) &= 2 \\T(x) &= 2^{T(x-1)} \\T(x) &= 2^{2^{\dots}} \quad x \text{ times} \\\log^* n &= \max\{x : T(x) \leq n\}\end{aligned}$$

- induction on  $\ell$
- $\ell = 0$ :
- $\ell \rightarrow \ell + 1$ :

$$e_0 = 1 < 2 = T(1) \leq T(k + 0)$$

### 6.1 Some very quickly growing sequences of numbers

Let

$$\begin{aligned}n &\geq T(4) = 2^{16} \\k &= \lceil \frac{\log^* n}{3} \rceil \\&\geq 2 \\e_0 &= 1 \\e_{\ell+1} &= k^{2+2e_\ell}\end{aligned}$$

$$\begin{aligned}e_{\ell+1} &\leq 2^{(\log k) \cdot (2+2T(k+2\ell))} \quad \text{IH} \\&\leq 2^{T(k+2\ell+1)} \\&= T(k + 2(\ell + 1))\end{aligned}$$

**Lemma 15.**

$$e_\ell \leq T(k + 2\ell)$$



**def:**  $\log^*$

## 6 Proof of the segregator lemma

$$T(1) = 2$$

$$T(x) = 2^{T(x-1)}$$

$$T(x) = 2^{2^{\dots}} \quad x \text{ times}$$

$$\log^* n = \max\{x : T(x) \leq n\}$$

$$\begin{aligned} e_{k-1} &\leq T(k + 2(k-1)) \text{ (lemma 15)} \\ &= T(3k-2) \\ &\leq T(3(\frac{\log^* n}{3} + 2/3) - 2) \\ &= T(\log^* n) \\ &\leq n \end{aligned}$$

### 6.1 Some very quickly growing sequences of numbers

Let

$$n \geq T(4) = 2^{16}$$

$$k = \lceil \frac{\log^* n}{3} \rceil$$

$$\geq 2$$

$$e_0 = 1$$

$$e_{\ell+1} = k^{2+2e_\ell}$$

**Lemma 15.**

$$e_\ell \leq T(k + 2\ell)$$

**Lemma 16.** *For sequence*

$$1 = e_0 < e_1 < \dots < e_{k-1}$$

*holds:*  $e_{k-1} \leq n$

**def:**  $\log^*$

## 6 Proof of the segregator lemma

$$\begin{aligned}T(1) &= 2 \\T(x) &= 2^{T(x-1)} \\T(x) &= 2^{2^{2^{\dots}}} \quad x \text{ times} \\ \log^* n &= \max\{x : T(x) \leq n\}\end{aligned}$$

Define for  $\ell \in [1 : k]$

$$\begin{aligned}d_0 &= 1 \\d_\ell &= 2^{\lceil \log(n/e_{k-\ell}) \rceil} \quad (\text{next power of two after } n/e_{k-\ell})\end{aligned}$$

$$n/(e_{k-\ell}) \leq d_\ell \leq 2n/e_{k-\ell}$$

$$e_{k-\ell} \leq 2n/d_\ell$$

### 6.1 Some very quickly growing sequences of numbers

Let

$$\begin{aligned}n &\geq T(4) = 2^{16} \\k &= \lceil \frac{\log^* n}{3} \rceil \\&\geq 2 \\e_0 &= 1 \\e_{\ell+1} &= k^{2+2e_\ell}\end{aligned}$$

**Lemma 15.**

$$e_\ell \leq T(k + 2\ell)$$

**Lemma 16.** *For sequence*

$$1 = e_0 < e_1 < \dots < e_{k-1}$$

*holds:*  $e_{k-1} \leq n$



**def:**  $\log^*$

## 6 Proof of the segregator lemma

$$\begin{aligned} T(1) &= 2 \\ T(x) &= 2^{T(x-1)} \\ T(x) &= 2^{2^{\dots}} \quad x \text{ times} \\ \log^* n &= \max\{x : T(x) \leq n\} \end{aligned}$$

### 6.1 Some very quickly growing sequences of numbers

Let

$$\begin{aligned} n &\geq T(4) = 2^{16} \\ k &= \lceil \frac{\log^* n}{3} \rceil \\ &\geq 2 \\ e_0 &= 1 \\ e_{\ell+1} &= k^{2+2e_\ell} \end{aligned}$$

**Lemma 15.**

$$e_\ell \leq T(k + 2\ell)$$

**Lemma 16.** *For sequence*

$$1 = e_0 < e_1 < \dots < e_{k-1}$$

*holds:*  $e_{k-1} \leq n$

Define for  $\ell \in [1 : k]$

$$\begin{aligned} d_0 &= 1 \\ d_\ell &= 2^{\lceil \log(n/e_{k-\ell}) \rceil} \quad (\text{next power of two after } n/e_{k-\ell}) \\ n/(e_{k-\ell}) &\leq d_\ell \leq 2n/e_{k-\ell} \\ n/d_\ell &\leq e_{k-\ell} \quad , \quad e_{k-\ell} \leq 2n/d_\ell \end{aligned}$$

**Lemma 17.**

$$d_0 = 1 \tag{1}$$

$$d_\ell \mid d_{\ell+1} \quad \text{for } 0 \leq \ell \leq k-1 \tag{2}$$

$$d_k \leq 2n \tag{3}$$

$$\lceil n/d_\ell \rceil \cdot d_\ell \leq 2n \quad \text{for } 0 \leq \ell \leq k-1 \tag{4}$$

$$k^{\lceil n/d_{\ell+1} \rceil} \leq \lceil n/d_\ell \rceil / k \quad \text{for } 0 \leq \ell \leq k-1 \tag{5}$$

**def:**  $\log^*$

## 6 Proof of the segregator lemma

$$\begin{aligned} T(1) &= 2 \\ T(x) &= 2^{T(x-1)} \\ T(x) &= 2^{2^{\dots}} \quad x \text{ times} \\ \log^* n &= \max\{x : T(x) \leq n\} \end{aligned}$$

### 6.1 Some very quickly growing sequences of numbers

Let

$$\begin{aligned} n &\geq T(4) = 2^{16} \\ k &= \lceil \frac{\log^* n}{3} \rceil \\ &\geq 2 \\ e_0 &= 1 \\ e_{\ell+1} &= k^{2+2e_\ell} \end{aligned}$$

**Lemma 15.**

$$e_\ell \leq T(k + 2\ell)$$

**Lemma 16.** *For sequence*

$$1 = e_0 < e_1 < \dots < e_{k-1}$$

*holds:*  $e_{k-1} \leq n$

Define for  $\ell \in [1 : k]$

$$\begin{aligned} d_0 &= 1 \\ d_\ell &= 2^{\lceil \log(n/e_{k-\ell}) \rceil} \quad (\text{next power of two after } n/e_{k-\ell}) \\ n/(e_{k-\ell}) &\leq d_\ell \leq 2n/e_{k-\ell} \\ n/d_\ell &\leq e_{k-\ell} \quad , \quad e_{k-\ell} \leq 2n/d_\ell \end{aligned}$$

**Lemma 17.**

$$d_0 = 1 \tag{1}$$

$$d_\ell \mid d_{\ell+1} \quad \text{for } 0 \leq \ell \leq k-1 \tag{2}$$

$$d_k \leq 2n \tag{3}$$

$$\lceil n/d_\ell \rceil \cdot d_\ell \leq 2n \quad \text{for } 0 \leq \ell \leq k-1 \tag{4}$$

$$k^{\lceil n/d_{\ell+1} \rceil} \leq \lceil n/d_\ell \rceil / k \quad \text{for } 0 \leq \ell \leq k-1 \tag{5}$$

- (1) to (3): obvious



def:  $\log^*$

## 6 Proof of the segregator lemma

$$\begin{aligned} T(1) &= 2 \\ T(x) &= 2^{T(x-1)} \\ T(x) &= 2^{2^{\dots}} \quad x \text{ times} \\ \log^* n &= \max\{x : T(x) \leq n\} \end{aligned}$$

### 6.1 Some very quickly growing sequences of numbers

Let

$$\begin{aligned} n &\geq T(4) = 2^{16} \\ k &= \lceil \frac{\log^* n}{3} \rceil \\ &\geq 2 \\ e_0 &= 1 \\ e_{\ell+1} &= k^{2+2e_\ell} \end{aligned}$$

**Lemma 15.**

$$e_\ell \leq T(k + 2\ell)$$

**Lemma 16.** For sequence

$$1 = e_0 < e_1 < \dots < e_{k-1}$$

holds:  $e_{k-1} \leq n$

Define for  $\ell \in [1 : k]$

$$\begin{aligned} d_0 &= 1 \\ d_\ell &= 2^{\lceil \log(n/e_{k-\ell}) \rceil} \quad (\text{next power of two after } n/e_{k-\ell}) \\ n/(e_{k-\ell}) &\leq d_\ell \leq 2n/e_{k-\ell} \\ n/d_\ell &\leq e_{k-\ell} \quad , \quad e_{k-\ell} \leq 2n/d_\ell \end{aligned}$$

**Lemma 17.**

$$d_0 = 1 \tag{1}$$

$$d_\ell \mid d_{\ell+1} \quad \text{for } 0 \leq \ell \leq k-1 \tag{2}$$

$$d_k \leq 2n \tag{3}$$

$$\lceil n/d_\ell \rceil \cdot d_\ell \leq 2n \quad \text{for } 0 \leq \ell \leq k-1 \tag{4}$$

$$k^{\lceil n/d_{\ell+1} \rceil} \leq \lceil n/d_\ell \rceil / k \quad \text{for } 0 \leq \ell \leq k-1 \tag{5}$$

• (1) to (3): obvious

• (4):

$$\begin{aligned} \lceil n/d_\ell \rceil \cdot d_\ell &\leq n + d_\ell \\ &< n + d_k/2 \quad (d_\ell \mid d_k) \\ &\leq n + 2n/2 \end{aligned}$$

def:  $\log^*$

## 6 Proof of the segregator lemma

$$\begin{aligned} T(1) &= 2 \\ T(x) &= 2^{T(x-1)} \\ T(x) &= 2^{2^{\dots}} \quad x \text{ times} \\ \log^* n &= \max\{x : T(x) \leq n\} \end{aligned}$$

### 6.1 Some very quickly growing sequences of numbers

Let

$$\begin{aligned} n &\geq T(4) = 2^{16} \\ k &= \lceil \frac{\log^* n}{3} \rceil \\ &\geq 2 \\ e_0 &= 1 \\ e_{\ell+1} &= k^{2+2e_\ell} \end{aligned}$$

**Lemma 15.**

$$e_\ell \leq T(k + 2\ell)$$

**Lemma 16.** For sequence

$$1 = e_0 < e_1 < \dots < e_{k-1}$$

holds:  $e_{k-1} \leq n$

Define for  $\ell \in [1 : k]$

$$\begin{aligned} d_0 &= 1 \\ d_\ell &= 2^{\lceil \log(n/e_{k-\ell}) \rceil} \quad (\text{next power of two after } n/e_{k-\ell}) \\ n/(e_{k-\ell}) &\leq d_\ell \leq 2n/e_{k-\ell} \\ n/d_\ell &\leq e_{k-\ell} \leq 2n/d_\ell \end{aligned}$$

**Lemma 17.**

$$d_0 = 1 \tag{1}$$

$$d_\ell \mid d_{\ell+1} \quad \text{for } 0 \leq \ell \leq k-1 \tag{2}$$

$$d_k \leq 2n \tag{3}$$

$$\lceil n/d_\ell \rceil \cdot d_\ell \leq 2n \quad \text{for } 0 \leq \ell \leq k-1 \tag{4}$$

$$k^{\lceil n/d_{\ell+1} \rceil} \leq \lceil n/d_\ell \rceil / k \quad \text{for } 0 \leq \ell \leq k-1 \tag{5}$$

• (5):

$$\begin{aligned} \frac{n}{d_{\ell+1}} &= \frac{n}{2^{\lceil \log(n/e_{k-\ell-1}) \rceil}} \\ &\leq \frac{n}{n/e_{k-\ell-1}} \quad \text{omit Gauss brackets} \\ &= e_{k-\ell-1} \\ k^{\lceil n/d_{\ell+1} \rceil} &\leq k^{2n/d_{\ell+1}} \\ &\leq k^{2e_{k-\ell-1}+2-2} \\ &= e_{k-\ell}/k^2 \\ &\leq 2n/(d_\ell k^2) \quad \text{above} \\ &\leq \lceil n/d_\ell \rceil / k \quad (k \geq 2) \end{aligned}$$



def:  $\log^*$

## 6 Proof of the segregator lemma

Define for  $\ell \in [1 : k]$

$$\begin{aligned} T(1) &= 2 \\ T(x) &= 2^{T(x-1)} \\ T(x) &= 2^{2^{\dots}} \quad x \text{ times} \\ \log^* n &= \max\{x : T(x) \leq n\} \end{aligned}$$

$$\begin{aligned} d_0 &= 1 \\ d_\ell &= 2^{\lceil \log(n/e_{k-\ell}) \rceil} \quad (\text{next power of two after } n/e_{k-\ell}) \end{aligned}$$

$$n/(e_{k-\ell}) \leq d_\ell \leq 2n/e_{k-\ell}$$

$$n/d_\ell \leq e_{k-\ell} \quad , \quad e_{k-\ell} \leq 2n/d_\ell$$

### 6.1 Some very quickly growing sequences of numbers

**Lemma 17.**

Let

$$\begin{aligned} n &\geq T(4) = 2^{16} \\ k &= \lceil \frac{\log^* n}{3} \rceil \\ &\geq 2 \\ e_0 &= 1 \\ e_{\ell+1} &= k^{2+2e_\ell} \end{aligned}$$

$$d_0 = 1 \tag{1}$$

$$d_\ell \mid d_{\ell+1} \quad \text{for } 0 \leq \ell \leq k-1 \tag{2}$$

$$d_k \leq 2n \tag{3}$$

$$\lceil n/d_\ell \rceil \cdot d_\ell \leq 2n \quad \text{for } 0 \leq \ell \leq k-1 \tag{4}$$

$$k^{\lceil n/d_{\ell+1} \rceil} \leq \lceil n/d_\ell \rceil / k \quad \text{for } 0 \leq \ell \leq k-1 \tag{5}$$

• (5):

$$\frac{n}{d_{\ell+1}} = \frac{n}{2^{\lceil \log(n/e_{k-\ell-1}) \rceil}}$$

$$\leq \frac{n}{n/e_{k-\ell-1}}$$

$$= e_{k-\ell-1}$$

$$k^{\lceil n/d_{\ell+1} \rceil} \leq k^{2n/d_{\ell+1}}$$


$$\leq k^{2e_{k-\ell-1}+2-2}$$

$$= e_{k-\ell}/k^2$$

$$\leq 2n/(d_\ell k^2) \quad \text{above}$$

$$\leq \lceil n/d_\ell \rceil / k \quad (k \geq 2)$$

$$n/d_{\ell+1} \geq n/e_{k-1} \geq 1$$



**Lemma 15.**

$$e_\ell \leq T(k+2\ell)$$

**Lemma 16.** For sequence

$$1 = e_0 < e_1 < \dots < e_{k-1}$$

holds:  $e_{k-1} \leq n$

def:  $\log^*$

## 6 Proof of the segregator lemma

$$\begin{aligned} T(1) &= 2 \\ T(x) &= 2^{T(x-1)} \\ T(x) &= 2^{2^{2^{\dots}}} \quad x \text{ times} \\ \log^* n &= \max\{x : T(x) \leq n\} \end{aligned}$$

### 6.1 Some very quickly growing sequences of numbers

Let

$$\begin{aligned} n &\geq T(4) = 2^{16} \\ k &= \lceil \frac{\log^* n}{3} \rceil \\ &\geq 2 \\ e_0 &= 1 \\ e_{\ell+1} &= k^{2+2e_\ell} \end{aligned}$$

**Lemma 15.**

$$e_\ell \leq T(k + 2\ell)$$

**Lemma 16.** For sequence

$$1 = e_0 < e_1 < \dots < e_{k-1}$$

holds:  $e_{k-1} \leq n$

Define for  $\ell \in [1 : k]$

$$\begin{aligned} d_0 &= 1 \\ d_\ell &= 2^{\lceil \log(n/e_{k-\ell}) \rceil} \quad (\text{next power of two after } n/e_{k-\ell}) \end{aligned}$$

$$n/(e_{k-\ell}) \leq d_\ell \leq 2n/e_{k-\ell}$$

$$n/d_\ell \leq e_{k-\ell} \quad , \quad e_{k-\ell} \leq 2n/d_\ell$$

**Lemma 17.**

$$d_0 = 1 \tag{1}$$

$$d_\ell \mid d_{\ell+1} \quad \text{for } 0 \leq \ell \leq k-1 \tag{2}$$

$$d_k \leq 2n \tag{3}$$

$$\lceil n/d_\ell \rceil \cdot d_\ell \leq 2n \quad \text{for } 0 \leq \ell \leq k-1 \tag{4}$$

$$k^{\lceil n/d_{\ell+1} \rceil} \leq \lceil n/d_\ell \rceil / k \quad \text{for } 0 \leq \ell \leq k-1 \tag{5}$$

• (5):

$$\begin{aligned} \frac{n}{d_{\ell+1}} &= \frac{n}{2^{\lceil \log(n/e_{k-\ell-1}) \rceil}} \\ &\leq \frac{n}{n/e_{k-\ell-1}} \\ &= e_{k-\ell-1} \\ k^{\lceil n/d_{\ell+1} \rceil} &\leq k^{2n/d_{\ell+1}} \\ &\leq k^{2e_{k-\ell-1}+2-2} \\ &= e_{k-\ell}/k^2 \\ &\leq 2n/(d_\ell k^2) \quad \text{above} \\ &\leq \lceil n/d_\ell \rceil / k \quad (k \geq 2) \end{aligned}$$



## 6.2 Partitioning of nodes and edges

from now on consider:

- TM computation graph  $G = (V, E)$  for  $k$ -tape TM
- indegree  $r \leq 2k + 1$
- $n$  nodes:  $V = [1 : n]$ .
- in order to show segregator lemma 13 it suffices to show

**Lemma 18.** *We can construct a segregator for  $G$  with*

1. *at most  $15rn/\log^* n$  nodes*
2. *whose removal leaves at most  $6rn/\log^* n$  predecessors for each node*

## 6.2 Partitioning of nodes and edges

from now on consider:

- TM computation graph  $G = (V, E)$  for  $k$ -tape TM
- indegree  $r \leq 2k + 1$
- $n$  nodes:  $V = [1 : n]$ .
- in order to show segregator lemma 13 it suffices to show

**Lemma 18.** *We can construct a segregator for  $G$  with*

1. *at most  $15rn/\log^* n$  nodes*
2. *whose removal leaves at most  $6rn/\log^* n$  predecessors for each node*

**def: partitions  $P_\ell$  of nodes** for  $0 \leq \ell \leq k - 1$ . See figure 3.

- for  $P_\ell$  partition  $V = [1 : n]$  into consecutive blocks of length  $d_\ell$  nodes, except the last block, which has  $\leq d_\ell$  nodes.
- interval sizes very quickly growing
- $P_\ell$  is refinement of  $P_{\ell+1}$  because  $d_\ell | d_{\ell+1}$




Figure 3: Node partition  $P_\ell$  refines  $P_{\ell+1}$ . Edges in  $E_\ell$  cross block boundaries in  $P_\ell$  but stay in the same block of  $P_{\ell+1}$ .



## 6.2 Partitioning of nodes and edges

from now on consider:

- TM computation graph  $G = (V, E)$  for  $k$ -tape TM
- indegree  $r \leq 2k + 1$
- $n$  nodes:  $V = [1 : n]$ .
- in order to show segregator lemma 13 it suffices to show

**Lemma 18.** *We can construct a segregator for  $G$  with*

1. *at most  $15rn / \log^* n$  nodes*
2. *whose removal leaves at most  $6rn / \log^* n$  predecessors for each node*

**def: partitions  $P_\ell$  of nodes** for  $0 \leq \ell \leq k - 1$ . See figure 3.

- for  $P_\ell$  partition  $V = [1 : n]$  into consecutive blocks of length  $d_\ell$  nodes, except the last block, which has  $\leq d_\ell$  nodes.
- interval sizes very quickly growing
- $P_\ell$  is refinement of  $P_{\ell+1}$  because  $d_\ell | d_{\ell+1}$

**partitioning of edges into sets  $E_\ell$**

- place edge  $e$  into set  $E_\ell$  if  $e$  crosses boundaries between blocks of  $P_\ell$  but stays within a single block of the next coarser partition  $P_{\ell+1}$




Figure 3: Node partition  $P_\ell$  refines  $P_{\ell+1}$ . Edges in  $E_\ell$  cross block boundaries in  $P_\ell$  but stay in the same block of  $P_{\ell+1}$ .



## 6.2 Partitioning of nodes and edges

from now on consider:

- TM computation graph  $G = (V, E)$  for  $k$ -tape TM
- indegree  $r \leq 2k + 1$
- $n$  nodes:  $V = [1 : n]$ .
- in order to show segregator lemma 13 it suffices to show

**Lemma 18.** *We can construct a segregator for  $G$  with*

1. *at most  $15rn/\log^* n$  nodes*
2. *whose removal leaves at most  $6rn/\log^* n$  predecessors for each node*

**def: partitions  $P_\ell$  of nodes** for  $0 \leq \ell \leq k - 1$ . See figure 3.

- for  $P_\ell$  partition  $V = [1 : n]$  into consecutive blocks of length  $d_\ell$  nodes, except the last block, which has  $\leq d_\ell$  nodes.
- interval sizes very quickly growing
- $P_\ell$  is refinement of  $P_{\ell+1}$  because  $d_\ell | d_{\ell+1}$

**partitioning of edges into sets  $E_\ell$**

- place edge  $e$  into set  $E_\ell$  if  $e$  crosses boundaries between blocks of  $P_\ell$  but stays within a single block of the next coarser partition  $P_{\ell+1}$




Figure 3: Node partition  $P_\ell$  refines  $P_{\ell+1}$ . Edges in  $E_\ell$  cross block boundaries in  $P_\ell$  but stay in the same block of  $P_{\ell+1}$ .

- the number of edges is bounded by

$$|E| \leq r \cdot n$$

and there are  $k$  classes  $E_\ell$  of edges


- in at least one of them the number of edges is at most

$$|E_\ell| \leq rn/k$$



**def: partitions  $P_\ell$  of nodes** for  $0 \leq \ell \leq k-1$ . See figure 3.

- for  $P_\ell$  partition  $V = [1 : n]$  into consecutive blocks of length  $d_\ell$  nodes, except the last block, which has  $\leq d_\ell$  nodes.
- interval sizes very quickly growing
- $P_\ell$  is refinement of  $P_{\ell+1}$  because  $d_\ell | d_{\ell+1}$




$$|E_\ell| \leq rn/k$$

Figure 3: Node partition  $P_\ell$  refines  $P_{\ell+1}$ . Edges in  $E_\ell$  cross block boundaries in  $P_\ell$  but stay in the same block of  $P_{\ell+1}$ .

**def: partitions  $P_\ell$  of nodes** for  $0 \leq \ell \leq k-1$ . See figure 3.

- for  $P_\ell$  partition  $V = [1 : n]$  into consecutive blocks of length  $d_\ell$  nodes, except the last block, which has  $\leq d_\ell$  nodes.
- interval sizes very quickly growing
- $P_\ell$  is refinement of  $P_{\ell+1}$  because  $d_\ell | d_{\ell+1}$



$$|E_\ell| \leq rn/k$$

Let  $A$  be the set of start points of these edges.

$$A = \{i : \exists j.(i,j) \in E\}$$

$$|A| \leq rn/k$$


- removing  $A$  and adjacent edges gives graph  $G - A$ .

Figure 3: Node partition  $P_\ell$  refines  $P_{\ell+1}$ . Edges in  $E_\ell$  cross block boundaries in  $P_\ell$  but stay in the same block of  $P_{\ell+1}$ .



**def: partitions  $P_\ell$  of nodes** for  $0 \leq \ell \leq k-1$ . See figure 3.

- for  $P_\ell$  partition  $V = [1 : n]$  into consecutive blocks of length  $d_\ell$  nodes, except the last block, which has  $\leq d_\ell$  nodes.
- interval sizes very quickly growing
- $P_\ell$  is refinement of  $P_{\ell+1}$  because  $d_\ell | d_{\ell+1}$



$$|E_\ell| \leq rn/k$$

Let  $A$  be the set of start points of these edges.

$$A = \{i : \exists j. (i, j) \in E\}$$

$$|A| \leq rn/k$$

- removing  $A$  and adjacent edges gives graph  $G - A$ .
- obtain graph  $G^* = (V^*, E^*)$  by

1. collapsing intervals in  $P_\ell$  into nodes

$$V^* = \{x^* : x^* \text{ is block of } P_\ell\}$$

hence

$$n^* = |V^*| = \lceil n/d_\ell \rceil$$


2. for  $x^* \neq y^*$  including an edge from  $x^*$  to  $y^*$  if there is an edge in  $G - A$  from a node  $x \in x^*$  to a node  $y \in y^*$

$$(x^*, y^*) \in E^* \leftrightarrow \exists x \in x^*, y \in y^*. (x, y) \in E \setminus E_\ell$$

Figure 3: Node partition  $P_\ell$  refines  $P_{\ell+1}$ . Edges in  $E_\ell$  cross block boundaries in  $P_\ell$  but stay in the same block of  $P_{\ell+1}$ .

**def: partitions  $P_\ell$  of nodes** for  $0 \leq \ell \leq k-1$ . See figure 3.

- for  $P_\ell$  partition  $V = [1 : n]$  into consecutive blocks of length  $d_\ell$  nodes, except the last block, which has  $\leq d_\ell$  nodes.
- interval sizes very quickly growing
- $P_\ell$  is refinement of  $P_{\ell+1}$  because  $d_\ell | d_{\ell+1}$



$$|E_\ell| \leq rn/k$$

Let  $A$  be the set of start points of these edges.

$$A = \{i : \exists j. (i, j) \in E\}$$

$$|A| \leq rn/k$$

- removing  $A$  and adjacent edges gives graph  $G - A$ .
- obtain graph  $G^* = (V^*, E^*)$  by

1. collapsing intervals in  $P_\ell$  into nodes

$$V^* = \{x^* : x^* \text{ is block of } P_\ell\}$$

hence

$$n^* = |V^*| = \lceil n/d_\ell \rceil$$

2. for  $x^* \neq y^*$  including an edge from  $x^*$  to  $y^*$  if there is an edge in  $G - A$  from a node  $x \in x^*$  to a node  $y \in y^*$

$$(x^*, y^*) \in E^* \leftrightarrow \exists x \in x^*, y \in y^*. (x, y) \in E \setminus E_\ell$$

- edges  $(x, y)$  are either in the same block of  $P_\ell$  or they go between different blocks of  $P_{\ell+1}$  (because edges of  $A$  are removed).
- therefore  $G^*$  is very shallow

**Lemma 19.**

$$\text{depth}(G^*) \leq \# \text{ blocks of } P_{\ell+1} = \lceil n/d_{\ell+1} \rceil$$


Figure 3: Node partition  $P_\ell$  refines  $P_{\ell+1}$ . Edges in  $E_\ell$  cross block boundaries in  $P_\ell$  but stay in the same block of  $P_{\ell+1}$ .



### 6.3 fan in reduction

TM computation graph  $G$  is composed of planar graphs  $G_s$  which are



- the spine
- left half or right half for a tape with edges other than the spine.
- this gives composition of  $G^*$  from graphs  $G_s^*$



## 6.3 fan in reduction

TM computation graph  $G$  is composed of planar graphs  $G_s$  which are

- the spine
- left half or right half for a tape with edges other than the spine.
- this gives composition of  $G^*$  from graphs  $G_s^*$





**Lemma 20.** In any compressed component graph  $G_i^*$  let  $y^* < z^*$  and let  $x^*$  be a direct predecessor of both  $x^*$  and  $y^*$ . Then  $x^*$  is first (earliest) direct predecessor of  $y^*$



## 6.3 fan in reduction

TM computation graph  $G$  is composed of planar graphs  $G_s$  which are

- the spine
- left half or right half for a tape with edges other than the spine.
- this gives composition of  $G^*$  from graphs  $G_s^*$





**Lemma 20.** In any compressed component graph  $G_i^*$  let  $y^* < z^*$  and let  $x^*$  be a direct predecessor of both  $x^*$  and  $y^*$ . Then  $x^*$  is first (earliest) direct predecessor of  $y^*$

- assume there is an earlier direct predecessor  $w^*$  of  $y$ .
- then edges  $(x^*, z^*)$  and  $(w^*, y^*)$  would cross, and so would the edges from which they were constructed.
- contradicting the bracket structure of edges in  $G_s$  would be violated

## 6.3 fan in reduction

TM computation graph  $G$  is composed of planar graphs  $G_s$  which are

- the spine
- left half or right half for a tape with edges other than the spine.
- this gives composition of  $G^*$  from graphs  $G_s^*$



**Lemma 20.** In any compressed component graph  $G_i^*$  let  $y^* < z^*$  and let  $x^*$  be a direct predecessor of both  $x^*$  and  $y^*$ . Then  $x^*$  is first (earliest) direct predecessor of  $y^*$

**def: indegree of nodes in  $G_s^*$**

$$D_s(x^*) = \# \text{ direct predecessors of } x^* \text{ in } G_s^*$$



$$D(x^*) = \# \text{ direct predecessors of } x^* \text{ in } G^*$$



### 6.3 fan in reduction

TM computation graph  $G$  is composed of planar graphs  $G_s$  which are

- the spine
- left half or right half for a tape with edges other than the spine.
- this gives composition of  $G^*$  from graphs  $G_s^*$



lemma 20  $\rightarrow$ : different nodes have distinct direct predecessors except possibly for the first one:

$$\sum_{x^*} (D_s(x^*) - 1) \leq n^*$$

$$\sum_{x^*} D_s(x^*) \leq 2n^*$$

$$\sum_{x^*} D(x^*) \leq 2rn^*$$

**Lemma 20.** In any compressed component graph  $G_i^*$  let  $y^* < z^*$  and let  $x^*$  be a direct predecessor of both  $x^*$  and  $y^*$ . Then  $x^*$  is first (earliest) direct predecessor of  $y^*$

**def: indegree of nodes in  $G_s^*$**

$$D_s(x^*) = \# \text{ direct predecessors of } x^* \text{ in } G_s^*$$



$$D(x^*) = \# \text{ direct predecessors of } x^* \text{ in } G^*$$



## 6.3 fan in reduction

TM computation graph  $G$  is composed of planar graphs  $G_s$  which are

- the spine
- left half or right half for a tape with edges other than the spine.
- this gives composition of  $G^*$  from graphs  $G_s^*$



**Lemma 20.** In any compressed component graph  $G_i^*$  let  $y^* < z^*$  and let  $x^*$  be a direct predecessor of both  $x^*$  and  $y^*$ . Then  $x^*$  is first (earliest) direct predecessor of  $y^*$

**def: indegree of nodes in  $G_s^*$**

$$D_s(x^*) = \# \text{ direct predecessors of } x^* \text{ in } G_s^*$$

$$D(x^*) = \# \text{ direct predecessors of } x^* \text{ in } G^*$$

lemma 20  $\rightarrow$ : different nodes have distinct direct predecessors except possibly for the first one:

$$\sum_{x^*} (D_s(x^*) - 1) \leq n^*$$

$$\sum_{x^*} D_s(x^*) \leq 2n^*$$

$$\sum_{x^*} D(x^*) \leq 2rn^*$$

**def: bad nodes**

•



$$x^* \text{ bad} \leftrightarrow D(x) > k$$



## 6.3 fan in reduction

TM computation graph  $G$  is composed of planar graphs  $G_s$  which are

- the spine
- left half or right half for a tape with edges other than the spine.
- this gives composition of  $G^*$  from graphs  $G_s^*$



**Lemma 20.** In any compressed component graph  $G_i^*$  let  $y^* < z^*$  and let  $x^*$  be a direct predecessor of both  $x^*$  and  $y^*$ . Then  $x^*$  is first (earliest) direct predecessor of  $y^*$

**def: indegree of nodes in  $G_s^*$**

$$\begin{aligned} D_s(x^*) &= \# \text{ direct predecessors of } x^* \text{ in } G_s^* \\ D(x^*) &= \# \text{ direct predecessors of } x^* \text{ in } G^* \end{aligned}$$

lemma 20  $\rightarrow$ : different nodes have distinct direct predecessors except possibly for the first one:

$$\sum_{x^*} (D_s(x^*) - 1) \leq n^*$$

$$\sum_{x^*} D_s(x^*) \leq 2n^*$$

$$\sum_{x^*} D(x^*) \leq 2rn^*$$

**def: bad nodes**

- 
- 

$$x^* \text{ bad} \leftrightarrow D(x) > k$$

$$B^* = \{x^* : x^* \text{ bad}\}$$

$$|B^*| \leq 2rn^*/k$$

$$B = \{x \in x^* : x^* \text{ bad}\}$$

$$|B| = |B^*| \cdot d_\ell$$

$$\leq 2rn^* d_\ell / k$$

$$\leq 2r \lceil n/d_\ell \rceil \cdot d_\ell / k$$



$$\leq 4rn/k \quad (\text{lemma 17})$$



## 6.3 fan in reduction

TM computation graph  $G$  is composed of planar graphs  $G_s$  which are

- the spine
- left half or right half for a tape with edges other than the spine.
- this gives composition of  $G^*$  from graphs  $G_s^*$



**Lemma 20.** In any compressed component graph  $G_i^*$  let  $y^* < z^*$  and let  $x^*$  be a direct predecessor of both  $x^*$  and  $y^*$ . Then  $x^*$  is first (earliest) direct predecessor of  $y^*$

**def: indegree of nodes in  $G_s^*$**

$$\begin{aligned} D_s(x^*) &= \# \text{ direct predecessors of } x^* \text{ in } G_s^* \\ D(x^*) &= \# \text{ direct predecessors of } x^* \text{ in } G^* \end{aligned}$$

lemma 20  $\rightarrow$ : different nodes have distinct direct predecessors except possibly for the first one:

$$\sum_{x^*} (D_s(x^*) - 1) \leq n^*$$

$$\sum_{x^*} D_s(x^*) \leq 2n^*$$

$$\sum_{x^*} D(x^*) \leq 2rn^*$$

**def: bad nodes**

- 
- 

$$x^* \text{ bad} \leftrightarrow D(x) > k$$

$$B^* = \{x^* : x^* \text{ bad}\}$$

$$|B^*| \leq 2rn^*/k$$

$$B = \{x \in x^* : x^* \text{ bad}\}$$

$$|B| = |B^*| \cdot d_\ell$$

$$\leq 2rn^* d_\ell / k$$

$$\leq 2r \lceil n/d_\ell \rceil \cdot d_\ell / k$$

$$\leq 4rn/k \quad (\text{lemma 17})$$



# 6.4 Segregator

choose

$$S = A \cup B$$

size

$$\begin{aligned} |S| &\leq |A| + |B| \\ &\leq rn/k + 4rn/k \\ &= 5rn/k \\ &\leq 15rn/\log^* n \end{aligned}$$

## 6.4 Segregator

choose

$$S = A \cup B$$

size

$$\begin{aligned} |S| &\leq |A| + |B| \\ &\leq rn/k + 4rn/k \\ &= 5rn/k \\ &\leq 15rn/\log^* n \end{aligned}$$

number of predecessors

- let  $U = G^* - B^*$
- $pred(x^*)$ : number of predecessors of  $x^*$  in  $U$

$$\begin{aligned} pred(x^*) &\leq D(x^*)^{depth(G^*)} \\ &\leq k^{depth(G^*)} \quad (x^* \text{ good}) \\ &\leq k^{\lceil n/d_{\ell+1} \rceil} \quad (\text{lemma 19}) \\ &\leq \lceil n/d_{\ell} \rceil / k \quad (\text{lemma 17}) \end{aligned}$$



# 6.4 Segregator

choose

$$S = A \cup B$$

size

$$\begin{aligned} |S| &\leq |A| + |B| \\ &\leq rn/k + 4rn/k \\ &= 5rn/k \\ &\leq 15rn/\log^* n \end{aligned}$$

number of predecessors

- let  $U = G^* - B^*$
- $pred(x^*)$ : number of predecessors of  $x^*$  in  $U$

$$\begin{aligned} pred(x^*) &\leq D(x^*)^{depth(G^*)} \\ &\leq k^{depth(G^*)} \quad (x^* \text{ good}) \\ &\leq k^{\lceil n/d_{\ell+1} \rceil} \quad (\text{lemma 19}) \\ &\leq \lceil n/d_{\ell} \rceil / k \quad (\text{lemma 17}) \end{aligned}$$

- $pred(x)$ : number of predecessors of  $x$  in  $G - (A \cup B)$

$$\begin{aligned} pred(x) &\leq d_{\ell} \cdot pred(x^*) \\ &\leq d_{\ell} \cdot \lceil n/d_{\ell} \rceil / k \\ &\leq 2n/k \quad (\text{lemma 17}) \\ &\leq 6rn/\log^* n \end{aligned}$$

def:  $\log^*$

## 6 Proof of the segregator lemma

$$\begin{aligned} T(1) &= 2 \\ T(x) &= 2^{T(x-1)} \\ T(x) &= 2^{2^{\dots}} \quad x \text{ times} \\ \log^* n &= \max\{x : T(x) \leq n\} \end{aligned}$$

### 6.1 Some very quickly growing sequences of numbers

Let

$$\begin{aligned} n &\geq T(4) = 2^{16} \\ k &= \lceil \frac{\log^* n}{3} \rceil \\ &\geq 2 \\ e_0 &= 1 \\ e_{\ell+1} &= k^{2+2e_\ell} \end{aligned}$$

**Lemma 15.**

$$e_\ell \leq T(k + 2\ell)$$

**Lemma 16.** For sequence

$$1 = e_0 < e_1 < \dots < e_{k-1}$$

holds:  $e_{k-1} \leq n$

Define for  $\ell \in [1 : k]$

$$\begin{aligned} d_0 &= 1 \\ d_\ell &= 2^{\lceil \log(n/e_{k-\ell}) \rceil} \quad (\text{next power of two after } n/e_{k-\ell}) \end{aligned}$$

$$n/(e_{k-\ell}) \leq d_\ell \leq 2n/e_{k-\ell}$$

$$e_{k-\ell} \leq 2n/d_\ell$$

**Lemma 17.**

$$d_0 = 1 \tag{1}$$

$$d_\ell \mid d_{\ell+1} \quad \text{for } 0 \leq \ell \leq k-1 \tag{2}$$

$$d_k \leq 2n \tag{3}$$

$$\lceil n/d_\ell \rceil \cdot d_\ell \leq 2n \quad \text{for } 0 \leq \ell \leq k-1 \tag{4}$$

$$k^{\lceil n/d_{\ell+1} \rceil} \leq \lceil n/d_\ell \rceil / k \quad \text{for } 0 \leq \ell \leq k-1 \tag{5}$$

• (5):

$$\frac{n}{d_{\ell+1}} = \frac{n}{2^{\lceil \log(n/e_{k-\ell-1}) \rceil}}$$

$$\leq \frac{n}{n/e_{k-\ell-1}}$$

$$= e_{k-\ell-1} \dots$$

$$k^{\lceil n/d_{\ell+1} \rceil} \leq k^{2e_{k-\ell-1} + 2^{\dots} + 2^{\dots}} \quad \text{and (4)}$$

$$= e_{k-\ell}/k^2$$

$$\leq 2n/(d_\ell k^2) \quad \text{above}$$

$$\leq \lceil n/d_\ell \rceil / k \quad (k \geq 2)$$