

NamingContest.com — Developer Handbook

Technical reference for maintaining and extending the platform

Technical reference for maintaining, reviewing, and extending the platform. Written for a senior developer arriving cold. The plain-English companion is `PLATFORM-GUIDE.md`; email-lifecycle testing lives in `TESTING-EMAILS.md`.

No credentials appear in this document. Access is shared privately.

1. Product in one paragraph

A paid naming-contest platform. A creator answers a guided brief, pays a one-time fee via Stripe (\$9/\$19/\$39 keyed to voter capacity 10/30/90), and shares one invitation link. Participants join via email magic link, submit names (creator-set cap, 1–5), then vote (up to 3 picks, tallies hidden until close). Phases advance automatically on timers. The creator crowns a winner from a leaderboard; lifecycle emails go out at each transition; there is a public reveal page per contest.

- Production: <https://namingcontest.com> (soft beta gate, client-side password)
 - Hosting: Vercel, project `namingcontest-prototype`
 - Supabase project ref: `kgcggyuoezaygyawnlcs`
-

2. Stack

LAYER	TECH	NOTES
Frontend	React 18.3, Vite 5.4, react-router 6	SPA, no SSR
Database	Supabase Postgres	RLS on every table
Server logic	Supabase Edge Functions (Deno)	5 functions, see §7
Auth	Supabase Auth, magic links only	implicit flow, no passwords
Payments	Stripe Payment Intents	in-modal confirmCardPayment, no hosted checkout
Email	Resend (API + SMTP)	plus 2 Supabase Auth templates
Scheduling	pg_cron	phase transitions + rate-limit pruning
Secrets	Supabase secrets + Vault	see §8
PDF export	jsPDF 4 + html-to-image	client-side capture of a hidden node
Analytics	@vercel/analytics	<code><Analytics /></code> in App.jsx

3. Repository layout

```

COMPLETE-FINAL/
├─ src/                # the app (working dir for dev)
│  ├─ pages/v4/        # the real product surfaces
│  ├─ pages/legal/     # /privacy, /terms (real, keep)
│  ├─ pages/system/    # 404, /link-expired, /error, /contact
│  ├─ pages/*.jsx      # LEGACY v1 prototype pages (see §12)
│  ├─ components/v4/   # product components (AvatarMenu, SignInModal...)
│  ├─ data/v4/         # briefQuestions, segmentTheme, voterTiers, mock data
│  ├─ lib/             # supabaseClient, AuthContext
│  ├─ utils/           # v4Brief (guest blob), v4Anonymity, exports...
│  └─ styles/          # v4.css (large), landing-v3.css, mobile.css...
├─ supabase/
│  ├─ migrations/      # 0001-0022, the full DB history (§6)
│  ├─ functions/       # edge functions + _shared/ (email.ts, rateLimit.ts)
│  └─ templates/       # copies of the 2 dashboard email templates
├─ docs/              # this file + guides
└─ public/            # favicons, email logo/icons PNGs

```

4. Branch and deploy workflow

- `backend` — working branch. All development lands here.

- `master` — production. **Pushing master auto-deploys to Vercel.**
- Promotion is always a `--no-ff` merge: `git checkout master && git merge --no-ff backend && git push`.
- Tags: `demo-complete-2026-07-20` is the snapshot with the demo surface still routed (see §12); older `v5-live` / `v6-live` / `pre-demo-teardown` predate the backend.
- Vercel also builds preview deployments per branch push (staging).

Verify a deploy landed: fetch `https://namingcontest.com/`, take the hashed `/assets/index-*.js` name, and grep it for a string from your change. Note the SPA rewrite (`vercel.json`) returns HTTP 200 + `index.html` for *every* path, so status codes prove nothing — check content-type / content.

5. Local development

```
npm install
cp .env.example .env      # fill in values (see §8)
npm run dev                # Vite on :5173
npm run build              # production build – run before every promote
```

The build must pass before promoting; there is no CI, the discipline is manual.

6. Database

Tables (`0001_initial_schema`)

`profiles` (1:1 auth.users; `display_name`, `avatar_url` — **no email stored**), `contests`, `participants`, `submissions`, `votes`. All RLS-enabled.

Migration catalog

Migrations are applied by pasting into the Supabase SQL editor, named `NNNN_slug`. **There is no migration runner** — the numbered files in `supabase/migrations/` are the source of truth and must be applied in order on a fresh environment.

#	PURPOSE
0001	Schema, RLS policies, submission/vote rule triggers, vote_count sync
0002	Storage bucket <code>uploads</code> (public read, per-user-folder writes), avatar_url
0003	RLS recursion fix (security definer helper)
0004	<code>get_join_info</code> — public join-page fields RPC
0005	<code>contest_is_joinable</code> — fixes 42501 on join
0006	user FK → auth.users
0007	Realtime publication for live dashboard
0008	<code>cancelled</code> status
0009	pg_cron <code>advance-contest-phases</code> (every minute; submission→voting→closed on deadlines)
0010	join info: creator name + deadlines
0011	<code>get_winner_info</code> — public reveal RPC (granted to anon)
0012	<code>auth_user_id_by_email</code> (avoids generateLink OTP-cooldown bug)
0013	pg_net trigger → notify function on voting/winner transitions
0014	<code>notified_voting_at</code> / <code>notified_winner_at</code> dedupe stamps
0015	notify secret moved to Vault
0016	Submission cap honours creator setting, clamped to 5
0017	Price derived server-side from voter_tier (trigger overwrites client value)
0018	<code>get_ballot</code> — resolved ballot RPC (anonymity + hidden tallies)
0019	<code>submissions_read</code> lockdown (own rows + creator only)
0020	Rate-limit table + <code>rate_limit_take</code> + hourly prune cron
0021	Payment-column guard trigger (client can't set paid/status/deadlines/creator/tier)
0022	Voter-tier capacity enforced on participant insert
0023	<code>voting_closed</code> notification to the creator + <code>contest_creator_email</code> + <code>notified_closed_at</code>

Server-enforced invariants (the security model)

Everything below is enforced in Postgres, not in the UI:

1. Price = f(voter_tier): 10→\$9, 30→\$19, 90→\$39; unknown → null (unpayable).
2. A contest cannot become paid/live except via the service role (confirm-launch after Stripe verification). Status can only move to `cancelled` from the client.

3. Participant count $\leq$ voter_tier (null tier = legacy, uncapped; over-capacity contests are grandfathered — next join blocked, nobody removed).
4. Submissions per user $\leq$ creator's setting, hard ceiling 5.
5. Votes: ≤ 3 , participants only, not for your own name, only while `voting`.
6. Participants never see `user_id` or mid-vote tallies (get_ballot resolves display names per the contest's anonymity mode; counts released when closed, or always to the creator).
7. Votes readable only by their caster. Creator sees aggregates, not ballots.
8. Rate limits: contact 3/h/IP; launch 5/h/IP + 3/h/email. **Fails open** by design (nuisance endpoints; availability > strictness). IPs stored only as date-salted SHA-256 hashes.
9. All user-controlled values escaped in email HTML (`esc()` in `_shared/email.ts` ; `bodyHtml` is the one field escaped at call sites — its type comment explains).

7. Edge functions

Deploy: `npx supabase functions deploy <name> [--no-verify-jwt] --project-ref kgcggyuoeyaygawnlcs`

FUNCTION	JWT	PURPOSE
<code>launch-contest</code>	no	Guest launch: find-or-create user by email, insert draft. Rate-limited. Never uses <code>admin.generateLink</code> (it trips the per-email OTP cooldown; the app sends the magic link via <code>signInWithOtp</code> so it carries the browser's context)
<code>create-payment-intent</code>	yes	PI for <code>contests.price</code> (server-authoritative), rejects < \$0.50
<code>confirm-launch</code>	yes	Retrieves PI from Stripe, checks status/metadata/amount, flips contest live, sends branded receipt
<code>notify</code>	no (secret header)	Lifecycle emails, called by DB trigger via <code>pg_net</code> with <code>x-notify-secret</code> (Vault). Dedupe stamps written BEFORE sending. Resend batch endpoint (100/call)
<code>contact</code>	no	Contact form → team inbox (reply_to = visitor) + visitor receipt. Rate-limited, escaped, field caps

Shared modules: `_shared/email.ts` (design system + `esc` + `sendEmail` + `FROM`), `_shared/rateLimit.ts` (IP hashing + fail-open take).

8. Environment variables and secrets

Vercel (build-time, inlined into the JS bundle — changing one requires a redeploy, and none of these are secret-safe): `VITE_SUPABASE_URL` , `VITE_SUPABASE_ANON_KEY` , `VITE_STRIPE_PUBLISHABLE_KEY` , `VITE_BETA_PASSWORD` (unset = gate off; it ships in the bundle — obscurity, not access control).

Supabase function secrets (`npx supabase secrets set K=V --project-ref ...`): `STRIPE_SECRET_KEY`, `RESEND_API_KEY`, `NOTIFY_SECRET`, `SITE_URL`, `CONTACT_TO` (defaults to `hello@namingcontest.com`).

Vault: the notify secret also lives in Supabase Vault (0015) for the DB trigger side. Rotating `NOTIFY_SECRET` means updating both (`vault.update_secret` + `secrets set`).

Supabase dashboard, not in repo: Auth SMTP settings (Resend, `smtp.resend.com:465`, sender `noreply@namingcontest.com`), the two Auth email templates (Magic Link, Confirm signup — repo copies in `supabase/templates/`, keep in sync by re-pasting), Redirect URLs allow-list.

9. Auth flow

- Magic links only, implicit flow (supabase-js default). `signInWithOtp` with `emailRedirectTo`; new addresses get the **Confirm signup** template, existing ones **Magic Link** — both restyled.
- Rejected links arrive as `#error=...&error_code=otp_expired` on the redirect URL. `AuthContext` parses this and `App` routes to `/link-expired` (links are one-time; mail scanners commonly consume them first).
- Sign-out awaits `auth.signOut()` and falls back to `{scope:'local'}` on failure — being unable to leave is worse than an unrevoked refresh token.
- **The guest blob** `localStorage.v4_contest_setup` (via `utils/v4Brief.js`) carries a guest's identity and in-progress contest before an account exists. Historic bug source: it must NEVER stand in for a real session. Current rules: `AuthContext` drops its identity fields when a session appears under a different email (brief answers are kept — that's the guest-to-user upgrade path); real contest pages never fall back to it; Settings guards against signed-out visitors unless the blob holds a genuinely-theirs `contestId`. **Review focus: any new `readSetup()` fallback must be gated on the absence of a session.**

10. Payment flow

1. Review page → `launch-contest` (guest) or direct insert (signed-in): draft row, `paid=false`. Trigger 0017 overwrites any client `price`.
2. `create-payment-intent` reads `contests.price` server-side → PI with `metadata.contestId`.
3. Browser confirms card in-modal (`stripe.confirmCardPayment`).
4. `confirm-launch` retrieves the PI (expand `latest_charge`), verifies `status === 'succeeded'`, `metadata.contestId`, `amount === price*100` (valid because price is server-authoritative), then service-role-updates: `paid`, `status='submission'`, `launched_at`, both phase deadlines — the columns trigger 0021 blocks from every non-service-role path. Sends the receipt email with Stripe's `receipt_url`.

No webhooks: verification is pull-based in `confirm-launch`. Equivalent guarantee for this flow since nothing goes live without step 4; a reviewer may still prefer adding a `payment_intent.succeeded` webhook as belt-and-braces for abandoned-tab cases.

Test → live switch: replace `STRIPE_SECRET_KEY` (Supabase secret) and `VITE_STRIPE_PUBLISHABLE_KEY` (Vercel env + redeploy) with live keys from the same Stripe account. Never paste the live secret key into chats or docs.

11. Contest lifecycle and email

States: `draft → submission → voting → closed` (+ terminal `cancelled`). Cron `advance-contest-phases` (every minute) moves on `submission_ends_at` / `voting_ends_at`. The notify trigger (0013, extended in 0023) fires on three transitions: entering `voting`, entering `closed` with no winner yet (creator only — the cue to pick), and `winner_submission_id` being set. Each has its own dedupe stamp (`notified_voting_at` / `notified_closed_at` / `notified_winner_at`) written before sending, so a status flip-flop can't re-email anyone.

Senders: all outbound = `noreply@namingcontest.com` (Resend domain-verified; DKIM on `resend._domainkey`, SPF/MX on `send.` subdomain). `hello@` is the inbound human channel only — **it has no mailbox until the client sets up eNom forwarding**; until then contact-form mail bounces. DMARC is `p=none`; tighten to quarantine after reviewing reports. Root SPF record: none (nothing sends from the root domain). Deliverability (Promotions-tab placement) is reputation-driven and improves with real volume.

Subjects: `Your contest is live – {name}`, `Your vote is needed – {name}`, `Time to crown the winner – {name}`, `The winning name – {name}`, `Your name won – {name}`, `Contact form – {topic} – {name}`, `We got your message – NamingContest`.

Fast-forwarding a contest for testing: `docs/TESTING-EMAILS.md`.

12. Demo/mock system (important context)

The app began as a front-end-only prototype. Remnants, deliberately kept:

- `/v4/map` and `/v4/demo` are **unrouted** (404) but `PlatformMap.jsx`, `DemoIndex.jsx` and `src/data/v4/mock*` remain in the tree.
- Real pages branch on `mockContest` in ~150 places across 14 files (30 in `ContestManage` alone). Removing the mock plumbing is a real refactor with regression risk on pages that need live session state to test — scoped out before handoff on purpose. Tag `demo-complete-2026-07-20` restores the routed demo if ever wanted.
- `src/pages/*.jsx` outside `v4/`, `legal/`, `system/` are the legacy v1 prototype (`BriefBuilder` etc.), still routed at legacy paths but not linked from the product. Candidates for deletion in a cleanup pass.
- Some files are oddly named (`PartnerSimulator`, `LegalCrumbs`) to dodge ad-blockers — do not rename back.

13. Known gaps / recommended review focus

1. `readSetup()` fallbacks vs. real sessions (see §9) — the historic bug source.
2. No Stripe webhook (see §10) — consider adding.
3. Social handles in email footers are **placeholder accounts nobody owns** (`x.com/namingcontest` etc., defined in `_shared/email.ts` SOCIAL const).
4. Landing testimonials are fictional; swap before launch.
5. Rich link previews: SPA serves one static `index.html`, so shared reveal links get a generic OG card. Fix = edge function serving crawler HTML.
6. Voting limit is hard-coded at 3 (DB trigger + UI clamp); the brief's `votingLimit` setting is vestigial.
7. `hello@` mailbox missing (client task, eNom forwarding).
8. Beta gate is client-side only.
9. No automated tests; the build (`npm run build`) is the only gate.
0. Bundle is one ~2.8 MB chunk — code-splitting would help mobile.

14. Operational runbook

```
-- Recent contests
select id, working_name, status, paid, voter_tier, created_at
from contests order by created_at desc limit 20;

-- Everything-applied check (all seven true)
select
  (select prosrc like '%submissionLimit%' from pg_proc where proname='enforce_submission_rules') as m0016,
  (select count(*) from pg_trigger where tgname='contests_set_price')=1 as m0017,
  (select count(*) from pg_proc where proname='get_ballot')=1 as m0018,
  (select count(*) from pg_policies where tablename='submissions'
    and policyname='submissions_read' and qual like '%creator_id%')>0 as m0019,
  (select count(*) from pg_proc where proname='rate_limit_take')=1 as m0020,
  (select count(*) from pg_trigger where tgname='contests_guard_payment')=1 as m0021,
  (select count(*) from pg_trigger where tgname='participants_tier_cap')=1 as m0022;

-- Did the DB actually call the notify function?
select id, status_code, left(content,300), created
from net._http_response order by id desc limit 5;

-- Cron health
select jobname, schedule, active from cron.job;
```


Function logs: Supabase dashboard → Edge Functions → function → Logs. Email deliveries: Resend dashboard. Payment records: Stripe → Payments.

15. Key rotation (when needed)

- `RESEND_API_KEY`: create new in Resend → `supabase secrets set` → done (functions read at runtime, no redeploy).
- `NOTIFY_SECRET`: generate → `vault.update_secret` for the DB side AND `supabase secrets set` for the function side. Both, or notify 401s.
- Stripe keys: dashboard roll → secret via `supabase secrets set`, publishable via Vercel env + redeploy (build-time inlined).
- Supabase anon key: dashboard → Vercel env + redeploy.