

# JavaScript

## Introduction

---

# The JavaScript language

---

- **JavaScript** is a programming language for use in HTML pages.
- Invented in 1995 at Netscape Corporation (LiveScript).
- **Script** means small piece of code. JavaScript is designed to add interactivity to HTML pages.
- JavaScript programs are run by an interpreter built into the user's web browser.
- While JavaScript programs are commonly executed by the user's web browser, they can also be run on the server-side using platforms such as Node.js.
- JavaScript can modify the contents of a web page when the page is loaded or in response to a user action.

# Using JavaScript in HTML Document

---

- JavaScript can be inserted into documents by using the **SCRIPT** tag.
- All java script statements end with a semicolon (;)  
... Not necessarily!...
- While JavaScript doesn't require semicolons after every statement, using them is considered good practice to prevent potential issues with Automatic Semicolon Insertion.
- JavaScript is case sensitive language.
- JavaScript uses C-style comments: // and /\* \*/

```
<html>
<head>
<title>Hello World in JavaScript</title>
</head>
<body>
  <script type="text/javascript">
    document.write("Hello World!");
  </script>
</body>
</html>
```

The **type** attribute used to be required. But in **HTML5** it can be left out.

# Using JavaScript in HTML Document

---

- You can have any number of scripts.
- Scripts can be placed in the **HEAD** or in the **BODY**.
  - In the HEAD, scripts are run before the page is displayed.
  - In the BODY, scripts are run as the page is displayed.
- Functions that may execute multiple times is typically placed in the `<HEAD>`. These are only interpreted when the relevant function or event-handler are called
- Also Scripts can be placed **within an HTML tag**, such as `<body>` or `<form>`—This is called an **event handler**, and it enables the script to work with HTML elements.

**Note:** When using JavaScript in event handlers, you don't need to use the `<script>` tag.

# Example

---

```
<html>
<head>
  <title>Hello World in JavaScript</title>
  <script>
    function helloWorld( ) {
      document.write("Hello World!"); }
  </script>
</head>
<body>
<h1>Event handler</h1>
<button type="button" onclick=" alert('You clicked the button.')"> Click</button>
  <script>
    helloWorld( );
  </script>
</body>
</html>
```

# External Scripts

---

- Scripts can also be loaded from an external file.
- This is useful if you have a complicated script or set of subroutines that are used in several different documents.
- JavaScript files have the file extension **.js**.
- To use an external script, put the name of the script file in the **src** (source) attribute of a `<script>` tag:

```
<script src="myscript.js"> </script>
```

- You can place an external script reference in `<head>` or `<body>`.
- You can add several script files to one page.

**Note:**

External scripts cannot contain `<script>` tags.

# JavaScript Data Types

---

- A value in JavaScript is always of a certain type. There are eight basic data types in JavaScript. They are:

Data Types	Description	Example
String	represents textual data	'hello', "hello world!"
Number	an integer or a floating-point number	3, 3.234, 3e-2 etc.
BigInt	an integer more than $(2^{53} - 1)$	900719925124740999n
Boolean	Any of two values: true or false	true and false
undefined	variable is declared but not initialized	var a;
null	denotes a null value	let a = null;
Object	key-value pairs of collection of data	let student = { };

# JavaScript Data Types

---

- all data types except Object are primitive data types, whereas Object is non-primitive.
- Strings may be enclosed in either single quotes or double quotes  
  \" (double quote), \' (single quote), etc.
- JavaScript is a dynamically typed language. It means that a **variable** doesn't associate with a type. In other words, a variable can hold a value of different types. For example:

```
let counter = 120;    // counter is a number
counter = false;     // counter is now a Boolean
counter = "foo";     // counter is now a string
```



# JavaScript Variables

---

- A **variable** is a named container used for storing values.
- There are two kind of variables in JavaScript : **local variable** and **global variable**.
- A local variable is declared inside block or function.
- A global variable is accessible from any function.
- JavaScript variable can be declared in different ways by using different keywords: **var**, **let** and **const** keyword. Each keyword is used in some specific conditions.
- **var** has been available since 1995, but with the release of ES6, **let** and **const** are now available to declare variables.

# JavaScript Variables

---

- **var** keyword used to declare a variable that can accessible globally and changeable.

```
var x = 10;
```

- **let** keyword used to declare a variable that can accessible locally and changeable.

```
let counter = 120;
```

- **const** keyword used to declare a variable that can accessible locally and it can't be reassigned.

```
const PI = 3.14;
```

# JavaScript Operators

---

- JavaScript has most of the operators we're used to from C/Java
  - Arithmetic (+, -, \*, /, %)
  - Assignment (=, +=, -=, \*= /=, %=, ++, --)
  - Logical (&&, ||, !)
  - Comparison (<, >, <=, >=, ==)

# JavaScript Output

---

- JavaScript output defines the ways to display the output of a given code.
- The output can be display by using four different ways which are listed below:
  - **document.write()** and **document.writeln()** //methods used to display some information on the HTML document.
  - **window.alert()**. //pop-up warning box.
  - **innerHTML**. //to write HTML elements.
  - **console.log()**. //is written to the browser console.

# Using document.write()

---

- Used to write any output into the HTML webpage.
- The `write()` method writes the HTML expressions or JavaScript code to a document.
- This method is mostly used for testing purposes.

```
document.write(" any message");  
document.writeln(" any message");
```

- The `document` is object name and `write()` or `writeln()` are methods.
- The difference between these two methods is carriage form feed character that is new line character automatically added into the `document.writeln()`, but it is not included in `document.write ()`.

# Using document.write()

- JavaScript Date Methods

```
<body>
  <p>
    <script>
      var today= new Date();
      document.write("Current date: <br/>" );
      document.write(today.toString());

      document.write("<br/>");
      document.write("&copy;&nbsp;");
      document.write(today.getFullYear());
    </script>
  </p>
</body>
```

HTML Character  
Entities:

- copyright
- non-breaking space


Current date:  
Sun May 12 2025  
© 2025

# Using window.alert()

- The `alert()` method in JavaScript is used to display a virtual alert box. It is mostly used to give a warning message to the users.
- The `alert()` method displays an alert box with a message and an OK button. When the dialog box pops up, we have to click "OK" to proceed.

```
window.alert("Welcome to\nJavaScript\nProgramming!");
```

- The `window` is object name and `alert()` is method.



**Note:** The `window.alert()` method can be written without the window prefix, like: `alert()`

# Using innerHTML

---

- JavaScript lets you write into an HTML element by using `innerHTML` property.
- you can add anything, it can be a text message, some HTML element or anything else.
- To do that first you need to provide a specific `id` to the **HTML element** that you want to access by the JavaScript code.
- To access an HTML element use `document.getElementById(id)` method, where `id` is the value of the `id` attribute of the HTML tag.

```
<p id="demo"></p>
<script>
    document.getElementById("demo").innerHTML = "JavaScript";
</script>
```



# Using innerHTML

---

```
<!DOCTYPE html>
<html>
<head>
  <title>JavaScript innerHTML</title>
</head>
<body>
  <div id="main"></div>
  <script src="app.js"></script>
</body>
</html>
```

[app.js file](#)

```
let mainDiv=document.getElementById('main');
mainDiv.innerHTML = "<h1>Welcome to JavaScript Programming</h1>";
mainDiv.style.color="orange";
```

# Using console.log()

---

- JavaScript also lets you create console logs which can be seen in the **browser's developers' tools(Console)** for debugging purposes.
- The statement written inside a console log will be executed but would not be displayed in the browser instead it will be displayed inside the console of the browser.

```
console.log(2+3);
```




# JavaScript Popup Boxes

---

- In addition to **alert(msg) box** JavaScript has another two kind of popup boxes: **Confirm box** and **Prompt box**.
- **confirm(msg) box**: asks the user to confirm (or cancel) something.

```
window.confirm( "Are you sure you want to submit?" );
```




**Note:** The `window.confirm()` method can be written without the window prefix, like: `confirm()`

# JavaScript Popup Boxes

---

- **prompt(msg, default) box**: asks the user to enter some text.
- The **prompt()** method returns the input value if the user clicks "OK", otherwise it returns **null** (if the user clicks "Cancel").

```
let name;  
name = window.prompt( "Please enter your name" );
```



## Example: Write a java script addition of two numbers.

---

```
<html>
<head>
<title>addition</title>
</head>
<body>
  <script>
    let a,b,c;
    a= parseInt(window.prompt("enter the a value"));
    b= parseInt(window.prompt("enter the b value"));
    c=a+b;
    document.write("The result="+c);
  </script>
</body>
</html>
```

The **parseInt** method parses a value as a string and returns an integer.

# Example:

---

```
<body>
```

```
  <p id="demo"></p>
```

```
  <script>
```

```
    let person = prompt("Please enter your name");
```

```
    if (person != null) {
```

```
      document.getElementById("demo").innerHTML = "Hello " +  
        person + "! How are you today?";
```

```
    }
```

```
  </script>
```

```
</body>
```