

```
Database changed
mysql> -- Create table
mysql> CREATE TABLE clss (name VARCHAR(10), id INT(5));
Query OK, 0 rows affected, 1 warning (0.17 sec)

mysql>
mysql> -- Insert first value and commit
mysql> INSERT INTO clss VALUES ("dj", 5);
Query OK, 1 row affected (0.03 sec)

mysql> COMMIT;
Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> -- Update the row
mysql> UPDATE clss SET name = "bravo" WHERE id = "5";
Query OK, 1 row affected (0.01 sec)
Rows matched: 1  Changed: 1  Warnings: 0

mysql>
mysql> -- Create Savepoint A
mysql> SAVEPOINT A;
Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> -- Insert second value
mysql> INSERT INTO clss VALUES ("uppal", 6);
Query OK, 1 row affected (0.00 sec)

mysql>
mysql> -- Create Savepoint B
mysql> SAVEPOINT B;
Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> -- Insert third value
mysql> INSERT INTO clss VALUES ("balu", 7);
Query OK, 1 row affected (0.01 sec)

mysql>
mysql> -- Create Savepoint C
```

```
mysql> -- Create Savepoint C
mysql> SAVEPOINT C;
Query OK, 0 rows affected (0.00 sec)
```

```
mysql>
mysql> -- Check all rows
mysql> SELECT * FROM clss;
```

name	id
bravo	5
uppal	6
balu	7

```
3 rows in set (0.00 sec)
```

```
mysql>
mysql> -- Rollback to Savepoint B (removes 'balu')
mysql> ROLLBACK TO B;
ERROR 1305 (42000): SAVEPOINT B does not exist
mysql> SELECT * FROM clss;
```

name	id
bravo	5
uppal	6
balu	7

```
3 rows in set (0.00 sec)
```

```
mysql>
mysql> -- Rollback to Savepoint A (removes 'uppal' too)
mysql> ROLLBACK TO A;
ERROR 1305 (42000): SAVEPOINT A does not exist
mysql> SELECT * FROM clss;
```

name	id
bravo	5
uppal	6
balu	7

```
mysql>
mysql> -- Rollback to Savepoint A (removes 'uppal' too)
mysql> ROLLBACK TO A;
ERROR 1305 (42000): SAVEPOINT A does not exist
mysql> SELECT * FROM clss;
+-----+-----+
| name  | id  |
+-----+-----+
| bravo | 5   |
| uppal | 6   |
| balu  | 7   |
+-----+-----+
3 rows in set (0.00 sec)

mysql> |
```