Nokia SONiC Chassis addressing in MSFT Lab

MSFT provided block of 11 IP addresses to use: 10.3.152.110 - .120/24 with GW address of 10.3.152.1

Chassis 2 (top) has IMMs only in slots 3 and 4
Chassis 1 (bottom) has IMMs only in slots 1 and 2

We have allocated addresses 10.3.152.110 - .114 to Chassis 1 (bottom) and 10.3.152.115 - .120 to Chassis 2 (top)

Our scheme is to assign the base/lowest address per chassis to CPM, then add the slot number for each IMM (in the same chassis) to determine/assign its address.

Below are the specifics:

- Chassis 2 (top chassis)
  - IMM slot 3 proxy eth mgmt IP: 10.3.152.118 (also accessible directly from Chassis 2 CPM at 10.0.0.3)
  - IMM slot 4 proxy eth mgmt IP: 10.3.152.119 (also accessible directly from Chassis 2 CPM at 10.0.0.4)
  - CPM front panel eth mgmt IP : 10.3.152.115

- Chassis 1 (bottom chassis)
  - IMM slot 1 proxy eth mgmt IP: 10.3.152.111 (also accessible directly from Chassis 1 CPM at 10.0.0.1)
  - IMM slot 2 proxy eth mgmt IP: 10.3.152.112 (also accessible directly from Chassis 1 CPM at 10.0.0.2)
  - CPM front panel eth mgmt IP : 10.3.152.110

For reference, these configurations are rolled up into a script on each CPM at
/etc/sonic/config_mgmt

