

Lab Report

Your Performance

Your Score: 0 of 3 (0%)

Elapsed Time: 1 minute 37 seconds

Pass Status: Not Passed

Required Score: 100%

Task Summary

✖ Configure CorpCluster2 as the preferred owner [Hide Details](#)

- ✖ CorpCluster2 selected as preferred
- ✖ CorpCluster2 at top of list

✖ Priority still set to High [Hide Details](#)

- ✖ CorpCluster2 selected as preferred

✖ Configure failover and failback settings [Hide Details](#)

- ✖ Maximum of 1 failure in a 2 hour period
- ✖ Allow failback
- ✖ Allow failback between 20 (2000 or 8:00 pm) and 5 (0500 or 5:00 am)

Explanation

In this lab, you use the Failover Cluster Manager console to configure failover settings.

- Preferred owner: **CorpCluster2**
- Placement in the list of preferred owners: **top**
- Priority: **high**
- Maximum failures: **one**
- Period: **two hours**
- Failback hours: between **8:00 pm** and **5:00 am**

Complete this lab as follows:

1. From Server Manager, select **Tools > Failover Cluster Manager**.
2. Expand the **cluster node**.
3. Select **Roles**.
4. In the center pane, right-click the **role** and select **Properties**.
5. On the General tab, select the **preferred owner** for this role.
6. Select **Up** to change the preferred order.
7. Select the **priority**.
8. On the Failover tab, set the **failover settings**.
9. Select **Allow failback**.
10. Select **Failback between**.
11. Set the **failback settings**; then click **OK**.