Exam Report: 4.2.4 Practice Questions			
Date: 3/12/2020 11:49:41 pm Time Spent: 26:05		Candidate: Garsteck, Matthew Login: mGarsteck	
Overall Performance			
Your Score: 92%			
		Passing Score: 80%	
View results by: Objective A	Analysis Individual Responses	3	
Individual Responses			
▼ Question 1:	Correct		
have set up and configured a from the same vendor. After twireless mouse is not working	new laptop computer. The computer he new employee begins work, you	e new employee's first day at work, you r and all of the peripherals were purchased receive a phone call stating that the t working?	
The USB mouse red	reiver is not plugged into the compu	iter.	
The USB mouse is	nalfunctioning.		
The USB mouse is	not a wireless mouse and needs to b	e plugged into the computer.	
The USB mouse dri	ver is too old for the current mouse.		
Explanation			
of the mouse and the driver n		d from the same vendor, the likelihood the MOST likely reason is that the USB	
References			
TestOut PC Pro - 4.2 USB [e_usb_pp6.exam.xml Q_US]	B_FACT_INPUT_MOUSE]		
▼ Question 2:	<u>Correct</u>		
	SB scanner to the USB port on your not recognized. What should you d	computer. However, the first time you lo?	
Start the Add a Dev	ice wizard and then connect the sca	nner to the USB port.	
Connect the scanner installing the driver	to the USB port. Complete the Adds.	d a Device wizard, which includes	
Install the scanner d Device wizard when		to the USB port and complete the Add a	
Connect the scanner	to the USB port.		

Explanation

To install USB devices, start by installing the driver. Then connect the device to the USB port. The operating system will detect the device and configure it automatically. The driver is used to tell the operating system how to communicate with the device.

References

TestOut PC Pro - 4.2 USB [e_usb_pp6.exam.xml Q_USB_FACT_INSTALL_USB_02]

Question 3: You are an IT technician for variety of devices.	Correct your company. As part of your job, you must manage and support a wide
Which of the following is the	e MOST common interface for peripheral devices?
USB	
FireWire	
Serial	
O PATA	
Explanation	
USB is the most common int	erface for peripheral devices, such as printers, keyboards, and mice.
adapters. Serial interfaces are	ace for digital video cameras and recorders, hard drives, and network e common for modems, older printers, and networking devices. PATA for internal HDDs and CD/DVD drives.
References	
TestOut PC Pro - 4.2 USB [e_usb_pp6.exam.xml Q_US	B_FACT_USB_01]
Question 4:	<u>Correct</u>
Which of the following stand of 5 meters?	lards provides data transfer rates up to 480 Mbps with a maximum cable length
→ (USB 2.0	
○ IEEE 1394	
RS-232	
○ IEEE 1284	
Explanation	
1394 (also known as FireWinmeters. IEEE 1284 (parallel)	r data transfer rates of 480 Mbps and cable lengths up to 5 meters. IEEE re) provides data transfers of up to 400 Mbps and a cable length of 4.5 has a data transfer maximum of 2 Mbps with a maximum cable length of 10 rates at relatively slow speeds, but over longer distances.
References	
TestOut PC Pro - 4.2 USB [e_usb_pp6.exam.xml Q_US	B_FACT_USB_02]
Question 5:	<u>Correct</u>
What is the maximum data to	ransfer speed for USB 3.0 devices?
400 Mbps	
1.5 Mbps	
→ ⑤ 5 Gbps	
480 Mbps	
12 Mbps	

Explanation

USB 3.0 specifies a maximum transmission speed of up to 5 Gbit/s. USB 2.0 devices have a maximum data transfer speed of 480 Mbps. USB 1.0 devices have a maximum data transfer speed of 1.5 Mbps or 12 Mbps.

References

TestOut PC Pro - 4.2 USB

[e_usb_pp6.exam.xml Q_USB_FACT_USB_03]

▼ Question 6:

Correct

Your company has just upgraded your laptop computer. After receiving your new computer, you plug your external USB 2.0 hard disk into your new USB 3.0 port.

Which of the following is the MOST accurate statement regarding how this device will function?

- The USB 2.0 device will not work in the USB 3.0 port.
- The device will be able to transfer at USB 3.0 speeds.
- → ① The device will work, but will only transfer at USB 2.0 speeds.
 - The device will require an external power source.

Explanation

USB 3.0 ports are backwards compatible with all previous USB versions. However, they can only transfer as fast as the slowest version being used. This means that a USB 2.0 device connected to a USB 3.0 port will transfer data at USB 2.0 speeds.

Devices only require an external power source if they require more than 500 mA or 900 mA of power (for USB 2.0 and USB 3.0, respectively).

References

TestOut PC Pro - 4.2 USB [e_usb_pp6.exam.xml Q_USB_FACT_USB_04]

▼ Question 7:

Correct



This question includes an image to help you answer the question.

Close



What type of USB 2.0 connector is shown here?

Type-A



Type-B

MiniUSB

Explanation

The microUSB connector is designed for smartphones and tablet devices. microUSB connectors are approximately half the thickness of miniUSB connectors, making them more appropriate for smaller devices.

The miniUSB connector is used by portable electronic devices, such as digital cameras and some portable storage devices.

The Type-B is a square connector with two beveled corners. Type-B connectors are mostly used with printers. Some networking devices, such as hubs and modems, also use this connector.

The Type-A connector is a rectangular connector that generally plugs directly into the computer or a hub. Almost all USB cables have one Type-A connector on one of its ends.


References

TestOut PC Pro - 4.2 USB

[e_usb_pp6.exam.xml Q_USB_FACT_USB_2-PB]

▼ Question 8: <u>Correct</u>

Match the USB connector types on the left with the image labels on the right. (Not all USB connector types will be used.)





Explanation

Connector 1 is a USB 2.0 Type-B connector which is a square connector with two beveled corners. Type-B connectors are mostly used with printers. Some networking devices, such as hubs and modems, also use this connector.

Connector 2 is a USB 2.0 microUSB connector designed for smartphones and tablet devices. microUSB connectors are approximately half the thickness of miniUSB connectors, making them more appropriate for smaller devices.

Connector 3 is a USB 2.0 miniUSB connector, which is used by portable electronic devices, such as digital cameras and some portable storage devices.

Connector 4 is a USB 3.0 Micro-B connector, which is used by small portable electronic devices, such as portable storage devices.

References

TestOut PC Pro - 4.2 USB

[e_usb_pp6.exam.xml Q_USB_FACT_USB_2_CONNECTORS-PB]

▼ Question 9:

Correct



This question includes an image to help you answer the question.

Close





What type of USB 3.0 connector is shown here?



Explanation

The blue tab indicates that the connector is a USB 3.0 Type-A connector and capable of USB 3.0 speeds. USB 3.0 Type-A connectors are backwards compatible with all previous USB versions.

The USB 3.0 Type-B connector is larger in size and designed to carry both data and power. Due to their increased size, USB 3.0 Type-B connectors cannot be plugged into older USB Type-B ports. However, USB 3.0 peripherals that use this port are able to accept older USB Type-B connectors.

The USB 3.0 Micro-B connector is used by portable devices, such as compact external storage devices, digital cameras, or smartphones.


References


TestOut PC Pro - 4.2 USB [e_usb_pp6.exam.xml Q_USB_FACT_USB_3-PB]

Incorrect

▼ Question 10:

Match the USB connector types on the left with the image labels on the right. (Not all USB connector types will be used.)





Expection USB 3.0 Type-A connector. The blue tab indicates that the connector is a USB 3.0 Type-A connector and capable of USB 3.0 speeds. USB 3.0 Type-A connectors are backwards compatible with all previous USB versions.

Connector 2 is a USB 3.0 Micro-B connector. The USB 3.0 Micro-B connector is used by portable devices, such as compact external storage devices, digital cameras, or smartphones.

Connector 3 is a USB 3.0 Type-B connector. The USB 3.0 Type-B connector is larger in size and designed to carry both data and power. Due to their increased size, USB 3.0 Type-B connectors cannot be plugged into older USB Type-B ports. However, USB 3.0 peripherals that use this port are able to accept older USB Type-B connectors.

Connector 4 is a USB 2.0 Type-A rectangular connector that generally plugs directly into the computer or a hub. Almost all USB cables have one Type-A connector on one of the ends.

References

TestOut PC Pro - 4.2 USB [e_usb_pp6.exam.xml Q_USB_FACT_USB_3_CONNECTORS-PB]

▼ Question 11:

Correct

You are an IT technician for your company. As part of your job, you must manage and support a wide variety of devices.

Which of the following devices MOST likely uses a micro-USB connector? (Select TWO).

ĺ	Printers
1	Printers

→ 🗸	Smartphone
-----	------------



Network hubs and modems

Scanners

Explanation

microUSB connectors are typically used by compact, portable electronic devices, such as smart phones, digital cameras, GPS devices, and some external storage peripherals.

Printers and scanners typically use a Type-B connector. Some networking devices, such as hubs and modems, also use Type-B connectors.

References

TestOut PC Pro - 4.2 USB [e_usb_pp6.exam.xml Q_USB_FACT_USB_5]

▼ Question 12:

Correct

Susan works in the research and development department. She has recently purchased a large high-speed external drive and has attached the drive to her computer using a USB cable. Her drive requires a minimum bandwidth of 400 Mbps and at least 900 milliamps (mA) to function.

Although the correct drivers are installed, the drive is not functioning. To troubleshoot the problem, she has connected her drive to her coworker's computer where the drive functions properly. No additional cables are required for this drive.

Which of the following is the MOST likely reason Susan's external hard drive is not working?

Susan has connected her drive to a USB $3.0\ port$, but the drive is only made to work with a $2.0\ port$
port.



Susan has connected her drive to a	USB 3.0 port,	which does	not have enou	gh power fo	r hei
drive.					

Susan has connected her drive to a USB 3.0 port, which does not support the maximum
bandwidth required.

Susan has connected her drive to a USB 2.0 port, which does not support the maximum bandwidth required.

Explanation

Susan has connected her drive to a USB 2.0 port, which does not support the requirements for her drive. Large high-speed USB drives require more power than a USB 1.0 or 2.0 can provide. USB 2.0 supports a maximum bandwidth of 480 Mbps and is, therefore, fast enough for Susan's drive. A 2.0 port only supports a maximum power consumption of 500 milliamps.

References

TestOut PC Pro - 4.2 USB [e_usb_pp6.exam.xml Q_USB_FACT_USB_POWER]