Lab Report

Your Performance

Your Score: 0 of 4 (0%)

Pass Status: Not Passed

Elapsed Time: 2 minutes 36 seconds

Required Score: 100%

Task Summary

✖ On SwitchA's Gi0/1 and Gi0/2 trunk ports, configure native VLAN to VLAN 10

✖ On SwitchB's Gi0/1 and Gi0/2 trunk ports, configure native VLAN to VLAN 10

✖ On SwitchC's Gi0/1 and Gi0/2 trunk ports, configure native VLAN to VLAN 10

✖ Save the changes   Hide Details

> ⊟ Save SwitchA's configurations
> ⊟ Save SwitchB's configurations
> ⊟ Save SwitchC's configurations

Explanation

In this lab, your task is to complete the following:

- On each switch, change the native VLAN from its default to VLAN 10 for each trunk port.
- Save changes to the startup-config file for each switch.

Complete the following on each switch:

1. Select the *switch*.
2. Press **Enter**.
3. At the prompt, enter:

    SwitchA>**ena**
    SwitchA#**conf t**
    SwitchA(config)#**int range gi 0/1 - 2**
    SwitchA(config-if-range)#**switchport trunk native vlan 10**

4. Press **Ctrl** + **Z**.
5. At the prompt, enter:

    SwitchC#**copy run start**

6. Press **Enter**.
7. Press **Enter** to save your changes.
8. Repeat steps 1–7 for each switch.